

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo		
Company name *	Lexmark International, Inc.			
Contact information *	Nadia Martin (USA)	LEXMARK		
Internet site *	www.lexmark.se / www.lexmark.com			
Additional information				

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.					
Type of product *					
Commercial name *	exmark C746n				
Model number *	C746n				
Issue date *	date * 01-09-2012				
Intended market *	nded market * 🛛 🖂 Global 🗌 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality Control			nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model nu Issue da		C746n 01-09-2012 Logo	LEXM		Z
			LEAN		
Product	t environ	mental attributes - Legal requirements	Require	ment	met
Item		V 1	Yes	No	n.a.
P1	Hazardo	ous substances and preparations			
P1.1*	0.1% po	s do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium lybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal e and Note B1)	ι, 🔀		
P1.2*	Products	s do not contain Asbestos (see legal reference). st: Legal reference has no maximum concentration value.	\square		
P1.3*		s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),			
-	hydrobro trichloro concent	pmofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- ethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum ration values.			
P1.4*		s do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated /l (PCT) in preparations (see legal reference).	\square		
P1.5*		s do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).	e 🖂		
P1.6*	Textile a Tris-(azi	nd leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), ridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). ht: Legal reference has no maximum concentration values.			
P1.7*	Textile a	nd leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split amines. (See legal reference and Note B1)			\square
P1.8*	Wooden pentach	parts do not contain arsenic and chromium as a wood preservation treatment as well as orophenol and derivatives (see legal reference). ht: Legal reference has no maximum concentration values.			
P1.9*	Parts wi microgra	h direct and prolonged skin contact do not release nickel in concentrations above 0.5 m/cm²/week (see legal reference). nt: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH	Article 33 information about substances in articles is available at (add URL or mail contact): Program Manager, HOD9237, 740 W. New Circle Rd., Lexington, KY 40550			
P2	Batterie	<u> </u>			
P2.1*	more tha marked	duct contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is I in user manual. (See legal reference)			
P2.2*		ells used in the product do not contain more than 2% by weight of mercury. Other batteries or ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\square		
P2.3*	design c	s and accumulators are easily removable by either users or service providers (as dependent on the f the product). Exception: Batteries that are permanently installed for safety, performance, medica ntegrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety,	EMC connection to the telephone network and labeling			
P3.1*	The proc	duct complies with legally required safety standards as specified (see legal reference).	\square		
P3.2*	The proc	duct complies with legally required standards for electromagnetic compatibility (see legal reference).		
P3.3*	If produc	t is intended for connection to a public telecom network or contains a radio transmitter, it complies ally required standards for radio and telecommunication devices (see legal reference).			
P3.4*	The pro	duct is labeled to show conformance with applicable legal requirements (see legal reference).			
P4		hable materials			
P4.1*	legal ref	o conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see erence and Note B1).			
P4.2*	If ink/tor	er is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	\square		
P4.3*	product/	/toner formulation/preparation is classified as hazardous according to applicable regulations, the packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these nents is available (see legal reference).			
P5		packaging			
P5.1*	Packagi	ng and packaging components do not contain more than 0.01% lead, mercury, cadmium an ent chromium by weight of these together.	d 🔀		
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).				
P5.3*	Protocol	duct packaging material is free from ozone depleting substances as specified in the Montre. (see legal reference). nt: Legal reference has no maximum concentration values.	al 🔀		

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number * C746n						
Issue dat	e* 01	Logo	LEXM	ARK		
Product	onvironmo	ntal attributos - Markot roquiroments - Environmental conscious design	Require	mont	mot	
Item	ct environmental attributes - Market requirements - Environmental conscious design R *=mandatory to fill in. Additional information regarding each item may be found under P14.				n.a.	
P6		information	Yes	No	n.a.	
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).					
P7	Design					
		ly, recycling				
P7.1*	Parts that ha	ave to be treated separately are easily separable	\boxtimes			
P7.2*	Plastic mate	rials in covers/housing have no surface coating.	\square			
P7.3*	Plastic parts	s >100g consist of one material or of easily separable materials.				
P7.4*	Plastic parts	>25g have material codes according to ISO 11469 referring ISO 1043.		Ē	Ē	
P7.5	Plastic parts	s are free from metal inlays or have inlays that can be removed with commonly available tools.		Ħ	Ħ	
P7.6*		easily separable. (This requirement does not apply to safety/regulatory labels).		H	H	
	Product life					
P7.7*		an be done e.g. with processor, memory, cards or drives				
P7.8*		an be done using commonly available tools		Ħ	Ħ	
P7.9.		are available after end of production for: 5 years			⊢⊢	
P7.10	<u> </u>				╘	
F7.10		vailable after end of production for: 5 years d substance requirements				
P7.11*		er/housing material type:				
1 7.11	Material typ		s			
P7.12		ble insulation materials of power cables are PVC free.		\square		
P7.13		ble insulation materials of signal cables are PVC free			Ħ	
P7.14		using plastic parts >25g are free from chlorine and bromine.			⊢⊢	
P7.15		circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (S			⊢⊢	
17.10	Note B2)					
P7.16	/	ded plastic parts >25g in covers / housings are marked according ISO 1043-4:				
P7.17	Alt. 1 Chemical sp	becifications of flame retardants in printed circuit boards >25g (without components): ditive) , TBBPA (reactive) , Other; chemical name: , CAS #:				
	Chemical sp ISO 1043-4	pecifications of flame retardants in printed circuit boards (without components) >25g according • FR(16)				
P7.18	concentratio	rded plastic parts >25g contain the following flame retardant substances/preparations ons above 0.1%:	in 🗌			
	 Chemical Chemical Chemical Chemical Alt. 2 	name: , CAS #: name: , CAS #:				
D7 40	FR(40), FR	becifications of flame retardants in plastic parts >25g according ISO 1043-4: (17), FR(16), FR(50)				
P7.19	R40, R46, F	 >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) 				
P7.20		tic parts' weight >25g, recycled material content is %.				
P7.21		tic parts' weight >25g, biobased material content is %.				
P7.22		es are free from mercury s used specify: Number of lamps: and max. mercury content per lamp: mg	\boxtimes			
P8	Batteries					
P8.1*		nical composition: Lithium Manganese Dioxide, LiMnO2				
		eet the requirements of the following voluntary program/s:				

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	C746n		
Issue date *	01-09-2012	Logo	LEXMARK

	environmenta	l attributes - Market re	quirements (con	tinued)		Requireme		
Item	-					Yes N	o n.a	
P9 9.1	Energy consu	mption the following power levels		tions are reported	d:			
-				-			- 1 -	
Energy m	ode *	Power level at 100 V AC	Power level at 115 V AC	Power level 230 V AC		Reference / Standard for energeneers nodes and test method *	ду _	
Printing		531.5 W	517.6 W	496.8 W	0	Corporate Standard		
Ready M	ode	43.8 W	43.5 W	43.1 W	E	Energy Star I E V1.2		
Sleep Mo	de	6.67 W	6.70 W	6.70 W	E	Energy Star I E V1.2		
Hibernate	e Mode	0.48 W	0.49 W	0.51 W	1	EC 62301		
Off Mode		0.00 W	0.00 W	0.00 W	1	EC 62301		
		W	W	W				
EPS No-lo	bad	W	W	W				
charger pl outlet but the produ	power supply / lugged in the wall disconnected from ct.)							
PTEC * Typical Er	nergy Consumptio	W Dn	W	W				
TEC * Typical Er	nergy Consumptio	3.561 kWh/week	3.535 kWh/week	3.544 kWh/weel	k L	Energy Star I E V1.2		
ETEC * Annual Energy Consumption		kWh/year	kWh/year	kWh/year				
Display re	solution* :	Megapixels						
Print Spee	ed * : 35 Im	ages per minute	per minute			Corporate Standard		
Default tir	ne to enter energ	y save mode: 30 minutes	utes			Energy Star I E V1.2		
P9.2*	Information abo	out the energy save function	n is provided with th	e product.				
P9.3*	The product me ENERGY STAI Others specify:	eets the energy requiremen R® version: Tier:	nts of the following v Product catego		/s:			
P10	Emissions							
P10.1	Noise emissio Mode	n – Declared according to Mode description	150 9296	Declared		Declared A-weighted		
. 10.1	WOUG			A-weighted sound power	5	sound pressure level L_{pAm} (dB)		
					Operat	tor position Bystander position		
					or	Desktop (only if product is n operator attende		
	Idle	* Ready		* 4.8		32		
	Operation	* Simplex Monochrom Default Mode	e Printing,	* 6.8		53		
	Other mode							
	Measured acco		ECMA-74		.1	noogurement distance (m)		
		Other Other			⊔∟ _{pAm} n⊓	neasurement distance m) n/s: RAL-UZ-122		

Model nu	mber *	C746n			
Issue date	9 *	01-09-2012 Logo L	EXM	NRK	
				T9	
Product	environr	nental attributes - Market requirements (continued) R	equire	ment	met
Item			Yes	No	n.a.
	Chemic	al emissions from printing products			
P10.3*	Test per	formed according to ECMA-328 (ISO/IEC 28360) standard, other specify: RAL-UZ-122	\square		
P10.4	Typical e	emission rate (print phase) is (mg/h):			
		Dust <0.7 Ozone <0.06 Styrene 0.87 Benzene <0.03 TVOC 8.0			
P10.5		al emission requirements of the following voluntary program/s RAL-UZ-122 are met for :	\boxtimes		
		Dust 🛛 Ozone 🖾 Styrene 🖾 Benzene 🖾 TVOC 🔀			
D40.0		magnetic emissions			
P10.6	program	er display meets the requirement for low frequency electromagnetic fields of the following voluntary			\bowtie
P11	1 0	nable materials for printing products			
P11.1*	A Safety	Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	\boxtimes		
P11.2*	Paper c	ontaining post-consumer recycled fibers can be used, provided that it meets the requirements of		Ē	Ħ
	EN1228				
P11.3*		(duplex) printing/copying is an integrated product function.			
P12		mics for computing products			
P12.1*		play meets the ergonomic requirements of ISO 9241-307 for visual display technologies.			\square
P12.2*	The phy	sical input device meets the requirements of ISO 9995 and ISO 9241-410.			\square
P13		ing and documentation			
P13.1*		packaging material type(s): Corrugated weight (kg): 3.601 kg			
		packaging material type(s): <i>Polyethylene Foam</i> weight (kg): <i>0.673 kg</i> packaging material type(s): <i>High Density Polyethylene (HDPE)</i> weight (kg): <i>0.165 kg</i>			
P13.2*	Product	plastic packaging is free from PVC.	\boxtimes		
P13.3*		media for user and product documentation (tick box):			╞
	Electron	ic 🔀, Paper 🔀, Other 🗌			<u> </u>
P13.4*	fiber: 0				
Rev. P13.5	_	d product documentation do not contain chlorine bleached paper			
P14		nal information (See Note B4)			
P1.1	This p	roduct uses RoHS exemptions for lead and mercury used in small amounts for spe	ecific		
	applic	ations.			
P2.1	The bo	ittery contained within this product should be disposed of properly with the proc	luct. T	The	
		ct is properly labeled with the WEEE disposal symbol and instructions for such dis			ted
	-	product User's Guide.			
P. 2. 3	in the	product oser's Guide.			
		ittery contained within this product meets the exception listed. The battery is no		nded	to
	be ren	noved by the customer; however, is designed for easy removal by recyclers and s	ervice		
	provid	ers.			
P. 10. 4	BOL =	Below Quantifiable Limits - Note: The data reported is for the color print test.			
		print test results: Ozone – <0.06; Styrene - 0.14 mg/hr; Benzene –<0.03; Dust – <	0 7. a	od TI	Inc
	– 0.80 mg/hr				UC
	- 0.80	///y////			
	Addi+i	and company information and company environmental policy may be found at			
	Additional company information and company environmental policy may be found at				
http://lexmark.com/environment					
	Specific printer and supply item recycling information for your area may be found at				
	http://	/lexmark.com/recycle			
	Lexma	rk Sweden is connected to REPA and El-kretsen			

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19