

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	
Contact information *	Nadia Martin (USA)	LEXM
Internet site *	www.lexmark.se / www.lexmark.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	oduct * Single Function Color Laser Printer			
Commercial name *	Lexmark C925de			
Model number *	C925de			
Issue date *	10/26/2010			
Intended market *	🔀 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 📃 Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Requirement met		
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model nu Issue da		C925de 10/26/2010 Logo	IEVA	AD	Z
issue ua	le	10/20/2010	LEXN	1 KI	
Product	t environ	mental attributes - Legal requirements	Require	emen	met
Item			Yes	No	n.a.
P1	Hazardo	ous substances and preparations	-		
P1.1*	Products 0.1% po	s do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chrom lybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal e and Note B1)	ium, 🔀		
P1.2*	Products	s do not contain Asbestos (see legal reference).	\boxtimes		
P1.3*		nt: Legal reference has no maximum concentration value. s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),			
-	hydrobro trichloro concent	pmofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1 ethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum ration values.	-		
P1.4*	terpheny	s do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated /I (PCT) in preparations (see legal reference).			
P1.5*		s do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in intaining at least 48% per mass of chlorine in the SCCP (see legal reference).	the 🔀		
P1.6*	Textile a Tris-(azi	Ind leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRI- ridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). nt: Legal reference has no maximum concentration values.	S),		
P1.7*	Textile a	and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that sp c amines. (See legal reference and Note B1)	lit 🗌		\square
P1.8*	Wooden pentach	parts do not contain arsenic and chromium as a wood preservation treatment as well as lorophenol and derivatives (see legal reference). nt: Legal reference has no maximum concentration values.			\square
P1.9*	Parts wi microgra	th direct and prolonged skin contact do not release nickel in concentrations above 0.5 am/cm²/week (see legal reference). nt: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH	Article 33 information about substances in articles is available at (add URL or mail contact): Program Manager, H0D9237, 740 W. New Circle Rd., Lexington, KY 40550	\square		
P2	Batterie				
P2.1*	If the pro more tha marked	oduct contains a battery or an accumulator, it is labeled with the disposal symbol and if it contair an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is I in user manual. (See legal reference)			
P2.2*		ells used in the product do not contain more than 2% by weight of mercury. Other batteries or lators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference	;e)		
P2.3*	design c	s and accumulators are easily removable by either users or service providers (as dependent on of the product). Exception: Batteries that are permanently installed for safety, performance, med ntegrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety,	EMC connection to the telephone network and labeling			
P3.1*	The proc	duct complies with legally required safety standards as specified (see legal reference).	\boxtimes		
P3.2*	The proc	duct complies with legally required standards for electromagnetic compatibility (see legal referer	nce). 🔀		
P3.3*	If produc	ct is intended for connection to a public telecom network or contains a radio transmitter, it compl ally required standards for radio and telecommunication devices (see legal reference).	· 🔼		
P3.4*	The pro	duct is labeled to show conformance with applicable legal requirements (see legal reference).			
P4		nable materials			
P4.1*	legal ref	o conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (se erence and Note B1).			
P4.2*	If ink/tor	her is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference	e). 🔀		
P4.3*	product/	//toner formulation/preparation is classified as hazardous according to applicable regulations, th packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these nents is available (see legal reference).	e 🔀		
P5		packaging			
P5.1*		ng and packaging components do not contain more than 0.01% lead, mercury, cadmium ent chromium by weight of these together.	and 🔀		
P5.2*		backaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\boxtimes		
P5.3*	Protocol	duct packaging material is free from ozone depleting substances as specified in the Mon (see legal reference). nt: Legal reference has no maximum concentration values.	itreal		

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number * C925de						
Issue da	te *	10/26/2010 Logo	LEXM	ARK		
Droduct	onviron	mentel attributes. Market requirements. Environmental conceicus design	Doguiro	mont mot		
Item		mental attributes - Market requirements - Environmental conscious design tory to fill in. Additional information regarding each item may be found under P14.	Yes	No n.a.		
P6		nt information	165	NU 11.a.		
P6.1*		on for recyclers/treatment facilities is available (see legal reference).				
P7	Design	· · · · · · · · · · · · · · · · · · ·				
	•	mbly, recycling				
P7.1*		t have to be treated separately are easily separable	\square			
P7.2*	Plastic m	aterials in covers/housing have no surface coating.				
P7.3*	Plastic p	arts >100g consist of one material or of easily separable materials.		H H		
P7.4*		arts >25g have material codes according to ISO 11469 referring ISO 1043.		\exists		
P7.5	-	arts are free from metal inlays or have inlays that can be removed with commonly available tools.		+		
P7.6*		re easily separable. (This requirement does not apply to safety/regulatory labels).		+		
17.0						
P7.7*	Product Upgradin	g can be done e.g. with processor, memory, cards or drives				
P7.8*		g can be done using commonly available tools				
				<u> </u>		
P7.9.		rts are available after end of production for: 5 years	<u> </u>	<u> </u>		
P7.10		s available after end of production for: 5 years				
D7 44*		and substance requirements				
P7.11*		cover/housing material type: type: PC+ABS Material type: Material type:				
P7.12		type: PC+ABS Material type: Material type: I cable insulation materials of power cables are PVC free.				
P7.13		I cable insulation materials of signal cables are PVC free				
P7.14						
		/housing plastic parts >25g are free from chlorine and bromine.				
P7.15	All printe Note B2)	d circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (S	bee			
P7.16	Flame re Marking:	tarded plastic parts >25g in covers / housings are marked according ISO 1043-4: <i>FR(40)</i>	\boxtimes			
P7.17	Alt. 1 Chemica TBBPA (I specifications of flame retardants in printed circuit boards >25g (without components): additive) , TBBPA (reactive), Other; chemical name: , CAS #:				
	ISO 1043	l specifications of flame retardants in printed circuit boards (without components) >25g according 3-4:				
P7.18	concentr	etarded plastic parts >25g contain the following flame retardant substances/preparations ations above 0.1%:	in 🗌			
	1. Chem 2. Chem 3. Chem Alt. 2	ent: No legal limits exist, this is a market requirement. ical name: , CAS #: ical name: , CAS #: ical name: , CAS #: I specifications of flame retardants in plastic parts >25g according ISO 1043-4:	_			
P7.19		arts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, 6, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)				
P7.20	Of total p	lastic parts' weight >25g, recycled material content is %.				
P7.21		lastic parts' weight >25g, biobased material content is %.				
P7.22		rces are free from mercury y is used specify: Number of lamps: and max. mercury content per lamp: mg	\boxtimes			
P8	Batterie					
P8.1*		hemical composition: Lithium Manganese Dioxide, LiMnO2				
P8.2	Batteries	meet the requirements of the following voluntary program/s:				

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Issue date * 10/26/2010 Logo EVM \ DE	Model number *	C925de		
	Issue date *	10/26/2010	Logo	LEXMARK

ltem P9			quirements (con	linueuj		Requirement	tmet
P9						Yes No	n.a.
-	Energy consum						
9.1	For the product	the following power levels	or energy consump	otions are reporte	ed:		
Energy mo	ode *	Power level at 100 V AC	Power level at 115 V AC	Power level 230 V AC	at	Reference / Standard for energy modes and test method *	
Printing		W	590.2 W	549.8 W		Corporate Standard	
Ready Mo	de	W	103.7 W	96 W		Energy Star TEC Test Procedure	
Sleep Mod	de	W	10.5 W	11.6 W		Energy Star TEC Test Procedure	
Hibernate	Mode	W	3.08 W	4.09 W		IEC 62301	
Off Mode		W	0.01 W	0.03 W		IEC 62301	
		W	W	W			
EPS No-lo	ad	W	W	W			
charger plu	oower supply / ugged in the wall disconnected from :t.)	1					
PTEC * Typical En	ergy Consumptior	W I	W	W			
TEC * Typical En	ergy Consumptior	kWh/week	5.409 kWh/week	5.705 kWh/wee	ək	Energy Star TEC Test Procedure	
Etec * Annual Ene	ergy Consumptior	kWh/year	kWh/year	kWh/yea	ar		
Display res	solution* :	Megapixels	•	•			\square
Print Speed * : 31 Images per minute Corporate Standard		Corporate Standard					
Default tim	e to enter enerav	save mode: 5 minutes					
P9.2*		ut the energy save functio	n is provided with th	ne product.			╵┝╴
P9.3*	ENERGY STAR	ets the energy requiremen version: 1.1 Tier: Blue Angel (RAL UZ 122	Product category		n/s:		
P10	Emissions		, 				
		- Declared according to	ISO 9296				
P10.1	Mode	Mode description		Declared A-weighted sound power		Declared A-weighted sound pressure level $L_{p\rm Am}$ (dB)	
				level L_{WAd} (B)		rator position Bystander positions Desktop Image: Complexity of the state of	
	Idle	* Ready		* 5.6		38	
	Operation	* Duplex Mono Printing		* 7.1	55		
	Other mode	Simplex Mono Printil	Printing, Normal 6.9 53		53		
	Measured accor	ding to: 🔀 ISO7779 🗌		by FCMA-74 with	hl	n measurement distance m)	
P10.2	The product me	ets the acoustic noise req					

Model num	nber *	C925de						
Issue date *		10/26/2010	Logo	LEXM	RK			
Product e	Require	ment	met					
Item				Yes	No	n.a.		
	Chemica	al emissions from printing products						
P10.3*		formed according to ECMA-328 (ISO/IEC 28360) standard 🗌, other specify: RAL	-UZ-122	\square				
P10.4	Typical e	emission rate (print phase) is (mg/h):						
		Dust 1.2 Ozone BQL Styrene 1.6 Benzene BQL TVOC 13						
P10.5	Chemical emission requirements of the following voluntary program/s RAL-UZ-122 are met for :							
	Dust 🛛 Ozone 🖾 Styrene 🖾 Benzene 🖾 TVOC 🖾							
D 40.0		nagnetic emissions						
P10.6	program/	er display meets the requirement for low frequency electromagnetic fields of the fol /s:	owing voluntary			\bowtie		
P11		able materials for printing products						
P11.1*	A Safety	Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ	uired (see P4.3).	\square				
P11.2*	Paper co EN1228	ontaining post-consumer recycled fibers can be used, provided that it meets t 1.	he requirements	of 🔀				
P11.3*	2-sided (duplex) printing/copying is an integrated product function.		\boxtimes				
P12		nics for computing products						
P12.1*	The disp	lay meets the ergonomic requirements of ISO 9241-307 for visual display technolo	gies.			\mathbb{X}		
P12.2*	The phys	sical input device meets the requirements of ISO 9995 and ISO 9241-410.				\times		
P13		ng and documentation						
P13.1*		packaging material type(s): <i>Wood</i> weight (kg): 8.314						
		packaging material type(s): <i>Corrugated</i> weight (kg): 7.846						
	Product	packaging material type(s): <i>Expanded Polystyrene (EPS)</i> weight (kg): <i>0.443</i> nsity Polyethylene (LDPE) = 0.127 kg						
P13.2*	Product	plastic packaging is free from PVC.		\square				
P13.3*		nedia for user and product documentation (tick box):				H		
1 1010	Electronic , Paper , Other							
P13.4*		er user and product documentation, please specify contained percentage of post-co	onsumer recycled	k				
	fiber: 0%							
P14	Addition	al information (See Note B4)						
P1.1	This product uses RoHS exemptions for lead used in small amounts for specific applications.							
P2.1	The battery contained within this product should be disposed of properly with the product. The product is properly labeled with the WEEE disposal symbol and instructions for such disposal is listed in the product User's Guide.							
P2.3	The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers.							
P9.1	31 pages per minute A4; 30 pages per minute Letter							
P10.4	BQL = Below Quantifiable Limits - Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone – BQL; Styrene - 0.38 mg/hr; Benzene – BQL; Dust – BQL; and TVOC – 2.7 mg/hr BQL = Below Quantifiable Limits (Benzene < 0.03, Ozone < 0.06, Dust < 0.7)							
	Specific	nal company information and company environmental policy may be found as printer and supply item recycling information for your area may be found as k Sweden is connected to REPA and El-kretsen				It		

Annex B of ECMA-370 4th edition, June 2009

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19