



Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	
Contact information *	Nadia Martin (USA)	LEXMARK
Internet site *	www.lexmark.se/www.lexmark.com	
Additional information		

The company declares (ba	The company declares (based on product specification or test results based obtained from sample testing), that the product		
conforms to the statement	ts given in this declaration.		
Type of product *	Single Function Color Laser Printer		
Commercial name *	Lexmark CS736dn		
Model number *	CS736dn		
Issue date *	12/16/2011		
Intended market *	🛛 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 🗌 Other		
Additional information			

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Quality Control		
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).	\square	

Model number *		CS736dn				
Issue date * 12		12/16/2011	Logo	LEXM	ARK	
	Product environmental attributes - Legal requirements					t met
Item					No	n.a.
P1		bus substances and preparations				
P1.1*	Products do not contain lead max 0.1%, cadmium max 0.01%, mercury max 0.1%, hexavalent chromium max 0.1%, polybrominated biphenyls (PBB) max 0.1% and polybrominated diphenyl ethers (PBDE) max 0,1% (see legal reference and ^{Note 1}).					
P1.2*	Products	s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.		\boxtimes		
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),					
	hydrobro trichloroe	profluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrach ethane, methyl bromide (see legal reference). Comment: Legal reference has no m ration values.				
P1.4*		s do not contain polychlorinated biphenyl (PCB) max 0.005% by weight, polychlorin ax 0.005% by weight (see legal reference).	ated terphenyl	\boxtimes		
P1.5*	Products	s do not contain short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the 18% per mass of chlorine in the SCCP max 0.1% (see legal reference).	chain containing			
P1.6*	Textile a Tris-(azi	nd leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-pho ridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference nt: Legal reference has no maximum concentration values.				
P1.7*	Textile a	nd leather parts with direct skin contact do not contain Azo colorants that split arom 03% by weight (see legal reference and Note 1).	natic amines			
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference). Comment: Legal reference has no maximum concentration values.					
P1.9*	Parts wit microgra	h direct and prolonged skin contact do not release nickel in concentrations above (m/cm2/week (see legal reference). ht: Max limit in legal reference when tested according to EN1811:1998.).5			
P2	Batterie					
P2.1*	more that marked	duct contains a battery or an accumulator, it is labeled with the disposal symbol an an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lea with the chemical symbol for the metal concerned, Hg or Pb. Information on proper I in user manual. (See legal reference)	id, it shall be			
P2.2*		ells used in the product do not contain more than 2% by weight of mercury. Other b ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See le		\square		
P2.3*	Batteries design o	s and accumulators are easily removable by either users or service providers (as de f the product). Exception: Batteries that are permanently installed for safety, perfor ntegrity reasons do not have to be "easily removable". (See legal reference)	ependent on the			
P3		EMC connection to the telephone network and labeling				
P3.1*		duct complies with legally required safety standards as specified (see legal reference	;e).	\square		
P3.2*	The proc	duct complies with legally required standards for electromagnetic compatibility (see	legal reference).		Ħ	
P3.3*	If produc	t is intended for connection to a public telecom network or contains a radio transmi ally required standards for radio and telecommunication devices (see legal reference)	tter, it complies			
P3.4*		duct is labeled to show conformance with applicable legal requirements (see legal release)				
P4		nable materials	/-			
P4.1*	If a phote	o conductor (drum, belt etc.) is used in the product, it does not contain cadmium ma erence and Note 1).	ax 0.01% (see			
P4.2*	If ink/ton	er is used in the product, it does not contain cadmium max 0.1% by weight (see leg	al reference).	\boxtimes		
P4.3*	If the ink product/	/toner formulation/preparation is classified as hazardous according to applicable re packaging is adequately labeled and a Safety Data Sheet (SDS/MSDS) in accordance to the second structure of the s	gulations, the			
P5		packaging				
P5.1*	Packagir	ng and packaging components do not contain lead, mercury, cadmium and hexaval 1% by weight of these together.	ent chromium			
P5.2*		ackaging material is marked according to ISO 11469 referring ISO 1043 (see legal	reference).	\boxtimes		
P5.3*	Protocol	duct packaging material is free from ozone depleting substances as specified in the (see legal reference). nt: Legal reference has no maximum concentration values.	Montreal			
	0011110	Lega relevance has no maximum concontration values.				

Note 1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model n		CS736dn			_
Issue da	te *	12/16/2011 Logo	LEXM	ARK	ŭ
Brodu	ot onviro	nmental attributes. Market requirements. Environmental conscious design	Poquir	mont	mot
Item		nmental attributes - Market requirements - Environmental conscious design tory to fill in. Additional information regarding each item may be found under P14.	Require Yes	No	
P6		nt information	Tes	INU	n.a.
P6.1*		on for recyclers/treatment facilities is available (see legal reference).			
P7	Design				
		mbly, recycling			
P7.1*	Parts that	t have to be treated separately are easily separable	\boxtimes		
P7.2*	Plastic m	aterials in covers/housing have no surface coating.			
P7.3*	Plastic p	arts >100g consist of one material or of easily separable materials.			Ē
P7.4*	Plastic p	arts >25g have material codes according to ISO 11469 referring ISO 1043.		Ħ	Ħ
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly available tools.		\exists	H
P7.6*		re easily separable. (This requirement does not apply to safety/regulatory labels).		-	⊢⊢
17.0	Product				
P7.7*		g can be done e.g. with processor, memory, cards or drives			
P7.8*		g can be done using commonly available tools		╞	╞
P7.9.		rts are available after end of production for: 5 years			⊢⊢
P7.9. P7.10		s available after end of production for: 5 years			<u> </u>
P7.10					
P7.11*		and substance requirements cover/housing material type:			
P7.11		type: ABS Material type: HIPS Material type: PC/AE	15		
P7.12		cable insulation material of power cables are halogen free (including PVC). (See Note 1)		\boxtimes	
P7.13		cable insulation material of signal cables are halogen free (including PVC). (See Note 1)			⊢⊢
P7.14					⊢⊢
P7.14					⊢⊢
-	All printed circuit boards (without components) >25g are halogen free. (See Note 2)				<u> </u>
P7.16	Marking:	tarded plastic parts >25g in covers / housings are marked according ISO 1043-4: <i>FR(40)</i>			
P7.17		I specifications of flame retardants in printed circuit boards >25g (without components):			
	TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #:			
	Alt. 2			_	_
		I specifications of flame retardants in printed circuit boards (without components) >25g according 3-4: FR(16)			
P7.18	Alt. 1	tarded plastic parts >25g contain the following flame retardant substances/preparations in			
		ations above 0.1%:			
	Commer	t: No legal limits exist, this is a market requirement.			
		cal name: , CAS #: cal name: , CAS #:			
		cal name: , CAS #:			
	o. onom				
	Alt. 2		\bowtie		
		I specifications of flame retardants in plastic parts >25g according ISO 1043-4:	_	_	
P7.19		FR(17), FR(16), FR(50) lastic parts' weight >25g, recycled material content is %.			
P7.19 P7.20		lastic parts' weight >25g, recycled material content is %.			
P7.20		rices are free from mercury	\square		
		y is used specify: Number of lamps: and max. mercury content per lamp: mg			
P8	Batterie	5			
P8.1*	Battery of	hemical composition: Lithium Manganese Dioxide (LiMnO2)			
P8.2	Batteries	meet the requirements of the following voluntary program/s:			Π

Note 1 For cables, covers & housing plastic parts and plastic packaging materials in this standard; halogens include fluorine, chlorine, bromine, and iodine.

Note 2 In accordance with JPCA-ES-01; printed wiring boards must not contain more than 0.09% by weight (900ppm) of chlorine or bromine.

Model number *	CS736dn		
Issue date *	12/16/2011	Logo	Lexm ^a rk"

Produc	ct environmental a	ttributes - Marke	t requirements (continued)		Requirem	nent	met
Item			•			Yes	No	n.a.
P9	Energy consumpt							
9.1	For the product the	following power leve	ls or energy consur	<u>nptions have beer</u>	<u>measured:</u>			
Energy	mode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Sta and test method	ndard for energy mod *	es	
Printing	1	525 W	521.9 W	502.3 W	Company Stan	dard		
Ready		42.5 W	42.3 W	42.9 W	Energy Star TE	C		
Sleep		15.25 W	15 W	15.81 W	Energy Star TE			H
Off		0 W	0 W	0 W	Energy Star TE			H
•		W	W	w				⊢⊢
		W	W	W				
charger	al power supply / plugged in the wall ut disconnected from	W	W	W				
PTEC * Typical	Energy Consumption	W	W	W				
TEC * Typical	Energy Consumption	4.67 kWh/week	4.62 kWh/week	4.69 kWh/wee	k			
Default 1	time to enter energy s	ave mode: 30 minute	es					
P9.2*		ne energy save funct		the product.		\square		H
P9.3*	The product meets ENERGY STAR® v Others specify:	the energy requirem version 1.0 Tier:1	ents of the following	y voluntary prograr	n/s:			
P10	Emissions							
	Noise emission –	Declared according t	o ISO 9296					
P10.1	Mode N	lode description		Declared A-weighted		A-weighted		
				sound power	sound pressure	e level $L_{p{\sf Am}}$ (dB)		
				level L_{WAd} (B)	Operator position	Bystander positions		
				Write -	Desktop	(only if product is		
					or Desk side	operator attend	uea)	
	Idle *	Idle/Ready		* 4.9		33		
	Operation *	Duplex Monochron	ne Printing	* 6.9		55		
	Other mode	Simplex Monochro	me Printing	6.9		54]
	Measured accordin	g to: 🔀 ISO7779 🗌 Other	_	d by ECMA-74 wit	th L _{pAm} measurement di	stance m)		
P10.2	The product meets	the acoustic noise re			program/s: RAL-UZ-12			
	Chemical emissions from printing products							
P10.3*		ording to ECMA-328		tandard 🔲, other	specify: RAL-UZ-122			
P10.4	••	te (print phase) is (m						
D40.5		Dust BQL Ozone		Benzene BQL				
P10.5	Cnemical emission	requirements of the	following voluntary Dust 🔀	program/s RAL-U Ozon		\boxtimes		
			Benzene	TVO				
	Electromagnetic emissions							
P10.6	Computer display n		t for low frequency	electromagnetic fi	elds of the following vol	untary		\square
	program/s:						_	_

Model n		CS736dn			_		
Issue date * 12/16/2011		12/16/2011	Logo		LEXM	RK	
Produc	Product environmental attributes - Market requirements (continued) Requirement me						
Item							
P11	Consum	able materials for printing products					
P11.1*		Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ	uired (see	P4.3).			
P11.2*	EN1228		luirements	of	\bowtie		
P11.3*	2-sided (duplex) printing/copying is an integrated product function.			\square		
P12	Ergonor	nics for computing products					
P11.1*	A Safety	Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ	ired (see	P4.3).	\boxtimes		
P12.1*	The disp	lay meets the ergonomic requirements of ISO 9241-307 for visual display technolo	gies.				\boxtimes
P12.2*	The phys	sical input device meets the requirements of ISO 9995 and ISO 9241-410.					\boxtimes
P13		ng and documentation					
P13.1*	Product Product	packaging material type(s): <i>Corrugated</i> weight (kg): <i>3.601 kg</i> packaging material type(s): <i>Polyethylene Foam</i> weight (kg): <i>0.673 kg</i> packaging material type(s): <i>High Density Polyethylene (HDPE)</i> weight (kg): <i>0.16</i>	5 kg				
P13.2*	Product	plastic packaging is halogen free (including PVC). (See Note 1)			\square		
P13.3*	Specify r Electroni	nedia for user and product documentation (tick box): c					
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber. 0%						
P14	Addition	al information					
P1.1		duct uses RoHS exemptions for lead used in small amounts for specific app					
P2.1	The battery contained within this product should be disposed of properly with the product. The product is properly labeled with the WEEE disposal symbol and instructions for such disposal is listed in the product User's Guide.						
P.2.3	The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers.						•
P.10.4	BQL = Below Quantifiable Limits - Note: The data reported is for the color print test. Mono print test results: Ozone – BQL; Styrene - 0.14 mg/hr; Benzene – BQL; Dust – BQL; and TVOC – 0.80 mg/hr						
	Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle Lexmark Sweden is connected to REPA and El-kretsen						

NOTE

Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Note 1 For cables, covers & housing plastic parts and plastic packaging materials in this standard; halogens include fluorine, chlorine, bromine, and iodine.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
76/769/EEC (Marketing and Use Directive)	P1.6, P1.8, P4.2
amendment 89/677/EEC	P1.4
amendment 1999/77/EC	P1.2
amendment 2003/3/EC	P1.7
amendment 94/27/EEC	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P4.2
1999/45/EC (Dangerous Preparations Directive)	P4.3
2001/58/EC (Directive on Safety Data Sheets)	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1