

Ecma/TC38-TG3/2015/025 (Rev. 1 – 15 April 2015)

Annex B1 - Product environmental attributes Imaging equipment

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

| Brand * | Lexmark | Logo |
|---|---|-----------|
| Company name * | Lexmark International, Inc. | |
| Contact information * e-mail address | Drew Zande Lexmark International 740 West New Circle Road, Bldg. 1 Lexington, KY 40550 dzande@lexmark.com | 🚺 Lexmark |
| Internet site * | www.lexmark.com/TED and csr.lexmark.com | |
| Additional information | | |

| The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration. | | | | | |
|--|--|--|--|--|--|
| Type of product * | Multi-function color laser device | | | | |
| Commercial name * | Lexmark CX924dte, Lexmark CX924dxe, Lexmark XC9265 | | | | |
| Model number * | CX924dte, CX924dxe, XC9265 | | | | |
| Issue date * | September 12, 2017 | | | | |
| Intended market * | 🛛 Global 📃 Europe 🔄 Asia, Pacific & Japan 🗌 Americas 🗌 Other | | | | |
| Additional information | | | | | |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B1

Annex B1 reflects Product environmental attributes relevant for Imaging products. The following items from the ECMA-370 Main body are not shown in the template:

P9.1 PTEC, ETEC and display resolution P12.1-P12.2 Ergonomic requirements.

| Model n | umber * | CX924dte, CX924db | ke, XC9265 | Logo | | | | TM | |
|--------------------|--|--|--|------------------|--------|-------------|---------|------|--|
| Issue date * | | September 12, 2017 | , | | | | Lexmark | | |
| Produc | t environ | mental attributes - | Legal requirements | | Re | quire | ment | met | |
| Item | | | | | | Yes | No | n.a. | |
| P1 | | us substances and p | • | | | | | | |
| P1.1* | | | urrent European RoHS Directive. (See legal reference and | d NOTE B1) | | \bowtie | | | |
| P1.2* | Comme | nt: Legal reference has | tos (see legal reference). s no maximum concentration value. | | | \square | | | |
| P1.3* | Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values. | | | | | | | | |
| P1.4* | | | han; 0,005% polychlorinated biphenyl (PCB), 0,005% pol s (see legal reference). | lychlorinated | | \boxtimes | | | |
| P1.5* | Products | do not contain more t | han 0,1% short chain chloroparaffins (SCCP) with 10-13 per mass of chlorine in the SCCP (see legal reference). | carbon atoms | in the | \square | | | |
| P1.6* | Parts wit (see lega | h direct and prolonged al reference). | I skin contact do not release nickel in concentrations above ference when tested according to EN1811:2011-5. | ve 0,5 μg/cm²/ | week | | | | |
| P1.7* | REACH REACH | Article 33 information a Program Manager, H | about substances in articles is available at (add URL or m IOD9237, 740 West New Circle Rd., Lexington, KY 405 | | | | | | |
| P2 | Batterie | - | | | | | | | |
| P2.1* | symbol. | Information on proper | y or an accumulator, the battery/accumulator is labeled w disposal is provided in user manual. (See legal reference |) | | | | | |
| P2.2* | Batteries referenc | | ot contain more than 0,0005% of mercury or 0,002% of c | admium. (See | legal | \boxtimes | | | |
| P2.3* | Batteries | and accumulators are | e readily removable. (See legal reference) | | | \times | | | |
| P3 | Conform | nity verification & Eco | o design (ErP) | | | | | | |
| P3.1* | The Dec | laration of Conformity | how conformance with applicable legal requirements (see can be requested at (add link or e-mail address): | - | ce). | \square | | | |
| | http://w conforn | ww.lexmark.com/en_ nity.html | us/about/regulatory-compliance/european-union-dec | laration-of- | | | | | |
| P3.2* | | luct complies with the al reference). | Eco design requirements for energy-related products, | | | \square | | | |
| | | information is; | given in item P15 or added to this document, | | | \boxtimes | | | |
| | • | · | available at (add URL): <u>http://csr.lexmark.com/eu</u> | regulations.s | html | _ | | | |
| P4 | Consun | able materials | | | | | | | |
| P4.1* | | o conductor (drum, bel erence and NOTE B1). | t etc.) is used in the product, it does not contain cadmium | n max 0,01% (s | see | \boxtimes | | | |
| P4.2* | | | ct, it does not contain cadmium max 0,1% by weight (see | e legal referenc | ;e). | \square | | | |
| P4.3* | are Com applicab | munity workplace expo | paration is classified as hazardous or contains a substance osure limits, the product/packaging is adequately labeled afety Data Sheet (SDS) in accordance with these requirer | according to | | | | | |
| P5 | Product | packaging | | | | | | | |
| P5.1* | | ng and packaging co ant chromium by weigh | mponents do not contain more than 0,01% lead, mer it of these together. | cury, cadmiur | n and | \square | | | |
| P5.2* | The pac used (se | kaging materials are m e legal reference). | narked with abbreviations and numbers indicating the natu | | . , | \square | | | |
| P5.3* | The pro Protocol Comme | The product packaging material is free from ozone depleting substances as specified in the Montreal X . Comment: Legal reference). | | | | | | | |
| | | | | | | | | | |
| P6 P6.1* | | nt information | ent facilities is available (see legal reference). | | | | | | |

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

| Model n | umber * | CX924dte, CX924dxe, XC9265 Log | | | | TM |
|----------|---|---|-------------|-------------------------|-------------|-------------|
| Issue da | ate * | September 12, 2017 | | Le | xmo | ark |
| | | mental attributes - Market requirements (See General NOTE GN below) nental conscious design | Re | quire | ment ı | net |
| Item | | tory to fill in. Additional information regarding each item may be found under P14. | | Yes | No r | n.a. |
| P7 | Design | mbly requeling | | | | |
| P7.1* | | nbly, recycling t have to be treated separately are easily separable | | \boxtimes | | |
| P7.2* | | aterials in covers/housing have no surface coating. | | $\overline{\mathbb{X}}$ | <u>+</u> | <u> </u> |
| P7.3* | | arts > 100 g consist of one material or of easily separable materials. | | $\overline{\boxtimes}$ | <u>+</u> | <u> </u> |
| P7.4* | | arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. | | <u> </u> | <u> </u> | <u> </u> |
| P7.5 | | arts are free from metal inlays or have inlays that can be removed with commonly available | la taola | | <u> </u> | <u> </u> |
| P7.6* | | re easily separable. (This requirement does not apply to safety/regulatory labels). | | | <u> </u> | <u> </u> |
| P7.0 | | | | | | |
| P7.7* | Product | g can be done e.g. with processor, memory, cards or drives | | \boxtimes | | |
| P7.8* | | g can be done using commonly available tools | | $\overline{\boxtimes}$ | + | <u>-</u> - |
| P7.9. | | rts are available after end of production for: 5 years | | | | <u> </u> |
| P7.10 | | s available after end of production for: 5 years | | | | <u> </u> |
| P7.10 | | and substance requirements | | | | |
| P7.11* | | cover/housing material type (e.g. plastics, metal, aluminum): | | | | |
| | Material | type: PC+PET Material type: PC+ABS Material type: | | | | |
| P7.12 | Insulation | materials of external electrical cables are PVC free. | | Π | \boxtimes | |
| P7.13 | Insulation | n materials of internal electrical cables are PVC free. | | Ē | | |
| P7.14 | weight (1 polyvinyl | plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine 000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retard chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorin | dants, and | | | |
| P7.15 | Printed of | g more than 25% post-consumer recycled content. circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g as defined in IEC 61249-2-21. (See NOTE B2) | are low | | | |
| P7.16 | Flame re | tarded plastic parts > 25 g in covers / housings are marked according ISO Marking: FR40 | | \boxtimes | | |
| P7.17 | TBBPA (| emical specifications of flame retardants in printed circuit boards > 25 g (without compon- additive) , TBBPA (reactive) (See NOTE B3), Other; chemical name: , CAS | S #: | | | |
| | | emical specifications of flame retardants in printed circuit boards (without components) > g ISO 1043-4: <i>FR17</i> | > 25 g | \boxtimes | | |
| P7.18 | <u>Alt. 1:</u> Fl concentr 1. Chemi 2. Chemi | ame retarded plastic parts > 25 g contain the following flame retardant substances/prepa ations above 0,1%: cal name: , CAS #: (See NOTE B4) cal name: , CAS #: " | arations in | | | |
| | <u>Alt. 2:</u> Cl | cal name: , CAS #: " nemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: R17, FR40, FR30+40 | | \boxtimes | | |
| P7.19 | In plastic assigned | parts > 25 g, flame retardant substances/preparations above 0,1% are used which have the following Risk phrases; and Hazard statements: | | | | |
| P7.20* | | ce(s) for these classifications is/are found at (add URL(s)): , (See NOTE umer recycled plastic material content is used in the product (See NOTE B6): | 00) | | | |
| , 7.20 | lf YES; a a) Of t | t least one of the two alternatives below shall be answered; table parts' weight > 25 g, the postconsumer recycled plastic material content (calculater centage of total plastic by weight) is <i>Up to 40</i> %. | ulated as a | | | |
| | b) The | weight of recycled material is g. | | | | |

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

| Model nu | mber * | CX924dte | , CX924dxe, XC9265 | | | Logo | | . 174 | |
|-----------------------------------|---|---------------|---|---------------------------------|--|------------------------------|--------------|--------------|--|
| Issue date | ssue date * September 12, 2017 | | | | | | 🚺 Lex | mark | |
| Product | Product environmental attributes - Market requirements (continued) Requirement m | | | | | | | | |
| Item | | | | | | | Yes | No n.a | |
| | Material | and subst | ance requirements (| continued) | | | | | |
| P7.21* | | | terial content is used | | | | \bowtie | | |
| | If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is .002%. | | | | | | | | |
| | or b) The | e weight of t | he biobased plastic m | aterial is g. | | | | | |
| P7.22* | | | ee from mercury, i.e. lo pecify: Number of lam | | ip. mum mercury content pe | er lamp: | mg | | |
| P8 | Batterie | S | | | | | | | |
| P8.1* | Battery of | chemical co | mposition: <i>Lithium M</i> | anganese Dioxide | (LiMnO2) | | | | |
| P9 | Energy | consumpti | on (See NOTE B8) | | | | | | |
| P9.1 | For the | product the | following power levels | or energy consump | otions are reported: | | | | |
| Energy mo | ode * | | Power level at 100 V AC | Power level at 115 V AC | Power level at 230 V AC | Reference/Si modes and te | | nergy | |
| Sleep moo STAR® O (OM) prod | perational | | W | W | W | | | | |
| Standby/o ENERGY Mode (ON | ff mode fo STAR Ope | erational | W | W | W | | | | |
| | for ENER | GY STAR | 5.0 kWh/week | 5.0 kWh/week | 4.7 kWh/week | Energy Star | I E V2.0 | | |
| (TEC= Typ | bical Energ | ду | | | | | | | |
| Printing | | | 1217 W | 1148 W | 1130 W | Corporate S | tandard | | |
| Ready Mo | ode 1 | | 189 W | 200 W | 183 W | Energy Star | I E V2.0 | | |
| Ready Mo | ode 2 | | NA W | NA W | NA W | Energy Star | I E V2.0 | | |
| Sleep | | | 2.8 W | 2.72 W | 2.67 W Energy S | | I E V2.0 | | |
| Hibernate | • | | 0.17 W | 0.16 W | 0.17 W | IEC 62301 | | | |
| Off | | | 0.016 W | 0.021 W | 0.041 W | IEC 62301 | | | |
| External P | ower Sup | ply Efficienc | cy Level (International Efficiency Marking Protocol) *: | | | | | \mathbf{X} | |
| Print/Scan | Speed * | : | 65 images per minute | | | ISO 24734 | | | |
| Default tim | ne to enter | energy sav | ve mode: 1 minutes | | | Energy Star | 1 E V2.0 | | |
| P9.2* | | | | | | | | | |
| P10 | Emissic | | | | | | | | |
| | 1 | | Declared according to | | | | | | |
| P10.1 | Mode | м | ode description | | Statistical upper limit A-v L _{WA,c} (B) | veighted sound | power level, | | |
| | Idle | * | ldle / Ready | | *4.5 | | | | |
| | Operatio | | Duplex Monochrome | _ | * 7.1 | | | | |
| | Other m | | Simple Monochrome | | 6.9 | | | | |
| | Measure | ed according | g to: 🔀 ISO 7779 🔀 | ECMA-74 (only if not covered | by ECMA-74) | | | | |

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic.

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

| modernu | mber * | CX924dte, CX924 | dxe, XC9265 | | Logo | A | | TM |
|--------------|---|---|--|-----------------------|--|-------------|------|------|
| Issue date | e * | September 12, 20 | 17 | | | Lex | ma | rk |
| Product | environ | mental attributes | s - Market requirements (co | ntinued) | | Require | ment | me |
| Item | | | | | | Yes | No | n.a |
| P10.2* | | | printing products (See NOTE o ECMA-328 Determination of C | | Potos from | | | |
| F 10.2 | | nic Equipment (ISO) | | | | \boxtimes | | |
| P10.3 | | | ation phase) is (mg/h): | | | | | |
| | Flectror | hotographic device | s: Ozone 0.04 Dust 2.57 | Styrene 0 | 426 Benzene 0.008 | | | |
| | TVOC | | | otyrene v. | | | | Н |
| | Ink devi | ces: | Dust | Styrene | Benzene TVOC | | | |
| | Note: co | ompliance with max | mum emission rates in eco label | s to be declared in | P14 | | | |
| P11 | | | r printing products | | | | | |
| P11.1* | | | is available for the ink/toner pre | paration, even if not | t legally required (see P4.3) | . 🛛 | | |
| P11.2* | Paper o EN 122 | | sumer recycled fibers can be u | used, provided that | t it meets the requirement | | | |
| P11.3* | 2-sided | (duplex) printing/co | pying is an integrated product fu | nction. | | \boxtimes | | |
| P11.4* | | | end-user with default auto-duple | x enabled. | | \square | | |
| P13 | | ing and document | | | | | | |
| P13.1* | Product Product Wood | packaging materia | type(s): Corrugated weight (H type(s): Plastic - PE type(s): Expanded Poylstyren | weight (kg): 0.295 | ; (kg): 1.61 | | | |
| P13.2* | | | kaging is free from PVC. | | | \boxtimes | | |
| P13.3* | For pro consum | duct primary corrug | gated fiberboard packaging, spe ontent: Recycled content > | | percentage of minimum p | ost- | | |
| P13.4* | Specify media for user and product documentation (tick box): | | | | | | | |
| P13.5 | Úser an | | item if paper documentation used tation on paper media is chlorine | | | \boxtimes | | |
| | Totally of | chlorine-free | | | | \boxtimes | | |
| | | tal chlorine-free | | | | | | |
| | | sed chlorine-free | | | | | | |
| P14 P14.1 | | ary programs: | irements of the following volunta | | | | | |
| F14.1 | • | • | Ũ | | | | | |
| | Eco-lab | GY STAR® el: Blue Angel | Criteria version: 2.0 2014 Criteria version: RAL-U Jan. 2017 | Z 205 Date: | Product category: Image Product category: Office printing function | | | |
| D46 | Eco-lab | | Criteria version: | Date: | Product category: | | | |
| P15 | P2.1 - 1 | | ee NOTE BIT) ed within this product should WEEE disposal symbol and in | | | | | uide |
| | P2.3 - The battery contained within this product meets the exception listed. The battery is not intended to be removed by | | | | | | | |
| | the customer; however, is designed for easy removal by recyclers and service providers. | | | | | | | |
| | P5.2 - The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s) used when | | | | | | | 11 |
| | they are >25g | | | | | | | |
| | P7.14 - A small amount of bromine may be present in covers due to sourcing post-consumer recycled content. No bromine was | | | | | | | |
| | intentionally added in the processing of these parts. | | | | | | | |
| | P7.20 - Per IEEE 1680.2 PCR calculation | | | | | | | |
| | | Color values above Packaging weights | , monochrome values are n/a for model CX921de | | | | | |

NOTE B10 A Guidance document on Chemical Emissions is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B11 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B1

| Reference | Declaration item |
|--|------------------------------|
| Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications. | P1.1, P4.1 |
| (EC) 1907/2006(REACH, Annex XVII | P1.2, P1.4, P1.6, P1.7, P4.2 |
| Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000, (Marketing and use of Ozone layer depleting substances) | P1.3, 5.3 |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002 | P1.5 |
| "REACH" Regulation (1907/2006), annex VII | P1.10 |
| Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator. | P2.1, P2.2, P2,3, P8.1 |
| Directive 2006/95/EC (Low Voltage Directive) | P3.1 |
| Directive 2004/108/EC (EMC Directive) | P3.1 |
| Directive 1999/5/EC (R&TTE Directive) | P3.1 |
| Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions | P3.1, P3.2 |
| Regulation (EC) 1907/2006 (REACH Regulation), Article 31, annex II) | P4.3 |
| Regulation (EC) 1272/2008 (CLP Regulation) | P4.3, P7.19 |
| Directive 2004/12/EC (Packaging Directive) | P5.1 |
| Decision 97/129/EC (Secondary packaging legislation) | P5.2 |
| Directive 2012/19/EU (WEEE directive) | P6.1 |