

## Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	
Contact information *	Nadia Martin (USA)	
Internet site *	www.lexmark.se / www.lexmark.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	ype of product * Multi-function Color Inkjet Printer			
Commercial name *	exmark Intuition S505, Lexmark Intuition S508			
Model number *	S505, S508			
Issue date *	8/25/2009			
Intended market *	tended market * 🛛 🖾 Global 🗌 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality Control			Requirement met		
Item		Yes	No		
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	$\boxtimes$			
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀			

Model number *		S505, S508					
Issue date *		8/25/2009 Logo	<b>EXM</b>	ARF	K.		
Dueslass							
Item		mental attributes - Legal requirements R	Require Yes	No No	n.a.		
P1	Hazardous substances and preparations				n.a.		
P1.1*	Products	$\square$					
	0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal						
P1.2*		e and Note B1) s do not contain Asbestos (see legal reference).					
P1.2		nt: Legal reference has no maximum concentration value.	$\boxtimes$				
P1.3*	Products	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),	$\boxtimes$				
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-						
		ethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum ration values.					
P1.4*		s do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated	$\boxtimes$				
		<i>I</i> (PCT) in preparations (see legal reference).					
P1.5*		s do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the	$\boxtimes$				
P1.6*	chain co	ntaining at least 48% per mass of chlorine in the SCCP (see legal reference). Ind leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS),					
P1.0		ridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference).			$\boxtimes$		
		nt: Legal reference has no maximum concentration values.					
P1.7*		nd leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split			$\boxtimes$		
P1.8*	aromatic	amines. (See legal reference and Note B1) parts do not contain arsenic and chromium as a wood preservation treatment as well as					
P1.0		orophenol and derivatives (see legal reference).			$\boxtimes$		
	Comme	nt: Legal reference has no maximum concentration values.					
P1.9*		th direct and prolonged skin contact do not release nickel in concentrations above 0.5	$\boxtimes$				
		am/cm <sup>2</sup> /week (see legal reference).					
P1.10*		nt: Max limit in legal reference when tested according to EN1811:1998. Article 33 information about substances in articles is available at (add URL or mail contact):	$\boxtimes$				
1 1.10		Program Manager, 508761x, 740 W. New Circle Rd., Lexington, KY 40550					
P2	Batterie	S					
P2.1*		oduct contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains	$\boxtimes$				
	more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is						
		l in user manual. (See legal reference)					
P2.2*		ells used in the product do not contain more than 2% by weight of mercury. Other batteries or	$\square$				
		ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)					
P2.3*		s and accumulators are easily removable by either users or service providers (as dependent on the	$\boxtimes$				
		f the product). Exception: Batteries that are permanently installed for safety, performance, medical ntegrity reasons do not have to be "easily removable". (See legal reference)					
P3		EMC connection to the telephone network and labeling					
P3.1*	The prod	duct complies with legally required safety standards as specified (see legal reference).	$\boxtimes$				
P3.2*	The proc	duct complies with legally required standards for electromagnetic compatibility (see legal reference).	$\boxtimes$				
P3.3*		t is intended for connection to a public telecom network or contains a radio transmitter, it complies	$\square$				
		ally required standards for radio and telecommunication devices (see legal reference).		_			
P3.4*		duct is labeled to show conformance with applicable legal requirements (see legal reference).					
P4.1*		nable materials o conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see					
F4.1		erence and Note B1).	$\boxtimes$				
P4.2*		er is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	$\boxtimes$				
P4.3*	If the ink	/toner formulation/preparation is classified as hazardous according to applicable regulations, the					
	product/	packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these	لالسع				
D5		nents is available (see legal reference).	·				
P5.1*		packaging components do not contain more than 0.01% lead, mercury, cadmium and					
		ent chromium by weight of these together.					
P5.2*		ackaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	$\boxtimes$				
P5.3*		duct packaging material is free from ozone depleting substances as specified in the Montreal	$\overline{\times}$				
		(see legal reference).					
	Comme	nt: Legal reference has no maximum concentration values.					

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *		S505, S508					
Issue date *		8/25/2009 Logo	LE	XM	ARI	<	
					<u></u>		
Product	Product environmental attributes - Market requirements - Environmental conscious design Requirement met						
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.						
P6	*=mandatory to fill in. Additional information regarding each item may be found under P14. Yes No n.a. Treatment information						
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).						
P7	Design Disassembly, recycling						
P7.1*	Parts that have to be treated separately are easily separable						
P7.2*	Plastic materials in covers/housing have no surface coating.						
P7.3*							
					⊢⊢	<u> </u>	
P7.4*		arts >25g have material codes according to ISO 11469 referring ISO 1043.	<u> </u>		<u> </u>	<u> </u>	
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly available too	ils.	$\square$			
P7.6*	Labels a	re easily separable. (This requirement does not apply to safety/regulatory labels).		$\square$			
	Product						
P7.7*		ng can be done e.g. with processor, memory, cards or drives				$\boxtimes$	
P7.8*	Upgradir	ng can be done using commonly available tools				$\boxtimes$	
P7.9.	Spare pa	arts are available after end of production for: years					
P7.10		s available after end of production for: years				Ē	
		and substance requirements					
P7.11*		cover/housing material type:					
		type: ABS Material type: HIPS Material type:					
P7.12	Electrica	I cable insulation materials of power cables are PVC free.			$\times$		
P7.13	Electrica	I cable insulation materials of signal cables are PVC free		一			
P7.14		/housing plastic parts >25g are free from chlorine and bromine.			Ħ	H	
P7.15		ed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21.	(See	8		⊢⊢	
	Note B2		(000				
P7.16	Flame re Marking:	tarded plastic parts >25g in covers / housings are marked according ISO 1043-4:					
P7.17		additive) , TBBPA (reactive), Other; chemical name: , CAS #:					
	ISO 1043	Il specifications of flame retardants in printed circuit boards (without components) >25g accordi 3-4: <i>FR(16)</i>	ing				
P7.18	concentr	etarded plastic parts >25g contain the following flame retardant substances/preparatio ations above 0.1%: ent: No legal limits exist, this is a market requirement.	ns in				
	2. Chem	ical name: , CAS #: ical name: , CAS #: ical name: , CAS #:					
	_	Il specifications of flame retardants in plastic parts >25g according ISO 1043-4:					
P7.19	R40, R40	arts >25g are free from flame retardant substances/ preparations above 0.1% classified as R4 6, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	5,				
P7.20		plastic parts' weight >25g, recycled material content is %.					
P7.21		plastic parts' weight >25g, biobased material content is %.					
P7.22	If mercur	irces are free from mercury y is used specify: Number of lamps: and max. mercury content per lamp: mg					
P8	Batterie						
P8.1*	-	hemical composition: Lithium Manganese Dioxide (LiMnO2)					
P8.2	Batteries	meet the requirements of the following voluntary program/s:					

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model nur		S505, S50							
Issue date	9*	8/25/2009	)					1	
Product	environr	nental att	ributes - Market re	quirements (co	ntinued)		Requirement	met	
					n.a.				
P9		consumpti							
9.1	For the p	product the	following power levels	or energy consum	ptions are report	ed:			
Energy mode *		Power level at 100 V AC	Power level a 115 V AC	t Power level 230 V AC	at	Reference / Standard for energy modes and test method *			
Printing		W	W	17 W		Corporate Standard			
Copying			W	W	11 W		Corporate Standard		
Scanning			W	W	10 W		Corporate Standard		
Ready Mo	ode		6.84 W	6.79 W	7.05 W		Energy Star OM Test Procedure		
Sleep Mo	de		3.05 W	3.06 W	3.26 W		Energy Star OM Test Procedure		
Off Mode			0.25 W	0.25 W	0.30 W		IEC 62301		
EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)		W	0.1 W	Energy Efficiency of Single		Test Method for Calculating the Energy Efficiency of Single Voltage External AC-DC and AC-AC Power Supplies			
PTEC * Typical En		sumption	W	W	W				
TEC * Typical Energy Consumption		sumption	kWh/week	kWh/week	kWh/week				
ETEC * Annual En	ETEC * Annual Energy Consumption		kWh/year	kWh/year	kWh/year				
Display res	solution*	: Me	gapixels						
Print Spee	ed *	: 17 Mono	chrome / 11 Color Im	ages per minute					
•			ve mode: 60 minutes					╞	
P9.2*			e energy save functio	n is provided with t	he product.			╵┝┤	
P9.3*	The proc ENERG Others s	duct meets Y STAR® v specify:	the energy requirement ersion: <b>1.1</b> Tier:		voluntary program	n/s:			
P10	Emissic Noise e		Declared according to	ISO 9296					
P10.1	Mode		ode description	100 9290	Declared Decla		Declared A-weighted sound pressure level $L_{pAm}$ (dB)		
					level $L_{WAd}$ (B)		ator position       Bystander positions         Desktop       Image: Construction of the sector		
	Idle		Ready		* n.a.		n.a.		
			* 5.6	41					
	Other m		Simplex Mono Printi	-	6.2		46	-	
	Measure	ed according		ECMA-74 (only if not covered	by ECMA-74 wit	h L <sub>pAm</sub>	measurement distance m)		
P10.2	The proc	duct meets	the acoustic noise req	uirements of the fo	llowing voluntary	progra	im/s: <b>RAL-UZ-122</b>		

Model nu	mber *	S505, S508					
Issue date * 8/25/2009 Logo		Logo	LEXM	RK			
		I			TH		
Product	environr	nental attributes - Market requirements (continued)		Require	ment	met	
Item				Yes	No	n.a.	
	Chemic	al emissions from printing products					
P10.3*	Test per	formed according to ECMA-328 (ISO/IEC 28360) standard 🔲, other specify:			$\boxtimes$		
P10.4							
		Dust Ozone Styrene Benzene TVOC					
P10.5	Chemica	al emission requirements of the following voluntary program/s are met for :					
		Dust Ozone Styrene Benzene	TVOC				
		magnetic emissions					
P10.6		er display meets the requirement for low frequency electromagnetic fields of the fol	lowing voluntary			$\bowtie$	
P11	program	vs: nable materials for printing products		·			
P11.1*		/ Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ	uired (see P4 3)				
P11.2*		containing post-consumer recycled fibers can be used, provided that it meets t			╞		
	EN1228	1.	ne requirements	s of 🔀			
P11.3*	2-sided	(duplex) printing/copying is an integrated product function.		$\square$			
P12	Ergonomics for computing products						
P12.1*	•	play meets the ergonomic requirements of ISO 9241-307 for visual display technolo	ogies.			$\mathbf{X}$	
P12.2*	The phy	sical input device meets the requirements of ISO 9995 and ISO 9241-410.				$\mathbf{X}$	
P13		ing and documentation					
P13.1*		packaging material type(s): Corrugated weight (kg): 0.880 kg packaging material type(s): Expanded Polystyrene (EPS) weight (kg): 0.132 l	ka				
			ig): <b>0.027 kg</b>				
	Paperb	oard = 0.023 kg	3,				
		ed Polyethylene Terephthalate (RPET) = 0.027 kg					
P13.2*		plastic packaging is free from PVC.		$\square$			
P13.3*		media for user and product documentation (tick box):					
	Electronic 🔀, Paper 🔀, Other 🗌						
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled						
P14	fiber: 0	mal information (See Note B4)					
P1.1		oduct uses RoHS exemptions for lead and mercury used in small amounts for	r specific appli	cations			
P2.1		ttery contained within this product should be disposed of properly with the			is pro	perly	
		with the WEEE disposal symbol and instructions for such disposal is listed i					
P.2.3	The bat	tery contained within this product meets the exception listed. The battery is	not intended to	o be remove	d bv t	he	
-	customer; however, is designed for easy removal by recyclers and service providers.					-	
	Additional company information and company environmental policy may be found at http://lexmark.com/environment					nt	
		c printer and supply item recycling information for your area may be found a	t http://lexmark.	.com/recycle	е		
	Lexmar	k Sweden is connected to REPA and El-kretsen					

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19