

## Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo		
Company name *	Lexmark International, Inc.			
Contact information *	Nadia Martin (USA)	LEXM		
Internet site *	www.lexmark.se / www.lexmark.com			
Additional information				

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.					
Type of product *	ingle Function Mono Laser Printer				
Commercial name *	Lexmark MS310d, Lexmark MS310dn				
Model number *	1S310d, MS310dn				
Issue date *	Rev. February 21, 2014				
Intended market *	Global 🗌 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Requireme	nt met	
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	$\boxtimes$	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model number *	MS310d, MS310dn		
Issue date *	Rev. February 21, 2014	Logo	LEXMARK

Product	environmental attributes - Legal requirements	Require	ement	met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)			
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.	$\boxtimes$		
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),	$\boxtimes$		
1 1.0	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	$\boxtimes$		
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	$\boxtimes$		
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			$\square$
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm <sup>2</sup> /week (see legal reference).			
P1.10*	Comment: Max limit in legal reference when tested according to EN1811:1998. REACH Article 33 information about substances in articles is available at (add URL or mail contact): REACH Program Manager, HOD9237, 740 W. New Circle Rd., Lexington, KY 40550			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is			
P2.2*	provided in user manual. (See legal reference) Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	$\square$		
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medica or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	$\square$		
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).			
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).	6		
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	$\square$		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	$\square$		
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium an hexavalent chromium by weight of these together.	d 🔀		
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	$\boxtimes$		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montre. Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.	al 🔀		

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model nu		MS310d, MS310dn							
Issue da	te *	Rev. February 21, 2014 Logo	LEXM	I <mark>ARK</mark>					
Product	Product environmental attributes - Market requirements - Environmental conscious design								
Item		atory to fill in. Additional information regarding each item may be found under P14.	Yes	ment met No n.a					
P6		nt information							
P6.1*		on for recyclers/treatment facilities is available (see legal reference).	$\square$						
P7	Design	mbly, recycling							
P7.1*		thave to be treated separately are easily separable							
P7.2*	Plastic materials in covers/housing have no surface coating.								
P7.3*	Plastic parts >100g consist of one material or of easily separable materials.								
P7.4*		arts >25g have material codes according to ISO 11469 referring ISO 1043.		+ $+$					
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly available							
P7.6*	-	re easily separable. (This requirement does not apply to safety/regulatory labels).							
P7.0	Product								
P7.7*		ing can be done e.g. with processor, memory, cards or drives							
P7.8*		g can be done using commonly available tools							
P7.9.									
P7.10		arts are available after end of production for: 5 years							
17.10		s available after end of production for: 5 years and substance requirements							
P7.11*		cover/housing material type:							
		type: ABS Material type: HIPS Material type: P	C/ABS						
P7.12		I cable insulation materials of power cables are PVC free.		$\square$					
P7.13	Electrica	I cable insulation materials of signal cables are PVC free	<u>_</u>						
P7.14	All cover	/housing plastic parts >25g are free from chlorine and bromine.	<u> </u>						
P7.15		d circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-2	21. (See						
P7.16		tarded plastic parts >25g in covers / housings are marked according ISO 1043-4:							
P7.17	Alt. 1 Chemica	I specifications of flame retardants in printed circuit boards >25g (without components): additive) , TBBPA (reactive) , Other; chemical name: , CAS #:							
	ISO 104	Il specifications of flame retardants in printed circuit boards (without components) >25g acc 3-4: <i>FR(16)</i>	ording 🔀						
P7.18	concentr	etarded plastic parts >25g contain the following flame retardant substances/prepara ations above 0.1%:	tions in						
	1. Chem 2. Chem 3. Chem Alt. 2 Chemica	ent: No legal limits exist, this is a market requirement. ical name: , CAS #: ical name: , CAS #: ical name: , CAS #: Il specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(17), FR(16), FR(50)							
P7.19	Plastic p	arts >25g are free from flame retardant substances/ preparations above 0.1% classified as 5, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	R45,						
P7.20		plastic parts' weight >25g, recycled material content is up to 6%.							
P7.21		plastic parts' weight >25g, biobased material content is %.							
P7.22	If mercu	rces are free from mercury y is used specify: Number of lamps: and max. mercury content per lamp: mg							
P8	Batterie								
P8.1*		hemical composition: Lithium Manganese Dioxide, LiMnO2							
P8.2	Batteries	meet the requirements of the following voluntary program/s:							

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model nur		MS310d,					-	-			
Issue date	* Rev. February 21, 2014 Logo LEXMARK										
Product	Product environmental attributes - Market requirements (continued) Requirement met								met		
Item											
P9 Energy consumption											
9.1	For the product the following power levels or energy consumptions are reported:										
Energy mo	de *		Power level at 100 V AC	Power level at 115 V AC	Power level 230 V AC	at Refere modes	ence / S and test r		for	energy	
Printing			<b>480</b> W	<b>477</b> W	<b>447</b> W	Corpo	orate Stan	dard			
Ready Mo	ode		7.7 W	7.8 W	7.8 W	Energ	y Star I E	V1.2			
Sleep Mod	le		4.9 W	5.0 W	5.0 W	Energ	y Star I E	V1.2			
Hibernate	Mode		0.4 W	0.4 W	0.5 W	IEC 62	2301				
Off Mode			0.00 W	0.00 W	0.00 W	<i>IEC</i> 62	2301				
			W	W	W						
EPS No-los (External p charger plu outlet but c the product	ower supp ugged in the lisconnect	ne wall	W	W	W						
PTEC * Typical En	ergy Cons	sumption	W	W	W						
TEC * Typical En	ergy Cons	sumption	2.02 kWh/week	1.97 kWh/week	1.95 kWh/wee	K Energ	y Star I E	V1.2			
Etec * Annual Ene	ETEC * Annual Energy Consumption		kWh/year	kWh/year	kWh/ye	ar					
Display res	olution* :	: Me	gapixels								$\square$
Print Spee	d* :	35 Images	s per minute			ISO 24	4734				
Default tim	e to enter	energy sav	ve mode: 30 minutes			Energ	y Star I E	V1.2			
P9.2*	Informati	on about th	ne energy save functio	n is provided with th	ne product.		-		$\square$		
P9.3*	ENERG		the energy requiremer rersion: <b>2.0</b> Tier: Prod L- UZ 171			n/s:					
P10	Emissio	-									
P10.1			Declared according to	ISO 9296	Doolored		Deelerar	1 woight-	4		
P10.1	Mode		ode description		Declared A-weighted sound power		Declared / pressure	-		)	
					level $L_{WAd}$ (B)	Operator po Des or Desk	sktop 🗌	Bystan (only if p opera	produc	$\boxtimes$	
	Idle		Ready		* 3.3		1	5			
	Operatio		Simplex Monochrom	e Printing,	* 6.7		5	3			
	Other mo	ode	ormal Mode Simplex Monochrom wiet Mode	e Printing,	6.4		5	0			
	Measure	d according	~	ECMA-74 (only if not covered	by ECMA-74 wit	h L <sub>pAm</sub> measu	urement di	stance	m	)	
P10.2	Other       Only if not covered by ECMA-74 with LpAm measurement distance       m)         The product meets the acoustic noise requirements of the following voluntary program/s: RAL-UZ 122       Image: Comparison of the following voluntary program/section of the following voluntary program of the following voluntary prog										

Model nur	nber *	MS310d, MS310dn							
Issue date	<b>;</b> *	Rev. February 21, 2014	Logo	<b>EXM</b>	RK				
					плž				
Product	onvironn	nental attributes - Market requirements (continued)		Require	nont	mot			
Item		iental attributes - Market requirements (continued)		Yes	No				
nem				Tes	INU	n.a.			
Dia at		al emissions from printing products							
P10.3*	Test per 171	formed according to ECMA-328 (ISO/IEC 28360) standard, other specify: <b>RAL</b> -	UZ-122/RAL-UZ	$\square$	Ш				
P10.4	Typical e	emission rate (print phase) is (mg/h):							
	Dust <0.7 Ozone <0.06 Styrene <0.12 Benzene <0.03 TVOC 2.0								
P10.5	Chemical emission requirements of the following voluntary program/s RAL-UZ 122/RAL-UZ 171 are met for:								
			TVOC 🔀						
		nagnetic emissions							
P10.6	Compute program	er display meets the requirement for low frequency electromagnetic fields of the foll /s:	owing voluntary						
P11	Consum	able materials for printing products							
P11.1*		Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ	ired (see P4.3).	$\square$					
P11.2*	Paper c EN1228	ontaining post-consumer recycled fibers can be used, provided that it meets th	e requirements of						
P11.3*		duplex) printing/copying is an integrated product function.		$\boxtimes$					
P12		nics for computing products							
P12.1*		lay meets the ergonomic requirements of ISO 9241-307 for visual display technolog	aies.			$\square$			
P12.2*		sical input device meets the requirements of ISO 9995 and ISO 9241-410.	5	<u> </u>	╘				
P13		ng and documentation							
P13.1*		packaging material type(s): Corrugated weight (kg): 2.04							
P 13.1	Product	packaging material type(s): <i>Polystyrene, Expanded</i> weight (kg): 0.2858							
D40 of		packaging material type(s): weight (kg):							
P13.2*		plastic packaging is free from PVC.		$\square$					
P13.3*		nedia for user and product documentation (tick box): c 🔯, Paper 🔯, Other 🔲							
P13.4*		r user and product documentation, please specify contained percentage of post-co	nsumer recycled						
Rev. P13.5		product documentation do not contain chlorine bleached paper							
P14	Additior	al information (See Note B4)							
P1.1		uct uses RoHS exemptions for lead used in small amounts for specific applications.							
P2.1	The batte	ry contained within this product should be disposed of properly with the product. The pr ymbol and instructions for such disposal is listed in the product User's Guide.	oduct is properly la	beled with	the W	EEE			
P2.3		ry contained within this product meets the exception listed. The battery is not intended is designed for easy removal by recyclers and service providers.	to be removed by t	he custom	er;				
P7.14		mount of bromine may be present in covers due to sourcing post consumer recycled cont acessing of these parts.	ent. No bromine wo	as intentio	nally a	dded			
P7.20	Per IEEE :	1680.2 PCR calculation.							
P9.1	-	on provided in P9.1 is for products with firmware FW LW30.PRL.P307 or higher. Print spo ving table provides energy data for products with lower levels of firmware:	eed listed is Letter; /	A4 speed i	s 33 pp	om.			

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

P9 Energy consumpt	tion			
9.1 For the product th	e following power le	evels or energy cor	nsumptions are repo	orted:
Energy mode *	Power level at 100 V AC	Power level at 115 VAC	Power level at 230 VAC	Reference / Standard for er modes and test method *
Printing	480 W	477 W	447 W	Corporate Standard
Ready Mode	7.7 W	7.8 W	7.8 W	Energy Star I E V1.2
Sleep Mode	4.9 W	5.0 W	5.0 W	Energy Star I E V1.2
Hibernate Mode	0.4 W	0.4 W	0.5 W	IEC 62301
OffMode	0.00 W	0.00 W	0.00 W	IEC 62301
	W	W	W	
EPS No- <u>load</u> (External powersupply/ chargerplugged in the wall outlet but disconnected from the product.)	W	W	W	
PTEC * Typical Energy Consumption	W	W	W	
TEC* Typical Energy Consumption	2.02 kWh/week	1.97 kWh/week	1.95 kWh/week	Energy Star I E V1.2
ETEC * Annual Energy Consumption	kWh/year	kWh/year	kWh/year	
Display resolution* : Me	gapixels			
Print Speed * : 35 Image	s per minute			Corporate Standard
Default time to enter energy sa	ve mode: <b>30</b> minutes			Energy Star I E V1.2
P9.2* Information about	the energy save fun	ction is provided v	vith the product.	$\boxtimes$
	the energy requireme version: <b>1.2</b> Tier: <b>1</b> Pr IL UZ 122			
	L UZ 122 and company enviro recycling informatio	onmental policy ma n for your area ma	y be found at http://	· · · · · · · · · · · · · · · · · · ·

## Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19