

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	
Contact information *	Nadia Martin (USA)	LEXMARK
Internet site *	www.lexmark.se / www.lexmark.com	·
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.						
Type of product *	ngle Function Mono Laser Printer					
Commercial name *	exmark MS410d, Lexmark MS410dn, Lexmark M1140					
Model number *	1S410d, MS410dn, M1140					
Issue date *	Rev. February 21, 2014					
Intended market *	🔀 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 📃 Other					
Additional information						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Requireme	ent met	
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🛛	

Model nu		MS410d, MS410dn, M1140	T		_
Issue dat	te *	Rev. February 21, 2014 Logo	LEXM	[∆ Rŀ	ζ.
Draduct			Desuine		
	environ	mental attributes - Legal requirements	Require		
Item P1	Honord	aus substances and preparations	Yes	No	n.a.
P1.1*		bus substances and preparations s do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent			
F1.1	chromiu	m, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See erence and Note B1)			
P1.2*	Product	s do not contain Asbestos (see legal reference).	\boxtimes		
P1.3*		nt: Legal reference has no maximum concentration value.			
P1.3	hydrobro trichloro	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), omofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- ethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum ration values.			
P1.4*	terpheny	s do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated yl (PCT) in preparations (see legal reference).	\boxtimes		
P1.5*	Product	s do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in n containing at least 48% per mass of chlorine in the SCCP (see legal reference).	\boxtimes		
P1.6*	Textile a Tris-(azi	and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), iridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). nt: Legal reference has no maximum concentration values.			
P1.7*	Textile a	and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split c amines. (See legal reference and Note B1)			\boxtimes
P1.8*	Wooder pentach) parts do not contain arsenic and chromium as a wood preservation treatment as well as lorophenol and derivatives (see legal reference). nt: Legal reference has no maximum concentration values.			
P1.9*	Parts wi microgra	th direct and prolonged skin contact do not release nickel in concentrations above 0.5 am/cm ² /week (see legal reference). nt: Max limit in legal reference when tested according to EN1811:1998.	\square		
P1.10*	REACH <i>REACH</i>	Article 33 information about substances in articles is available at (add URL or mail contact): Program Manager, HOD9237, 740 W. New Circle Rd., Lexington, KY 40550	\square		
P2	Batterie				
P2.1*	more the marked	oduct contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is d in user manual. (See legal reference)			
P2.2*	Button of	cells used in the product do not contain more than 2% by weight of mercury. Other batteries or lators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\boxtimes		
P2.3*	Batterie design d	s and accumulators are easily removable by either users or service providers (as dependent on the of the product). Exception: Batteries that are permanently installed for safety, performance, medica integrity reasons do not have to be "easily removable". (See legal reference)			
P3		EMC connection to the telephone network and labeling			
P3.1*	The pro	duct complies with legally required safety standards as specified (see legal reference).	\square		
P3.2*	The pro	duct complies with legally required standards for electromagnetic compatibility (see legal			
P3.3*	If produ	ct is intended for connection to a public telecom network or contains a radio transmitter, it complies ally required standards for radio and telecommunication devices (see legal reference).			
P3.4*		duct is labeled to show conformance with applicable legal requirements (see legal reference).	\square		
P4	Consur	nable materials			
P4.1*	If a phot	to conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see erence and Note B1).			
P4.2*	<u> </u>	her is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	\square		
P4.3*	If the inl product/	/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these nents is available (see legal reference).			
P5		t packaging			
P5.1*	hexaval	ng and packaging components do not contain more than 0.01% lead, mercury, cadmium and ent chromium by weight of these together.	d 🔀		
P5.2*	Plastic p	backaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\boxtimes		
P5.3*	The pro	duct packaging material is free from ozone depleting substances as specified in the Montreal (see legal reference).			

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model nu		MS410d, MS410dn, M1140						
Issue date *		Rev. February 21, 2014	go I	EXM	ARK			
Product	environ	mental attributes - Market requirements - Environmental conscious desi	ian R	equire	ment	met		
Item		atory to fill in. Additional information regarding each item may be found under P14.	ign in	Yes	No	n.a.		
P6		nt information						
P6.1*		ion for recyclers/treatment facilities is available (see legal reference).		\square				
P7	Design							
	•	mbly, recycling						
P7.1*	Parts that have to be treated separately are easily separable							
P7.2*	Parts that have to be treated separately are easily separable Image: Comparison of the separately are easily separable Plastic materials in covers/housing have no surface coating. Image: Comparison of the separately are easily separable							
P7.3*	Plastic p	arts >100g consist of one material or of easily separable materials.						
P7.4*	-	arts >25g have material codes according to ISO 11469 referring ISO 1043.			Ħ	Ħ		
P7.5	-	arts are free from metal inlays or have inlays that can be removed with commonly avail	able tools.		H	H		
P7.6*	-	re easily separable. (This requirement does not apply to safety/regulatory labels).			⊢⊢	⊢⊢		
17.0	Product							
P7.7*		ng can be done e.g. with processor, memory, cards or drives						
P7.8*		ng can be done using commonly available tools			╞	╞		
P7.9.						╞╋		
		arts are available after end of production for: 5 years				<u> </u>		
P7.10		s available after end of production for: 5 years						
D7 44		and substance requirements						
P7.11*		cover/housing material type:						
P7.12		type: ABS Material type: HIPS Material type I cable insulation materials of power cables are PVC free.	be: PC/ABS					
P7.12		I cable insulation materials of signal cables are PVC free		<u> </u>		╞╋		
		5		<u> </u>		ᆜ		
P7.14		/housing plastic parts >25g are free from chlorine and bromine.		<u> </u>		<u> </u>		
P7.15	Note B2		9-2-21. (See					
P7.16	Marking:	etarded plastic parts >25g in covers / housings are marked according ISO 1043-4:		\square				
P7.17		al specifications of flame retardants in printed circuit boards >25g (without components) (additive) , TBBPA (reactive) , Other; chemical name: , CAS #:	:					
	ISO 104	Il specifications of flame retardants in printed circuit boards (without components) >25g 3-4: <i>FR(16)</i>	according					
P7.18	Alt. 1 Flame r concenti	etarded plastic parts >25g contain the following flame retardant substances/pre ations above 0.1%:	parations in					
	1. Chem 2. Chem	ent: No legal limits exist, this is a market requirement. ical name: , CAS #: ical name: , CAS #: ical name: , CAS #:						
D7 40	Chemica FR(40),	Il specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(17), FR(16), FR(50)	- D.45					
P7.19	R40, R4	arts >25g are free from flame retardant substances/ preparations above 0.1% classified 6, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	u as K45,					
P7.20		plastic parts' weight >25g, recycled material content is <i>up to 6%</i> .						
P7.21		blastic parts' weight >25g, biobased material content is %.						
P7.22	If mercu	ry is used specify: Number of lamps: and max. mercury content per lamp:	mg					
P8	Batterie							
P8.1*		chemical composition: <i>Lithium Manganese Dioxide, LiMnO2</i>				<u> </u>		
P8.2	Batteries	meet the requirements of the following voluntary program/s:						

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number * Issue date *		MS410dn, M1140 ruary 21, 2014				Logo	LE	XM	\RK	
Product onvironm	ontal att	ributes - Market re	quiromonts (con	tinued)				equire		
Item	ieniai all	IDULES - Market le	quirements (con	illilueu)				Yes	No	n.a.
	onsumpti	on						100	110	
		following power levels	or energy consump	otions are report	ted:					
Energy mode *		Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC		Reference / S modes and test r		for e	nergy	
Printing		514 W	480 W	468 W		Corporate Standard				
Ready Mode		5.3 W	5.3 W	5.9 W		Energy Star I E	V2.0			
Sleep Mode		2.3 W	2.3 W	2.4 W		Energy Star I E	V2.0			
Hibernate Mode		0.4 W	0.4 W	0.5 W		IEC 62301				
Off Mode		0.00 W	0.00 W	0.00 W		IEC 62301				
		W	W	W						
EPS No-load		W	W	W						
(External power supp charger plugged in th outlet but disconnected the product.)	e wall									
PTEC * Typical Energy Const	umption	W	W	W						
TEC * Typical Energy Consumption		1.8 kWh/week	1.8 kWh/week	1.8 kWh/week		Energy Star I E	V2.0			
ETEC * Annual Energy Consumption		kWh/year	kWh/year	kWh/year						
Display resolution* :	Me	gapixels								
Print Speed * :	40 Images	s per minute				ISO 24734 (US I	.etter)			
Default time to enter	energy sav	ve mode: 30 minutes			Energy Star I E V2.0					
P9.2* Information	on about th	e energy save functio	n is provided with th	ne product.				\boxtimes		Ħ
ENERGY		the energy requiremer ersion: 2.0 Tier: Prod L- UZ 171			m/s:					
P10 Emission										
		Declared according to	ISO 9296	Declarad		Declared	woighted			
P10.1 Mode	IVI	ode description		Declared A-weighted		Declared A sound pressure I	0			
				sound power		ator position	Bystand		itions	
				level L_{WAd} (B)		Desktop	(only if p		is not	
Idle	*	Ready		* 3.3		1	5			
Operation	N	Simplex Monochrom ormal Mode		* 6.8		5	4			
Other mo		Simplex Monochrom uiet Mode	e Printing,	6.5		5	0			
		Other	ECMA-74 (only if not covered					m)		
P10.2 The prod UZ 171	uct meets	the acoustic noise req	uirements of the fol	iowing voluntary	progra	m/s: <i>kal-UZ</i> 12	Z/RAL-			

Model nur	nber *	MS410d, MS410dn, M1140						
Issue date	*	Rev. February 21, 2014	Logo	EXM	RK			
					шиž			
Product	environn	nental attributes - Market requirements (continued)	F	Require	ment	met		
Item				Yes	No	n.a.		
item	Chamia	al amignions from printing products		163	NO	n.a.		
P10.3*		al emissions from printing products						
P10.3	171	formed according to ECMA-328 (ISO/IEC 28360) standard, other specify: RAL -	UZ-122/RAL-UZ					
P10.4	Typical e	emission rate (print phase) is (mg/h):						
		Dust <0.7 Ozone <0.06 Styrene <0.12 Benzene <0.03 TVOC 2.0						
P10.5	Chemical emission requirements of the following voluntary program/s RAL-UZ 122/RAL-UZ 171 are met for:							
			Γνος 🔀					
		nagnetic emissions						
P10.6	Compute program	er display meets the requirement for low frequency electromagnetic fields of the follo /s:	owing voluntary					
P11		able materials for printing products						
P11.1*	A Safety	Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requi	red (see P4.3).	\square				
P11.2*	Paper c EN1228	ontaining post-consumer recycled fibers can be used, provided that it meets the	e requirements of					
P11.3*		(duplex) printing/copying is an integrated product function.		\boxtimes				
P12		nics for computing products						
P12.1*		lay meets the ergonomic requirements of ISO 9241-307 for visual display technolog	jies.			\boxtimes		
P12.2*		sical input device meets the requirements of ISO 9995 and ISO 9241-410.	,	- -	H	X		
P13		ng and documentation						
P13.1*		packaging material type(s): Corrugated weight (kg): 1.58						
1 10.1	Product	packaging material type(s): Polystyrene, Expanded weight (kg): 0.2858						
D40 of		packaging material type(s): weight (kg):				_		
P13.2*		plastic packaging is free from PVC.		\square				
P13.3*		nedia for user and product documentation (tick box): ic 🔀, Paper 🔀, Other 📃						
P13.4*	For pape fiber: 0	er user and product documentation, please specify contained percentage of post-cor	nsumer recycled					
Rev.		d product documentation do not contain chlorine bleached paper						
P13.5								
P14		hal information (See Note B4)						
P1.1		uct uses RoHS exemptions for lead used in small amounts for specific applications.						
P2.1		ery contained within this product should be disposed of properly with the product. The pro symbol and instructions for such disposal is listed in the product User's Guide.	oduct is properly lai	oeled with	the W	EEE		
P2.3		ery contained within this product meets the exception listed. The battery is not intended t is designed for easy removal by recyclers and service providers.	to be removed by t	he custom	er;			
P7.14		mount of bromine may be present in covers due to sourcing post consumer recycled conte ocessing of these parts.	ent. No bromine wo	is intentio	nally a	dded		
P7.20	Per IEE	E 1680.2 PCR calculation.						
P9.1	speed is	tion provided in P9.1 is for products with firmware FW LW30.PRL.P307 or higl s 38 ppm. owing table provides energy data for products with lower levels of firmware:	her. Print speed	isted is I	Letter,	; A4		

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Item				Yes No	n.a.
P9 Energy consumpt					
9.1 For the product the	following power levels	•, •	tions are reported:		
Energy mode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	t Reference / Standard for energy modes and test method *	/
Printing	514 W	480 W	468 W	Corporate Standard	
Ready Mode	6.8 W	6.9 W	7.0	Energy Star I E V1.2	
Sleep Mode	4.1 W	4.2 W	4.2 W	Energy Star I E V1.2	
Hibernate Mode	0.40 W	0.41 W	0.45 W	IEC 62301	
Off Mode	0.00 W	0.00 W	0.00 W	IEC 62301	
	W	W	W		
EPS No-load (External power supply /	w	w	w		
charger plugged in the wall outlet but disconnected from the product.)					
PTEC * Typical Energy Consumption	W	W	W		
TEC * Typical Energy Consumption	2.08 kWh/week	1.95 kWh/week	1.97 kWh/week	Energy Star I E V1.2	
ETEC * Annual Energy Consumption	kWh/year	kWh/year	kWh/year		
Display resolution* : Me	egapixels		I		
Print Speed * : 40 Image	s per minute			Corporate Standard	
Default time to enter energy sa	ve mode: 30 minutes			Energy Star I E V1.2	
P9.2* Information about t	he energy save functio	on is provided with th	e product.		
ENERGY STAR®	the energy requirement version: 1.2 Tier: 1 Pro L UZ 122				

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19