

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	754
Contact information *	Drew Zande (USA)	🚺 Lexmark
Internet site *	www.lexmark.ted / www.lexmark.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.					
Type of product *	Single Function Mono Laser Printer				
Commercial name *	exmark MS810dn, Lexmark MS810dtn, Lexmark MS817dn				
Model number *	IS810dn, MS810dtn, MS817dn				
Issue date *	ebruary 24, 2014 (Revised June 1, 2017)				
Intended market *	Global 🗌 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality Control			nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model number *	MS810dn, MS810dtn, MS817dn			
Issue date *	February 24, 2014 (Revised June 1, 2017)	Logo	- •	Lexmark

Product	environmental attributes - Legal requirements	Require	ment	met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)	\square		
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.	\boxtimes		
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),	\square		
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-			
	trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).			
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).			
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			\boxtimes
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			\square
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as			\square
	pentachlorophenol and derivatives (see legal reference).			
D4 of	Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm ² /week (see legal reference).	\boxtimes		
	Comment: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact):	\square		
	REACH Program Manager, HOD9237, 740 W. New Circle Rd., Lexington, KY 40550			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is			
	provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or	\square		
	accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)			
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medica or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	\square		
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).			
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).			
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\boxtimes		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	\square		
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the		╞	
	product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.	d 🔀		
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\boxtimes		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montrea Protocol (see legal reference).	il 🔀		
	Comment: Legal reference has no maximum concentration values.			

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model nu	Model number * MS810dn, MS810dtn, MS817dn						
Issue dat	te *	February 24, 2014 (Revised June 1, 2017)Logo	Lexm	Lexmark			
Product	environ	mental attributes - Market requirements - Environmental conscious design R	equire	ment	met		
Item	*=manda	atory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.		
P6		nt information					
P6.1*	Informati	ion for recyclers/treatment facilities is available (see legal reference).	\square				
P7	Design Disasse	mbly, recycling					
P7.1*		at have to be treated separately are easily separable	\square				
P7.2*	Plastic materials in covers/housing have no surface coating.						
P7.3*							
P7.4*		arts >25g have material codes according to ISO 11469 referring ISO 1043.		╞	╞		
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly available tools.		╞	╞		
P7.6*		re easily separable. (This requirement does not apply to safety/regulatory labels).		╞	<u> </u>		
F7.0	Product						
P7.7*		ng can be done e.g. with processor, memory, cards or drives					
P7.8*		ng can be done using commonly available tools		╞	⊢⊢		
P7.9.					╞		
P7.10	- · · ·	arts are available after end of production for: 5 years			╞		
17.10		s available after end of production for: 5 years and substance requirements					
P7.11*		cover/housing material type:					
		type: ABS Material type: HIPS Material type: PC/ABS					
P7.12		I cable insulation materials of power cables are PVC free.		\mathbf{X}			
P7.13	Electrica	I cable insulation materials of signal cables are PVC free			Ē		
P7.14		/housing plastic parts >25g are free from chlorine and bromine.			H		
P7.15		ed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See	- 1		H		
	Note B2)						
P7.16	Flame re Marking:	etarded plastic parts >25g in covers / housings are marked according ISO 1043-4:	\boxtimes				
P7.17	Alt. 1 Chemica	al specifications of flame retardants in printed circuit boards >25g (without components): (additive) , TBBPA (reactive) , Other; chemical name: , CAS #:					
	ISO 1043	Il specifications of flame retardants in printed circuit boards (without components) >25g according 3-4: <i>FR(16)</i>					
P7.18	concentr	etarded plastic parts >25g contain the following flame retardant substances/preparations in ations above 0.1%: ent: No legal limits exist, this is a market requirement.					
	1. Chemi 2. Chemi	ical name: , CAS #: ical name: , CAS #: ical name: , CAS #:					
P7.19	FR(40), I	Il specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(17), FR(16), FR(50) arts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45,					
	R40, R46	6, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)					
P7.20		plastic parts' weight >25g, recycled material content is <i>up to 16%</i> .					
P7.21 P7.22		blastic parts' weight >25g, biobased material content is %.					
F1.22		ry is used specify: Number of lamps: and max. mercury content per lamp: mg	\boxtimes				
P8	Batteries						
P8.1*		hemical composition: Lithium Manganese Dioxide, LiMnO2					
P8.2	Batteries	meet the requirements of the following voluntary program/s:					

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	MS810dn, MS810dtn, MS817dn		
Issue date *	February 24, 2014 (Revised June 1, 2017)	Logo	🔨 Lexmark

Product environmental attributes - Market requirements (continued) Requirement met							
Item Yes No i							
P9 Energy consumption							
9.1 For the product the following power levels or energy consumptions are reported:							
Energy mode *	Power level at 100 V AC	Power level at 115 V AC	Power level 230 V AC	at Reference / Standard for energy modes and test method *			
Printing	663 W	663 W	671 W	Corporate Standard			
Ready 1 Mode	eady 1 Mode 45.2 W 47.8 W 52 W		Energy Star I E V2.0				
Ready 2 Mode	eady 2 Mode 24.5 W 25.3 W 26.5 W		Energy Star I E V2.0				
Sleep Mode	2.7 W	2.7 W	2.8 W	Energy Star I E V2.0			
Hibernate Mode	0.42 W	0.44 W	0.45 W	IEC 62301			
Off Mode	0.1 W	0.1 W	0.1 W	IEC 62301			
EPS No-load	W	W	W				
(External power supply / charger plugged in the wall outlet but disconnected from the product.)							
PTEC * Typical Energy Consumption	W	W	W				
TEC * Typical Energy Consumption	3.4 kWh/week	3.4 kWh/week	3.5 kWh/week	Energy Star I E V2.0			
Etec *	kWh/year	kWh/year	kWh/yea	ar 🛛			
Annual Energy Consumption							
Display resolution* : Me	egapixels						
Print Speed * : 63 Image	s per minute			ISO 24734			
Default time to enter energy sa	ve mode: 30 minutes			Energy Star I E V2.0			
P9.2* Information about t	he energy save functio	n is provided with th	ne product.				
	the energy requirement version: 2.0 Tier: Prod L-UZ 171			n/s:			
P10 Emissions		100 0000					
	Declared according to lode description	150 9296	Declared	Declared A-weighted			
			A-weighted	sound pressure level L_{pAm} (dB)			
			sound power level L_{WAd} (B)	Operator position Bystander positions			
				Desktop			
				or Desk side (only if product is not operator attended)			
Idle *	Ready	t l	* 4.8	32			
Operation *	Simplex Monochrom	e Printing,	7.2	57			
Other mode	Other mode Simplex Monochrome Printing, Quiet Mode 6.8 53		53				
Measured accordin		ECMA-74	by ECMA-74 with	h L _{pAm} measurement distance m)			
P10.2 The product meets UZ 171				program/s: RAL-UZ 122/RAL-			

Model nu	mber *	MS810dn, MS810dtn, MS817dn						
Issue date	date *February 24, 2014 (Revised June 1, 2017)LogoLogoLexman							
Product	Product environmental attributes - Market requirements (continued) Requirement met							
Item				Yes	No	n.a.		
		al emissions from printing products						
P10.3*	171	formed according to ECMA-328 (ISO/IEC 28360) standard, other specify: RAL	-UZ-122/RAL-UZ					
P10.4		emission rate (print phase) is (mg/h):						
P10.5	Dust <0.8 Ozone <0.06 Styrene <0.14 Benzene <0.03 TVOC 3.5							
P10.5		al emission requirements of the following voluntary program/s <i>RAL-UZ-122/RAL-U</i> .	TVOC X					
		nagnetic emissions						
P10.6		er display meets the requirement for low frequency electromagnetic fields of the fol	lowing voluntary					
P11		able materials for printing products						
P11.1*	A Safety	Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ	uired (see P4.3).	\boxtimes				
P11.2*	EN1228		ne requirements	of 🔀				
P11.3*	2-sided ((duplex) printing/copying is an integrated product function.		\boxtimes				
P12		mics for computing products						
P12.1*		lay meets the ergonomic requirements of ISO 9241-307 for visual display technolo	ogies.			\square		
P12.2*		sical input device meets the requirements of ISO 9995 and ISO 9241-410.				\square		
P13		ng and documentation						
P13.1*	Product Product Polypro	packaging material type(s): Corrugatedweight (kg): 2.654packaging material type(s): Polystyrene, expandedweight (kg): 0.634packaging material type(s): Low Density Polyethyleneweight (kg): 0.081pylene - 0.065 kgweight (kg): 0.081						
P13.2*		plastic packaging is free from PVC.		\square				
P13.3*	Electron	media for user and product documentation (tick box): ic ⊠, Paper ⊠, Other 🔲						
P13.4*	fiber: 0		onsumer recycled					
Rev. P13.5		d product documentation do not contain chlorine bleached paper						
P14		hal information (See Note B4)						
P1.1 P2.1		luct uses RoHS exemptions for lead used in small amounts for specific applications. ery contained within this product should be disposed of properly with the product. The p	voductio nyonovlu l	wholed with	+ + + + + + + + + + + + + + + + + + + +			
P2.1		symbol and instructions for such disposal is listed in the product User's Guide.	roduct is property i	ubelea with	the w			
P2.3		ery contained within this product meets the exception listed. The battery is not intendea is designed for easy removal by recyclers and service providers.	l to be removed by	the custom	er;			
P7.2	Special p	art: Small op panel screen (less than 25g) is backpainted.						
P7.14		mount of bromine may be present in covers due to sourcing post consumer recycled cont ocessing of these parts.	tent. No bromine v	vas intentio	nally a	dded		
P7.20	Per IEEE	1680.2 PCR calculation.						
P9.1		ion provided in P9.1 is for products with firmware FW LW30.DN2.P311 or higher. Print sp wing table provides energy data for products with lower levels of firmware:	eed listed is Letter	; A4 speed i	is 52 pp	m.		

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

D0 5	1				
P9 Energy consumpt			e		
	following power levels				
Energy mode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standard for energy modes and test method *	
Printing	663 W	663 W	671 W	Corporate Standard	
Ready 1 Mode	46.4 W	43.6 W	44.6 W	Energy Star I E V1.2	
Ready 2 Mode	31.8 W	29.7 W	28.6 W	Energy Star I E V1.2	
Sleep Mode	4.0 W	4.1 W	4.0 W	Energy Star I E V1.2	
Hibernate Mode	0.42 W	0.43 W	0.45 W	IEC 62301	
Off Mode	0.1 W	0.1 W	0.1 W	IEC 62301	
EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)	W	W	W		
PTEC * Typical Energy Consumption	W	W	W		\boxtimes
TEC * Typical Energy Consumption	3.8 kWh/week	3.8 kWh/week	3.7 kWh/week	Energy Star I E V1.2	
ETEC * Annual Energy Consumption	kWh/year	kWh/year	kWh/year		
Display resolution* : Me	egapixels				\boxtimes
Print Speed * : 55 Image	s per minute			Corporate Standard	
Default time to enter energy sa	ve mode: 30 minutes			Energy Star I E V1.2	
P9.2* Information about t	he energy save functio	n is provided with th	e product.		
	the energy requiremer version: 1.2 Tier: 1 Pro L UZ 122				
Packaging data display Packaging for MS810di Product packaging m	tn:		weight (kg): 2	678	
Product packaging m Product packaging m Product packaging m Polypropylene – 0.0	aterial type(s): aterial type(s):	Polystyrene,	expanded	weight (kg): 0.7247	
	ply item recycli	ng information	n for your area i	may be found at http://lexmo nay be found at http://lexmo	

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19