

## Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an \* are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	I DAZNA A DIZ
Contact information *	Nadia Martin (USA)	<b>LEXM</b> ARK <sub>™</sub>
Internet site *	www.lexmark.se / www.lexmark.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.							
Type of product *	Type of product * Single Function Mono Laser Printer						
Commercial name *	Lexmark MS812dn, Lexmark MS812dtn						
Model number *	MS812dn, MS812dtn						
Issue date *	Rev. February 25, 2014						
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other						
Additional information							

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control	Requireme	nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration		
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model number *	MS812dn, MS812dtn			
Issue date *	Rev. February 25, 2014	Logo	]	LEXMARK

Product	roduct environmental attributes - Legal requirements				
Item		Yes	No	n.a.	
P1	Hazardous substances and preparations				
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)				
P1.2*	Products do not contain Asbestos (see legal reference).  Comment: Legal reference has no maximum concentration value.				
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.				
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).				
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	$\boxtimes$			
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.				
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)				
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference).  Comment: Legal reference has no maximum concentration values.				
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm²/week (see legal reference).  Comment: Max limit in legal reference when tested according to EN1811:1998.				
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): REACH Program Manager, HOD9237, 740 W. New Circle Rd., Lexington, KY 40550				
P2	Batteries				
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)				
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	$\boxtimes$			
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medica or data integrity reasons do not have to be "easily removable". (See legal reference)				
P3	Safety, EMC connection to the telephone network and labeling				
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	$\boxtimes$			
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).	$\boxtimes$			
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).	$\boxtimes$			
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	$\boxtimes$			
P4	Consumable materials				
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).				
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	X			
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the		Ħ	Ħ	
	product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).				
P5	Product packaging				
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.	k 🔀			
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	$\boxtimes$			
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montrea Protocol (see legal reference).  Comment: Legal reference has no maximum concentration values.	l 🔀			

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model nu	umber *	MS812dn, MS812dtn						
Issue da		Rev. February 25, 2014	Logo	LEXM	ARK			
				LEZXIVI	mzi			
Product	t environ	mental attributes - Market requirements - Environmental conscious of	desian	Require	ment	met		
Item		atory to fill in. Additional information regarding each item may be found under P14.	<u> </u>	Yes	No	n.a.		
P6	Treatme	nt information						
P6.1*	Informati	on for recyclers/treatment facilities is available (see legal reference).		$\boxtimes$				
P7	Design							
		mbly, recycling						
P7.1*		t have to be treated separately are easily separable						
P7.2*	7.2* Plastic materials in covers/housing have no surface coating.							
P7.3*	Plastic p	arts >100g consist of one material or of easily separable materials.		$\boxtimes$				
P7.4*	Plastic p	arts >25g have material codes according to ISO 11469 referring ISO 1043.		$\boxtimes$				
P7.5	Plastic p	arts are free from metal inlays or have inlays that can be removed with commonly	available tools.	$\boxtimes$				
P7.6*	Labels a	re easily separable. (This requirement does not apply to safety/regulatory labels).		$\overline{\boxtimes}$	$\top$			
	Product	lifetime						
P7.7*	Upgradin	g can be done e.g. with processor, memory, cards or drives		$\boxtimes$	$\Box$			
P7.8*	Upgradin	g can be done using commonly available tools			Ħ			
P7.9.	Spare pa	arts are available after end of production for: 5 years				Ħ		
P7.10		s available after end of production for: 5 years				$\Box$		
		and substance requirements						
P7.11*		cover/housing material type:						
			al type: PC/ABS	;				
P7.12	Electrica	I cable insulation materials of power cables are PVC free.			$\boxtimes$			
P7.13	Electrica	cable insulation materials of signal cables are PVC free			$\boxtimes$			
P7.14	All cover	/housing plastic parts >25g are free from chlorine and bromine.			X			
P7.15	All printe	d circuit boards (without components) >25g are halogen free. as defined in IEC6	31249-2-21. (Se	е	$\overline{\square}$			
	Note B2)					_		
P7.16	Flame re Marking:	tarded plastic parts >25g in covers / housings are marked according ISO 1043-4:						
P7.17	Alt. 1							
		I specifications of flame retardants in printed circuit boards >25g (without compone	ents):					
	TBBPA (	additive) , TBBPA (reactive) , Other; chemical name: , CAS #:						
	Alt. 2							
		I specifications of flame retardants in printed circuit boards (without components) >	>25a accordina	$\boxtimes$				
		3-4: <b>FR(16)</b>	9					
P7.18	Alt. 1							
		etarded plastic parts >25g contain the following flame retardant substances	s/preparations i	n 🗌				
		ations above 0.1%:						
		ent: No legal limits exist, this is a market requirement.						
	1. Chemical name: , CAS #: 2. Chemical name: , CAS #:							
		ical name: , CAS #: ical name: , CAS #:						
	Alt. 2	our name.						
		I specifications of flame retardants in plastic parts >25g according ISO 1043-4:		K-7				
	FR(40), I	FR(17), FR(16), FR(50)		$\boxtimes$				

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45,

and max. mercury content per lamp:

mg

R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)

Of total plastic parts' weight >25g, recycled material content is up to 16%.

Battery chemical composition: Lithium Manganese Dioxide, LiMnO2

Batteries meet the requirements of the following voluntary program/s:

Of total plastic parts' weight >25g, biobased material content is

Light sources are free from mercury If mercury is used specify: Number of lamps:

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

P7.19

P7.20

P7.21

P7.22

**P8** 

P8.2

Model number *	MS812dn, MS812dtn		
Issue date *	Rev. February 25, 2014	Logo	LEXMARK

Product e	environmental at	tributes - Market re	quirements (con	tinued)			Requi	remer	t met
Item							Ye	s No	n.a.
P9	Energy consumpt	ion							
9.1	For the product the	following power levels	or energy consump	tions are report	ted:				
Energy mod	Energy mode * Power level at Power level at Power level at Reference / Standard for energy modes and test method *				/				
Printing	Printing 818 W 805 W 818 W			Corporate Standard					
Ready 1 M	ode	41.7 W	<b>43.6</b> W	38.8 W		Energy Star I E V2.0			
Ready 2 M	ode	24.1 W	<b>24.6</b> W	<b>23.8</b> W		Energy Star I E V2.0			
Sleep Mod	le e	2.7 W	<b>2.7</b> W	<b>2.7</b> W		Energy Star I E V2.0			
Hibernate	Mode	0.42 W	0.44 W	<b>0.44</b> W		IEC 62301			
Off Mode		0.1 W	0.1 W	0.1 W		IEC 62301			
charger plu outlet but d the product	ower supply / gged in the wall isconnected from	W	W	W					
PTEC * Typical Ene	ergy Consumption	W	W	W					
TEC * Typical Ene	ergy Consumption	4.3 kWh/week	4.3 kWh/week	4.5 kWh/week		Energy Star I E V2.0			
ETEC * Annual Ene	ergy Consumption	kWh/year	kWh/year	kWh/ye	ar				
Display res	olution* : Me	egapixels	l	l .					
Print Speed	d * : <b>70</b> Image	s per minute				ISO 24734 (US Letter)			
Default time	e to enter energy sa	ve mode: 30 minutes				Energy Star I E V2.0			
P9.2*	Information about t	he energy save functio	n is provided with th	e product.			X		
P9.3*		the energy requirement version: 2.0 Tier: Prod L-UZ 171			m/s:		X		
P10	Emissions								
D40.4		Declared according to	ISO 9296		1	D 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			T
P10.1	Mode	Mode description		Declared A-weighted sound power		Declared A-weight sound pressure level $L_{\it p}$		B)	
				level $L_{W\!Ad}$ (B)	Ope	rator position Bysta	ander p	osition	3
								ct is no ttended	
-	Idle *	Ready	1	4.7		32	ator a	toriada	ΉП
-	Operation *	Simplex Monochrom Normal Mode	e Printing,	7.3		58			
	Other mode	Simplex Monochrom Quiet Mode	e Printing,	6.8		53			
	Measured according	3 ** 📒 * * * * * * * *	ECMA-74 (only if not covered	bv ECMA-74 wit	th Lnar	m measurement distance	r	n)	
P10.2	The product meets					am/s: RAL-UZ 122/RAL-	×		

Model number *	MS812dn, MS812dtn			
Issue date *	Rev. February 25, 2014	Logo	]	LEXMARK

Product	environmental attributes - Market requirements (continued)	Require	ment	met
Item		Yes	No	n.a.
	Chemical emissions from printing products			
P10.3*	Test performed according to ECMA-328 (ISO/IEC 28360) standard, other specify: RAL-UZ-122/RAL-UZ 171			
P10.4	Typical emission rate (print phase) is (mg/h):  Dust <0.9 Ozone <0.06 Styrene <0.2 Benzene <0.03 TVOC 5.8			
P10.5	Chemical emission requirements of the following voluntary program/s RAL-UZ-122/RAL-UZ 171 are met for:			
	Dust    Ozone    Styrene    Benzene    TVOC			
P10.6	Electromagnetic emissions  Computer display meets the requirement for low frequency electromagnetic fields of the following voluntary			
	program/s:		<u>Ц</u>	
P11	Consumable materials for printing products			
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).		<u></u>	<u>Ц</u>
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN12281.		<u>Ц</u>	<u>Ц</u>
P11.3*	2-sided (duplex) printing/copying is an integrated product function.			
P12	Ergonomics for computing products			
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.			$\boxtimes$
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.		$\Box$	X
P13	Packaging and documentation			
P13.1*	Product packaging material type(s): Corrugated weight (kg): 2.654 Product packaging material type(s): Polystyrene, expanded weight (kg): 0.634 Product packaging material type(s): Low Density Polyethylene weight (kg): 0.081 Polypropylene – 0.065 kg			
P13.2*	Product plastic packaging is free from PVC.	$\square$	$\overline{}$	$\overline{}$
P13.3*	Specify media for user and product documentation (tick box):			
D40.4*	Electronic , Paper , Other .			_
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber: 0%			<u> </u>
Rev. P13.5	User and product documentation do not contain chlorine bleached paper		Ш	Ш
P14	Additional information (See Note B4)			
P1.1	This product uses RoHS exemptions for lead used in small amounts for specific applications.			
P2.1	The battery contained within this product should be disposed of properly with the product. The product is properly ladisposal symbol and instructions for such disposal is listed in the product User's Guide.	beled witl	1 the W	'EEE
P2.3	The battery contained within this product meets the exception listed. The battery is not intended to be removed by the however, is designed for easy removal by recyclers and service providers.	he custom	ier;	
P7.2	Special part: small op panel screen (less than 25g) is backpainted.			
P7.14	A small amount of bromine may be present in covers due to sourcing post consumer recycled content. No bromine we in the processing of these parts.	as intentic	nally a	ıdded
P7.20	Per IEEE 1680.2 PCR calculation.			
P9.1	Information provided in P9.1 is for products with firmware FW LW30.DN2.P311 or higher. Print speed listed is Letter; The following table provides energy data for products with lower levels of firmware:	44 speed	is 66 pp	om.

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

P9 Energy consumpti	on					
9.1 For the product the	following power levels	or energy consump	tions are reported:			
Energy mode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standard modes and test method *	for energy	
Printing	818 W	805 W	818 W	Corporate Standard		
Ready 1 Mode	53.7 W	40.8 W	40.3 W	Energy Star I E V1.2		
Ready 2 Mode	30.9 W	27.6 W	27.6 W	Energy Star I E V1.2		
Sleep Mode	4.0 W	4.1 W	4.1 W	Energy Star I E V1.2		
Hibernate Mode	0.42 W	0.44 W	0.44 W	IEC 62301		
Off Mode	0.1 W	0.1 W	0.1 W	IEC 62301		
EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)	W	W	W			
PTEC * Typical Energy Consumption	W	W	W			
TEC * Typical Energy Consumption	4.82 kWh/week	4.76 kWh/week	4.59 kWh/week	Energy Star I E V1.2		
ETEC * Annual Energy Consumption	kWh/year	kWh/year	kWh/year			$\boxtimes$
Display resolution* : Me	gapixels					$\boxtimes$
Print Speed * : 70 Images	s per minute			Corporate Standard		〒
Default time to enter energy sav	e mode: 30 minutes			Energy Star I E V1.2		Ħ
P9.2* Information about th	ne energy save function	n is provided with th	e product.			Ī
	the energy requirement ersion: 1.2 Tier: 1 Pro L UZ 122					
Packaging data display Packaging data for MSc Product packaging mat Product packaging mat Product packaging mat Polypropylene – 0.065 to Additional company inf Specific printer and sup	812dtn: terial type(s): Co terial type(s): Po terial type(s): Lo kg formation and c	orrugated olystyrene, exp ow Density Poly ompany enviro	yethylene we	ight (kg): 0.7247 ight (kg): 0.081 may be found at h		

## Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19