

## Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo				
Company name *	Lexmark International, Inc.	774				
Contact information *	Nadia Martin (USA)	Lexmark				
Internet site *	www.lexmark.se / www.lexmark.com					
Additional information						

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.						
Type of product *	Multi Function Mono Laser Printer					
Commercial name *	exmark MX410de, Lexmark XM1140, Lexmark MX417de					
Model number *	MX410de, XM1140, MX417de					
Issue date *	Rev. February 24, 2014 (Update March 1, 2017)					
Intended market *	Global 🗌 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other					
Additional information						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Requireme	nt met	
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	$\boxtimes$	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model number *	MX410de, XM1140, MX417de		
Issue date *	Rev. February 24, 2014 (Updated March 1, 2017)	Logo	🚺 Lexmark

Product	environmental attributes - Legal requirements	Require	ment	met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)	$\square$		
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.	$\boxtimes$		
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),	$\square$		
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	$\square$		
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	$\boxtimes$		
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			$\boxtimes$
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference).			
	Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm <sup>2</sup> /week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): REACH Program Manager, HOD9237, 740 W. New Circle Rd., Lexington, KY 40550			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or	$\boxtimes$		
P2.3*	accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference) Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medica or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).			
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).			
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).			
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	$\boxtimes$		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).	$\boxtimes$		
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	$\boxtimes$		
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.	d 🔀		
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	$\square$		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montrea Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.	il 🔀		

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model nu	umber *	MX410de, XM1140 , MX417de									
Issue dat	date * Rev. February 24, 2014 (Update March 1, 2017) Logo				Lexmark						
Product	Product environmental attributes - Market requirements - Environmental conscious design Requirement met										
Item		atory to fill in. Additional information regarding each item may be found under P14.	- 3	Yes	No	n.a.					
P6		nt information									
P6.1*	Informati	on for recyclers/treatment facilities is available (see legal reference).		$\boxtimes$							
P7	Design										
	Disasse	mbly, recycling									
P7.1*	Parts that have to be treated separately are easily separable										
P7.2*	Plastic materials in covers/housing have no surface coating.										
P7.3*	Plastic p	arts >100g consist of one material or of easily separable materials.		$\square$							
P7.4*	Plastic p	arts >25g have material codes according to ISO 11469 referring ISO 1043.			Ē						
P7.5	Plastic p	arts are free from metal inlays or have inlays that can be removed with commonly ava	ailable tools.		Ħ						
P7.6*		re easily separable. (This requirement does not apply to safety/regulatory labels).			H	H					
	Product										
P7.7*		ig can be done e.g. with processor, memory, cards or drives									
P7.8*		g can be done using commonly available tools			H						
P7.9.		arts are available after end of production for: 5 years				+					
P7.10		•									
17.10		s available after end of production for: 5 years									
P7.11*		and substance requirements cover/housing material type:									
F7.11			vpe: <b>PC/ABS</b>								
P7.12		I cable insulation materials of power cables are PVC free.			$\boxtimes$						
P7.13		I cable insulation materials of signal cables are PVC free		╞		-					
P7.14		/housing plastic parts >25g are free from chlorine and bromine.		<u> </u>							
P7.14				<u> </u>							
P7.15	Note B2)	ed circuit boards (without components) >25g are halogen free. as defined in IEC612	249-2-21. (See		$\bowtie$						
P7.16		/ tarded plastic parts >25g in covers / housings are marked according ISO 1043-4:		$\boxtimes$							
	Marking:										
P7.17	Alt. 1	I apositionations of flows retardants in printed airquit boards > 25g (without component	o).								
		I specifications of flame retardants in printed circuit boards >25g (without component additive) , TBBPA (reactive) , Other; chemical name: , CAS #:	5).								
	I DDFA (										
	Alt. 2										
		I specifications of flame retardants in printed circuit boards (without components) >25	5g according	$\boxtimes$							
		3-4: <b>FR(16)</b>									
P7.18	Alt. 1			_	_						
		etarded plastic parts >25g contain the following flame retardant substances/p ations above 0.1%:	reparations in								
		ent: No legal limits exist, this is a market requirement.									
		ical name: , CAS #:									
		ical name: , CAS #:									
	3. Chemi	ical name: , CAS #:									
	Alt. 2										
		I specifications of flame retardants in plastic parts >25g according ISO 1043-4:									
P7.19	Plastic n	FR(17), FR(16), FR(50) arts >25g are free from flame retardant substances/ preparations above 0.1% classifi	ed as R45		╞	+					
	R40, R46	6, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	cu as 1140,								
P7.20		plastic parts' weight >25g, recycled material content is up to 6%.									
P7.21 P7.22		blastic parts' weight >25g, biobased material content is %.									
F1.22		y is used specify: Number of lamps: and max. mercury content per lamp:	mg	$\boxtimes$							
P8	Batteries										
P8.1*		hemical composition: Lithium Manganese Dioxide, LiMnO2									
P8.2		meet the requirements of the following voluntary program/s:				H					
L											

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number * MX410de, XM1140, MX417de										
Issue date *	te * Rev. February 24, 2014 (Updated March 1, 2017) Logo									
Product environ	mental att	ributes - Market re	quirements (con	tinued)	Requirement	met				
Item			4		Yes No	n.a.				
P9 Energy	consumpti	on								
9.1 For the	product the	following power levels	or energy consump	otions are report	ted:					
Energy mode *		Power level at 100 V AC	Power level at 115 V AC	Power level 230 V AC	I at Reference / Standard for energy modes and test method *					
Printing		534 W	509 W	<b>482</b> W	Corporate Standard					
Сору		<b>546</b> W	<b>516</b> W	<b>493</b> W	Corporate Standard					
Ready Mode		9.8 W	9.8 W	<b>10.0</b> W	Energy Star I E V2.0					
Sleep Mode		3.0 W	3.0 W	3.1 W	Energy Star I E V2.0					
Hibernate Mode		0.26 W	0.28 W	0.39 W	IEC 62301					
Off Mode		0.0 W	0.0 W	0.0 W	IEC 62301					
EPS No-load		W	W	W		$\boxtimes$				
(External power sup charger plugged in t outlet but disconnec the product.)	the wall									
PTEC * Typical Energy Con	sumption	W	W	W						
TEC * Typical Energy Con	TEC * Typical Energy Consumption		2.0 kWh/week	2.0 kWh/week	Energy Star I E V2.0					
ETEC * Annual Energy Consumption		kWh/year	kWh/year	kWh/ye	ear					
Display resolution*	: Me	gapixels								
Print Speed *	: 40 Images	s per minute			ISO 24734 (US Letter)					
Default time to ente	r energy sav	ve mode: 30 minutes		Energy Star I E V2.0						
P9.2* Informa	tion about th	ne energy save functio	n is provided with th	ne product.						
ENERG		the energy requiremer version: 2.0 Tier: Prod L UZ 171								
P10 Emissio										
	1	Declared according to	150 9296	Dealers d	Declared A weighted					
P10.1 Mode	M	lode description		Declared A-weighted	Declared A-weighted sound pressure level $L_{pAm}$ (dB)					
				sound power level $L_{WAd}$ (B)	Operator position Bystander positions					
				iever <i>L</i> <sub>WAd</sub> (B)	Desktop or Desk side (only if product is not operator attended)					
Idle	*	Ready		* 3.3	15					
Operatio		Simplex Monochrom Iormal Mode	e Printing,	* 6.9	55					
Other m		Simplex Monochrom Wiet Mode	e Printing,	6.4	50					
Measure	ed according		ECMA-74 (only if not covered	by FCMA-74 wit	th L <sub>pAm</sub> measurement distance m)	1				
P10.2 The pro UZ 171					v program/s: RAL-UZ 122/RAL-					

Model nu	nber *		, XM1140, MX4						-			
Issue date	*	Rev. Febr	wary 24, 2014	(Updat	ted March 1,	2017			Logo	🚺 Lexm	ark	
Product	environn	nental attri	butes - Mark	tet req	quirements	(contin	ued)			Require	ment	met
Item										Yes	No	n.a.
	Chemica	al emissions	s from printing	g produ	ucts							
P10.3*	Test perf 171	formed acco	rding to ECMA	-328 (15	SO/IEC 2836	i0) standa	ard, other s	pecify: RAL	-UZ-122/RAL-U	z 🖂		
P10.4		emission rate	(print phase) i	s (mg/r	n):							
			Ozone <0.06			enzene <	.03 TVOC 3	.1				
P10.5									Z 171 are met fo	r: 🔀		
	C	Dust 🔀	Ozone 🔀		Styrene 🔀		Benzene 🔀		TVOC 🔀			
		nagnetic em										
P10.6	Compute program/		ets the require	ment fo	or low freque	ncy elect	romagnetic fiel	ds of the fo	llowing voluntary			
P11	Consum	able materi	als for printing	g prod	ucts							
P11.1*									uired (see P4.3).	$\square$		
P11.2*	Paper co EN12282		st-consumer re	ecycled	fibers can	be used,	provided that	it meets t	he requirements	of 🔀		
P11.3*	2-sided (	(duplex) print	ing/copying is a	an integ	grated produ	ct functio	n.			$\boxtimes$		
P12			nputing produ									
P12.1*	The disp	lay meets th	e ergonomic re	quirem	nents of ISO	9241-307	for visual disp	lay technolo	ogies.			$\mathbf{X}$
P12.2*	The phys	sical input de	vice meets the	require	ements of IS	O 9995 a	nd ISO 9241-4	10.				$\times$
P13	Packagi	ing and doc	umentation									
P13.1*	Product	packaging m	aterial type(s): aterial type(s): aterial type(s):	Polysi	tyrene, expa	nded	weight (	kg): <b>0.387</b> kg): <b>0.062</b>				
P13.2*	Product	plastic packa	aging is free fro	m PV0	C.		0 (	0/		$\boxtimes$		
P13.3*		media for use ic 🔀, Paper	er and product	docum	entation (tick	: box):						
P13.4*		er user and p		ntation	i, please spe	cify conta	ined percentag	ge of post-c	onsumer recycle	d		
Rev. P13.5			cumentation do	not co	ntain chlorin	e bleache	ed paper					
P14	Addition	nal informati	on (See Note	B4)								
P1.1			exemptions for		sed in small a	mounts fo	r specific applice	ations.				
P2.1			within this prod structions for su						roduct is properly	labeled witl	h the V	/EEE
P.2.3	The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers.											
P7.14	A small amount of bromine may be present in covers due to sourcing post consumer recycled content. No bromine was intentionally added in the processing of these parts.								added			
P7.20	Per IEEE 1	1680.2 PCR ca	lculation.									
P9.1			n P9.1 is for pro ovides energy do						eed listed is Letter	r; A4 speed i	is 38 pp	om.

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Energy mode *	Power level at 100 V AC	Power level at 115 V AC	230 V AC	Reference / Standard for energy modes and test method *			
Printing	534 W	509 W	482 W	Corporate Standard			
Сору	546 W	516 W	493 W	Corporate Standard			
Ready Mode	11.5 W	11.1 W	11.6 W	Energy Star I E V1.2			
Sleep Mode	5.1 W	5.1 W	5.3 W	Energy Star I E V1.2			
Hibernate Mode	0.26 W	0.28 W	0.39 W	IEC 62301			
Off Mode	0.0 W	0.0 W	0.0 W	IEC 62301			
EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)	w	W	w				
PTEC * Typical Energy Consumption	W	W	W				
TEC * Typical Energy Consumption	2.4 kWh/week	2.3 kWh/week	2.4 kWh/week	Energy Star I E V1.2			
ETEC * Annual Energy Consumption	kWh/year	kWh/year	kWh/year				
Display resolution* : Me	egapixels						
Print Speed * : 40 Image	s per minute			Corporate Standard			
Default time to enter energy sa	ve mode: 30 minutes			Energy Star I E V1.2	t <del>n</del>		
P9.2* Information about t	he energy save functio	n is provided with th	e product.				
P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: 1.2 Tier: 1 Product category: Imaging Equipment Others specify: RAL UZ 122							

## Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19