

Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo	
Company name *	Lexmark International, Inc.		TM
Contact information *	Drew Zande (USA)		Lexmark
Internet site *	www.lexmark.ted / www.lexmark.com		
Additional information			

	pased on product specification or test results based obtained from sample testing), that the product ts given in this declaration.
Type of product *	Multi Function Mono Laser Printer
Commercial name *	Lexmark MX510de, Lexmark MX511de, Lexmark MX511dte, Lexmark MX511dhe, Lexmark XM1145, MX517dn
Model number *	MX510de, MX511de, MX511dte, MX511dhe, XM1145, MX517dn
Issue date *	February 24, 2014 (Revised June 1, 2017)
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other
Additional information	

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control	Requireme	nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration		
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	l 🛛	

Model number *	MX510de, MX511de, MX511dte, MX511dhe, XM1145, MX517dn		
Issue date *	February 24, 2014 (Revised June 1, 2017)	Logo	Lexmark

Product	environmental attributes - Legal requirements	Require	ment	met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent	\boxtimes		
	chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See	_	_	
	legal reference and Note B1)			
P1.2*	Products do not contain Asbestos (see legal reference).	\boxtimes		
	Comment: Legal reference has no maximum concentration value.			
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),	\boxtimes		
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-			
	trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum			
P1.4*	concentration values. Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated		_	
F1.4	terphenyl (PCT) in preparations (see legal reference).	\boxtimes	Ш	
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in		$\overline{}$	
1 1.5	the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	\bowtie	ш	
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS),			\boxtimes
1 1.0	Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference).		ш	
	Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split		\Box	\boxtimes
	aromatic amines. (See legal reference and Note B1)			
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as			\boxtimes
	pentachlorophenol and derivatives (see legal reference).		_	
	Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5	\boxtimes		
	microgram/cm ² /week (see legal reference).			
	Comment: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact):	\boxtimes		
	REACH Program Manager, HOD9237, 740 W. New Circle Rd., Lexington, KY 40550			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains	\boxtimes		
	more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be			
	marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is			
P2.2*	provided in user manual. (See legal reference)		_	
P2.2	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\boxtimes	Ш	
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the	· 🔀	$\overline{}$	$\overline{}$
1 2.0	design of the product). Exception: Batteries that are permanently installed for safety, performance, medical		ш	Ш
	or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	\square	$\overline{\Box}$	\Box
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal	X	∺	∺
1 0.2	reference).		ш	Ш
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies	; X		
	with legally required standards for radio and telecommunication devices (see legal reference).		ш	ш
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\boxtimes		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see		$\overline{}$	
	legal reference and Note B1).		ш	ш
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	\boxtimes		$\neg \neg$
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the		∺	∺
1 4.5	product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these		ш	
	requirements is available (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium an	d 🔀		
-	hexavalent chromium by weight of these together.			
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	X		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montrea		Ħ	\dashv
. 0.0	Protocol (see legal reference).	. 🔼	ш	ш
	Comment: Legal reference has no maximum concentration values.			

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *	MX510de, MX511de, MX511dte, MX511dhe, XM1145, MX517dn		
Issue date *	February 24, 2014 (Revised June 1, 2017)	Logo	Lexmark

Product	environmental attributes - Market requirements - Environmental conscious design R	equire	ment	met
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P6	Treatment information			
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).	\boxtimes		
P7	Design			
D7.4*	Disassembly, recycling		_	
P7.1*	Parts that have to be treated separately are easily separable		Щ.	<u> </u>
P7.2*	Plastic materials in covers/housing have no surface coating.		<u>Ц</u>	<u>Ц</u>
P7.3*	Plastic parts >100g consist of one material or of easily separable materials.		Щ	
P7.4*	Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.	\boxtimes		
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.	\boxtimes		
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	\boxtimes		
	Product lifetime			
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes		
P7.8*	Upgrading can be done using commonly available tools	\boxtimes		
P7.9.	Spare parts are available after end of production for: 5 years			
P7.10	Service is available after end of production for: 5 years			
	Material and substance requirements			
P7.11*	Product cover/housing material type:			
	Material type: ABS Material type: HIPS Material type: PC/ABS			
P7.12	Electrical cable insulation materials of power cables are PVC free.		\boxtimes	
P7.13	Electrical cable insulation materials of signal cables are PVC free		\boxtimes	
P7.14	All cover/housing plastic parts >25g are free from chlorine and bromine.		\boxtimes	
P7.15	All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See		$\overline{\boxtimes}$	
	Note B2)			
P7.16	Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking:			
P7.17	Alt. 1		_	_
	Chemical specifications of flame retardants in printed circuit boards >25g (without components):			
	TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #:			
	Alt. 2			
	Chemical specifications of flame retardants in printed circuit boards (without components) >25g according	\bowtie		
	ISO 1043-4: <i>FR(16)</i>			
P7.18	Alt. 1			
	Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in			
	concentrations above 0.1%:			
	Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #:			
	2. Chemical name: , CAS #:			
	3. Chemical name: , CAS #:			
	Alt. 2			
	Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50)	\boxtimes		
P7.19	Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)			
P7.20	Of total plastic parts' weight >25g, recycled material content is <i>up to</i> 6%.			
P7.21	Of total plastic parts' weight >25g, biobased material content is %.			
P7.22	Light sources are free from mercury	\boxtimes		
	If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg			
P8	Batteries Detter sharped composition Lithium Managemen District Lithe C2			
P8.1*	Battery chemical composition: Lithium Manganese Dioxide, LiMnO2			<u> </u>
P8.2	Batteries meet the requirements of the following voluntary program/s:			

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	MX510de, MX511de, MX511dte, MX511dhe, XM1145, MX517dn		
Issue date *	February 24, 2014 (Revised June 1, 2017)	Logo	Lexmark

Product 6	<u>environ</u> mental a	ittributes - Market re	quirements (con	tinued)			Requi	remen	t met
Item							Ye	s No	n.a.
P9	Energy consump	otion							
9.1	For the product th	ne following power levels	or energy consump	tions are report	ted:				
Energy mo	de *	Power level at 100 V AC	Power level at 115 V AC	Power level 230 V AC	at	Reference / Standard modes and test method		energy	'
Printing		586 W	569 W	537 W		Corporate Standard			
Сору		596 W	618 W	541 W		Corporate Standard			
Ready Mo	ode	11.1 W	11.1 W	11.5 W		Energy Star I E V2.0			
Sleep Mod	de	3.3 W	3.3 W	3.4 W		Energy Star I E V2.0			
Hibernate	Mode	0.26 W	0.27 W	0.39 W		IEC 62301			
Off Mode		0.0 W	0.0 W	<i>0.0</i> W		IEC 62301			
EPS No-lo	ad	W	W	W					
charger plu	oower supply / ugged in the wall disconnected from								
PTEC *	,	W	W	W					
Typical En	ergy Consumption								
TEC *		2.4 kWh/week	2.3 kWh/week	2.3 kWh/week		Energy Star I E V2.0			+
-	ergy Consumption	2.4 KWIII WEEK	2.3 KVIII/ WEEK	2.3 KWII/WEEK		Lifergy Star 1 L V2.0			
ETEC * Annual En	ergy Consumption	kWh/year	kWh/year	kWh/ye	ar				
Display res		Megapixels							
Print Spee	d * : 45 Imag	ges per minute				ISO 24734 (US Letter)			
Default tim	e to enter energy s	save mode: 30 minutes				Energy Star I E V2.0			
P9.2*	Information about	the energy save function	on is provided with th	e product.			\boxtimes		
P9.3*	•	ts the energy requirement version: 2.0 Tier: Prod		,, ,	m/s:				
P10	Emissions	AL 02 171					X		
1 10		- Declared according to	ISO 9296						
P10.1	Mode	Mode description		Declared		Declared A-weight			
				A-weighted sound power		sound pressure level L_{I}	_{oAm} (d	В)	
				level $L_{W\! ext{Ad}}$ (B)	Ope	rator position Bysta	ander p	ositions	
				/// Kd		Desktop (only i	f produ	ct is not	
								ttended)	
	Idle	* Ready		3.3		15			
	Operation	* Simplex Monochrom Normal Mode	e Printing,	[•] 7.1		56			
	Other mode	Simplex Monochrom Quiet Mode	e Printing,	6.5		51]
	Measured accord	ŭ <u>=</u> _	ECMA-74	by ΕCMΔ-74 wit	h I	n measurement distance	,	m)	1
P10.2	The product meet					am/s: RAL-UZ 122/RAL-	<u></u>		
	117 171			gy	F. 591			ل ،	

Model number *	MX510de, MX511de, MX511dte, MX511dhe, XM1145, MX517dn		
Issue date *	February 24, 2014 (Revised June 1, 2017)	Logo	Lexmark

Product	environmental attributes - Market requirements (continued)	Require	ment	met
Item		Yes	No	n.a.
	Chemical emissions from printing products			
P10.3*	Test performed according to ECMA-328 (ISO/IEC 28360) standard, other specify: RAL-UZ-122/RAL-UZ 171			
P10.4	Typical emission rate (print phase) is (mg/h): Dust 1.3 Ozone <0.06 Styrene <0.12 Benzene <0.03 TVOC 3.4			
P10.5	Chemical emission requirements of the following voluntary program/s RAL-UZ-122/RAL-UZ 171 are met for:			
	Dust ✓ Ozone ✓ Styrene ✓ Benzene ✓ TVOC			
D40.0	Electromagnetic emissions		_	_
P10.6	Computer display meets the requirement for low frequency electromagnetic fields of the following voluntary program/s:			
P11	Consumable materials for printing products			
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).		<u>Ц</u>	Щ.
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN12281.			Ц_
P11.3*	2-sided (duplex) printing/copying is an integrated product function.	\boxtimes		
P12	Ergonomics for computing products			
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.			\boxtimes
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.			\boxtimes
P13	Packaging and documentation			
P13.1*	Product packaging material type(s): Corrugated weight (kg): 2.167			
	Product packaging material type(s): <i>Polystyrene, expanded</i> weight (kg): <i>0.595</i> Product packaging material type(s): <i>Low Density Polyethylene</i> weight (kg): <i>0.081</i>			
P13.2*	Product plastic packaging is free from PVC.	\boxtimes		
P13.3*	Specify media for user and product documentation (tick box): Electronic , Paper , Other			
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber: 0%			
Rev. P13.5	User and product documentation do not contain chlorine bleached paper			
P14	Additional information (See Note B4)			
P1.1	This product uses RoHS exemptions for lead used in small amounts for specific applications.			
P2.1	The battery contained within this product should be disposed of properly with the product. The product is properly lab disposal symbol and instructions for such disposal is listed in the product User's Guide.	eled witl	h the W	/EEE
P2.3	The battery contained within this product meets the exception listed. The battery is not intended to be removed by the however, is designed for easy removal by recyclers and service providers.	ne custon	ner;	
P7.14	A small amount of bromine may be present in covers due to sourcing post consumer recycled content. No bromine we in the processing of these parts.	ıs intentic	onally o	ıdded
P7.20	Per IEEE 1680.2 PCR calculation.			
P9.1	Information provided in P9.1 is for products with firmware FW LW30.SB4.P307 or higher. Print speed listed is Letter; A	4 speed i	s 42 pp	m.

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

					$\overline{}$
P9 Energy cons					
9.1 For the produc	ct the following power level	s or energy consump	otions are reported:		
Energy mode *	Power level a 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standard for energy modes and test method *	
Printing	586 W	569 W	537 W	Corporate Standard	
Сору	596 W	618 W	541 W	Corporate Standard	
Ready Mode	13.2 W	12.8 W	13.5 W	Energy Star I E V1.2	
Sleep Mode	5.7 W	5.8 W	6.0 W	Energy Star I E V1.2	
Hibernate Mode	0.26 W	0.27 W	0.39 W	IEC 62301	
Off Mode	0.0 W	0.0 W	0.0 W	IEC 62301	
EPS No-load	W	W	W		
(External power supply / charger plugged in the wa outlet but disconnected fro the product.)					
PTEC * Typical Energy Consumpt	ion	W	W		
TEC * Typical Energy Consumpt	2.8 kWh/week	2.7 kWh/week	2.7 kWh/week	Energy Star I E V1.2	
ETEC * Annual Energy Consumpt	kWh/year ion	kWh/year	kWh/year		\boxtimes
Display resolution* :	Megapixels		•		\boxtimes
Print Speed * : 45 In	mages per minute			Corporate Standard	
Default time to enter energ	gy save mode: 30 minutes			Energy Star I E V1.2	
P9.2* Information al	out the energy save functi	on is provided with th	ne product.		
ENERGY STA	neets the energy requireme AR® version: 1.2 Tier: 1 P r: RAL UZ 122			X D	R
Packaging displayed Packaging for MX50 Product packaging Product packaging Product packaging	The following table provides energy data for products with lower levels of firmware: Packaging displayed in P13.1 is for MX510de, MX511de, MX511dhe, and XM1145. Packaging for MX511dte: Product packaging material type(s): Corrugated weight (kg): 3.016 Product packaging material type(s): Polystyrene, expanded weight (kg): 0.6 Product packaging material type(s): Low Density Polyethylene weight (kg): 0.081				
				nay be found at http://lexmar	
Specific printer and Lexmark Sweden is		-	for your area m	ay be found at http://lexmark	.com

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19