

Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	7M
Contact information *	Drew Zande (USA)	Lexmark
Internet site *	www.lexmark.ted / www.lexmark.com	
Additional information		

	pased on product specification or test results based obtained from sample testing), that the product ts given in this declaration.
Type of product *	Multi Function Mono Laser Printer
Commercial name *	Lexmark MX610de, Lexmark MX611de, Lexmark MX611dte, MX611dhe, Lexmark XM3150, Lexmark MX617de
Model number *	MX610de, MX611de, MX611dte, MX611dhe, XM3150, MX617de
Issue date *	February 24, 2014 (Revised June 1, 2017)
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other
Additional information	

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control	Requireme	nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration		
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model number *	MX610de, MX611de, MX611dte, MX611dhe, XM3150, MX617de		
Issue date *	February 24, 2014 (Revised June 1, 2017)	Logo	Lexmark

Product	environmental attributes - Legal requirements	Require	men	met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent			
	chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See		ш	
5.1.01	legal reference and Note B1)			
P1.2*	Products do not contain Asbestos (see legal reference).	\boxtimes		
	Comment: Legal reference has no maximum concentration value.			
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),	\boxtimes		
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-			
	trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum			
	concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated			
	terphenyl (PCT) in preparations (see legal reference).			
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in	\square		
	the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).			
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS),			\boxtimes
	Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference).	ш	ш	
	Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split			\boxtimes
	aromatic amines. (See legal reference and Note B1)		ш	
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as			X
1 1.0	pentachlorophenol and derivatives (see legal reference).		ш	
	Comment: Legal reference has no maximum concentration values.			
P1.9*	•		_	
P1.9	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5	\boxtimes	Ш	
	microgram/cm ² /week (see legal reference).			
5.4.404	Comment: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact):	\boxtimes		
	REACH Program Manager, HOD9237, 740 W. New Circle Rd., Lexington, KY 40550			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains	\boxtimes		
	more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be		ш	ш
	marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is			
	provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or	\boxtimes		
	accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)		ш	ш
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the	\square		
. 2.0	design of the product). Exception: Batteries that are permanently installed for safety, performance, medica		ш	ш
	or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*			_	
	The product complies with legally required safety standards as specified (see legal reference).			_Ц_
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal			
	reference).			
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies	\square		
	with legally required standards for radio and telecommunication devices (see legal reference).	_	_	_
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\boxtimes		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see		$\overline{}$	
1 4.1	legal reference and Note B1).		ш	ш
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).		$\overline{}$	
	7 3 (9 7		Щ.	_ <u>_</u> _
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the	\boxtimes		
	product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these			
	requirements is available (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and	I 🛛		
	hexavalent chromium by weight of these together.			
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\square		
P5.3*			+	+
1.0.0	The product packaging material is free from ozone depleting substances as specified in the Montrea Protocol (see legal reference).	ı 🖂	Ш	Ш
	Comment: Legal reference has no maximum concentration values.			
	Comment. Legal reference has no maximum concentration values.			

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *	MX610de, MX611de, MX611dte, MX611dhe, XM3150, MX617de		
Issue date *	February 24, 2014 (Revised June 1, 2017)	Logo	Lexmark

Product	environmental attributes - Market requirements - Environmental conscious design Re	quire	ment	met
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P6	Treatment information			
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).	\boxtimes		
P7	Design Discounting			
P7.1*	Disassembly, recycling Parts that have to be treated separately are easily separable	\square	$\overline{}$	
P7.2*	Plastic materials in covers/housing have no surface coating.	$\overline{\mathbb{X}}$	$^{+}$	╫
P7.3*	Plastic parts >100g consist of one material or of easily separable materials.	$\overline{\mathbb{X}}$	\overline{H}	∺
P7.4*	Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.		H	∺
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.	X	H	+
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).		H	∺
1 1.0	Product lifetime			
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives			
P7.8*	Upgrading can be done using commonly available tools	X	Ħ	Ħ
P7.9.	Spare parts are available after end of production for: 5 years			Ħ
P7.10	Service is available after end of production for: 5 years			Ħ
	Material and substance requirements			
P7.11*	Product cover/housing material type:			
	Material type: ABS Material type: HIPS Material type: PC/ABS			
P7.12	Electrical cable insulation materials of power cables are PVC free.		\boxtimes	
P7.13	Electrical cable insulation materials of signal cables are PVC free		\boxtimes	
P7.14	All cover/housing plastic parts >25g are free from chlorine and bromine.		\boxtimes	
P7.15	All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See		\boxtimes	
D = 40	Note B2)			
P7.16	Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking:		Ш	Ш
P7.17	Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components):			
	TBBPA (additive), TBBPA (reactive), Other; chemical name:, CAS #:	Ш	Ш	Ш
	, one in			
	Alt. 2	_	_	
	Chemical specifications of flame retardants in printed circuit boards (without components) >25g according	\boxtimes		
P7.18	ISO 1043-4: <i>FR(16)</i> Alt. 1			
F1.10	Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in			
	concentrations above 0.1%:		ш	Ш,
	Comment: No legal limits exist, this is a market requirement.			
	1. Chemical name: , CAS #:			
	2. Chemical name: , CAS #: 3. Chemical name: , CAS #:			
	Alt. 2			
	Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50)	\boxtimes		
P7.19	Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)			
P7.20	Of total plastic parts' weight >25g, recycled material content is <i>up to 6</i> %.			
P7.21	Of total plastic parts' weight >25g, biobased material content is 4b to 66. Of total plastic parts' weight >25g, biobased material content is %.			
P7.22	Light sources are free from mercury			
	If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg]
P8	Batteries			
P8.1*	Battery chemical composition: Lithium Manganese Dioxide, LiMnO2			
P8.2	Batteries meet the requirements of the following voluntary program/s:			

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	MX610de, MX611de, MX611dte, MX611dhe, XM3150, MX617de		
Issue date *	February 24, 2014 (Revised June 1, 2017)	Logo	Lexmark

	Product e	environmental at	tributes - Market re	quirements (con	tinued)			Requi	rement	met
For the product the following power levels or energy consumptions are reported:								Yes	s No	n.a.
Power level at 100 V AC 115 V AC 230 V AC 175 V AC 230 V										
100 V AC	9.1	For the product the	following power levels	or energy consump	tions are report	ted:				
Ready Mode	Energy mod	de *				at			energy	
Ready Mode	Printing		618 W	603 W	573 W		Corporate Standar	rd		
Siep Mode 3.3 W 3.4 W Energy Star I E V2.0	Сору		610 W	601 W	578 W		Corporate Standa	rd		
## Declared Mode	Ready Mo	de	14.3 W	14.1 W	15.0 W		Energy Star I E V2	2.0		
Off Mode	Sleep Mod	'e	3.3 W	3.3 W	3.4 W		Energy Star I E V2	2.0		
EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.) TEC * Typical Energy Consumption	Hibernate	Mode	0.27 W	0.28 W	0.39 W		IEC 62301			
(External power supply / charger plugged in the wall outlet but disconnected from the product.) TEC * Typical Energy Consumption	Off Mode		0.0 W	0.0 W	0.0 W		IEC 62301			
TEC* Typical Energy Consumption 2.7 kWh/week 2.6 kWh/week 2.7 kWh/week Energy Star I E V2.0 Star I E V2.0	(External po charger plu outlet but d the product	ower supply / gged in the wall isconnected from	W		W					
Typical Energy Consumption ETEC * Annual Energy Consumption		ergy Consumption	W	W	W					
Annual Energy Consumption Display resolution*: Megapixels Print Speed * : 50 Images per minute Default time to enter energy save mode: 30 minutes P9.2* Information about the energy save function is provided with the product. P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL-UZ 171 P10 Emissions Noise emission - Declared according to ISO 9296 P10.1 Mode Mode description Declared according to ISO 9296 Node description Declared A-weighted sound power level L _{WAd} (B) Operator position Bystander positions Operator position Desktop Operator attended) or Desktop Operator attended) Other mode Simplex Monochrome Printing, Normal Mode Measured according to: Simplex Monochrome Printing, Outer Mode Measured according to: ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with L _{PAm} measurement distance m)		ergy Consumption	2.7 kWh/week	2.6 kWh/week	2.7 kWh/week		Energy Star I E V2	t.0		
Print Speed * : 50 Images per minute Default time to enter energy save mode: 30 minutes P9.2* Information about the energy save function is provided with the product. P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL-UZ 171 P10 Emissions Noise emission – Declared according to ISO 9296 P10.1 Mode Mode description P10.1 Declared A-weighted sound power level L _{WAd} (B) Operator position Bystander positions Operator position Operator attended) Idle * Ready * 3.3		ergy Consumption	kWh/year	kWh/year	kWh/ye	ar				
Default time to enter energy save mode: 30 minutes P9.2* Information about the energy save function is provided with the product. P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL-UZ 171 P10 Emissions Noise emission – Declared according to ISO 9296 P10.1 Mode Mode description Declared A-weighted sound power level L _{WAd} (B) Declared A-weighted sound pressure level L _{pAm} (dB) Operator position Desktop Or Desk side Operator attended) Idle Ready 3.3 16 Operation Simplex Monochrome Printing, 7.0 55 Other mode Simplex Monochrome Printing, 6.5 50 Weasured according to: SISO7779 ECMA-74 Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)	Display res	olution* : Me	egapixels	L						
P9.2* Information about the energy save function is provided with the product. P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL-UZ 171 P10 Emissions Noise emission – Declared according to ISO 9296 P10.1 Mode	Print Speed	d * : 50 Image	s per minute				ISO 24734 (US Le	tter)		
P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL-UZ 171 P10 Emissions Noise emission – Declared according to ISO 9296 P10.1 Mode	Default time	e to enter energy sa	ve mode: 30 minutes				Energy Star I E V2	2.0		
ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL-UZ 171 P10 Emissions Noise emission – Declared according to ISO 9296 P10.1 Mode Mode description Declared A-weighted Sound power level L _{pAm} (dB) Idle Ready Simplex Monochrome Printing, Normal Mode	P9.2*	Information about t	he energy save functio	n is provided with th	ne product.		l			
$ \begin{array}{ c c c c c } \hline \textbf{Noise emission} - \textbf{Declared according to ISO 9296} \\ \hline \textbf{P10.1} & \textbf{Mode} & \textbf{Mode description} & \textbf{Declared A-weighted sound power} \\ \hline \textbf{Idle} & \textbf{Ready} & \textbf{Simplex Monochrome Printing, Normal Mode} \\ \hline \textbf{Other mode} & \textbf{Simplex Monochrome Printing, Quiet Mode} \\ \hline \textbf{Measured according to: } & \textbf{ISO7779} & \textbf{ECMA-74} \\ \hline \textbf{ECMA-74} & \textbf{Other (only if not covered by ECMA-74 with L_{pAm} measurement distance} \\ \hline \textbf{Mode} & \textbf{Mode description} & \textbf{Declared A-weighted sound pressure level L_{pAm} (dB)} \\ \hline \textbf{Operator position} & \textbf{Bystander positions} \\ \hline \textbf{Operator Desk side} & \textbf{Operator position} & \textbf{Bystander positions} \\ \hline \textbf{Operator Desk side} & \textbf{Operator position} & \textbf{Bystander positions} \\ \hline \textbf{Other mode} & \textbf{Simplex Monochrome Printing, According to: } & \textbf{55} \\ \hline \textbf{Other mode} & \textbf{Simplex Monochrome Printing, According to: } & \textbf{50} \\ \hline \textbf{Measured according to: } & \textbf{ISO7779} & \textbf{ECMA-74} \\ \hline \textbf{Other} & \textbf{(only if not covered by ECMA-74 with L_{pAm} measurement distance} & \textbf{m}) \\ \hline \end{array}$	P9.3*	ENERGY STAR®	version: 2.0 Tier: Prod			m/s:		× ×		П
$ \begin{array}{ c c c c c }\hline P10.1 & Mode & Mode description & Declared A-weighted sound power level L_{PAm} (dB) \\ \hline & & & & & & & & & & & & \\ \hline & & & &$	P10	Emissions								
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$				ISO 9296						
Desktop Only if product is not operator attended Operation Simplex Monochrome Printing, Normal Mode Other mode Simplex Monochrome Printing, Quiet Mode Other mode Simplex Monochrome Printing, Quiet Mode Other	P10.1	Mode	Mode description		A-weighted		sound pressure leve	rel L_{pAm} (dl		
Conly if product is not operator attended Conly if product is					level L_{WAd} (B)	Ope		Bystander p	ositions	
Idle * Ready * 3.3 16 Operation * Simplex Monochrome Printing, Normal Mode Other mode Simplex Monochrome Printing, Quiet Mode Measured according to: ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with LpAm measurement distance m)							· — /		ct is not	
Normal Mode Other mode Simplex Monochrome Printing, Quiet Mode Measured according to: SISO7779 ECMA-74 □ Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)	-	Idle *	Ready	*	3.3		16	operate: at	10.1000)	П
Quiet Mode Measured according to: ☐ ISO7779 ☐ ECMA-74 ☐ Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)	-			e Printing,	* 7.0		55			
Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)				e Printing,	6.5		50			
		Measured according	· =		bv ECMA-74 wit	th Las	measurement dista	ance r	n)	
P10.2 The product meets the acoustic noise requirements of the following voluntary program/s: RAL-UZ 122/RAL-	P10.2								•	

Model number *	MX610de, MX611de, MX611dte, MX611dhe, XM3150, MX617de		
Issue date *	February 24, 2014 (Revised June 1, 2017)	Logo	Lexmark

Product	environmental attributes - Market requirements (continued)	Require	ment	met
Item		Yes	No	n.a.
	Chemical emissions from printing products			
P10.3*	Test performed according to ECMA-328 (ISO/IEC 28360) standard, other specify: RAL-UZ-122/RAL-UZ 171			
P10.4	Typical emission rate (print phase) is (mg/h): Dust <0.7 Ozone <0.06 Styrene <0.12 Benzene <0.03 TVOC 0.74			
P10.5	Chemical emission requirements of the following voluntary program/s RAL-UZ-122/RAL-UZ 171 are met for:			
	Dust ✓ Ozone ✓ Styrene ✓ Benzene ✓ TVOC			
D40.0	Electromagnetic emissions			_
P10.6	Computer display meets the requirement for low frequency electromagnetic fields of the following voluntary program/s:	Ш		<u> Ц</u>
P11	Consumable materials for printing products	<u> </u>		_
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).		<u>Ц</u>	<u>Ц</u>
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN12281.		<u> </u>	<u> </u>
P11.3*	2-sided (duplex) printing/copying is an integrated product function.	\boxtimes		
P12	Ergonomics for computing products			
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.			\boxtimes
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.			\boxtimes
P13	Packaging and documentation			
P13.1*	Product packaging material type(s): Corrugated weight (kg): 2.456			
	Product packaging material type(s): <i>Polystyrene, expanded</i> weight (kg): <i>0.6</i> Product packaging material type(s): <i>Low Density Polyethylene</i> weight (kg): <i>0.081</i>			
P13.2*	Product plastic packaging is free from PVC.	\boxtimes		
P13.3*	Specify media for user and product documentation (tick box): Electronic , Paper , Other			
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber: 0%			
Rev. P13.5	User and product documentation do not contain chlorine bleached paper			
P14	Additional information (See Note B4)			
P1.1	This product uses RoHS exemptions for lead used in small amounts for specific applications.			
P2.1	The battery contained within this product should be disposed of properly with the product. The product is properly lab disposal symbol and instructions for such disposal is listed in the product User's Guide.	eled with	the W	EEE
P2.3	The battery contained within this product meets the exception listed. The battery is not intended to be removed by the however, is designed for easy removal by recyclers and service providers.	e custom	er;	
P7.14	A small amount of bromine may be present in covers due to sourcing post consumer recycled content. No bromine we in the processing of these parts.	s intentic	nally a	dded
P7.20	Per IEEE 1680.2 PCR calculation.			
P9.1	Information provided in P9.1 is for products with firmware FW LW30.SB7.P307 or higher. Print speed listed is Letter; A The following table provides energy data for products with lower levels of firmware:	4 speed i	s 47 pp	m.

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

P9 Energy cons	sumption					
	ct the following power levels	or energy consump	tions are reported:			
Energy mode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standard for energy modes and test method *		
Printing	618 W	603 W	573 W	Corporate Standard		
Сору	610 W	601 W	578 W	Corporate Standard		
Ready Mode	16.7 W	16.5 W	16.3 W	Energy Star I E V1.2		
Sleep Mode	6.4 W	6.5 W	6.5 W	Energy Star I E V1.2		
Hibernate Mode	0.27 W	0.28 W	0.39 W	IEC 62301		
Off Mode	0.0 W	0.0 W	0.0 W	IEC 62301		
EPS No-load (External power supply / charger plugged in the wa outlet but disconnected for the product.)	om	W	W			
PTEC * Typical Energy Consump	tion	W	W			
TEC * Typical Energy Consump	3.2 kWh/week	3.1 kWh/week	3.1 kWh/week	Energy Star I E V1.2		
ETEC * Annual Energy Consumpt	kWh/year tion	kWh/year	kWh/year			
Display resolution* :	Megapixels				\boxtimes	
Print Speed * : 50 I	Images per minute			Corporate Standard	П	
Default time to enter ener	rgy save mode: 30 minutes			Energy Star I E V1.2		
P9.2* Information al	bout the energy save function	n is provided with th	e product.			
ENERGY ST	meets the energy requirement AR® version: 1.2 Tier: 1 Profy: RAL UZ 122					
Packaging for MX63 Product packaging Product packaging Product packaging	Packaging displayed in P13.1 is for MX610de, MX611de, MX611dhe, and XM3150. Packaging for MX611dte: Product packaging material type(s): Corrugated weight (kg): 3.279 Product packaging material type(s): Polystyrene, expanded weight (kg): 0.595 Product packaging material type(s): Low Density Polyethylene weight (kg): 0.081					
Specific printer and	Additional company information and company environmental policy may be found at http://lexmark Specific printer and supply item recycling information for your area may be found at http://lexmark. Lexmark Sweden is connected to REPA and El-kretsen					

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19