

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	I DVA ADIZ
Contact information *	Nadia Martin (USA)	LEXMARK
Internet site *	www.lexmark.se/www.lexmark.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	Type of product * Multi-Function Color Inkjet Printer			
Commercial name *	Lexmark S410 Series			
Model number *	S410 Series			
Issue date *	ssue date * 1/12/2012			
Intended market * 🛛 🖾 Global 🗌 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other				
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality Control			nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model number *		S410 Series					
Issue dat	sue date * 1/12/2012		Logo	LEXM	ARK		
Product	Product environmental attributes - Legal requirements Requirement me						
Item				Yes	No	n.a.	
P1		ous substances and preparations					
P1.1*		s do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexa m, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers		\boxtimes			
	legal ref	erence and Note B1)					
P1.2*	Products		\boxtimes				
P1.3*		nt: Legal reference has no maximum concentration value. s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),		\square			
		mofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetract	hloride, 1,1,1-				
		ethane, methyl bromide (see legal reference). Comment: Legal reference has no i	maximum				
D 4 4		ration values.					
P1.4*		s do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polyc (I (PCT) in preparations (see legal reference).	niorinated	\square			
P1.5*	Products	s do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 ca	rbon atoms in	\boxtimes			
		n containing at least 48% per mass of chlorine in the SCCP (see legal reference).	a amh ata (TDIC)				
P1.6*		nd leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-ph ridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference		,		\boxtimes	
		nt: Legal reference has no maximum concentration values.	/ -				
P1.7*		nd leather parts with direct skin contact do not contain more than 0.003% Azo colo	orants that split			\square	
P1.8*		amines. (See legal reference and Note B1) parts do not contain arsenic and chromium as a wood preservation treatment as v	well as				
1 1.0		orophenol and derivatives (see legal reference).					
	Comme	nt: Legal reference has no maximum concentration values.					
P1.9*		th direct and prolonged skin contact do not release nickel in concentrations above	0.5	\boxtimes			
		am/cm ² /week (see legal reference). ht: Max limit in legal reference when tested according to EN1811:1998.					
P1.10*		Article 33 information about substances in articles is available at (add URL or mai	contact):	\square			
		Program Manager, H0D9237x, 740 W. New Circle Rd., Lexington, KY 40550					
P2	Batterie	S					
P2.1*	If the pro	oduct contains a battery or an accumulator, it is labeled with the disposal symbol a					
	If the pro more tha	oduct contains a battery or an accumulator, it is labeled with the disposal symbol a an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le	ad, it shall be				
	If the pro more tha marked	oduct contains a battery or an accumulator, it is labeled with the disposal symbol a an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope	ad, it shall be				
P2.1*	If the pro more that marked provided	oduct contains a battery or an accumulator, it is labeled with the disposal symbol a an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope I in user manual. (See legal reference)	ad, it shall be r disposal is				
	If the pro more that marked provided Button c	oduct contains a battery or an accumulator, it is labeled with the disposal symbol a an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope	ad, it shall be r disposal is batteries or				
P2.1*	If the pro- more that marked provided Button c accumul Batteries	oduct contains a battery or an accumulator, it is labeled with the disposal symbol a an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope I in user manual. (See legal reference) ells used in the product do not contain more than 2% by weight of mercury. Other ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See and accumulators are easily removable by either users or service providers (as d	ad, it shall be r disposal is batteries or legal reference) lependent on th				
P2.1* P2.2*	If the pro- more that marked provided Button c accumul Batteries design c	oduct contains a battery or an accumulator, it is labeled with the disposal symbol a an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope l in user manual. (See legal reference) ells used in the product do not contain more than 2% by weight of mercury. Other ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See and accumulators are easily removable by either users or service providers (as d f the product). Exception: Batteries that are permanently installed for safety, perfor	ad, it shall be r disposal is batteries or legal reference) lependent on th				
P2.1* P2.2* P2.3*	If the pro- more that marked provided Button c accumul Batteries design c or data i	oduct contains a battery or an accumulator, it is labeled with the disposal symbol a an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope l in user manual. (See legal reference) ells used in the product do not contain more than 2% by weight of mercury. Other ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See and accumulators are easily removable by either users or service providers (as d f the product). Exception: Batteries that are permanently installed for safety, perfor ntegrity reasons do not have to be "easily removable". (See legal reference)	ad, it shall be r disposal is batteries or legal reference) lependent on th				
P2.1* P2.2* P2.3* P3	If the pro- more that marked provideo Button c accumul Batteries design c or data i Safety,	oduct contains a battery or an accumulator, it is labeled with the disposal symbol a an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope lin user manual. (See legal reference) ells used in the product do not contain more than 2% by weight of mercury. Other ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See and accumulators are easily removable by either users or service providers (as d f the product). Exception: Batteries that are permanently installed for safety, perfor ntegrity reasons do not have to be "easily removable". (See legal reference) EMC connection to the telephone network and labeling	ad, it shall be r disposal is batteries or legal reference) lependent on th ormance, medic				
P2.1* P2.2* P2.3* P3.1*	If the pro- more that marked provided Button c accumul Batteries design c or data i Safety , The prod	an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope l in user manual. (See legal reference) ells used in the product do not contain more than 2% by weight of mercury. Other ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See s and accumulators are easily removable by either users or service providers (as d f the product). Exception: Batteries that are permanently installed for safety, perfor ntegrity reasons do not have to be "easily removable". (See legal reference) EMC connection to the telephone network and labeling duct complies with legally required safety standards as specified (see legal reference	ad, it shall be r disposal is batteries or legal reference lependent on th ormance, medic ce).				
P2.1* P2.2* P2.3* P3.1* P3.2*	If the pro- more that marked provided Button c accumul Batteries design c or data i Safety , The pro- reference	an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope l in user manual. (See legal reference) ells used in the product do not contain more than 2% by weight of mercury. Other ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See and accumulators are easily removable by either users or service providers (as d f the product). Exception: Batteries that are permanently installed for safety, perfor ntegrity reasons do not have to be "easily removable". (See legal reference) EMC connection to the telephone network and labeling duct complies with legally required standards for electromagnetic compatibility (see e).	ad, it shall be r disposal is batteries or legal reference) lependent on th ormance, medic ce). e legal	e X al			
P2.1* P2.2* P2.3* P3.1*	If the pro- more that marked provided Button c accumul Batteries design c or data i Safety , The pro- reference If produc	an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope l in user manual. (See legal reference) ells used in the product do not contain more than 2% by weight of mercury. Other ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See and accumulators are easily removable by either users or service providers (as d f the product). Exception: Batteries that are permanently installed for safety, perfor ntegrity reasons do not have to be "easily removable". (See legal reference) EMC connection to the telephone network and labeling duct complies with legally required safety standards as specified (see legal reference e). t is intended for connection to a public telecom network or contains a radio transm	ad, it shall be r disposal is batteries or legal reference) lependent on th ormance, medic ce). e legal hitter, it complie	e X			
P2.1* P2.2* P2.3* P3.1* P3.2*	If the pro- more that marked provided Button c accumul Batteries design c or data i Safety , The pro- reference If production	an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope l in user manual. (See legal reference) ells used in the product do not contain more than 2% by weight of mercury. Other ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See and accumulators are easily removable by either users or service providers (as d f the product). Exception: Batteries that are permanently installed for safety, perfor ntegrity reasons do not have to be "easily removable". (See legal reference) EMC connection to the telephone network and labeling duct complies with legally required standards for electromagnetic compatibility (see e).	ad, it shall be r disposal is batteries or legal reference) lependent on th ormance, medic ce). e legal hitter, it complie ce).	e X al			
P2.1* P2.2* P2.3* P3.1* P3.1* P3.2* P3.3* P3.4*	If the pro- more that marked provided Button c accumul Batteries design c or data i Safety, The pro- reference If product with lega The pro-	an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope l in user manual. (See legal reference) ells used in the product do not contain more than 2% by weight of mercury. Other ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See s and accumulators are easily removable by either users or service providers (as d f the product). Exception: Batteries that are permanently installed for safety, perfor ntegrity reasons do not have to be "easily removable". (See legal reference) EMC connection to the telephone network and labeling duct complies with legally required safety standards as specified (see legal reference e). t is intended for connection to a public telecom network or contains a radio transm ally required standards for radio and telecommunication devices (see legal reference duct is labeled to show conformance with applicable legal requirements (see legal	ad, it shall be r disposal is batteries or legal reference) lependent on th ormance, medic ce). e legal hitter, it complie ce).	e X al			
P2.1* P2.2* P2.3* P3.1* P3.2* P3.3*	If the pro- more that marked provided Button c accumul Batteries design c or data i Safety , The prod reference If product with lega The prod If a phot	an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope l in user manual. (See legal reference) ells used in the product do not contain more than 2% by weight of mercury. Other ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See a and accumulators are easily removable by either users or service providers (as d f the product). Exception: Batteries that are permanently installed for safety, perfor ntegrity reasons do not have to be "easily removable". (See legal reference) EMC connection to the telephone network and labeling duct complies with legally required safety standards as specified (see legal reference e). et is intended for connection to a public telecom network or contains a radio transmally required standards for radio and telecommunication devices (see legal reference duct is labeled to show conformance with applicable legal requirements (see legal nable materials o conductor (drum, belt etc.) is used in the product, it does not contain cadmium r	ad, it shall be r disposal is batteries or legal reference) lependent on th ormance, medic ce). e legal hitter, it complie ce). reference).	e X al			
P2.1* P2.2* P2.3* P3.1* P3.2* P3.3* P3.4* P3.4* P4	If the pro- more that marked provided Button c accumul Batteries design c or data i Safety, The product with lega The product with lega The product with lega The product with legal reference	an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope l in user manual. (See legal reference) ells used in the product do not contain more than 2% by weight of mercury. Other ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See and accumulators are easily removable by either users or service providers (as d f the product). Exception: Batteries that are permanently installed for safety, perfor ntegrity reasons do not have to be "easily removable". (See legal reference) EMC connection to the telephone network and labeling duct complies with legally required safety standards as specified (see legal reference e). et is intended for connection to a public telecom network or contains a radio transm ally required standards for radio and telecommunication devices (see legal reference duct is labeled to show conformance with applicable legal requirements (see legal nable materials o conductor (drum, belt etc.) is used in the product, it does not contain cadmium m erence and Note B1).	ad, it shall be r disposal is batteries or legal reference) lependent on th ormance, medic ce). e legal nitter, it complie ce). reference).				
P2.1* P2.2* P2.3* P3.1* P3.2* P3.3* P3.4* P3.4* P4.1* P4.2*	If the pro- more tha marked provided Button c accumul Batteries design c or data i Safety , The prod reference If produc with lega The prod Consun If a phot legal refi	an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope l in user manual. (See legal reference) ells used in the product do not contain more than 2% by weight of mercury. Other ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See s and accumulators are easily removable by either users or service providers (as d f the product). Exception: Batteries that are permanently installed for safety, perfor ntegrity reasons do not have to be "easily removable". (See legal reference) EMC connection to the telephone network and labeling duct complies with legally required safety standards as specified (see legal reference e). t is intended for connection to a public telecom network or contains a radio transm ally required standards for radio and telecommunication devices (see legal reference duct is labeled to show conformance with applicable legal requirements (see legal nable materials o conductor (drum, belt etc.) is used in the product, it does not contain cadmium m erence and Note B1). er is used in the product, it does not contain cadmium max 0.1% by weight (see legal	ad, it shall be r disposal is batteries or legal reference) lependent on th ormance, medic ce). e legal nitter, it complie ce). reference). nax 0.01% (see egal reference).	e X al			
P2.1* P2.2* P2.3* P3.1* P3.2* P3.3* P3.4* P3.4* P4.1*	If the pro- more that marked provided Button c accumul Batteries design c or data i Safety , The prod reference If produc with lega The prod Consun If a phot legal refi- If ink/tor	an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope l in user manual. (See legal reference) ells used in the product do not contain more than 2% by weight of mercury. Other ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See and accumulators are easily removable by either users or service providers (as d f the product). Exception: Batteries that are permanently installed for safety, perfor ntegrity reasons do not have to be "easily removable". (See legal reference) EMC connection to the telephone network and labeling duct complies with legally required safety standards as specified (see legal reference e). et is intended for connection to a public telecom network or contains a radio transm ally required standards for radio and telecommunication devices (see legal reference duct is labeled to show conformance with applicable legal requirements (see legal nable materials o conductor (drum, belt etc.) is used in the product, it does not contain cadmium m erence and Note B1).	ad, it shall be r disposal is batteries or legal reference) lependent on th ormance, medic ce). e legal nitter, it complie ce). reference). nax 0.01% (see egal reference). egal reference).				
P2.1* P2.2* P2.3* P3.1* P3.2* P3.3* P3.4* P3.4* P4.1* P4.2*	If the pro- more that marked provided Button c accumul Batteries design c or data i Safety , The prod reference If produc with lega The prod Consum If a phot legal refi- If ink/tor	an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope l in user manual. (See legal reference) ells used in the product do not contain more than 2% by weight of mercury. Other ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See s and accumulators are easily removable by either users or service providers (as d f the product). Exception: Batteries that are permanently installed for safety, perfor ntegrity reasons do not have to be "easily removable". (See legal reference) EMC connection to the telephone network and labeling duct complies with legally required safety standards as specified (see legal reference duct complies with legally required standards for electromagnetic compatibility (see e). tt is intended for connection to a public telecom network or contains a radio transmally required standards for radio and telecommunication devices (see legal reference) duct is labeled to show conformance with applicable legal requirements (see legal nable materials o conductor (drum, belt etc.) is used in the product, it does not contain cadmium m erence and Note B1). ter is used in the product, it does not contain cadmium max 0.1% by weight (see legal //toner formulation/preparation is classified as hazardous according to applicable m packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with	ad, it shall be r disposal is batteries or legal reference) lependent on th ormance, medic ce). e legal nitter, it complie ce). reference). nax 0.01% (see egal reference). egal reference).	e X al			
P2.1* P2.2* P2.3* P3.1* P3.2* P3.3* P3.4* P3.4* P4.1* P4.1* P4.2* P4.3*	If the pro- more tha marked provided Button c accumul Batteries design c or data i Safety . The prod The prod Consun If a phot legal refi If ink/tor If the ink product/ requirem	an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope l in user manual. (See legal reference) ells used in the product do not contain more than 2% by weight of mercury. Other ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See s and accumulators are easily removable by either users or service providers (as d f the product). Exception: Batteries that are permanently installed for safety, perfor ntegrity reasons do not have to be "easily removable". (See legal reference) EMC connection to the telephone network and labeling duct complies with legally required safety standards as specified (see legal reference e). t is intended for connection to a public telecom network or contains a radio transmally required standards for radio and telecommunication devices (see legal reference duct is labeled to show conformance with applicable legal requirements (see legal nable materials o conductor (drum, belt etc.) is used in the product, it does not contain cadmium m erence and Note B1). ter is used in the product, it does not contain cadmium max 0.1% by weight (see legal rotor formulation/preparation is classified as hazardous according to applicable m packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with ents is available (see legal reference).	ad, it shall be r disposal is batteries or legal reference) lependent on th ormance, medic ce). e legal hitter, it complie ce). reference). hax 0.01% (see legal reference). egulations, the th these	s			
P2.1* P2.2* P2.3* P3.1* P3.2* P3.3* P3.4* P4.1* P4.1* P4.2* P4.3*	If the pro- more tha marked provided Button c accumul Batteries design c or data i Safety . The product if produc with lega The product Consun If a phot legal refi If ink/tor If the ink product/ requirem Product	an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope lin user manual. (See legal reference) ells used in the product do not contain more than 2% by weight of mercury. Other ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See s and accumulators are easily removable by either users or service providers (as d f the product). Exception: Batteries that are permanently installed for safety, perfor ntegrity reasons do not have to be "easily removable". (See legal reference) EMC connection to the telephone network and labeling duct complies with legally required safety standards as specified (see legal reference) e). t is intended for connection to a public telecom network or contains a radio transm ally required standards for radio and telecommunication devices (see legal reference) uct is labeled to show conformance with applicable legal requirements (see legal nable materials o conductor (drum, belt etc.) is used in the product, it does not contain cadmium m erence and Note B1). er is used in the product, it does not contain cadmium max 0.1% by weight (see legal /toner formulation/preparation is classified as hazardous according to applicable re packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with nents is available (see legal reference).	ad, it shall be r disposal is batteries or legal reference) lependent on th ormance, medic ce). ce). e legal nitter, it complie ce). reference). nax 0.01% (see egal reference). egulations, the th these				
P2.1* P2.2* P2.3* P3.1* P3.2* P3.3* P3.4* P4.1* P4.2* P4.3* P4.3*	If the pro- more tha marked provided Button c accumul Batteries design c or data i Safety. The prod The prod Consun If a phot legal refi- If ink/tor If the ink product/ requirem Product Packagi hexavale Plastic p	an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope lin user manual. (See legal reference) ells used in the product do not contain more than 2% by weight of mercury. Other ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See s and accumulators are easily removable by either users or service providers (as d f the product). Exception: Batteries that are permanently installed for safety, perfor ntegrity reasons do not have to be "easily removable". (See legal reference) EMC connection to the telephone network and labeling duct complies with legally required safety standards as specified (see legal reference e). tt is intended for connection to a public telecom network or contains a radio transm ally required standards for radio and telecommunication devices (see legal reference) duct is labeled to show conformance with applicable legal requirements (see legal nable materials o conductor (drum, belt etc.) is used in the product, it does not contain cadmium m erence and Note B1). Her is used in the product, it does not contain cadmium max 0.1% by weight (see lef /toner formulation/preparation is classified as hazardous according to applicable re packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with ents is available (see legal reference). Epackaging mg and packaging components do not contain more than 0.01% lead, mercure ent chromium by weight of these together.	ad, it shall be r disposal is batteries or legal reference) lependent on th ormance, medic ce). e legal hitter, it complie ce). reference). hax 0.01% (see legal reference). egulations, the th these y, cadmium ar al reference).	s X			
P2.1* P2.2* P2.3* P3.1* P3.2* P3.3* P3.4* P4.1* P4.1* P4.2* P4.3* P4.3*	If the pro- more tha marked provided Button c accumul Batteries design c or data i Safety , The product reference If produc with lega The product/ requirem Product / Packagi hexavale Plastic p The pro Protocol	an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of le with the chemical symbol for the metal concerned, Hg or Pb. Information on prope lin user manual. (See legal reference) ells used in the product do not contain more than 2% by weight of mercury. Other ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See s and accumulators are easily removable by either users or service providers (as d f the product). Exception: Batteries that are permanently installed for safety, perfor ntegrity reasons do not have to be "easily removable". (See legal reference) EMC connection to the telephone network and labeling duct complies with legally required safety standards as specified (see legal reference) e). t is intended for connection to a public telecom network or contains a radio transm ally required standards for radio and telecommunication devices (see legal reference) duct is labeled to show conformance with applicable legal requirements (see legal nable materials o conductor (drum, belt etc.) is used in the product, it does not contain cadmium m erence and Note B1). The is used in the product, it does not contain cadmium max 0.1% by weight (see legal /toner formulation/preparation is classified as hazardous according to applicable r packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with tents is available (see legal reference). * packaging mg and packaging components do not contain more than 0.01% lead, mercur ent chromium by weight of these together. aackaging material is marked according to ISO 11469 referring ISO 1043 (see legal	ad, it shall be r disposal is batteries or legal reference) lependent on th ormance, medic ce). e legal hitter, it complie ce). reference). hax 0.01% (see legal reference). egulations, the th these y, cadmium ar al reference).	s X			

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *		S410 Series					
Issue date *		1/12/2012	Logo	LEXM	ARK		
Product	Product environmental attributes - Market requirements - Environmental conscious design Requirement						
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.				No	n.a.	
P6	*=mandatory to fill in. Additional information regarding each item may be found under P14. Yes No n.a Treatment information						
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).						
P7	Design						
	Disassembly, recycling						
P7.1*	Parts that	t have to be treated separately are easily separable		\boxtimes			
P7.2*	Plastic m	aterials in covers/housing have no surface coating.			\boxtimes		
P7.3*	Plastic p	arts >100g consist of one material or of easily separable materials.			Ē		
P7.4*	Plastic p	arts >25g have material codes according to ISO 11469 referring ISO 1043.			Ħ	Ħ	
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly a	vailable tools.		\exists	H	
P7.6*	-	re easily separable. (This requirement does not apply to safety/regulatory labels).			╞	\mathbf{H}	
17.0	Product						
P7.7*		g can be done e.g. with processor, memory, cards or drives					
P7.8*				<u> </u>	╞		
		g can be done using commonly available tools				\boxtimes	
P7.9.	<u> </u>	rts are available after end of production for: years					
P7.10		s available after end of production for: years					
D7 44		and substance requirements					
P7.11*		cover/housing material type:	L to use a c				
P7.12	Flootrigo	type: ABS Material type: HIPS Materia I cable insulation materials of power cables are PVC free. VC Free. VC	і туре:				
				<u> </u>			
P7.13		I cable insulation materials of signal cables are PVC free					
P7.14		/housing plastic parts >25g are free from chlorine and bromine.					
P7.15	Note B2)		1249-2-21. (See	•			
P7.16	Flame re Marking:	tarded plastic parts >25g in covers / housings are marked according ISO 1043-4:				\boxtimes	
P7.17		I specifications of flame retardants in printed circuit boards >25g (without compone additive) , TBBPA (reactive) , Other; chemical name: , CAS #:	nts):				
	ISO 1043	l specifications of flame retardants in printed circuit boards (without components) > 3-4: <i>FR</i> (16)	25g according				
P7.18	concentr	etarded plastic parts >25g contain the following flame retardant substances ations above 0.1%: ent: No legal limits exist, this is a market requirement.	/preparations in				
	2. Chem 3. Chem Alt. 2	ical name: , CAS #: ical name: , CAS #: ical name: , CAS #:					
		I specifications of flame retardants in plastic parts >25g according ISO 1043-4:					
P7.19	R40, R46	arts >25g are free from flame retardant substances/ preparations above 0.1% class 5, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	atied as R45,				
P7.20		plastic parts' weight >25g, recycled material content is %.					
P7.21		plastic parts' weight >25g, biobased material content is %.					
P7.22		Irces are free from mercury	ma	\boxtimes			
P8	Batterie	y is used specify: Number of lamps: and max. mercury content per lamp:	mg				
P8.1*		hemical composition: Lithium Manganese Dioxide (LiMnO2)					
P8.2		meet the requirements of the following voluntary program/s:					
F 0.2	Datteries	meet me requirements of the following voluntary program/s.					

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	S410 Seri	ies					
Issue date *	•* 1/12/2012 Logo LEXMARK						
Des des transistant		-		· (
Item	Product environmental attributes - Market requirements (continued) Requirement meters tem Yes No n.a						n.a.
	consumpti	on				163 110	n.a.
		following power levels	or energy consump	otions are report	ted:		
Energy mode *		Power level at 100 V AC	Power level at 115 V AC	Power level 230 V AC	at	Reference / Standard for energy modes and test method *	
Printing		W	W	16.1 W		Corporate Standard	
Ready Mode		5.64 W	5.70 W	6.40 W		Energy Star I E V1.2	
Sleep Mode		2.7 W	2.8 W	3.1 W		Energy Star I E V1.2	
Off Mode		0.25 W	0.27 W	0.36 W		IEC 62301	H
Scan		W	W	11.4 W		Corporate Standard	H
Сору		W	W	14.8 W		Corporate Standard	H
EPS No-load (External power sup charger plugged in th	is No-load W 0.12 W 0.20 W Energy Star External Power S remain power supply / ger plugged in the wall but disconnected from 0.12 W 0.20 W Energy Star External Power S Test Procedure		Energy Star External Power Supply				
PTEC * Typical Energy Cons	sumption	W	W	W			
TEC * Typical Energy Consumption		kWh/week	kWh/week	kWh/week			
ETEC * Annual Energy Cons	sumption	kWh/year	kWh/year	kWh/year			
Display resolution*	: Me	gapixels					
Print Speed *	: 35 Images	s per minute				Corporate Standard	
		ve mode: 60 minutes			Energy Star I E V1.2		
			n is provided with th	ne product			
P9.3* The proc ENERG Others s							
P10 Emissio		Declared according to	150 9296				
P10.1 Mode	A-weighted sound powersound pressure level L_{pAm} (dlevel L_{WAd} (B)Operator positionBystander pDesktopOperator positionOperator pointOperator positionOperator positionOperator position		sound pressure level L_{pAm} (dB) rator position Bystander positions Desktop (only if product is not				
Idle	*	Ready		* 3.3		operator attended)	
Operatio		Monochrome Printing	g, Default Mode	* 6.0		46	18
Other m	ode	Monochrome Scanni		5.9	45		
							-
		Other				n measurement distance m)	
P10.2 The proc	duct meets	the acoustic noise req	uirements of the fol	lowing voluntary	progra	am/s: RAL-UZ-122	

Model nu	mber *	S410 Series				
Issue date	e *	1/12/2012 Logo	LE	XM	RK	
					TN	
Product environmental attributes - Market requirements (continued)						met
Item				Yes	No	n.a.
	Chemic	al emissions from printing products				
P10.3*	Test per	rformed according to ECMA-328 (ISO/IEC 28360) standard 🔲, other specify:			\boxtimes	
P10.4		emission rate (print phase) is (mg/h):				
		Dust Ozone Styrene Benzene TVOC				
P10.5	Chemica	al emission requirements of the following voluntary program/s are met for :				
		Dust Ozone Styrene Benzene TVOC				
		magnetic emissions				
P10.6	Comput program	er display meets the requirement for low frequency electromagnetic fields of the following v n/s :	oluntary			
P11		nable materials for printing products				
P11.1*		y Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (se		\bowtie		
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of 🔀 🔲					
P11.3*	2-sided	(duplex) printing/copying is an integrated product function.		\boxtimes		
P12	Ergono	mics for computing products				
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.					
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.					
P13		ing and documentation				
P13.1*		packaging material type(s): Corrugated weight (kg): 1.189				
		packaging material type(s): <i>EPS Foam</i> weight (kg): 0.195				
P13.2*	Product	packaging material type(s): weight (kg): plastic packaging is free from PVC.		\square		
P13.3*		media for user and product documentation (tick box):				
1 10.0		c				
P13.4*		er user and product documentation, please specify contained percentage of post-consume	r recycled			
P14		nal information (See Note B4)				
P1.1		oduct uses RoHS exemptions for lead used in small amounts for specific application	s.			
P2.1	The ba	ttery contained within this product should be disposed of properly with the produ	ict. The pro	oduct i	s pro	perly
	labeled	with the WEEE disposal symbol and instructions for such disposal is listed in the p	roduct User'	s Guid	е.	
P.2.3	The bat	ttery contained within this product meets the exception listed. The battery is not into	ended to be	remov	ed by	the
		er; however, is designed for easy removal by recyclers and service providers.				
	Additio	nal company information and company environmental policy may be found at http://	/lexmark.cor	n/envir	onme	nt
	Specific	c printer and supply item recycling information for your area may be found at http://l				
	Lexmar	k Sweden is connected to REPA and El-kretsen				

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19