



Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	
Contact information *	Nadia Martin (USA)	LEXM ARK _™
Internet site *	www.lexmark.se / www.lexmark.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.					
Type of product *	lulti-Function Monochrome Laser Printer				
Commercial name *	exmark X203n				
Model number *	X203n				
Issue date *	5/28/2009				
Intended market *	Global Europe Asia, Pacific & Japan Americas Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control	Requireme	ent met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration		
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).	\boxtimes	

Model number *	X203n		
Issue date *	5/28/2009	Logo	LEXMARK

Product	duct environmental attributes - Legal requirements			Requirement met		
Item		Yes	No	n.a.		
P1	Hazardous substances and preparations					
P1.1*	Products do not contain lead max 0.1%, cadmium max 0.01%, mercury max 0.1%, hexavalent chromium	\boxtimes				
	max 0.1%, polybrominated biphenyls (PBB) max 0.1% and polybrominated diphenyl ethers (PBDE) max		_			
	0,1% (see legal reference and Note 1).					
P1.2*	Products do not contain Asbestos (see legal reference).	\boxtimes				
	Comment: Legal reference has no maximum concentration value.					
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),	\boxtimes				
	hydrobromofluorocarbons (HBFC), hydrochlorofluorocarbons (HCFC), Halons, carbontetrachloride, 1,1,1-					
	trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.					
P1.4*	Products do not contain polychlorinated biphenyl (PCB) max 0.005% by weight, polychlorinated terphenyl		$\overline{}$			
Г 1. 4	(PCT) max 0.005% by weight (see legal reference).		Ш			
P1.5*	Products do not contain short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing		\neg			
1 1.5	at least 48% per mass of chlorine in the SCCP max 0.1% (see legal reference).		Ш			
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS),	\neg	$\overline{}$	\boxtimes		
1 1.0	Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference).		Ш			
	Comment: Legal reference has no maximum concentration values.					
P1.7*	Textile and leather parts with direct skin contact do not contain Azo colorants that split aromatic amines		\Box	X		
	max 0.003% by weight (see legal reference and Note 1).	ш	ш			
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as		П	\boxtimes		
	pentachlorophenol and derivatives (see legal reference).					
	Comment: Legal reference has no maximum concentration values.					
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5	\boxtimes	П			
	microgram/cm2/week (see legal reference).			_		
	Comment: Max limit in legal reference when tested according to EN1811:1998.					
P2	Batteries					
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains	\boxtimes				
	more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be					
	marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is					
P2.2*	provided in user manual. (See legal reference)		$\overline{}$			
P2.2	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\boxtimes	Ш	Ш		
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the	\boxtimes	$\overline{}$	$\overline{}$		
1 2.5	design of the product). Exception: Batteries that are permanently installed for safety, performance, medical		Ш	Ш		
	or data integrity reasons do not have to be "easily removable". (See legal reference)					
P3	Safety, EMC connection to the telephone network and labeling					
P3.1*	The product complies with legally required safety standards as specified (see legal reference).		$\overline{\Box}$			
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).		∺	+		
			Щ.			
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies	\boxtimes				
D2 4*	with legally required standards for radio and telecommunication devices (see legal reference).					
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).		<u>Ш</u>			
P4	Consumable materials					
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see	\boxtimes				
	legal reference and Note 1).					
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).					
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the	\square				
	product/packaging is adequately labeled and a Safety Data Sheet (SDS/MSDS) in accordance with these					
	requirements (see legal reference).					
P5	Product packaging					
P5.1*	Packaging and packaging components do not contain lead, mercury, cadmium and hexavalent chromium	\boxtimes				
DE 0*	max 0.01% by weight of these together.					
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\boxtimes				
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal	\boxtimes				
	Protocol (see legal reference).			_ _		
	Comment: Legal reference has no maximum concentration values.					

Note 1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *	X203n		
Issue date *	5/28/2009	Logo	LEXMARK

**mandatory to fill in . Additional information regarding each item may be found under P14.	Produc	ct environmental attributes - Market requirements - Environmental conscious design	Require	men	met			
Pictification for recyclers/restment facilities is available (see legal reference).		*=mandatory to fill in. Additional information regarding each item may be found under P14.						
Disassembly, recycling P7.1* Parts that have to be treated separately are easily separable P7.2* Plastic materials in covers/housing have no surface coating. P7.3* Plastic parts -1200 consist of one material or of sasily separable materials. P7.4* Plastic parts -1200 consist of one material or of sasily separable materials. P7.4* Plastic parts -1200 consist of one material or of sasily separable materials. P7.5* Plastic parts -1200 consist of one material or of sasily separable materials. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.8* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done using commonly available tools P7.9* Spere parts are available after end of production for: 5 years P7.10* Service is available after end of production for: 5 years P7.10* Product cover/housing material type: Material and substance requirements P7.11* Product cover/housing material type: Material type: HIPS Material type: PC/ABS Material type: PC/ABS Material type: PC/ABS Material type: PC/ABS P7.12* Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1) P7.14* All cover/housing plastic parts >25g are halogen free (including PVC). (See Note 1) P7.15* All printed circuit boards (without components) >25g are halogen free. (See Note 2) P7.16* P7.16* P7.16* P7.17* P7.10* P7.17* P7.10* P7								
Disassembly, recycling		<u> </u>						
P7.1° Plastic materials in covers/housing plastic parts 25g are halogen free (including PVC). (See Note 1) P7.1° Plastic parts 25g are halogen free (including PVC). (See Note 1) P7.1° Plastic parts 25g are halogen free (including PVC). (See Note 1) P7.1° Plastic parts 25g are halogen free. (See Note 2) P7.1° All cover/housing plastic parts 25g in covers / housings are marked according ISO 1043-4: #R/46) P7.1° Product lifetime P7.2° Product lifetime P7.3° Upgrading can be done e.g. with processor, memory, cards or drives P7.8° Upgrading can be done e.g. with processor, memory, cards or drives P7.8° Upgrading can be done using commonly available tools P7.9° Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11¹ Product cover/housing material type: Material type: HIPS Material type: PC/ABS Electrical cable insulation material of power cables are halogen free (including PVC). (See Note 1) P7.14 All cover/housing plastic parts >25g are halogen free. (See Note 2) P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2) P7.16 P1.17 Alt 1 P6.17 Alt 1 P6.18 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (radditive)	P7							
P7.2* Plastic materials in covers/housing have no surface coating. P7.3* Plastic parts >100g consist of one material or of easily separable materials. P7.4* Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043. P7.5* Plastic parts 25g have material codes according to ISO 11469 referring ISO 1043. P7.5* Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.6* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done e.g. with processor, memory, cards or drives P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11* Product cover/housing material type: Material type: Material type: PC/ABS P7.12 Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1) P7.13 Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1) P7.14 All cover/housing plastic parts >25g are halogen free. (See Note 1) P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #: Alt. 2 Chemical name: , CAS #: Alt. 1 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according Dr. P7.18 Alt. 1 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according Dr. P7.18 Alt. 1 Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g	P7.1*		\boxtimes	П	П			
P7.3° Plastic parts >100g consist of one material or of easily separable materials. P7.4° Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043. P1.5° Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6° Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Product lifetime P7.7° Upgrading can be done e.g. with processor, memory, cards or drives P7.8° Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 5 years Material and substance requirements P7.11° Product cover/housing material type: Materi	P7.2*	Plastic materials in covers/housing have no surface coating.		Ħ	Ħ			
P7.4* Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043. P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.6* Usgrading can be done e.g. with processor, memory, cards or drives P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 5 years Material and substance requirements P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11* Product cover/housing material type: HIPS Material type: ABS Material type: ABS Material type: ABS Material type: HIPS Material type: HIPS Material type: ABS Material adough free (including PVC). (See Note 1) P7.13 Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1) P7.14 All cover/housing plastic parts >25g are halogen free. (See Note 2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive)	P7.3*			Ħ				
P7.6 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7 Upgrading can be done e.g. with processor, memory, cards or drives P7.8 Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11 Product cover/housing material type: MIPS Material and substance requirements P7.12 Electrical cable insulation material of power cables are halogen free (including PVC). (See Note 1) P7.13 Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1) P7.14 All cover/housing plastic parts >25g are halogen free. (See Note 1) P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR(16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 2. Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50) P7.19 Of total plastic parts yeight >25g, biobased material content is %.	P7.4*	Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.		Ħ				
P7.6° Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Product lifetime Product on the production for: 5 years Product on the production for: 5 years Product over/housing naterial production for: 5 years Product over/housing material type: Material and substance requirements Product over/housing material type: Material type: ABS Material type: ABS Material type: ABS Material type: ABS Product over/housing material of power cables are halogen free (including PVC). (See Note 1) Product over/housing plastic parts >25g are halogen free (including PVC). (See Note 1) Product over/housing plastic parts >25g are halogen free (including PVC). (See Note 1) Product over/housing plastic parts >25g are halogen free. (See Note 1) Product over/housing plastic parts >25g are halogen free. (See Note 2) Product over/housing plastic parts >25g in covers / housings are marked according ISO 1043-4: Product over/housing sare marked according ISO 1043-4: Product over/housing ISO 1043-4	P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.		Ħ	Ħ			
P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11* Product cover/housing material type: Material type: ABS P7.12 Electrical cable insulation material of power cables are halogen free (including PVC). (See Note 1) P7.13 Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1) P7.14 All cover/housing plastic parts >25g are halogen free. (See Note 1) P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR/40) P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) TBBPA (reactive) Other; chemical name: CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR/16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: 2. Chemical name: 3. Chemical name: 4. Chemical name: CAS #: 3. Chemical name: CAS #: Alt. 2 Chemical name: CAS #: Alt. 3 Chemical name: CAS #: Alt. 4 CAP #: Alt. 4 CAP #: Alt. 5 CAP #: Alt. 6 CAP #: Alt. 7 CAP #: Alt. 8 Alt. 9 Alt. 9 Alt. 1 CAP #: Alt. 1 CAP #: Alt. 1 CAP #: Alt. 1 CAP #: Alt. 2 CAP #: Alt. 3 CAP #: Alt. 4 CAP #: Alt. 4 CAP #: Alt. 4 CA	P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).		$\overline{\sqcap}$	П			
P7.8' Upgrading can be done using commonly available tools Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11' Product cover/housing material type: Material type: ABS Material type: HIPS Material type: ABS Material type: HIPS Material type: ABS Material type: HIPS Material type: PC/ABS		Product lifetime						
P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11 Service is available after end of production for: 5 years P7.11 Product cover/housing material type: Material type: ABS Material type: HIPS Material type: PC/ABS P7.12 Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1)	P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	$\overline{\boxtimes}$					
P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11* Product cover/housing material type: Material type: ABS Material type: HIPS Material type: PC/ABS P7.12 Electrical cable insulation material of power cables are halogen free (including PVC). (See Note 1)	P7.8*	Upgrading can be done using commonly available tools	_	П				
Material and substance requirements	P7.9.	Spare parts are available after end of production for: 5 years						
P7.11* Product cover/housing material type: Material type: Material type: ABS Material type: ABS Material type: PC/ABS P7.12 Electrical cable insulation material of power cables are halogen free (including PVC). (See Note 1) P7.13 Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1) P7.14 All cover/housing plastic parts >25g are halogen free. (See Note 1) P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR(16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4. CAS #: 3. Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50) P7.19 Of total plastic parts' weight >25g, recycled material content is %. P7.20 Of total plastic parts' weight >25g, biobased material content is %.	P7.10	Service is available after end of production for: 5 years			Ħ			
Material type: ABS Material type: HIPS Material type: PC/ABS P7.12 Electrical cable insulation material of power cables are halogen free (including PVC). (See Note 1) P7.13 Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1) P7.14 All cover/housing plastic parts >25g are halogen free. (See Note 1) P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) , TBBPA (reactive) , Other; chemical name: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR(16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: 2. Chemical name: 3. Chemical name: 4. CAS #: 3. Chemical name: CAS #: CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50), FR(50) P7.19 Of total plastic parts' weight >25g, recycled material content is %.		Material and substance requirements						
P7.12 Electrical cable insulation material of power cables are halogen free (including PVC). (See Note 1) P7.13 Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1) P7.14 All cover/housing plastic parts >25g are halogen free. (See Note 1) P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive), TBBPA (reactive), Other; chemical name:, CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR(16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name:, CAS #: 2. Chemical name:, CAS #: 3. Chemical name:, CAS #: 4.1. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50) P7.19 Of total plastic parts' weight >25g, recycled material content is	P7.11*							
P7.13 Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1) P7.14 All cover/housing plastic parts >25g are halogen free. (See Note 1) P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive), TBBPA (reactive), Other; chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR(16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4lt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50) P7.19 Of total plastic parts' weight >25g, recycled material content is %. P7.20 Of total plastic parts' weight >25g, biobased material content is %.	D= 10							
P7.14 All cover/housing plastic parts >25g are halogen free. (See Note 1) P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:			<u>L</u> _		Щ			
P7.15 All printed circuit boards (without components) >25g are halogen free. (See Note 2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:				\boxtimes				
P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR(16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4lt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50) P7.19 Of total plastic parts' weight >25g, recycled material content is %. P7.20 Of total plastic parts' weight >25g, recycled material content is %.			\boxtimes					
Marking: FR(40) P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR(16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4.1. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50) P7.19 Of total plastic parts' weight >25g, recycled material content is %. P7.20 Of total plastic parts' weight >25g, biobased material content is %.		, , , , , , , , , , , , , , , , , , , ,		\boxtimes				
Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR(16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4lt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50) P7.19 Of total plastic parts' weight >25g, recycled material content is %. P7.20 Of total plastic parts' weight >25g, biobased material content is %.		Marking: FR(40)						
Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR(16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: 2. Chemical name: 3. Chemical name: 4. CAS #: 3. Chemical name: 5. CAS #: 4. CAS #: 6. CAS #: 7. Of total plastic parts' weight >25g, recycled material content is 7. CAS #: 8. CAS #: 97.19 Of total plastic parts' weight >25g, biobased material content is 96.	P7.17			П				
Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR(16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4lt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50) P7.19 Of total plastic parts' weight >25g, recycled material content is %. P7.20 Of total plastic parts' weight >25g, biobased material content is %.		TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #:	_		_			
ISO 1043-4: FR(16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: 2. Chemical name: 3. Chemical name: 4. CAS #: 3. Chemical name: 5. CAS #: 4lt. 2 6. Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50) P7.19 Of total plastic parts' weight >25g, recycled material content is 7. CAS #: 8. CAS #:		Alt. 2						
P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: 2. Chemical name: 3. Chemical name: 4. CAS #: 2. Chemical name: 5. CAS #: 6. CAS #: 6. CAS #: 7. CAS #: 7. CAS #: 8. CAS #: 9.								
concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: 2. Chemical name: 3. Chemical name: 4. CAS #: CAS #: CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50) P7.19 Of total plastic parts' weight >25g, recycled material content is P7.20 Of total plastic parts' weight >25g, biobased material content is %.	P7.18	Alt. 1						
1. Chemical name: 2. Chemical name: 3. Chemical name: 4. CAS #: CAS #: CAS #: CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50) P7.19 Of total plastic parts' weight >25g, recycled material content is P7.20 Of total plastic parts' weight >25g, biobased material content is %.		concentrations above 0.1%:	Ш					
2. Chemical name: 3. Chemical name: CAS #: CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50) P7.19 Of total plastic parts' weight >25g, recycled material content is P7.20 Of total plastic parts' weight >25g, biobased material content is %.		Comment: No legal limits exist, this is a market requirement.						
3. Chemical name: CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50) P7.19 Of total plastic parts' weight >25g, recycled material content is %. P7.20 Of total plastic parts' weight >25g, biobased material content is %.		1. Chemical name: , CAS #:						
Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50) P7.19 Of total plastic parts' weight >25g, recycled material content is %. P7.20 Of total plastic parts' weight >25g, biobased material content is %.		·						
Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50) P7.19 Of total plastic parts' weight >25g, recycled material content is %. P7.20 Of total plastic parts' weight >25g, biobased material content is %.		3. Chemical name: CAS #:						
Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50) P7.19 Of total plastic parts' weight >25g, recycled material content is %. P7.20 Of total plastic parts' weight >25g, biobased material content is %.		Alt. 2	\square					
P7.19 Of total plastic parts' weight >25g, recycled material content is %. P7.20 Of total plastic parts' weight >25g, biobased material content is %.		Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:		Ш	Ш			
P7.20 Of total plastic parts' weight >25g, biobased material content is %.	P7.19							
	P7.21	Light sources are free from mercury						
If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg	Do							
P8 Batteries P8.1* Battery chemical composition: Lithium Manganese Dioxide (LiMnO2)								
P8.2 Batteries meet the requirements of the following voluntary program/s:		Battery chemical composition: Lithium Manganese Dioxide (LiMnO2)						

Note 1 For cables, covers & housing plastic parts and plastic packaging materials in this standard; halogens include fluorine, chlorine, bromine, and iodine.

Note 2 In accordance with JPCA-ES-01; printed wiring boards must not contain more than 0.09% by weight (900ppm) of chlorine or bromine.

Model number *	X203n		
Issue date *	5/28/2009	Logo	LEXMARK

Produc	Product environmental attributes - Market requirements (continued) Requirement met							met	
Item			Yes No n.a					n.a.	
P9	Energy consump								
9.1 For the product the following power levels or energy consumptions have been measured:									
Energy n	node *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC		Reference / Star and test method	ndard for energy r	nodes	
Printing		W	341.3 W	327.6 W		Corporate Stan	dard		
Copying	J	W	301.5 W	294.9 W		Corporate Stan	dard		
Scannin	g	W	44.3 W	51.7 W		Corporate Stan	dard		
Ready N	lode	W	50.0 W	52.4 W		Energy Star TE	C Test Procedur	'e	
Sleep M	ode	W	8.65 W	8.79 W		Energy Star TE	C Test Procedur	e e	
Off		W	0.00 W	0.00 W		IEC 62301 / Ene	rgy Star		
charger p	I power supply / olugged in the wall t disconnected from	W	W	W					
PTEC * Typical E	Energy Consumptio	W	W	W					
TEC * Typical E	Energy Consumptio	kWh/week	2.75 kWh/week	2.74 kWh/weel	k				
Default ti	me to enter energy	save mode: 5 minutes	<u> </u>						
P9.2*	Information about	the energy save function	n is provided with t	he product.			×	1 🗆	Ħ
P9.3*	The product meet ENERGY STAR® Others specify:	s the energy requirement version 1.1 Tier:	nts of the following	voluntary progran	n/s:				
P10	Emissions								
	Noise emission -	 Declared according to 	ISO 9296						
P10.1	Mode	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$			ions 🔀	-			
	Idle	* Ready		* 3.9			23		
	Operation	* Simplex Monochrom	o Printing	* 6.5			51		-
	Operation	Simplex Monochroni	le Printing	0.5			31		Ш
	Other mode	"Quiet Mode" Monoc	chrome Printing	6.1			47		
	Measured accordi	Ŭ <u>=</u> _	ECMA-74 (only if not covered	d by ECMA-74 wit	h L _{pAn}	n measurement dis	stance m)		
P10.2 The product meets the acoustic noise requirements of the following voluntary program/s: RAL-UZ 122									
Chemical emissions from printing products						_			
P10.3* Test performed according to ECMA-328 (ISO/IEC 28360) standard, other specify: RAL-UZ-122									
P10.4 Typical emission rate (print phase) is (mg/h):						\square			
P10.5	Dust <0.7 Ozone <0.06 Styrene 0.19 Benzene <0.03 TVOC 1.3 P10.5 Chemical emission requirements of the following voluntary program/s RAL-UZ-122 are met for: Dust Ozone Styrene Styrene □								
			Benzene 🔀	TVO		Styrene			
	Electromagnetic		-5.120110 <u>/ \</u>	1 1 0 0	<u> </u>				
P10.6									

Model number *	X203n		
Issue date *	5/28/2009	Logo	LEXMARK

Produc	t environmental attributes - Market requirements (continued)	Require	ment	met			
Item		Yes	No	n.a.			
P11	Consumable materials for printing products						
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).						
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN12281.	\boxtimes					
P11.3*	2-sided (duplex) printing/copying is an integrated product function.		\boxtimes				
P12	Ergonomics for computing products						
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	\boxtimes					
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.			\boxtimes			
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.			\boxtimes			
P13	Packaging and documentation						
P13.1*	Product packaging material type(s): Expanded Polystyrene (EPS) weight (kg): 0.343 Product packaging material type(s): High Density Polyethylene (HDPE) weight (kg): 0.073 Product packaging material type(s): Corrugated weight (kg): 1.432						
P13.2*	Product plastic packaging is halogen free (including PVC). (See Note 1)	\boxtimes					
P13.3*	Specify media for user and product documentation (tick box): Electronic						
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber. <i>0</i> %						
P14	Additional information						
P1.1	The second secon						
P2.1	labeled with the WEEE disposal symbol and instructions for such disposal is listed in the product User's Guide.						
P.2.3	customer; however, is designed for easy removal by recyclers and service providers.						
P.10.4	BQL = Below Quantifiable Limits Additional company information and company environmental policy may be found at http://lexmark.co Specific printer and supply item recycling information for your area may be found at http://lexmark.co Lexmark Sweden is connected to REPA and El-kretsen		nment	•			

NOTE

Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Note 1 For cables, covers & housing plastic parts and plastic packaging materials in this standard; halogens include fluorine, chlorine, bromine, and iodine.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
76/769/EEC (Marketing and Use Directive)	P1.6, P1.8, P4.2
amendment 89/677/EEC	P1.4
amendment 1999/77/EC	P1.2
amendment 2003/3/EC	P1.7
amendment 94/27/EEC	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P4.2
1999/45/EC (Dangerous Preparations Directive)	P4.3
2001/58/EC (Directive on Safety Data Sheets)	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1