



Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	
Contact information *	Nadia Martin (USA)	LEXM ARK
Internet site *	www.lexmark.se / www.lexmark.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	ultifunction Color Laser Printer			
Commercial name *	exmark X738de, Lexmark X738dte			
Model number *	'38de, X738dte			
Issue date *	3/4/2009			
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control	Requireme	ent met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).		

Model number *	X738de, X738dte			
Issue date *	3/4/2009	Logo]	EXMARK

Product	environmental attributes - Legal requirements	Require	emei	nt met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain lead max 0.1%, cadmium max 0.01%, mercury max 0.1%, hexavalent chromium max 0.1%, polybrominated biphenyls (PBB) max 0.1% and polybrominated diphenyl ethers (PBDE) max 0,1% (see legal reference and Note 1).			
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.			
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain polychlorinated biphenyl (PCB) max 0.005% by weight, polychlorinated terphenyl (PCT) max 0.005% by weight (see legal reference).			
P1.5*	Products do not contain short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP max 0.1% (see legal reference).			
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain Azo colorants that split aromatic amines max 0.003% by weight (see legal reference and Note 1).			
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm2/week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)			
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medical or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	\boxtimes		
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).	\boxtimes		
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).			
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\boxtimes		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note 1).	\boxtimes		
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	\boxtimes		
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS/MSDS) in accordance with these requirements (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain lead, mercury, cadmium and hexavalent chromium max 0.01% by weight of these together.			
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).			
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.			

Note 1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *	X738de, X738dte		
Issue date *	3/4/2009	Logo	LEXMARK

Produc	roduct environmental attributes - Market requirements - Environmental conscious design Requirement met						
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n	.a.		
P6	Treatment information			_			
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).	\boxtimes					
P7	Design Disassembly, recycling						
P7.1*	Parts that have to be treated separately are easily separable	\boxtimes					
P7.2*	Plastic materials in covers/housing have no surface coating.						
P7.3*	Plastic parts >100g consist of one material or of easily separable materials.	\boxtimes					
P7.4*	Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.	\boxtimes					
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.	\boxtimes					
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	\boxtimes					
	Product lifetime						
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes					
P7.8*	Upgrading can be done using commonly available tools				Ī		
P7.9.	Spare parts are available after end of production for: 5 years						
P7.10	Service is available after end of production for: 5 years						
	Material and substance requirements						
P7.11*	Product cover/housing material type:						
	Material type: ABS Material type: HIPS Material type: PC/ABS						
P7.12	Electrical cable insulation material of power cables are halogen free (including PVC). (See Note 1)	_ <u> </u> _					
P7.13	Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1)	_ <u>_</u>	\boxtimes				
P7.14	All cover/housing plastic parts >25g are halogen free. (See Note 1)		Щ				
P7.15	All printed circuit boards (without components) >25g are halogen free. (See Note 2)		\boxtimes				
P7.16	Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40)			L			
P7.17	Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components):			Г	\neg		
	TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #:			_	1		
	Alt. 2						
	Chemical specifications of flame retardants in printed circuit boards (without components) >25g according	\boxtimes		Γ	$\neg \mid$		
	ISO 1043-4: <i>FR(16)</i>						
P7.18	Alt. 1			_	_		
	Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:	Ш	Ш	L			
	Comment: No legal limits exist, this is a market requirement.						
	1. Chemical name: CAS #:						
	2. Chemical name: CAS #:						
	3. Chemical name: CAS #:						
	A14 O			_	_		
	Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:	\boxtimes		L			
	FR(40), FR(17), FR(16), FR(50)						
P7.19	Of total plastic parts' weight >25g, recycled material content is %.						
P7.20	Of total plastic parts' weight >25g, biobased material content is %.						
P7.21	Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg	\boxtimes					
P8	If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg Batteries mg						
P8.1*	Battery chemical composition: Lithium Manganese Dioxide (LiMnO2)			Ī	\neg		
P8.2	Batteries meet the requirements of the following voluntary program/s:			+	+		

Note 1 For cables, covers & housing plastic parts and plastic packaging materials in this standard; halogens include fluorine, chlorine, bromine, and iodine.

Note 2 In accordance with JPCA-ES-01; printed wiring boards must not contain more than 0.09% by weight (900ppm) of chlorine or bromine.

Model number *	X738de, X738dte		
Issue date *	3/4/2009	Logo	LEXMARK

Produc	t environmental	attributes - Market	requirements (co	ontinued)					ment	met
Item		Yes No n.a.						n.a.		
P9	Energy consump									
9.1	For the product th	e following power levels	s or energy consum	ptions have been	meas	sured:				
Energy n	node *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC		Reference / Star and test method		jy mod	es	
Printing		550.7 W	554.8 W	542.8 W		Company Stand	lard			
Copying		599.1 W	599.5 W	558.8 W		Company Stand	lard			
Scannin	g	100.6 W	101.7 W	100.8 W		Company Stand	lard			
Ready		66.3 W	64.6 W	68.7 W		Energy Star TE	С			
Sleep		26.35 W	26.2 W	26.81 W		Energy Star TE	C			
Off		<i>0</i> W	<i>0</i> W	<i>0</i> W		Energy Star TE	C			
charger p	power supply / blugged in the wall t disconnected from	W	W	W						
PTEC * Typical E	energy Consumption	W n	W	W						
TEC * Typical E	Energy Consumption	7.11 kWh/week	7.14 kWh/week	7.22 kWh/weel	k					
Default ti	me to enter energy	save mode: 30 minutes	S	l.		l				
P9.2*		the energy save function		ne product.				\boxtimes		Ħ
P9.3*		s the energy requirement version 1.0 Tier:1	nts of the following	voluntary progran	n/s:				<u> </u>	<u> </u>
P10	Emissions									
	Noise emission -	- Declared according to	ISO 9296							
P10.1	Mode	Mode description		$\begin{array}{c} \text{Declared} \\ \text{A-weighted} \\ \text{sound power} \\ \text{level } L_{W\!\text{Ad}} \left(\text{B} \right) \end{array}$		Declared sound pressure rator position Desktop or Desk side	A-weighted level $L_{p{\rm Am}}$ (Bystander po operato	osition oduct i	is not	
	Idle	* Idle/Ready		* 4.7			31			
	Operation	* Simplex Monochrom	ne Printing	* 6.9			53			
	·									ш
	Other mode	Duplex Monochrome	e Printing	6.8			53			
	Measured accordi	ing to: ISO7779 Other	ECMA-74 (only if not covered	by ECMA-74 wit	h L _{pAn}	measurement dis	stance	m)		
P10.2										
	Chemical emissions from printing products									
P10.3*		ccording to ECMA-328 (indard, other	specif	y: RAL-UZ-122		\boxtimes		
P10.4	Typical emission r	rate (print phase) is (mg Dust BQL Ozone B 0		Ponzona BOI	T) (O	C 6 9	\boxtimes			
P10.5	Chemical emission	n requirements of the fo	•	Benzene BQL					$\overline{}$	
			Dust 🔀	Ozone		Styrene	\boxtimes			
			Benzene 🔀	TVO		,				
	Electromagnetic emissions									
P10.6	P10.6 Computer display meets the requirement for low frequency electromagnetic fields of the following voluntary \bigcup \infty \bigcup \bigcu									

Model number *	X736de, X738de, X738dte		
Issue date *	3/4/2009	Logo	LEXMARK

Produc	roduct environmental attributes - Market requirements (continued) Requirement m			met		
Item		Yes	No	n.a.		
P11	Consumable materials for printing products					
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	\boxtimes				
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN12281.					
P11.3*	2-sided (duplex) printing/copying is an integrated product function.	\boxtimes				
P12	Ergonomics for computing products					
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	\boxtimes				
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.			\boxtimes		
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.			\boxtimes		
P13	Packaging and documentation					
P13.1*	Product packaging material type(s): Wood Product packaging material type(s): Corrugated Product packaging material type(s): Polyethylene Foam Paperboard = 0.295 kg High Density Polyethylene (HDPE) = 0.233 kg Polypropylene = 0.065 kg weight (kg): 6.505 kg weight (kg): 5.260 kg weight (kg): 2.411 kg					
P13.2*	Product plastic packaging is halogen free (including PVC). (See Note 1)	X				
P13.3*	Specify media for user and product documentation (tick box): Electronic Paper Other Other					
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber. 0%					
P14	Additional information					
P1.1	This product uses RoHS exemptions for lead and mercury used in small amounts for specific applicat	ions.				
P2.1	The battery contained within this product should be disposed of properly with the product. The product labeled with the WEEE disposal symbol and instructions for such disposal is listed in the product Use		erly			
P.2.3	The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers.					
P.10.4	BQL = Below Quantifiable Limits - Note: The data reported is for the color print test.					
	Mono print test results: Ozone – BQL; Styrene - 0.14 mg/hr; Benzene – BQL; Dust – BQL; and TVOC –	0.74 mg/hr	•			
	Additional company information and company environmental policy may be found at http://lexmark.co Specific printer and supply item recycling information for your area may be found at http://lexmark.co Lexmark Sweden is connected to REPA and El-kretsen		nment			

NOTE

Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Note 1 For cables, covers & housing plastic parts and plastic packaging materials in this standard; halogens include fluorine, chlorine, bromine, and iodine.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
76/769/EEC (Marketing and Use Directive)	P1.6, P1.8, P4.2
amendment 89/677/EEC	P1.4
amendment 1999/77/EC	P1.2
amendment 2003/3/EC	P1.7
amendment 94/27/EEC	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P4.2
1999/45/EC (Dangerous Preparations Directive)	P4.3
2001/58/EC (Directive on Safety Data Sheets)	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1