

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	
Contact information *	Nadia Martin (USA)	
Internet site *	www.lexmark.se / www.lexmark.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	Type of product * Multi Function Color Laser Printer			
Commercial name *	xmark X792de, Lexmark XS796de			
Model number *	X792de, XS796de			
Issue date *	10/13/2010			
Intended market *	ntended market * 🛛 🔀 Global 🗌 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality Control			Requirement met		
Item		Yes	No		
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes			
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).				

Model number *	X792de, XS796de		
Issue date *	10/13/2010	Logo	LEXMARK

Product	Require	ment	met	
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)			
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.	\square		
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	\square		
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	\square		
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm ² /week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): REACH Program Manager, H0D9237, 740 W. New Circle Rd., Lexington, KY 40550	\square		
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\square		
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medica or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	\square		
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).	\square		
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).	3		
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\boxtimes		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).	\boxtimes		
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	\boxtimes		
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium an hexavalent chromium by weight of these together.	d 🔀		
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\square		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montrea Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.	al 🔀		

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *		X792de, XS796de					
Issue date *		10/13/2010	Logo	LEXM	ARK		
Product	Product environmental attributes - Market requirements - Environmental conscious design Requirement me						
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.			Yes	No	n.a.	
P6	Treatment information						
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).						
P7	Design						
		mbly, recycling					
P7.1*		at have to be treated separately are easily separable			Ц_		
P7.2*		naterials in covers/housing have no surface coating.		\square			
P7.3*	Plastic p	arts >100g consist of one material or of easily separable materials.		\square			
P7.4*	Plastic p	arts >25g have material codes according to ISO 11469 referring ISO 1043.		\boxtimes			
P7.5	Plastic p	arts are free from metal inlays or have inlays that can be removed with commonly a	available tools.	\square			
P7.6*	Labels a	re easily separable. (This requirement does not apply to safety/regulatory labels).					
	Product	lifetime					
P7.7*	Upgradir	ng can be done e.g. with processor, memory, cards or drives		\square			
P7.8*	Upgradir	g can be done using commonly available tools			Ħ	Ē	
P7.9.		arts are available after end of production for: 5 years				H	
P7.10		s available after end of production for: 5 years					
-		and substance requirements					
P7.11*		cover/housing material type:					
			al type: PC/AB	S			
P7.12		I cable insulation materials of power cables are PVC free.			\boxtimes		
P7.13	Electrica	I cable insulation materials of signal cables are PVC free					
P7.14	All cover	/housing plastic parts >25g are free from chlorine and bromine.					
P7.15		ed circuit boards (without components) >25g are halogen free. as defined in IEC6	61249-2-21. (Se			H	
	Note B2						
P7.16	Flame re Marking:	etarded plastic parts >25g in covers / housings are marked according ISO 1043-4: FR(40)		\boxtimes			
P7.17		al specifications of flame retardants in printed circuit boards >25g (without compone (additive) , TBBPA (reactive) , Other; chemical name: , CAS #:	ents):				
	ISO 104	Il specifications of flame retardants in printed circuit boards (without components) > 3-4: <i>FR(16)</i>	>25g according				
P7.18	concentr Comm	etarded plastic parts >25g contain the following flame retardant substances ations above 0.1%: ent: No legal limits exist, this is a market requirement.	s/preparations	in 🗌			
	2. Chem 3. Chem Alt. 2	ical name: , CAS #: ical name: , CAS #: ical name: , CAS #:					
	FR(40),	Il specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(17), FR(16), FR(50)		\boxtimes			
P7.19		arts >25g are free from flame retardant substances/ preparations above 0.1% class 6, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	sified as R45,				
P7.20		plastic parts' weight >25g, recycled material content is %.					
P7.21							
P7.22							
Do		ry is used specify: Number of lamps: and max. mercury content per lamp:	mg				
P8 P8.1*	Batterie	s chemical composition: Lithium Manganese Dioxide, LiMnO2					
	,						
P8.2	Batteries	meet the requirements of the following voluntary program/s:					

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model nu		X792de, X						_	
Issue dat	late * 10/13/2010 Logo LEXMARK					TM			
Product	environr	nental att	ributes - Market re	auirements (co	ntinued)		Requiremer	nt met	
Item									
P9 Energy consumption									
9.1	For the p	product the	following power levels	or energy consum	ptions are report	ed:			
Energy mode *		Power level at 100 V AC	Power level a 115 V AC	t Power level 230 V AC	at	Reference / Standard for energ modes and test method *	у 🗌		
Printing		862.8 W	840.4 W	820.7 W Corporate S		Corporate Standard			
Сору			994 W	862.9 W	925.1 W		Corporate Standard		
Scan			106.4 W	98.3 W	99.6 W		Corporate Standard		
Ready Mo	ode		65.3 W	70.7 W	67 W		Energy Star TEC Test Procedure		
Sleep Mo	de		16.09 W	16.13 W	16.48 W		Energy Star TEC Test Procedure		
Off Mode			0.003 W	0.003 W	0.016 W		IEC 62301		
charger pl	power sup lugged in t disconnec	he wall	W	W	W				
PTEC *	nergy Cons	sumption	W	W	W				
TEC * Typical Energy Consumption		sumption	5.25 kWh/week	5.14 kWh/week	5.17 kWh/week		Energy Star TEC Test Procedure		
ETEC * Annual Energy Consumption		sumption	kWh/year	kWh/year	kWh/year				
Display re	solution*	: Me	gapixels						
Print Spee	ed *	: 48 Images	s per minute				Corporate Standard		
•		-	ve mode: 30 minutes						
P9.2*			e energy save functio	n is provided with t	the product.				
P9.3*	ENERG Others s	Y STAR® v specify: Blu	the energy requiremenersion: <i>1.1</i> Tier: ersion: <i>1.1</i> Tier: e Angel (RAL UZ 122)	Product category		n/s:			
P10	Emissic Noise e		Declared according to	ISO 9296					
P10.1	Noise emission – Declared according to ISO 9296 P10.1 Mode Mode Mode description			Declared A-weighted sound power level <i>L</i> _{WAd} (B)			S		
	Idle	*	Poodu				or Desk side (only if product is no operator attended		
	Operatio		Ready Duplex Mono Printing	a. Normal Mode	* 4.3 * 6.9	27 52			
	Other m		Simplex Mono Printi				52		
	-		g to: 🔀 ISO7779 📘 I	ECMA-74		h	m measurement distance m)		
P10.2	The proc	duct meets	the acoustic noise req						

Model nur	nber *	X792de, XS796de					
Issue date *		10/13/2010 Logo	LEXM	ARK			
				ТМ	I		
Product environmental attributes - Market requirements (continued) Req							
Item			Yes	No	n.a.		
	Chemic	al emissions from printing products					
P10.3*		formed according to ECMA-328 (ISO/IEC 28360) standard 🗌, other specify: RAL-UZ-122	\boxtimes				
P10.4	Typical emission rate (print phase) is (mg/h):						
		Dust 0.6 Ozone <0.05 Styrene 0.36 Benzene <0.02 TVOC 15.6					
P10.5	Chemical emission requirements of the following voluntary program/s RAL-UZ-122 are met for :						
		Dust 🛛 🛛 Ozone 🖾 Styrene 🖾 Benzene 🖾 TVOC 🔀					
D (0, 0		nagnetic emissions					
P10.6	program	er display meets the requirement for low frequency electromagnetic fields of the following voluntary			\bowtie		
P11		nable materials for printing products					
P11.1*		Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).					
P11.2*		ontaining post-consumer recycled fibers can be used, provided that it meets the requirements		╶╞┤	╞		
1 11.2	EN1228						
P11.3*	2-sided	(duplex) printing/copying is an integrated product function.	\boxtimes				
P12		mics for computing products					
P12.1*	The disp	lay meets the ergonomic requirements of ISO 9241-307 for visual display technologies.			\boxtimes		
P12.2*	The phy	sical input device meets the requirements of ISO 9995 and ISO 9241-410.			\boxtimes		
P13		ing and documentation					
P13.1*		packaging material type(s): Wood weight (kg): 6.282					
		packaging material type(s): Corrugated weight (kg): 6.633 packaging material type(s): Low Density Polyethylene (LDPE) weight (kg): 1.629					
		packaging material type(s): Low Density Polyethylene (LDPE) weight (kg): 1.629 ensity Polyethylene (HDPE) = 0.346 kg					
		0.604 kg					
	Metal (S	Steel or tinplate) = 0.064 kg					
P13.2*	Product	plastic packaging is free from PVC.	\boxtimes				
P13.3*		media for user and product documentation (tick box):					
		ic 🔀, Paper 🔀, Other 🗌					
P13.4*		er user and product documentation, please specify contained percentage of post-consumer recycled	l				
D44	fiber: 0	% nal information (See Note B4)					
P14 P1.1		boduct uses RoHS exemptions for lead used in small amounts for specific applications.					
P2.1	The bat	tery contained within this product should be disposed of properly with the product. The product	duct is pr	operly	,		
		with the WEEE disposal symbol and instructions for such disposal is listed in the product U					
P2.3	The bat	tery contained within this product meets the exception listed. The battery is not intended to	be remov	/ed by	the		
	custom	er; however, is designed for easy removal by recyclers and service providers.					
	Note: T	he data reported in P10.4 is for the color print test.					
P10.4	Mono print test results: Ozone – <0.05 mg/h; Styrene - 0.14 mg/h; Benzene – <0.02 mg/h; Dust – 0.3 mg/h ; and TVOC –				C-		
	7.68 mg/h						
		nal company information and company environmental policy may be found at http://lexmark.			ent		
		; printer and supply item recycling information for your area may be found at http://lexmark.o	com/recy	cle			
	Lexmar	k Sweden is connected to REPA and El-kretsen					

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19