



Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	I DESCRIPTION
Contact information *	Nadia Martin (USA)	LEXIVI NK
Internet site *	www.lexmark.se/www.lexmark.com	
Additional information		

	The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	Multifunction Monochrome Laser Printer				
Commercial name *	Lexmark X862dte				
Model number *	X862dte				
Issue date *	5/13/2009				
Intended market *	Global Europe Asia, Pacific & Japan Americas Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control	Requireme	ent met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).		

Model number *	X862dte		
Issue date *	5/13/2009	Logo	LEXMARK

Product	duct environmental attributes - Legal requirements			Requirement met			
Item		Yes	No	n.a.			
P1	Hazardous substances and preparations						
P1.1*	Products do not contain lead max 0.1%, cadmium max 0.01%, mercury max 0.1%, hexavalent chromium	\boxtimes					
	max 0.1%, polybrominated biphenyls (PBB) max 0.1% and polybrominated diphenyl ethers (PBDE) max		_				
	0,1% (see legal reference and Note 1).						
P1.2*	Products do not contain Asbestos (see legal reference).	\boxtimes					
	Comment: Legal reference has no maximum concentration value.						
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),	\boxtimes					
	hydrobromofluorocarbons (HBFC), hydrochlorofluorocarbons (HCFC), Halons, carbontetrachloride, 1,1,1-						
	trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.						
P1.4*	Products do not contain polychlorinated biphenyl (PCB) max 0.005% by weight, polychlorinated terphenyl		$\overline{}$				
Г 1. 4	(PCT) max 0.005% by weight (see legal reference).		Ш				
P1.5*	Products do not contain short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing		\neg				
1 1.5	at least 48% per mass of chlorine in the SCCP max 0.1% (see legal reference).		Ш				
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS),	\neg	$\overline{}$	\boxtimes			
1 1.0	Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference).		Ш				
	Comment: Legal reference has no maximum concentration values.						
P1.7*	Textile and leather parts with direct skin contact do not contain Azo colorants that split aromatic amines		\Box	X			
	max 0.003% by weight (see legal reference and Note 1).	ш	ш				
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as		П	\boxtimes			
	pentachlorophenol and derivatives (see legal reference).		_				
	Comment: Legal reference has no maximum concentration values.						
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5	\boxtimes	П				
	microgram/cm2/week (see legal reference).			_			
	Comment: Max limit in legal reference when tested according to EN1811:1998.						
P2	Batteries						
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains	\boxtimes					
	more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be						
	marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is						
P2.2*	provided in user manual. (See legal reference)		$\overline{}$				
P2.2	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\boxtimes	Ш	Ш			
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the	\boxtimes	$\overline{}$	$\overline{}$			
1 2.5	design of the product). Exception: Batteries that are permanently installed for safety, performance, medical		Ш	Ш			
	or data integrity reasons do not have to be "easily removable". (See legal reference)						
P3	Safety, EMC connection to the telephone network and labeling						
P3.1*	The product complies with legally required safety standards as specified (see legal reference).		$\overline{\Box}$				
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).		∺	+			
			Щ.				
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies	\boxtimes					
D2 4*	with legally required standards for radio and telecommunication devices (see legal reference).						
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).		<u>Ш</u>				
P4	Consumable materials						
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see	\boxtimes					
	legal reference and Note 1).						
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).						
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the	\square					
	product/packaging is adequately labeled and a Safety Data Sheet (SDS/MSDS) in accordance with these						
	requirements (see legal reference).						
P5	Product packaging						
P5.1*	Packaging and packaging components do not contain lead, mercury, cadmium and hexavalent chromium	\boxtimes					
DE 0*	max 0.01% by weight of these together.						
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\boxtimes					
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal	\boxtimes					
	Protocol (see legal reference).			_ _			
	Comment: Legal reference has no maximum concentration values.						

Note 1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *	X862dte		
Issue date *	5/13/2009	Logo	LEXMARK

Produc	oduct environmental attributes - Market requirements - Environmental conscious design Requirement met						
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.			
P6	Treatment information						
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).	\boxtimes					
P7	Design Disassembly, recycling			_			
P7.1*	Parts that have to be treated separately are easily separable						
P7.2*	Plastic materials in covers/housing have no surface coating.	\boxtimes					
P7.3*	Plastic parts >100g consist of one material or of easily separable materials.	\boxtimes					
P7.4*	Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.	\boxtimes					
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.	\boxtimes					
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	\boxtimes					
	Product lifetime						
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes					
P7.8*	Upgrading can be done using commonly available tools	$\overline{\boxtimes}$					
P7.9.	Spare parts are available after end of production for: 5 years						
P7.10	Service is available after end of production for: 5 years			Ħ			
	Material and substance requirements						
P7.11*	Product cover/housing material type:						
	Material type: ABS Material type: HIPS Material type: PC/ABS						
P7.12	Electrical cable insulation material of power cables are halogen free (including PVC). (See Note 1)		\boxtimes				
P7.13	Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1)		\boxtimes				
P7.14	All cover/housing plastic parts >25g are halogen free. (See Note 1)	\boxtimes					
P7.15	All printed circuit boards (without components) >25g are halogen free. (See Note 2)		\boxtimes				
P7.16							
P7.17	Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components):						
	TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #:	_					
	Alt. 2						
	Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: <i>FR(16)</i>						
P7.18	Alt. 1						
	Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:			Ш			
	Comment: No legal limits exist, this is a market requirement.						
	1. Chemical name: , CAS #:						
	2. Chemical name: , CAS #:						
	3. Chemical name: CAS #:						
	Alt. 2						
	Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:		ш	ш			
	FR(40), FR(17), FR(16), FR(50)						
P7.19	Of total plastic parts' weight >25g, recycled material content is %.						
P7.20	Of total plastic parts' weight >25g, biobased material content is %.						
P7.21	Light sources are free from mercury						
P8	If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg Batteries mg						
P8.1*	Battery chemical composition: Lithium Manganese Dioxide (LiMnO2)						
P8.2	Batteries meet the requirements of the following voluntary program/s:						

Note 1 For cables, covers & housing plastic parts and plastic packaging materials in this standard; halogens include fluorine, chlorine, bromine, and iodine.

Note 2 In accordance with JPCA-ES-01; printed wiring boards must not contain more than 0.09% by weight (900ppm) of chlorine or bromine.

Model number *	X862dte		
Issue date *	5/13/2009	Logo	LEXMARK

Produc	Product environmental attributes - Market requirements (continued) Requirement met						met		
Item			Yes No n				n.a.		
P9									
9.1 For the product the following power levels or energy consumptions have been measured:									
Energy n	node *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC		Reference / Star and test method	ndard for energy m	odes	
Printing		798 W	775.6 W	770 W		Corporate Stan	dard		
Copying		829.8 W	827.5 W	838 W		Corporate Stan	dard		
Scannin	g	163.6 W	191.9 W	164 W		Corporate Stan	dard		
Ready N	lode	122.4 W	130.9 W	115.6 W		Energy Star TE	C Test Procedure	,	
Sleep M	ode	21.03 W	21.33 W	20.53 W		Energy Star TE	C Test Procedure)	
Off		0.09 W	0.011 W	<i>0.48</i> W		IEC 62301 / Ene	rgy Star		
charger p	power supply / plugged in the wall t disconnected from	W W	W	W					
PTEC * Typical E	energy Consumptio	n W	W	W					
TEC * Typical E	Energy Consumptio	7.43 kWh/week	7.65 kWh/week	7.88 kWh/weel	k				
Default ti	me to enter energy	save mode: 5 minutes		1			-		
P9.2*	Information about	the energy save function	n is provided with t	he product.			\boxtimes		$\overline{\Box}$
P9.3*	The product meet ENERGY STAR® Others specify: R		nts of the following	voluntary progran	n/s:				
P10	Emissions								
	Noise emission -	 Declared according to 	ISO 9296						
P10.1	Mode	Mode description		$\begin{array}{c} \text{Declared} \\ \text{A-weighted} \\ \text{sound power} \\ \text{level } L_{W\!\text{Ad}} \left(\text{B} \right) \end{array}$			A-weighted elevel $L_{p{\rm Am}}$ (dB) Bystander position (only if product operator att	ons 🔀	
	Idle	* Ready		* 4.6			30		
	Operation	* Cimpley Manachrom	o Printing	* 6.9			52		-
	Operation	* Simplex Monochrom	le Frinting	0.9			32		Ш
	Other mode	Duplex Monochrome	e Printing	7.2			55		
	Measured accordi	· = -	ECMA-74 (only if not covered	by ECMA-74 wit	h L _{pAm}	measurement dis	stance m)		
P10.2	P10.2 The product meets the acoustic noise requirements of the following voluntary program/s: RAL-UZ 122								
D40.0*		ons from printing prod					K-7		
P10.3* Test performed according to ECMA-328 (ISO/IEC 28360) standard, other specify: RAL-UZ-122									
P10.4 Typical emission rate (print phase) is (mg/h): Dust <0.7 Ozone <0.06 Styrene <0.12 Benzene <0.03 TVOC 0.24						\square			
P10.5	Chemical emissio	n requirements of the fo							
	2		Dust 🔀	Ozone		Styrene			ш
			Benzene 🔀	TVO		,			
	Electromagnetic								
P10.6	P10.6 Computer display meets the requirement for low frequency electromagnetic fields of the following voluntary					\boxtimes			

Model number *	X862dte		
Issue date *	5/13/2009	Logo	LEXMARK

Produc	t environmental attributes - Market requirements (continued)	Require	ment	met	
Item	to the control of the	Yes	No	n.a.	
P11	Consumable materials for printing products				
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).				
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN12281.	\boxtimes			
P11.3*	2-sided (duplex) printing/copying is an integrated product function.	\boxtimes			
P12	Ergonomics for computing products				
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	\boxtimes			
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.			\boxtimes	
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.				
P13	Packaging and documentation				
P13.1*	Product packaging material type(s): Corrugated Product packaging material type(s): Expanded Polystyrene (EPS) weight (kg): 0.454 Product packaging material type(s): Polyethylene (PE) High Density Polyethylene (HDPE) = 0.091 kg Polypropylene (PP) = 0.227 kg Wood = 6.350 kg				
P13.2*	Product plastic packaging is halogen free (including PVC). (See Note 1)	\boxtimes			
P13.3*	Specify media for user and product documentation (tick box): Electronic				
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber. 0%				
P14	Additional information				
P1.1	This product uses RoHS exemptions for lead used in small amounts for specific applications.				
P2.1	labeled with the WEEE disposal symbol and instructions for such disposal is listed in the product User's Guide.				
F.2.3	customer; however, is designed for easy removal by recyclers and service providers.	e removed	i oy tr	ie	
	Additional company information and company environmental policy may be found at http://lexmark.co Specific printer and supply item recycling information for your area may be found at http://lexmark.co Lexmark Sweden is connected to REPA and El-kretsen			t T	

NOTE

Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Note 1 For cables, covers & housing plastic parts and plastic packaging materials in this standard; halogens include fluorine, chlorine, bromine, and iodine.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
76/769/EEC (Marketing and Use Directive)	P1.6, P1.8, P4.2
amendment 89/677/EEC	P1.4
amendment 1999/77/EC	P1.2
amendment 2003/3/EC	P1.7
amendment 94/27/EEC	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P4.2
1999/45/EC (Dangerous Preparations Directive)	P4.3
2001/58/EC (Directive on Safety Data Sheets)	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1