



Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	ITSTATABLE
Contact information *	Nadia Martin (USA)	LEXIVI NK
Internet site *	www.lexmark.se/www.lexmark.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	Multifunction Monochrome Laser Printer			
Commercial name *	Lexmark X864dhe			
Model number *	X864dhe			
Issue date *	5/13/2009			
Intended market *	Global Europe Asia, Pacific & Japan Americas Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Quality Control		
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).		

Model number *	X864dhe		
Issue date *	5/13/2009	Logo	LEXMARK

Product	uct environmental attributes - Legal requirements			t met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain lead max 0.1%, cadmium max 0.01%, mercury max 0.1%, hexavalent chromium	\boxtimes		
	max 0.1%, polybrominated biphenyls (PBB) max 0.1% and polybrominated diphenyl ethers (PBDE) max 0,1% (see legal reference and Note 1).			
P1.2*	Products do not contain Asbestos (see legal reference).		$\overline{}$	
1 1.2	Comment: Legal reference has no maximum concentration value.		ш	
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),			
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-		_	
	trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum			
P1.4*	concentration values.	<u> </u>	$\overline{}$	
P1.4	Products do not contain polychlorinated biphenyl (PCB) max 0.005% by weight, polychlorinated terphenyl (PCT) max 0.005% by weight (see legal reference).		Ш	
P1.5*	Products do not contain short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing	\boxtimes	\Box	
	at least 48% per mass of chlorine in the SCCP max 0.1% (see legal reference).			
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS),			\boxtimes
	Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference).			
- · - ·	Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain Azo colorants that split aromatic amines max 0.003% by weight (see legal reference and Note 1).		Ш	
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as		\Box	\boxtimes
	pentachlorophenol and derivatives (see legal reference).	ш	ш	
	Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5	\boxtimes		
	microgram/cm2/week (see legal reference).			
Do	Comment: Max limit in legal reference when tested according to EN1811:1998.			
P2	Batteries Vitable Land Vitable		_	_
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be		Ш	
	marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is			
	provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or	\boxtimes		
	accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)			
P2.3*				
	design of the product). Exception: Batteries that are permanently installed for safety, performance, medical or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).		$\overline{}$	
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).	\square	∺	\blacksquare
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies		₩	+
1 3.3	with legally required standards for radio and telecommunication devices (see legal reference).		Ш	
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\boxtimes		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note 1).	\boxtimes		
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	\boxtimes		
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the	X		
	product/packaging is adequately labeled and a Safety Data Sheet (SDS/MSDS) in accordance with these			
	requirements (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain lead, mercury, cadmium and hexavalent chromium max 0.01% by weight of these together.			
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).			
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal	\boxtimes		
	Protocol (see legal reference).			
	Comment: Legal reference has no maximum concentration values.			

Note 1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *	X864dhe		
Issue date *	5/13/2009	Logo	LEXMARK

Produc	duct environmental attributes - Market requirements - Environmental conscious design Requirement met					
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14. Yes No					
P6	Treatment information					
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).					
P7	Design Disassembly, recycling					
P7.1*	Parts that have to be treated separately are easily separable	\square	П			
P7.2*	Plastic materials in covers/housing have no surface coating.					
P7.3*	Plastic parts >100g consist of one material or of easily separable materials.		П			
P7.4*	Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.					
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.					
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	\boxtimes				
	Product lifetime					
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes				
P7.8*	Upgrading can be done using commonly available tools	$\overline{\boxtimes}$				
P7.9.	Spare parts are available after end of production for: 5 years					
P7.10	Service is available after end of production for: 5 years					
	Material and substance requirements					
P7.11*	Product cover/housing material type:					
	Material type: ABS Material type: HIPS Material type: PC/ABS					
P7.12	Electrical cable insulation material of power cables are halogen free (including PVC). (See Note 1)		\times			
P7.13	Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1)		\boxtimes			
P7.14	All cover/housing plastic parts >25g are halogen free. (See Note 1)	\boxtimes				
P7.15	All printed circuit boards (without components) >25g are halogen free. (See Note 2)		\boxtimes			
P7.16	Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40)					
P7.17	Alt. 1 Chamical appointance of flowe retardants in printed circuit boards > 25g (without components):					
	Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive), TBBPA (reactive), Other; chemical name: , CAS #:	Ш				
	Tobli A (additive) , Tobli A (reactive) , Other, Chemical Hame. , OAO #.					
	Alt. 2					
	Chemical specifications of flame retardants in printed circuit boards (without components) >25g according	\boxtimes				
	ISO 1043-4: <i>FR(16)</i>					
P7.18	Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in					
	concentrations above 0.1%:	Ш				
	Comment: No legal limits exist, this is a market requirement.					
	4. Chamical name:					
	1. Chemical name: , CAS #: 2. Chemical name: , CAS #:					
	3. Chemical name: CAS #:					
	one manual name.					
	Alt. 2	\boxtimes				
	Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50)					
P7.19	Of total plastic parts' weight >25g, recycled material content is %.		-			
P7.20	Of total plastic parts' weight >25g, biobased material content is %.					
P7.21	Light sources are free from mercury					
P8	If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg Batteries mg					
P8.1*	Battery chemical composition: Lithium Manganese Dioxide (LiMnO2)					
P8.2	Batteries meet the requirements of the following voluntary program/s:					

Note 1 For cables, covers & housing plastic parts and plastic packaging materials in this standard; halogens include fluorine, chlorine, bromine, and iodine.

Note 2 In accordance with JPCA-ES-01; printed wiring boards must not contain more than 0.09% by weight (900ppm) of chlorine or bromine.

Model number *	X864dhe		
Issue date *	5/13/2009	Logo	LEXMARK.

Produc	t environmental	attributes - Market	requirements (c	ontinued)			Require	ment	met
Item	Yes No				n.a.				
P9 Energy consumption									
9.1	For the product th	e following power levels	or energy consum	ptions have been	meas	sured:			
Energy n	node *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC		Reference / Star and test method	ndard for energy mo	des	
Printing		828.7 W	821.3 W	741.9 W		Corporate Stan	dard		
Copying	J	809.1 W	783.6 W	824.4 W		Corporate Stan	dard		
Scannin	ıg	191.5 W	175.8 W	179.7 W		Corporate Stan	dard		$\overline{\Box}$
Ready N	lode	155.3 W	129.9 W	125.6 W		Energy Star TE	C Test Procedure		Ħ
Sleep M	ode	21.09 W	21.21 W	20.11 W		Energy Star TE	C Test Procedure		$\overline{\Box}$
Off		0.09 W	0.10 W	0.48 W		IEC 62301 / Ene	ergy Star		$\overline{\Box}$
charger	I power supply / plugged in the wall t disconnected from	W	W	W					
PTEC * Typical E	Energy Consumption	W	W	W					
TEC * Typical E	Energy Consumption	10.52 kWh/week	10.24 kWh/week	10.01 kWh/we	ek				
Default ti	ime to enter energy	save mode: 60 minutes	S			1			
P9.2*		the energy save function		he product.			\square		$\overline{\Box}$
P9.3*	The product meet ENERGY STAR® Others specify: R		nts of the following	voluntary progran	n/s:				
P10	Emissions								
	Noise emission -	 Declared according to 	ISO 9296						
P10.1	Mode	Mode description		$\begin{array}{c} \text{Declared} \\ \text{A-weighted} \\ \text{sound power} \\ \text{level } L_{W\!\text{Ad}} \left(\text{B} \right) \end{array}$			A-weighted level $L_{p{\rm Am}}$ (dB) Bystander position (only if product operator atte	is not	
	Idle	* Ready		* 4.6			30		
	Operation	* Simplex Monochrom	o Printing	* 6.9			53		
	Operation	Simplex Monochion	le Fillung	0.9			33		Ш
	Other mode	Duplex Monochrome	Printing	7.2			56		
	Measured accordi	· = -	ECMA-74 (only if not covered	by ECMA-74 wit	h L _{pAn}	measurement dis	stance m)		
P10.2									
Chemical emissions from printing products									
P10.3*		cording to ECMA-328 (andard, other	speci	fy: RAL-UZ-122			Ш
P10.4	ı ypıcal emission r	ate (print phase) is (mg		40 Dan 0		TV00 001			
P10.5	Chemical emissio	Dust <0.7 Ozone <0		12 Benzene <0.			\square		
1 10.5	Onemical emissio		Dust 🔀	ring voluntary program/s <i>RAL-UZ-122</i> are met for :		Ш			
			Benzene 🔀	TVO		2.7.0.10	<u></u>		
Electromagnetic emissions									
P10.6	P10.6 Computer display meets the requirement for low frequency electromagnetic fields of the following voluntary program/s:								

Model number *	X864dhe		
Issue date *	5/13/2009	Logo	LEXMARK

Produc	Product environmental attributes - Market requirements (continued) Requirement m					
Item		Yes	No	n.a.		
P11	Consumable materials for printing products					
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	\boxtimes				
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN12281.					
P11.3*	2-sided (duplex) printing/copying is an integrated product function.	\boxtimes				
P12	Ergonomics for computing products					
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	\boxtimes				
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.			\boxtimes		
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.					
P13	Packaging and documentation	·		•		
P13.1*	Product packaging material type(s): Corrugated Product packaging material type(s): Expanded Polystyrene (EPS) weight (kg): 0.454 Product packaging material type(s): Polyethylene (PE) High Density Polyethylene (HDPE) = 0.091 kg Polypropylene (PP) = 0.227 kg Wood = 6.350 kg					
P13.2*	Product plastic packaging is halogen free (including PVC). (See Note 1)					
P13.3*	Specify media for user and product documentation (tick box): Electronic					
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber. 0%					
P14	Additional information					
P1.1	This product uses RoHS exemptions for lead used in small amounts for specific applications.					
P2.1	labeled with the WEEE disposal symbol and instructions for such disposal is listed in the product User's Guide.					
F.2.3	.3 The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers.					
	Additional company information and company environmental policy may be found at http://lexmark.co Specific printer and supply item recycling information for your area may be found at http://lexmark.co Lexmark Sweden is connected to REPA and El-kretsen		ment	t		

NOTE

Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Note 1 For cables, covers & housing plastic parts and plastic packaging materials in this standard; halogens include fluorine, chlorine, bromine, and iodine.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
76/769/EEC (Marketing and Use Directive)	P1.6, P1.8, P4.2
amendment 89/677/EEC	P1.4
amendment 1999/77/EC	P1.2
amendment 2003/3/EC	P1.7
amendment 94/27/EEC	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P4.2
1999/45/EC (Dangerous Preparations Directive)	P4.3
2001/58/EC (Directive on Safety Data Sheets)	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1