

Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	I DAZNA A DIZ
Contact information *	Nadia Martin (USA)	LEXMARK
Internet site *	www.lexmark.se / www.lexmark.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	Type of product * Multifunction Color Laser Printer			
Commercial name *	Lexmark X950de			
Model number *	X950de			
Issue date *	6-9-2011			
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality Control		Requireme	nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration		
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	l 🖂	

Model number *	X950de		
Issue date *	6-9-2011	Logo	LEXMARK.

Product environmental attributes - Legal requirements			emen	t met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)			
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.			
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).			
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	\boxtimes		
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm²/week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): REACH Program Manager, HOD9237, 740 W. New Circle Rd., Lexington, KY 40550			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)			
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medica or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	\square		
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).			
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).	\boxtimes		
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\boxtimes		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	\boxtimes		
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.	l 🔀		
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\boxtimes		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montrea Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.	I 🔀		

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model nu	ımber *	X950de				
Issue date *		6-9-2011	Logo	LEXM	۸RK	
			222111	TW		
Product	environ	mental attributes - Market requirements - Environmental conscious	design	Requirer	nent	met
Item	*=manda	atory to fill in. Additional information regarding each item may be found under P14.	_	Yes	No	n.a.
P6		ent information				
P6.1*		ion for recyclers/treatment facilities is available (see legal reference).			Ш	
P7	Design	mbly, recycling				
P7.1*		at have to be treated separately are easily separable			$\overline{}$	
P7.2*		naterials in covers/housing have no surface coating.			Ħ	\vdash
P7.3*		arts >100g consist of one material or of easily separable materials.			\dashv	\vdash
P7.4*		arts >25g have material codes according to ISO 11469 referring ISO 1043.				\vdash
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly	available tools			\dashv
P7.6*		re easily separable. (This requirement does not apply to safety/regulatory labels).	available teele.			\vdash
17.0		lifetime				
P7.7*		ng can be done e.g. with processor, memory, cards or drives				
P7.8*		ng can be done using commonly available tools			Ħ	\vdash
P7.9.		arts are available after end of production for: 5 years				\vdash
P7.10						\vdash
1 7.10		is available after end of production for: 5 years and substance requirements				
P7.11*		cover/housing material type:				
			al type: PC ABS	PS		
P7.12	Electrica	Il cable insulation materials of power cables are PVC free.		\boxtimes		
P7.13	Electrica	ll cable insulation materials of signal cables are PVC free		\boxtimes		
P7.14	All cover	/housing plastic parts >25g are free from chlorine and bromine.		\boxtimes		
P7.15	All printe	ed circuit boards (without components) >25g are halogen free. as defined in IEC6	61249-2-21. (Se	ee 🔀		
P7.16		etarded plastic parts >25g in covers / housings are marked according ISO 1043-4: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC+ABS+PS-H	I FR(40)<			
P7.17		al specifications of flame retardants in printed circuit boards >25g (without compone (additive) , TBBPA (reactive) , Other; chemical name: , CAS #:	ents):			
	ISO 104	al specifications of flame retardants in printed circuit boards (without components) > 3-4:	>25g according			
P7.18	concenti	retarded plastic parts >25g contain the following flame retardant substances rations above 0.1%: ent: No legal limits exist, this is a market requirement.	s/preparations i	n 🗌		
	2. Chem 3. Chem Alt. 2	ical name: , CAS #: al specifications of flame retardants in plastic parts >25g according ISO 1043-4:		\boxtimes	П	
P7.19	R40, R4	arts >25g are free from flame retardant substances/ preparations above 0.1% clas 6, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	sified as R45,			
P7.20		plastic parts' weight >25g, recycled material content is %.				
P7.21		plastic parts' weight >25g, biobased material content is %.		K 7		
P7.22	Light sol	urces are free from mercury		\bowtie		

Batteries meet the requirements of the following voluntary program/s: Lithium Manganese Dioxide

and max. mercury content per lamp:

mg

If mercury is used specify: Number of lamps:

Battery chemical composition:

P8

P8.1

P8.2

Batteries

(LiMnO2)

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	X950de		
Issue date *	6-9-2011	Logo	EXMARK.

Power Level at Power Level at Power Level at Power Level at Reference Standard Frinting 100 V AC AC AC AC AC AC AC	n.a.
9.1 For the product the following power levels or energy consumptions are reported: Energy mode * Power level at 100 V AC Printing 671.7 W 672.2 W 666.5 W Corporate Standard	
Energy mode * Power level at 100 V AC Printing Power level at 15 V AC Power level at 230 V AC Power le	
100 V AC 115 V AC 230 V AC modes and test method * Printing 671.7 W 672.2 W 666.5 W Corporate Standard	
Conv. 200 0 W 705 1 W 730 1 W Corporate Standard	
Copy 809.9 W 705.1 W 739.1 W Corporate Standard	
Scan 124.8 W 114.2 W 113.1 W Corporate Standard	-
Ready Mode 103.9 W 106.7 W 109.3 W Energy Star TEC Test Procedure	
Sleep Mode 16.26 W 16.02 W 16.14 W Energy Star TEC Test Procedure	
Off Mode 0.06 W 0.08 W 0.35 W IEC 62301	
EPS No-load W W W	
(External power supply / charger plugged in the wall outlet but disconnected from the product.)	
PTEC * W W W Typical Energy Consumption	
TEC * Typical Energy Consumption 7.868 kWh/week Typical Energy Consumption 7.929 kWh/week T.932 kWh/week T.932 kWh/week T.932 kWh/week	
ETEC * kWh/year kWh/year kWh/year kWh/year	
Display resolution* : Megapixels	
Print Speed * : 45 Images per minute Corporate Standard	
Default time to enter energy save mode: 30 minutes	
P9.2* Information about the energy save function is provided with the product.	
P9.3* The product meets the energy requirements of the following voluntary program/s:	
ENERGY STAR® version: 1.1 Tier: Product category: TEC Table 4	
Others specify: RAL UZ 122 (Blue Angel) P10 Emissions	
Noise emission – Declared according to ISO 9296	
P10.1 Mode Mode description Declared Declared A-weighted	1
A-weighted sound pressure level $L_{p{\sf Am}}$ (dB)	
$\begin{array}{c c} \textbf{Sound power} \\ \textbf{level } L_{W\!A\!d}\left(\textbf{B}\right) & \textbf{Operator position} & \textbf{Bystander position} \end{array}$	1
│	
or Desk side (only if product is no operator attended	
Idle * Ready * 4.0 25	
Operation * Duplex Monochrome Printing * 7.0 55	
Other mode Simplex Monochrome Printing 6.9 53	
Measured according to: ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)	
P10.2 The product meets the acoustic noise requirements of the following voluntary program/s: RAL UZ 122 (Blue Angel)	

Model number *	X950de		
Issue date *	6-9-2011	Logo	LEXMARK.

Product	environmental attributes - Market requirements (continued)	Require	ment	met
Item		Yes	No	n.a.
	Chemical emissions from printing products			
P10.3*	Test performed according to ECMA-328 (ISO/IEC 28360) standard X, other specify: RA- UZ122	\boxtimes		
P10.4	Typical emission rate (print phase) is (mg/h):			
	Dust <0.40 Ozone <0.29 Styrene 0.071 Benzene 0.014 TVOC 6.2			
P10.5	Chemical emission requirements of the following voluntary program/s are met for :	\boxtimes		
	Dust ☑ Ozone ☑ Styrene ☑ Benzene ☑ TVOC ☑			
5.00	Electromagnetic emissions			
P10.6	Computer display meets the requirement for low frequency electromagnetic fields of the following voluntary program/s:			\boxtimes
P11	Consumable materials for printing products			
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).			
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of		Ħ	Ħ
	EN12281.		ш	ш
P11.3*	2-sided (duplex) printing/copying is an integrated product function.	\boxtimes		
P12	Ergonomics for computing products			
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.			\boxtimes
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.			$\overline{\boxtimes}$
P13	Packaging and documentation			
P13.1*	Product packaging material type(s): paper weight (kg): 11.632			
	Product packaging material type(s): PE weight (kg): 0.242			
	Product packaging material type(s): wood weight (kg): 11			
	Product packaging material type(s):PP weight(kg):0.359			
	Product packaging material type(s):PS weight(kg):0.193			
P13.2*	Product packaging material type(s):Metal weight(kg):0.024 Product plastic packaging is free from PVC.			
P13.3*	Specify media for user and product documentation (tick box):			+
	Electronic , Paper , Other			Ш
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber: 0%			
Rev. P13.5	User and product documentation do not contain chlorine bleached paper			
P14	Additional information (See Note B4)			
P1. 1	This product uses RoHS exemptions for lead used in small amounts for specific applications.			
P2. 1	The battery contained within this product should be disposed of properly with the product. I	The prod	luct i	S
	properly labeled with the WEEE disposal symbol and instructions for such disposal is listed in	n the p	roduc	t
	User's Guide.			
P. 2. 3				
	The battery contained within this product meets the exception listed. The battery is not in		to be	
	removed by the customer; however, is designed for easy removal by recyclers and service provi	ders.		
P. 7. 4	Please note that all parts greater than 25g and 200mm2 have material are marked according to ISO 114 1043.	169 refer	ing IS	0
P. 7. 5	Please note that all large case parts are free from metal inlays.			
P. 9. 1	Print speed listed is for Mono Letter speed. Color letter speed is 40 ppm.			
P10. 4	Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone – 0.32 mg/h; Styrene - 0.030 mg/h; Benzene – 0.011 mg/h; Dust – <0.40 – 2.6 mg/h	mg/h ; ε	and T\	/OC
	Additional company information and company environmental policy may be found at http://lexmark.com/environment			
	Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle			
	Lexmark Sweden is connected to REPA and El-kretsen			

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19