

Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	LENZALADIZ
Contact information *	Nadia Martin (USA)	LEXMARK
Internet cite *	unun laymark aa / unun laymark aam	L. V. 185
Internet site *	www.lexmark.se / www.lexmark.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.					
Type of product *	Multifunction Color Laser Printer				
Commercial name *	Lexmark XS548de				
Model number *	XS548de				
Issue date *	12/16/2011				
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Quality Control		
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model number *	XS548de		
Issue date *	12/16/2011	Logo	LEXMARK.

Product	Product environmental attributes - Legal requirements				
Item		Yes	No	n.a.	
P1	Hazardous substances and preparations				
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)				
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.				
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.				
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	\boxtimes			
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	\boxtimes			
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.				
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			\boxtimes	
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference). Comment: Legal reference has no maximum concentration values.				
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm²/week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.				
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): REACH Program Manager, HOD9237, 740 W. New Circle Rd., Lexington, KY 40550				
P2	Batteries				
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)				
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\boxtimes			
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medica or data integrity reasons do not have to be "easily removable". (See legal reference)				
P3	Safety, EMC connection to the telephone network and labeling				
P3.1*	The product complies with legally required safety standards as specified (see legal reference).				
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).				
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).	\boxtimes			
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\boxtimes			
P4	Consumable materials				
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).				
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	\boxtimes			
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).				
P5	Product packaging				
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.	I 🔀			
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\boxtimes			
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montrea Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.	I 🔀			

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model ni	ımbor *	VCE40do				
Model number * XS548de Issue date * 12/16/2011			Logo	IEVM	\ DIZ	,
133uc uui	ssue date * 12/16/2011 Logo LEXMARK					
Droduct	environ	mental attributes - Market requirements - Environmental conscious	design	Require	mont	mot
Item		atory to fill in. Additional information regarding each item may be found under P14.	uesigii	Yes	No	n.a.
P6		nt information		100	110	ii.a.
P6.1*		on for recyclers/treatment facilities is available (see legal reference).		\boxtimes		
P7	Design	· · · · · · · · · · · · · · · · · · ·				
	_	mbly, recycling				
P7.1*	Parts tha	at have to be treated separately are easily separable		\boxtimes		
P7.2*	Plastic m	naterials in covers/housing have no surface coating.		\boxtimes		
P7.3*	Plastic p	arts >100g consist of one material or of easily separable materials.		\boxtimes		
P7.4*	Plastic p	arts >25g have material codes according to ISO 11469 referring ISO 1043.		\boxtimes	$\overline{\sqcap}$	
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly	available tools.		П	П
P7.6*	Labels a	re easily separable. (This requirement does not apply to safety/regulatory labels).			Ħ	
	Product	lifetime				
P7.7*	Upgradir	ng can be done e.g. with processor, memory, cards or drives		\boxtimes		
P7.8*	Upgradir	ng can be done using commonly available tools				
P7.9.	Spare pa	arts are available after end of production for: 5 years				
P7.10		s available after end of production for: 5 years		,		
		and substance requirements				
P7.11*	Product	cover/housing material type:				
			al type: PC/AB	<u> </u>		
P7.12		I cable insulation materials of power cables are PVC free.				Ш
P7.13		I cable insulation materials of signal cables are PVC free			\boxtimes	
P7.14	All cover	/housing plastic parts >25g are free from chlorine and bromine.		\boxtimes		
P7.15	All printe Note B2)	ed circuit boards (without components) >25g are halogen free. as defined in IEC6	61249-2-21. (Se	ee 🗌		
P7.16	Flame re Marking:	etarded plastic parts >25g in covers / housings are marked according ISO 1043-4:				
P7.17		additive) , TBBPA (reactive) , Other; chemical name: , CAS #:	ents):			
	ISO 1043	Il specifications of flame retardants in printed circuit boards (without components) > 3-4: <i>FR(16)</i>	>25g according			
P7.18	Commondation Commondation Commondation Commondation Commondation Commondation Commondation Concentration Concentration Concentration Commondation Concentration Commondation Concentration Commondation	etarded plastic parts >25g contain the following flame retardant substances ations above 0.1%: ent: No legal limits exist, this is a market requirement. ical name: , CAS #: ical name: , CAS #:	s/preparations	in 🗌		
P7.19	Alt. 2 Chemica FR(40), I	ical name: , CAS #: Il specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(17), FR(16), FR(50) arts >25g are free from flame retardant substances/ preparations above 0.1% clas	sified as R45			

%.

and max. mercury content per lamp:

mg

R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)

Of total plastic parts' weight >25g, recycled material content is

Of total plastic parts' weight >25g, biobased material content is

Battery chemical composition: Lithium Manganese Dioxide (LiMn02)

Batteries meet the requirements of the following voluntary program/s:

Light sources are free from mercury If mercury is used specify: Number of lamps:

Batteries

P7.20

P7.21 P7.22

P8

P8.1

P8.2

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	XS548de		
Issue date *	12/16/2011	Logo	LEXMARK

Product er	duct environmental attributes - Market requirements (continued) Requirement met							
Item							Yes N	o n.a.
P9 I	Energy consumpti	ion						
9.1 I	For the product the	following power levels	or energy consum	ptions are report	ted:			
Energy mod	e *	Power level at 100 V AC	Power level at	Power level	at	Reference / Standard modes and test method *	for energ	Jy 🔲
Printing		516.6 W	506.4 W	496 W		Corporate Standard		
Сору		498.1 W	526.3 W	510.7 W		Corporate Standard		
Scan		56.5 W	53.4 W	56.8 W		Corporate Standard		
Ready Mod	'e	48.5 W	50.0 W	49.2 W		Energy Star TEC Test Pro	ocedure	
Sleep Mode	•	19.1 W	22.4 W	20.6 W		Energy Star TEC Test Pro	ocedure	
Off Mode		0.019 W	0.022 W	0.117 W		IEC 62301		
EPS No-load	d	W	W	W				\boxtimes
charger plug	ower supply / gged in the wall sconnected from)							
PTEC * Typical Ener	rgy Consumption	W	W	W				
TEC * Typical Ener	rgy Consumption	4.935 kWh/week	5.378 kWh/week	5.129 kWh/we	ek	Energy Star TEC Test Pro	ocedure	
ETEC * Annual Ener	rgy Consumption	kWh/year	kWh/year	kWh/ye	ear			
Display reso	olution* : Me	egapixels		1				
Print Speed	* : 23 Image	s per minute						
Default time	to enter energy sa	ve mode: 30 minutes						$+\overline{\Box}$
		he energy save functio	n is provided with t	he product.				╅
P9.3*	The product meets	the energy requiremen	nts of the following	voluntary program	m/s·			
	ENERGY STAR® \		Product category					
P10	Emissions							
	Noise emission -	Declared according to	ISO 9296					
P10.1	Mode M	lode description		Declared		Declared A-weighted		
				A-weighted sound power		sound pressure level $L_{p{\mathsf A}}$	m (dB)	
				level L_{WAd} (B)	Ope	rator position Bystan	der position	IS
				max ,		Desktop		
						Or Deck side \ ' '	oroduct is no ator attended	
	Idle *	Ready		* 3.8		23		
	Operation *	Duplex Mono Printin	g, Normal Mode	* 6.5		49		
Other mode Simplex Mono Printing, Normal		ng, Normal	6.3		47			
	Measured accordin	· <u> </u>	ECMA-74 (only if not covered	by FCMA-74 wit	th I na	m measurement distance	m)	
P10.2	Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m) The product meets the acoustic noise requirements of the following voluntary program/s: RAL UZ 122 (Blue							
	Angel)							

Model number *	XS548de		
Issue date *	12/16/2011	Logo	LEXMARK

Chemical emissions from printing products	Product	environmental attributes - Market requirements (continued)	equire	ment	met	
Pi0.3 Test performed according to ECMA-328 (ISO/IEC 28360) standard other specify: RAL UZ 122 (Blue Depail of the product of the following voluntary program/s Dust <0.5 Ozone 0.27 Styrene 0.017 Benzene <0.01 TVOC 2.8 Dust <0.5 Ozone Styrene 0.017 Benzene <0.01 TVOC 2.8 Dust <0.5 Ozone Styrene 0.017 Benzene <0.01 TVOC Dust <0.5 D	Item		Yes	No	n.a.	
Product The display meteral type(s): Corrugated weight (kg): 2.978 Product packaging material type(s): Low Density Polyethylene Polytopopylene: 0.05 kg/lene Polytopopylene: 0.0		Chemical emissions from printing products				
Dust <a.5 0.017="" 0.27="" 2.8<="" <a.0.01="" benzene="" ozone="" styrene="" td="" tvoc=""><td>P10.3*</td><td></td><td></td><td></td><td></td></a.5>	P10.3*					
Pilot Chemical emission requirements of the following voluntary program/s are met for: Dust Ozone Styrene Benzene TVOC	P10.4	Typical emission rate (print phase) is (mg/h):				
Styrene Styrene Styrene Styrene TVOC Styrene						
P11.1 Consumable materials for printing products P11.1 A Salety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3). P11.2 Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN12281. P11.3 2-sided (duplex) printing/copying is an integrated product function. P12.1 The display meets the ergonomic requirements of ISO 99241-307 for visual display technologies. P12.1 The physical input device meets the requirements of ISO 99395 and ISO 9241-410. P13.1 Packaging and documentation P13.1 Product packaging material type(s): Corrugated weight (kg): 2.978 Product packaging material type(s): Low Density Polyathylone, Expanded weight (kg): 0.571 Product packaging material type(s): High Density Polyathylone, Expanded weight (kg): 0.571 Product packaging material type(s): High Density Polyathylone Density Polyathy	P10.5	Dust ☑ Ozone ☑ Styrene ☑ Benzene ☑ TVOC ☑				
P11.1° A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3). P11.1° Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of P12.2° Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of P12.1° Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of P12.1° Promonics for computing products P12.1° The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies. P12.1° The physical input device meets the requirements of ISO 9241-307 for visual display technologies. P13.2° Product packaging material type(s): Corrugated weight (kg): 2.978 Product packaging material type(s): Corrugated weight (kg): 2.978 Product packaging material type(s): Corrugated weight (kg): 0.277 Polypropylene: 0.065 kg P13.2° Product packaging material type(s): Low Density Polyethylene, Expanded weight (kg): 0.277 Polypropylene: 0.065 kg P13.3° Specily media for user and product documentation (tick box): □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □						
P11.2		program/s:			Ш	
P11.2* Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN12281. P11.3* 2-sided (duplex) printing/copying is an integrated product function. P12 Ergonomics for computing products P12.1* The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies. P12.1* The physical input device meets the requirements of ISO 9395 and ISO 9241-410. P13.1* Product packaging material type(s): Corrugated weight (kg): 2.978 Product packaging material type(s): Low Density Polyethylene, Expanded weight (kg): 0.571 Product packaging material type(s): Low Density Polyethylene, Expanded weight (kg): 0.571 Product packaging material type(s): High Density Polyethylene weight (kg): 0.277 Polypropylene: 0.065 kg P13.2* Product packaging is free from PVC. P13.3* Specify media for user and product documentation (tick box): Electronic ②, Paper ②, Other □ P13.4* For paper user and product documentation, please specify contained percentage of post-consumer recycled □ P13.5* P14 Additional information (See Note B4) P1.1* This product uses RoHS exemptions for lead and mercury used in small amounts for specific applications. P2.1* The battery contained within this product should be disposed of properly with the product. The product is properly labeled with the WEEE disposal symbol and instruction for such disposal is listed in the product User's Guide. The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers. Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone = <0.21 mg/h; Styrene * 0.013 mg/h; Benzene = 0.006 mg/h; Dust = <0.5 mg/h; and TVOC = 0.77 mg/h Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/ercy			<u> </u>		_	
EN12281. P12.1* The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies. P12.1* The physical input device meets the requirements of ISO 9995 and ISO 9241-410. P13.2* Product packaging material type(s): Corrugated weight (kg): 2.978 Product packaging material type(s): Low Density Polyethylene, Expanded weight (kg): 0.277 Product packaging material type(s): High Density Polyethylene, Expanded weight (kg): 0.277 Product packaging material type(s): High Density Polyethylene, Expanded weight (kg): 0.277 Product packaging material type(s): High Density Polyethylene, Expanded weight (kg): 0.277 Product packaging material type(s): High Density Polyethylene weight (kg): 0.277 Product packaging is free from PVC. P13.2* Product plastic packaging is free from PVC. P13.4* For paper user and product documentation (tick box): Electronic ②, Paper ②, Other ③ P13.5. P14. Additional information (See Note B4) P1.1 This product uses Rolfs exemptions for lead and mercury used in small amounts for specific applications. P2.1 The battery contained within this product should be disposed of properly with the product. The product is properly labeled with the WEEE disposal symbol and instruction for such disposal is listed in the product User's Guide. The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers. Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone = <0.21 mg/h; Styrene = 0.013 mg/h; Benzene = 0.006 mg/h; Dust = <0.5 mg/h; and TVOC = 0.77 mg/h Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle				Щ.	Щ.	
P12.1 The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.		EN12281.		<u> </u>	<u> </u>	
P12.1* The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.						
P12.2* The physical input device meets the requirements of ISO 9995 and ISO 9241-410. P13.1* Product packaging and documentation P13.1* Product packaging material type(s): Corrugated weight (kg): 2.978 Product packaging material type(s): Low Density Polyethylene, Expanded weight (kg): 0.571 Product packaging material type(s): High Density Polyethylene, Expanded weight (kg): 0.277 Product packaging in gaterial type(s): High Density Polyethylene weight (kg): 0.277 Product packaging in gaterial type(s): High Density Polyethylene weight (kg): 0.277 Product packaging is free from PVC. P13.2* Product plastic packaging is free from PVC. P13.3* Specify media for user and product documentation (tick box): Electronic S. Paper S. Other D. P13.4* For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber: 0% Rev. User and product documentation do not contain chlorine bleached paper P14. Additional information (See Note B4) P1.1 This product uses RoHS exemptions for lead and mercury used in small amounts for specific applications. P2.1 The battery contained within this product should be disposed of properly with the product. The product is properly labeled with the WEEE disposal symbol and instruction for such disposal is listed in the product User's Guide. The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers. Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone — <0.21 mg/h; Styrene - 0.013 mg/h; Benzene — 0.006 mg/h; Dust — <0.5 mg/h; and TVOC — 0.77 mg/h Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/environment						
P13. Packaging and documentation P13.1 Product packaging material type(s): Corrugated weight (kg): 2.978 Product packaging material type(s): Low Density Polyethylene, Expanded weight (kg): 0.571 Product packaging material type(s): High Density Polyethylene weight (kg): 0.277 Polypropylene: 0.065 kg Product plastic packaging is free from PVC. P13.3 Specify media for user and product documentation (tick box): Electronic Ng. Paper Ng. Other P13.4 For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber: 0% Rev. P13.5 User and product documentation do not contain chlorine bleached paper P14 Additional information (See Note B4) P1.1 This product uses RoHS exemptions for lead and mercury used in small amounts for specific applications. P2.1 The battery contained within this product should be disposed of properly with the product. The product is properly labeled with the WEEE disposal symbol and instruction for such disposal is listed in the product User's Guide. P10.4 The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers. Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone – <0.21 mg/h; Styrene - 0.013 mg/h; Benzene – 0.006 mg/h; Dust – <0.5 mg/h; and TVOC – 0.77 mg/h Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle			_ <u>_</u> _	Щ.		
P13.1* Product packaging material type(s): Low Density Polyethylene, Expanded weight (kg): 0.571 Product packaging material type(s): Low Density Polyethylene, Expanded weight (kg): 0.277 Product packaging material type(s): High Density Polyethylene weight (kg): 0.277 Product packaging is free from PVC.						
Product packaging material type(s): Low Density Polyethylene, Expanded Product packaging material type(s): High Density Polyethylene Weight (kg): 0.277 Polypropylene: 0.065 kg Product plastic packaging is free from PVC. P13.3* Specify media for user and product documentation (tick box): Electronic Now Paper Now Polypropylene: 0.065 kg P13.4* For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber: 0% Rev. User and product documentation do not contain chlorine bleached paper P1.1 This product uses RoHS exemptions for lead and mercury used in small amounts for specific applications. P2.1 The battery contained within this product should be disposed of properly with the product. The product is properly labeled with the WEEE disposal symbol and instruction for such disposal is listed in the product User's Guide. The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers. Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone = <0.21 mg/h; Styrene = 0.013 mg/h; Benzene = 0.006 mg/h; Dust = <0.5 mg/h; and TVOC = 0.77 mg/h Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle						
P13.3* Specify media for user and product documentation (tick box): Electronic ☑, Paper ☑, Other ☐ P13.4* For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber: 0% Rev. User and product documentation do not contain chlorine bleached paper ☐ ☑ ☐ P14 Additional information (See Note B4) P1.1 This product uses RoHS exemptions for lead and mercury used in small amounts for specific applications. P2.1 The battery contained within this product should be disposed of properly with the product. The product is properly labeled with the WEEE disposal symbol and instruction for such disposal is listed in the product User's Guide. The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers. Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone = <0.21 mg/h; Styrene = 0.013 mg/h; Benzene = 0.006 mg/h; Dust = <0.5 mg/h; and TVOC = 0.77 mg/h Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle	-	Product packaging material type(s): Low Density Polyethylene, Expanded weight (kg): 0.571 Product packaging material type(s): High Density Polyethylene weight (kg): 0.277 Polypropylene: 0.065 kg				
Electronic No. Paper No. Other P13.4* For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber: % Rev. P13.5 P14 Additional information (See Note B4) P1.1 This product uses RoHS exemptions for lead and mercury used in small amounts for specific applications. P2.1 The battery contained within this product should be disposed of properly with the product. The product is properly labeled with the WEEE disposal symbol and instruction for such disposal is listed in the product User's Guide. The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers. Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone - <0.21 mg/h; Styrene - 0.013 mg/h; Benzene - 0.006 mg/h; Dust - <0.5 mg/h; and TVOC - 0.77 mg/h Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle	P13.2*		\square			
Rev. Description of the product documentation do not contain chlorine bleached paper P13.5 P14 Additional information (See Note B4) P1.1 This product uses RoHS exemptions for lead and mercury used in small amounts for specific applications. P2.1 The battery contained within this product should be disposed of properly with the product. The product is properly labeled with the WEEE disposal symbol and instruction for such disposal is listed in the product User's Guide. The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers. Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone - <0.21 mg/h; Styrene - 0.013 mg/h; Benzene - 0.006 mg/h; Dust - <0.5 mg/h; and TVOC - 0.77 mg/h Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle	P13.3*					
P13.5 P14 Additional information (See Note B4) P1.1 This product uses RoHS exemptions for lead and mercury used in small amounts for specific applications. P2.1 The battery contained within this product should be disposed of properly with the product. The product is properly labeled with the WEEE disposal symbol and instruction for such disposal is listed in the product User's Guide. The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers. Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone -<0.21 mg/h; Styrene - 0.013 mg/h; Benzene - 0.006 mg/h; Dust -<0.5 mg/h; and TVOC - 0.77 mg/h Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle	P13.4*					
P1.1 This product uses RoHS exemptions for lead and mercury used in small amounts for specific applications. P2.1 The battery contained within this product should be disposed of properly with the product. The product is properly labeled with the WEEE disposal symbol and instruction for such disposal is listed in the product User's Guide. The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers. Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone -<0.21 mg/h; Styrene - 0.013 mg/h; Benzene - 0.006 mg/h; Dust - <0.5 mg/h; and TVOC - 0.77 mg/h Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle		User and product documentation do not contain chlorine bleached paper				
P2.1 The battery contained within this product should be disposed of properly with the product. The product is properly labeled with the WEEE disposal symbol and instruction for such disposal is listed in the product User's Guide. The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers. Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone - <0.21 mg/h; Styrene - 0.013 mg/h; Benzene - 0.006 mg/h; Dust - <0.5 mg/h; and TVOC - 0.77 mg/h Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle						
The battery contained within this product should be disposed of properly with the product. The product is properly labeled with the WEEE disposal symbol and instruction for such disposal is listed in the product User's Guide. The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers. Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone - <0.21 mg/h; Styrene - 0.013 mg/h; Benzene - 0.006 mg/h; Dust - <0.5 mg/h; and TVOC - 0.77 mg/h Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle	P1. 1		or spe	∍cifi	.C	
product is properly labeled with the WEEE disposal symbol and instruction for such disposal is listed in the product User's Guide. The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers. Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone - <0.21 mg/h; Styrene - 0.013 mg/h; Benzene - 0.006 mg/h; Dust - <0.5 mg/h; and TVOC - 0.77 mg/h Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle	P2. 1		oduet	Tho		
Ilisted in the product User's Guide. The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers. Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone — <0.21 mg/h; Styrene - 0.013 mg/h; Benzene — 0.006 mg/h; Dust — <0.5 mg/h; and TVOC — 0.77 mg/h Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle						
The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers. Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone - <0.21 mg/h; Styrene - 0.013 mg/h; Benzene - 0.006 mg/h; Dust - <0.5 mg/h; and TVOC - 0.77 mg/h Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle			uispos	ai is		
to be removed by the customer; however, is designed for easy removal by recyclers and service providers. Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone - <0.21 mg/h; Styrene - 0.013 mg/h; Benzene - 0.006 mg/h; Dust - <0.5 mg/h; and TVOC - 0.77 mg/h Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle	P. 2. 3	listed in the product User's Guide.				
P10.4 providers. Note: The data reported in P10.4 is for the color print test. Mono print test results: Ozone - <0.21 mg/h; Styrene - 0.013 mg/h; Benzene - 0.006 mg/h; Dust - <0.5 mg/h; and TVOC - 0.77 mg/h Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle					∍d	
Mono print test results: Ozone - <0.21 mg/h; Styrene - 0.013 mg/h; Benzene - 0.006 mg/h; Dust - <0.5 mg/h; and TVOC - 0.77 mg/h Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle	P10. 4		501 7	100		
http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle		Mono print test results: Ozone – <0.21 mg/h; Styrene - 0.013 mg/h; Benzene – 0.006 m <0.5 mg/h ; and TVOC – 0.77 mg/h		Oust	_	
http://lexmark.com/recycle			ıt			

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19