



Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	
Contact information *	Nadia Martin (USA)	LEXMARK.
Internet site *	www.lexmark.se / www.lexmark.com	
Additional information		

	The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.					
Type of product *	ype of product * Multifunction Color Laser Printer					
Commercial name *	Lexmark XS734de					
Model number *	XS734de					
Issue date *	12/16/2011					
Intended market *	Global Europe Asia, Pacific & Japan Americas Other					
Additional information						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Quality Control		
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).		

Model number *	XS734de			
Issue date *	12/16/2011	Logo	1	EXMARK

Product	environmental attributes - Legal requirements	Require	emen	t met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain lead max 0.1%, cadmium max 0.01%, mercury max 0.1%, hexavalent chromium max 0.1%, polybrominated biphenyls (PBB) max 0.1% and polybrominated diphenyl ethers (PBDE) max 0,1% (see legal reference and Note 1).			
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.	\boxtimes		
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorocarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain polychlorinated biphenyl (PCB) max 0.005% by weight, polychlorinated terphenyl (PCT) max 0.005% by weight (see legal reference).	\boxtimes		
P1.5*	Products do not contain short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP max 0.1% (see legal reference).			
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain Azo colorants that split aromatic amines max 0.003% by weight (see legal reference and Note 1).			
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm2/week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\boxtimes		
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medical or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	\boxtimes		
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).	\boxtimes	T	
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).			
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\boxtimes		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note 1).			
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	\boxtimes		
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS/MSDS) in accordance with these requirements (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain lead, mercury, cadmium and hexavalent chromium max 0.01% by weight of these together.			
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\boxtimes		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.			

Note 1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *	XS734de		
Issue date *	12/16/2011	Logo	EXMARK.

Produc	ct environmental attributes - Market requirements - Environmental conscious design	Require	men	met
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P6	Treatment information			
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).	\boxtimes		
P7	Design Disassembly, recycling			
P7.1*	Parts that have to be treated separately are easily separable		П	
P7.2*	Plastic materials in covers/housing have no surface coating.		Ħ	Ħ
P7.3*	Plastic parts >100g consist of one material or of easily separable materials.		Ħ	Ħ
P7.4*	Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.		Ħ	
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.			
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).			
	Product lifetime			
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes		
P7.8*	Upgrading can be done using commonly available tools	$\overline{\boxtimes}$	Ħ	
P7.9.	Spare parts are available after end of production for: 5 years			
P7.10	Service is available after end of production for: 5 years			
	Material and substance requirements			
P7.11*	Product cover/housing material type:			
	Material type: ABS Material type: HIPS Material type: PC/ABS			
P7.12	Electrical cable insulation material of power cables are halogen free (including PVC). (See Note 1)		\boxtimes	
P7.13	Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1)		\boxtimes	
P7.14	All cover/housing plastic parts >25g are halogen free. (See Note 1)			
P7.15	All printed circuit boards (without components) >25g are halogen free. (See Note 2)		\boxtimes	
P7.16	Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40)			
P7.17	Alt. 1]
	Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive), TBBPA (reactive), Other; chemical name: , CAS #:		Ш	Ш
	TBBFA (additive) , TBBFA (reactive) , Other, Chemical Hame. , CAS #.			
	Alt. 2			
	Chemical specifications of flame retardants in printed circuit boards (without components) >25g according			
	ISO 1043-4: <i>FR(16)</i>			
P7.18	Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in			
	concentrations above 0.1%:	Ш	Ш	Ш
	Comment: No legal limits exist, this is a market requirement.			
	4.01			
	1. Chemical name: , CAS #: 2. Chemical name: , CAS #:			
	3. Chemical name: , CAS #:			
	o. Shormodi harro.			
	Alt. 2			
	Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:		_	
D7.40	FR(40), FR(17), FR(16), FR(50)			
P7.19 P7.20	Of total plastic parts' weight >25g, recycled material content is Of total plastic parts' weight >25g, biobased material content is %.			
P7.20	Light sources are free from mercury			
	If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg		Ш	
P8	Batteries			
P8.1*	Battery chemical composition: Lithium Manganese Dioxide (LiMnO2)	· <u></u>		
P8.2	Batteries meet the requirements of the following voluntary program/s:			

Note 1 For cables, covers & housing plastic parts and plastic packaging materials in this standard; halogens include fluorine, chlorine, bromine, and iodine.

Note 2 In accordance with JPCA-ES-01; printed wiring boards must not contain more than 0.09% by weight (900ppm) of chlorine or bromine.

Model number *	XS734de		
Issue date *	12/16/2011	Logo	LEXMARK.

Product environmental attributes - Market requirements (continued) Requirement met							met			
Item	_							Yes	No	n.a.
P9	Energy consumpt					<u> </u>				
9.1	For the product the	e following power levels	s or energy consum	ptions have been	measure	<u>:d:</u>				
Energy n	node *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC		eference / Star d test method		gy mode	es	
Printing		510.3 W	524.8 W	497.6 W	Co	ompany Stand	dard			
Copying	l	459 W	509 W	461 W	Co	ompany Stand	dard			
Scannin	g	54.1 W	53.5 W	57.6 W	Co	ompany Stand	dard			
Ready		37.1 W	42.6 W	46.2 W	Er	nergy Star TE	С			
Sleep		21.9 W	20.9 W	22.9 W	Er	nergy Star TE	С			
Off		<i>0</i> W	<i>0</i> W	<i>0</i> W	Er	nergy Star TE	С			
charger p	I power supply / plugged in the wall t disconnected from	W	W	W						
PTEC * Typical E	Energy Consumption	W	W	W						
TEC * Typical E	Energy Consumption	6.085 kWh/week	6.10 kWh/week	6.18 kWh/weel	k					
Default ti	ime to enter energy	save mode: 30 minutes	3	I						
P9.2*		he energy save function		he product.				\boxtimes		$\overline{}$
P9.3*	The product meets ENERGY STAR® Others specify:	the energy requirement version 1.0 Tier:1	nts of the following	voluntary progran	n/s:					
P10	Emissions									
	Noise emission -	Declared according to	ISO 9296							
P10.1	Mode N	Mode description		Declared A-weighted sound power	s	Declared ound pressure	A-weighted level $L_{p{\rm Am}}$	(dB)		
				level L_{WAd} (B)		pr position Desktop	Bystander po (only if pro operato	oduct is	not	
	Idle *	Idle/Ready		* 4.6	or [Desk side	35	- attoria	iou,	
	Operation *	Simplex Monochron	ne Printing	* 6.9			53			
	Other mode	Duplex Monochrome	e Printing	6.9			53			
	Measured according	ng to: ISO7779 Other	ECMA-74 (only if not covered	I by ECMA-74 wit	th L _{pAm} me	easurement dis	stance	m)		
P10.2										
	Chemical emissions from printing products									
P10.3*		cording to ECMA-328 (andard, other	specify: F	RAL-UZ-122		\boxtimes		
P10.4		ate (print phase) is (mg	/h):		-					
D10 5	Chaminal aminais	Dust BQL Ozone Bo					\boxtimes	N		
P10.5	Chemical emission	n requirements of the fo ר	Dust 🔀	rogram/s RAL-02 Ozone		Styrene	\boxtimes		Ш	
			Benzene 🔀	TVO	_	Gtyrene				
	Electromagnetic emissions									
P10.6		meets the requirement	for low frequency e	lectromagnetic fie	elds of the	e following volu	ıntary			

Model number *	XS734de			
Issue date *	12/16/2011	Logo]	EXMARK

Produc	oduct environmental attributes - Market requirements (continued) Requirement met				
Item		Yes	No	n.a.	
P11	Consumable materials for printing products				
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	\boxtimes			
P11.2*	Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN12281.				
P11.3*	2-sided (duplex) printing/copying is an integrated product function.	\boxtimes			
P12	Ergonomics for computing products				
P11.1*	A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).	\boxtimes			
P12.1*	The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.			\boxtimes	
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.			\boxtimes	
P13	Packaging and documentation				
P13.1*	Product packaging material type(s): Wood Product packaging material type(s): Corrugated Product packaging material type(s): Polyethylene Foam Paperboard = 0.295 kg High Density Polyethylene (HDPE) = 0.233 kg Polypropylene = 0.065 kg weight (kg): 6.505 kg weight (kg): 5.260 kg weight (kg): 2.411 kg				
P13.2*	Product plastic packaging is halogen free (including PVC). (See Note 1)	\boxtimes			
P13.3*	Specify media for user and product documentation (tick box): Electronic				
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber. 0%				
P14	Additional information				
P1.1	This product uses RoHS exemptions for lead and mercury used in small amounts for specific applicat				
P2.1	The battery contained within this product should be disposed of properly with the product. The product labeled with the WEEE disposal symbol and instructions for such disposal is listed in the product Use		erly		
P.2.3	customer; however, is designed for easy removal by recyclers and service providers.				
P.10.4	BQL = Below Quantifiable Limits - Note: The data reported is for the color print test. Mono print test results: Ozone – BQL; Styrene - 0.14 mg/hr; Benzene – BQL; Dust – BQL; and TVOC –	0.74 mg/hr	•		
	Additional company information and company environmental policy may be found at http://lexmark.co Specific printer and supply item recycling information for your area may be found at http://lexmark.co Lexmark Sweden is connected to REPA and El-kretsen		iment		

NOTE

Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Note 1 For cables, covers & housing plastic parts and plastic packaging materials in this standard; halogens include fluorine, chlorine, bromine, and iodine.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
76/769/EEC (Marketing and Use Directive)	P1.6, P1.8, P4.2
amendment 89/677/EEC	P1.4
amendment 1999/77/EC	P1.2
amendment 2003/3/EC	P1.7
amendment 94/27/EEC	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P4.2
1999/45/EC (Dangerous Preparations Directive)	P4.3
2001/58/EC (Directive on Safety Data Sheets)	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1