



## Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an \* are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	I DIZA A DIZ
Contact information *	Nadia Martin (USA)	LEXMARK.
Internet site *	www.lexmark.se / www.lexmark.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	Multifunction Monochrome Laser Printer			
Commercial name *	exmark XS860de 4			
Model number *	XS860de 4			
Issue date *	12/16/2011			
Intended market *	🔀 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 🗌 Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Requirement met		
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	$\square$	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).	$\square$	

Model number *		XS860de 4				
Issue date *		12/16/2011	Logo	EXM	ARI	K
Product environmental attributes - Legal requirements						tmet
Item			Yes	No	n.a.	
P1		bus substances and preparations				
P1.1*	Products do not contain lead max 0.1%, cadmium max 0.01%, mercury max 0.1%, hexavalent chromium max 0.1%, polybrominated biphenyls (PBB) max 0.1% and polybrominated diphenyl ethers (PBDE) max 0,1% (see legal reference and <sup>Note 1</sup> ).					
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.		$\boxtimes$			
P1.3*	Products hydrobro trichloroe	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), pmofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrach ethane, methyl bromide (see legal reference). Comment: Legal reference has no m				
P1.4*	Products	ation values. 6 do not contain polychlorinated biphenyl (PCB) max 0.005% by weight, polychlorina ax 0.005% by weight (accelerated streams)	ated terphenyl	$\boxtimes$		
P1.5*	Products	ax 0.005% by weight (see legal reference). do not contain short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the 100 (see users) of chloride in the 200P mere 2.40 (see users)	chain containing	$\square$		
P1.6*		48% per mass of chlorine in the SCCP max 0.1% (see legal reference). nd leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-pho	sphate (TRIS)			
1 1.0	Tris-(azi	ridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal referencent: t: Legal reference has no maximum concentration values.				
P1.7*	Textile a	nd leather parts with direct skin contact do not contain Azo colorants that split arom 03% by weight (see legal reference and Note 1).	natic amines			$\boxtimes$
P1.8*	Wooden pentachl	parts do not contain arsenic and chromium as a wood preservation treatment as w orophenol and derivatives (see legal reference).	ell as			
P1.9*	Comment: Legal reference has no maximum concentration values. Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm2/week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.					
P2	Batterie					
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)					
P2.2*		ells used in the product do not contain more than 2% by weight of mercury. Other b ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See le		$\boxtimes$		
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medical or data integrity reasons do not have to be "easily removable". (See legal reference)		$\boxtimes$			
P3		EMC connection to the telephone network and labeling				
P3.1*		duct complies with legally required safety standards as specified (see legal reference	;e).	$\square$		
P3.2*	The proc	duct complies with legally required standards for electromagnetic compatibility (see	legal reference).		Ħ	Ħ
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).					
P3.4*		duct is labeled to show conformance with applicable legal requirements (see legal re		$\square$		
P4	Consum	nable materials				
P4.1*	legal refe	o conductor (drum, belt etc.) is used in the product, it does not contain cadmium ma erence and Note 1).	,	$\boxtimes$		
P4.2*	If ink/ton	er is used in the product, it does not contain cadmium max 0.1% by weight (see leg	al reference).	$\boxtimes$		
P4.3*	product/	/toner formulation/preparation is classified as hazardous according to applicable re- packaging is adequately labeled and a Safety Data Sheet (SDS/MSDS) in accordar ients (see legal reference).				
P5		packaging				
P5.1*	max 0.0	ng and packaging components do not contain lead, mercury, cadmium and hexaval 1% by weight of these together.				
P5.2*	Plastic p	ackaging material is marked according to ISO 11469 referring ISO 1043 (see legal	reference).	$\square$		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.					
	-	-				

Note 1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model nu		XS860de 4			
Issue da	te *	12/16/2011 Logo	LEXM	ARK	
Produ	ct enviro	nmental attributes - Market requirements - Environmental conscious design	Require	mont	mot
Item		atory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P6		nt information	103	INU	n.a.
P6.1*		on for recyclers/treatment facilities is available (see legal reference).			
P7	Design				
		mbly, recycling			
P7.1*		t have to be treated separately are easily separable	$\square$		
P7.2*	Plastic m	naterials in covers/housing have no surface coating.	$\square$		
P7.3*	Plastic p	arts >100g consist of one material or of easily separable materials.	$\boxtimes$		
P7.4*	Plastic p	arts >25g have material codes according to ISO 11469 referring ISO 1043.	$\square$		
P7.5	Plastic p	arts are free from metal inlays or have inlays that can be removed with commonly available tools.	$\boxtimes$		
P7.6*	Labels a	re easily separable. (This requirement does not apply to safety/regulatory labels).	$\square$		
	Product	lifetime			
P7.7*	Upgradir	g can be done e.g. with processor, memory, cards or drives	$\boxtimes$		
P7.8*	Upgradir	g can be done using commonly available tools	$\square$		
P7.9.	Spare pa	arts are available after end of production for: 5 years			Π
P7.10	Service	s available after end of production for: 5 years			Ē
	Material	and substance requirements			
P7.11*		cover/housing material type:			
		type: ABS Material type: HIPS Material type: PC/AB	<u>s</u>		
P7.12		I cable insulation material of power cables are halogen free (including PVC). (See Note 1)			
P7.13	Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1)				
P7.14	All cover/housing plastic parts >25g are halogen free. (See Note 1)				
P7.15	All printed circuit boards (without components) >25g are halogen free. (See Note 2)				
P7.16	Flame re Marking:	tarded plastic parts >25g in covers / housings are marked according ISO 1043-4: <i>FR(40)</i>			
P7.17		I specifications of flame retardants in printed circuit boards >25g (without components): additive) , TBBPA (reactive) , Other; chemical name: , CAS #:			
	ISO 104	I specifications of flame retardants in printed circuit boards (without components) >25g according 3-4: <i>FR(16)</i>			
P7.18	concentr	tarded plastic parts >25g contain the following flame retardant substances/preparations in ations above 0.1%: it: No legal limits exist, this is a market requirement.			
	2. Chem	ical name: , CAS #: ical name: , CAS #: ical name: , CAS #:			
	FR(40),	I specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(17), FR(16), FR(50)			
P7.19		plastic parts' weight >25g, recycled material content is %.			
P7.20 P7.21		plastic parts' weight >25g, biobased material content is %.			
F1.21		rces are free from mercury y is used specify: Number of lamps: and max. mercury content per lamp: mg	$\bowtie$		
P8	Batterie				
P8.1*		hemical composition: Lithium Manganese Dioxide (LiMnO2)			
P8.2	Pottorios	meet the requirements of the following voluntary program/s:			H

Note 1 For cables, covers & housing plastic parts and plastic packaging materials in this standard; halogens include fluorine, chlorine, bromine, and iodine.

Note 2 In accordance with JPCA-ES-01; printed wiring boards must not contain more than 0.09% by weight (900ppm) of chlorine or bromine.

Model number *	XS860de 4		
Issue date *	12/16/2011	Logo	LEXMARK

Produc	ct environmental a	attributes - Marke	t requirements (	continued)	Requirement m	
Item			•	-	Yes No n	
P9	Energy consumpt					
9.1	For the product the	following power leve	ls or energy consur	nptions have beer	n measured:	
Energy	mode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standard for energy modes and test method *	
Printing	3	724.7 W	642.1 W	666.7W	Corporate Standard	
Copyin	q	727.8 W	749.8 W	781.1 W	Corporate Standard	
Scannir	-	158.4 W	137.6 W	163.2 W	Corporate Standard	
	-	W	W	W		
Sleep N	lode	20.5 W	20.9 W	20.16 W	Energy Star TEC Test Procedure	
Off		0.09 W	0.12 W	0.48 W	IEC 62301 / Energy Star	
EPS No	load	W	W	W		
(Externa charger	al power supply / plugged in the wall ut disconnected from		, vv	vv		
PTEC * Typical	Energy Consumption	W	W	W		
TEC * Typical	Energy Consumption	6.18 kWh/week	6.15 kWh/week	6.11 kWh/wee	ικ [	
	time to enter energy s	ave mode: 1 minutes	3		l	
P9.2*	•••	ne energy save funct		the product		
P9.3*	The product meets ENERGY STAR® A Others specify: <b>RA</b>		ents of the following	i voluntary prograr	m/s:	
P10	Emissions					
1 10		Declared according t	o ISO 9296			
P10.1		lode description		Declared	Declared A-weighted	
				A-weighted	sound pressure level $L_{pAm}$ (dB)	
				sound power	Operator position Bystander positions	
				level $L_{WAd}$ (B)	Desktop (only if product is not	
					or Desk side operator attended)	
	Idle *	Ready		* 4.5	30	
		<u></u>		* • • •		
	Operation *	Simplex Monochro	me Printing	* 6.8	53	
	Other mode	Duplex Monochron	ne Printing	7.1	55	
	Measured accordin	g to: 🛛 ISO7779 🗌 Other	_	d by ECMA-74 wi	th L <sub>pAm</sub> measurement distance m)	
P10.2	The product meets				program/s: RAL-UZ 122	
	Chemical emissions from printing products					
P10.3*		Test performed according to ECMA-328 (ISO/IEC 28360) standard , other specify: RAL-UZ-122				
P10.4	4 Typical emission rate (print phase) is (mg/h):					
	Dust <0.7 Ozone <0.06 Styrene <0.12 Benzene <0.03 TVOC 0.99					
P10.5						
	Dust 🛛 Ozone 🖄 Styrene 🖂 Benzene 🖾 TVOC 🔀					
	Electromagnetic e	missions		100		
P10.6	Computer display n		t for low frequency	electromagnetic fi	elds of the following voluntary	
	program/s:					

Model n		XS860de 4					
Issue date *		12/16/2011	Logo		LEXM	RK	
Produc	t enviror	nmental attributes - Market requirements (continued)			Require	ment	met
Item					Yes	No	n.a.
P11	Consum	able materials for printing products					
P11.1*		Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ	uired (see	P4.3).	$\boxtimes$		
P11.2*	Paper co EN1228	ontaining post-consumer recycled fibers can be used, provided that it meets the rec 1.	quirements	of	$\square$		
P11.3*	2-sided (	duplex) printing/copying is an integrated product function.			$\boxtimes$		
P12		nics for computing products					
P11.1*		Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ		P4.3).	$\boxtimes$		
P12.1*	The disp	lay meets the ergonomic requirements of ISO 9241-307 for visual display technolo	gies.				X
P12.2*	The phys	sical input device meets the requirements of ISO 9995 and ISO 9241-410.					$\mathbf{X}$
P13	Packagi	ng and documentation					
P13.1*	Product Product <i>Polypro</i>	packaging material type(s): <i>Corrugated</i> weight (kg): <i>8.505</i> packaging material type(s): <i>Expanded Polystyrene (EPS)</i> weight (kg): <i>1.179</i> packaging material type(s): <i>High Density Polyethylene (HDPE)</i> weight (kg): <i>0.09</i> <i>pylene (PP) = 0.113 kg</i> <i>5.942 kg</i>	)1				
P13.2*	Product	plastic packaging is halogen free (including PVC). (See Note 1)			$\square$		
P13.3*	Specify r Electroni	nedia for user and product documentation (tick box): ic Paper 🛛 Other 🗌					
P13.4*	* For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber. 0%						
P14		nal information					
P1.1	This product uses RoHS exemptions for lead used in small amounts for specific applications.						
P2.1	labeled with the WEEE disposal symbol and instructions for such disposal is listed in the product User's Guide.						
P.2.3	3 The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers.						
	Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle Lexmark Sweden is connected to REPA and El-kretsen						

NOTE

Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Note 1 For cables, covers & housing plastic parts and plastic packaging materials in this standard; halogens include fluorine, chlorine, bromine, and iodine.

## Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
76/769/EEC (Marketing and Use Directive)	P1.6, P1.8, P4.2
amendment 89/677/EEC	P1.4
amendment 1999/77/EC	P1.2
amendment 2003/3/EC	P1.7
amendment 94/27/EEC	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P4.2
1999/45/EC (Dangerous Preparations Directive)	P4.3
2001/58/EC (Directive on Safety Data Sheets)	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1