



Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	I DIZA A DIZ
Contact information *	Nadia Martin (USA)	LEXIMARK.
Internet site *	www.lexmark.se / www.lexmark.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	Multifunction Monochrome Laser Printer			
Commercial name *	exmark XS864de 4			
Model number *	XS864de 4			
Issue date *	12/16/2011			
Intended market *	Global 📃 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other			
Additional information	Additional information			

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality Control			Requirement met		
Item		Yes	No		
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes			
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).	\square			

Model number *		XS864de 4				
Issue date *		12/16/2011	Logo	EXM	AR	K
Product environmental attributes - Legal requirements					emen	t met
Item					No	n.a.
P1		bus substances and preparations				
P1.1*	max 0.19	6 do not contain lead max 0.1%, cadmium max 0.01%, mercury max 0.1%, hexavale %, polybrominated biphenyls (PBB) max 0.1% and polybrominated diphenyl ethers be legal reference and ^{Note 1}).	ent chromium (PBDE) max			
P1.2*	Products	s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.		\square		
P1.3*		the Logar Performed has the maximum concernmenter varies.		\boxtimes		
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.					
P1.4*		s do not contain polychlorinated biphenyl (PCB) max 0.005% by weight, polychlorin ax 0.005% by weight (see legal reference).	ated terphenyl	\square		
P1.5*		s do not contain short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the 48% per mass of chlorine in the SCCP max 0.1% (see legal reference).	chain containing			
P1.6*	Textile a Tris-(azi	nd leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-pho ridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference nt: Legal reference has no maximum concentration values.				
P1.7*	Textile a	nd leather parts with direct skin contact do not contain Azo colorants that split arom 03% by weight (see legal reference and Note 1).	natic amines			\square
P1.8*	Wooden pentachl	parts do not contain arsenic and chromium as a wood preservation treatment as w orophenol and derivatives (see legal reference). ht: Legal reference has no maximum concentration values.	ell as			
P1.9*	Parts wit microgra	h direct and prolonged skin contact do not release nickel in concentrations above (m/cm2/week (see legal reference).	0.5			
Do		ht: Max limit in legal reference when tested according to EN1811:1998.				
P2	Batterie		d if it contains			_
P2.1*	more that marked	oduct contains a battery or an accumulator, it is labeled with the disposal symbol an an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lea with the chemical symbol for the metal concerned, Hg or Pb. Information on proper in user manual. (See legal reference)	ad, it shall be			
P2.2*		ells used in the product do not contain more than 2% by weight of mercury. Other b ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See le		\square		
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medical or data integrity reasons do not have to be "easily removable". (See legal reference)					
P3		EMC connection to the telephone network and labeling				
P3.1*	The proc	duct complies with legally required safety standards as specified (see legal reference	ce).	\boxtimes		
P3.2*	The proc	duct complies with legally required standards for electromagnetic compatibility (see	legal reference).			
P3.3*	If produc	t is intended for connection to a public telecom network or contains a radio transmi ally required standards for radio and telecommunication devices (see legal referenc	tter, it complies			
P3.4*		duct is labeled to show conformance with applicable legal requirements (see legal r		\boxtimes		
P4		nable materials	,			
P4.1*	If a phot	o conductor (drum, belt etc.) is used in the product, it does not contain cadmium ma erence and Note 1).	ax 0.01% (see			
P4.2*	If ink/ton	er is used in the product, it does not contain cadmium max 0.1% by weight (see leg	gal reference).	\square		
P4.3*	product/	/toner formulation/preparation is classified as hazardous according to applicable re packaging is adequately labeled and a Safety Data Sheet (SDS/MSDS) in accordant tents (see legal reference).				
P5		packaging				
P5.1*		ng and packaging components do not contain lead, mercury, cadmium and hexaval 1% by weight of these together.	ent chromium	\square		
P5.2*	Plastic p	ackaging material is marked according to ISO 11469 referring ISO 1043 (see legal	reference).	\boxtimes		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.		Montreal			
	÷.					

Note 1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *		XS864de 4				
Issue date *		12/16/2011 Logo	LEXM	AR	K	
Product environmental attributes - Market requirements - Environmental conscious			Require	men	t met	
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.			No	n.a.	
P6	Treatment information					
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).					
P7	Design Disasse	mbly, recycling				
P7.1*	Parts that	t have to be treated separately are easily separable	\square			
P7.2*	Plastic m	naterials in covers/housing have no surface coating.	\square			
P7.3*	Plastic p	arts >100g consist of one material or of easily separable materials.				
P7.4*	Plastic p	arts >25g have material codes according to ISO 11469 referring ISO 1043.				
P7.5	Plastic p	arts are free from metal inlays or have inlays that can be removed with commonly available tools.		Ē		
P7.6*		re easily separable. (This requirement does not apply to safety/regulatory labels).		Ħ		
	Product					
P7.7*		ng can be done e.g. with processor, memory, cards or drives	\square			
P7.8*	Upgradir	ng can be done using commonly available tools		Ē		
P7.9.		arts are available after end of production for: 5 years				
P7.10		s available after end of production for: 5 years			H	
		and substance requirements				
P7.11*		cover/housing material type:				
		type: ABS Material type: HIPS Material type: PC/ABS				
P7.12		I cable insulation material of power cables are halogen free (including PVC). (See Note 1)		\boxtimes		
P7.13	Electrical cable insulation material of signal cables are halogen free (including PVC). (See Note 1)					
P7.14	All cover/housing plastic parts >25g are halogen free. (See Note 1)					
P7.15	All printed circuit boards (without components) >25g are halogen free. (See Note 2)					
P7.16	Flame re Marking:	etarded plastic parts >25g in covers / housings are marked according ISO 1043-4: FR(40)	\square			
P7.17	Alt. 1	I specifications of flame retardants in printed circuit boards >25g (without components):				
		additive) , TBBPA (reactive) , Other; chemical name: , CAS #:				
	Alt. 2			_		
		Il specifications of flame retardants in printed circuit boards (without components) >25g according 3-4: <i>FR(16)</i>	\square			
P7.18	Alt. 1 Flame re	tarded plastic parts >25g contain the following flame retardant substances/preparations in				
	concentr	ations above 0.1%:				
	Commer	t: No legal limits exist, this is a market requirement.				
	1 Chom	ical name: , CAS #:				
		ical name: , CAS #:				
		ical name: CAS #:				
	Alt. 2	l aposifications of flome reterdents in plastic parts > 25g according ISO 1042 4:	\boxtimes			
		Il specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(17), FR(16), FR(50)				
P7.19	Of total p	plastic parts' weight >25g, recycled material content is %.				
P7.20	Of total p	plastic parts' weight >25g, biobased material content is %.				
P7.21		Irces are free from mercury	\square			
Do		y is used specify: Number of lamps: and max. mercury content per lamp: mg				
P8 P8.1*	Batterie:	s hemical composition: Lithium Manganese Dioxide (LiMnO2)				
P8.2	-	meet the requirements of the following voluntary program/s:				
1 0.2	Datteries	meet the requirements of the following voluntary program/s.				

Note 1 For cables, covers & housing plastic parts and plastic packaging materials in this standard; halogens include fluorine, chlorine, bromine, and iodine.

Note 2 In accordance with JPCA-ES-01; printed wiring boards must not contain more than 0.09% by weight (900ppm) of chlorine or bromine.

Model number *	XS864de 4		
Issue date *	12/16/2011	Logo	LEXMARK

	t environmental a	attributes - Market	requirements (c	ontinued)	Rec	quirement	met
Item						Yes No	n.a.
P9	Energy consumpt						
9.1	For the product the	following power level	s or energy consum	ptions have been	<u>n measured:</u>		
Energy r	mode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standard for energy and test method *	gy modes	
Printing	l	828.7W	821.3 W	741.9 W	Corporate Standard		
Copying	3	809.1 W	783.6 W	824.4 W	Corporate Standard		ħ
Scannin	ng	191.5 W	175.8 W	179.7 W	Corporate Standard		ħ
Ready M	lode	155.3 W	129.9 W	125.6 W	Energy Star TEC Test Proce	dure	Ħ
Sleep M	lode	21.09 W	21.21 W	20.11 W	Energy Star TEC Test Proce	dure	Ħ
Off		0.09 W	0.10 W	0.48 W	IEC 62301 / Energy Star		H
EPS No	load	W	W	W			
(Externa charger	I power supply / plugged in the wall ut disconnected from	vv					
PTEC * Typical I	Energy Consumption	W	W	W			
TEC * Typical I	Energy Consumption	10.52 kWh/week	10.24 kWh/week	10.01 kWh/we	ek		
		ave mode: 60 minute	s				
P9.2*		ne energy save function		he product.			H
P9.3*	The product meets ENERGY STAR® v Others specify: RA		ents of the following	voluntary prograr	n/s:		
P10	Emissions						
		Declared according to	ISO 9296				
P10.1	Mode M	lode description		Declared A-weighted	5		
				A-weighted sound pressure level L_{pAm}		(dB)	
				level L_{WAd} (B)	Operator position Bystander po		
						oduct is not r attended)	
	1.00	Death		+ 10	or Desk side	i allonaca)	
	Idle *	Ready		* 4.6	30		
	Operation *	Simplex Monochron	ne Printing	* 6.9	53		
	Other mode	Duplex Monochrom	e Printing	7.2	56		
	Measured accordin	g to: 🛛 ISO7779 🗌 Other	ECMA-74 (only if not covered	d by ECMA-74 wit	th L _{pAm} measurement distance	m)	
P10.2							
	Chemical emissions from printing products						
P10.3*	Test performed according to ECMA-328 (ISO/IEC 28360) standard , other specify: RAL-UZ-122						
P10.4		te (print phase) is (mo					
P10.5		Dust <0.7 Ozone <			.03 TVOC 0.24		
F 10.3	Chemical emission	Chemical emission requirements of the following voluntary program/s <i>RAL-UZ-122</i> are met for : Dust Ozone Ozone Styrene					
	Benzene X TVOC X						
	Electromagnetic emissions						
P10.6		neets the requirement	for low frequency e	electromagnetic fi	elds of the following voluntary		\boxtimes
	program/s:						

Model n		XS864de 4					
Issue date *		12/16/2011	Logo		LEXM	RK	
Produc	t enviror	nmental attributes - Market requirements (continued)			Require	ment	met
Item					Yes	No	n.a.
P11	Consum	able materials for printing products					
P11.1*		Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ	uired (see	P4.3).	\boxtimes		
P11.2*	Paper co EN1228	ontaining post-consumer recycled fibers can be used, provided that it meets the rec 1.	quirements	of	\square		
P11.3*	2-sided (duplex) printing/copying is an integrated product function.			\boxtimes		
P12		nics for computing products					
P11.1*		Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ		P4.3).	\boxtimes		
P12.1*	The disp	lay meets the ergonomic requirements of ISO 9241-307 for visual display technolo	gies.				X
P12.2*	The phys	sical input device meets the requirements of ISO 9995 and ISO 9241-410.					\mathbf{X}
P13	Packagi	ng and documentation					
P13.1*	Product Product <i>Polypro</i>	packaging material type(s): <i>Corrugated</i> weight (kg): <i>8.505</i> packaging material type(s): <i>Expanded Polystyrene (EPS)</i> weight (kg): <i>1.179</i> packaging material type(s): <i>High Density Polyethylene (HDPE)</i> weight (kg): <i>0.09</i> <i>pylene (PP) = 0.113 kg</i> <i>5.942 kg</i>)1				
P13.2*	Product	plastic packaging is halogen free (including PVC). (See Note 1)			\square		
P13.3*	Specify media for user and product documentation (tick box):						
P13.4*	For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber. 0%						
P14	Additional information						
P1.1	This product uses RoHS exemptions for lead used in small amounts for specific applications.						
P2.1	The battery contained within this product should be disposed of properly with the product. The product is properly labeled with the WEEE disposal symbol and instructions for such disposal is listed in the product User's Guide.						
P.2.3	The battery contained within this product meets the exception listed. The battery is not intended to be removed by the customer; however, is designed for easy removal by recyclers and service providers.						
	Additional company information and company environmental policy may be found at http://lexmark.com/environment Specific printer and supply item recycling information for your area may be found at http://lexmark.com/recycle Lexmark Sweden is connected to REPA and El-kretsen						

NOTE

Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Note 1 For cables, covers & housing plastic parts and plastic packaging materials in this standard; halogens include fluorine, chlorine, bromine, and iodine.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
76/769/EEC (Marketing and Use Directive)	P1.6, P1.8, P4.2
amendment 89/677/EEC	P1.4
amendment 1999/77/EC	P1.2
amendment 2003/3/EC	P1.7
amendment 94/27/EEC	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P4.2
1999/45/EC (Dangerous Preparations Directive)	P4.3
2001/58/EC (Directive on Safety Data Sheets)	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1