

## Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an \* are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lexmark	Logo
Company name *	Lexmark International, Inc.	I DOZBA A DIZ
Contact information *	Nadia Martin (USA)	LEXMARK,
Internet site *	www.lexmark.se / www.lexmark.com	
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.					
Type of product *	Multifunction Color Laser Printer				
Commercial name *	Lexmark XS955dhe				
Model number *	XS955dhe				
Issue date *	6-9-2011				
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Qualit	y Control	Requireme	nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	$\boxtimes$	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contributes as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model number *	XS955dhe		
Issue date *	6-9-2011	Logo	LEXMARK

Product	Product environmental attributes - Legal requirements				
Item		Yes	No	n.a.	
P1	Hazardous substances and preparations			-	
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)				
P1.2*	Products do not contain Asbestos (see legal reference).  Comment: Legal reference has no maximum concentration value.				
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.				
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	$\boxtimes$			
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	$\boxtimes$			
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.				
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			$\boxtimes$	
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference).  Comment: Legal reference has no maximum concentration values.				
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm²/week (see legal reference).  Comment: Max limit in legal reference when tested according to EN1811:1998.				
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): REACH Program Manager, HOD9237, 740 W. New Circle Rd., Lexington, KY 40550				
P2	Batteries				
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)				
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)				
P2.3*					
P3	Safety, EMC connection to the telephone network and labeling				
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	$\boxtimes$			
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).	$\boxtimes$			
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).	$\boxtimes$			
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	$\boxtimes$	П		
P4	Consumable materials				
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).	$\boxtimes$			
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).	$\boxtimes$			
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).				
P5	Product packaging				
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.	I 🔯			
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	$\boxtimes$			
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see legal reference).  Comment: Legal reference has no maximum concentration values.	I 🔀			

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Product   environmental attributes - Market requirements - Environmental conscious design   Requirement metter	Issue date * 6-9-2011		6-9-2011 Logo	LEXM	<b>NRK</b>	
tem						
P6.1* Information for recyclers/treatment facilities is available (see legal reference).  P7. Design Disassembly, recycling  P7.1* Parts that have to be treated separately are easily separable P7.2* Plastic materials in covers/housing have no surface coating. P7.3* Plastic parts >100g consist of one material or of easily separable materials. P7.4* Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043. P7.5* Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels).  P7.6* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years  Material and substance requirements P7.11* Product cover/housing material type: Material type: PC ABS Material type: PC Material type: PC ABS PS  Material type: PC ABS Material type: PC ABS PS  P7.12 Electrical cable insulation materials of signal cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, >PC+ABS+PS-HI FR(40)<						
P6.1* Information for recyclers/treatment facilities is available (see legal reference).    P7			7 0 0 7	Yes	NO	n.a.
Design   Disassembly, recycling				$\square$		$\overline{}$
Pr.1*   Parts that have to be treated separately are easily separable   Pr.2*   Plastic materials in covers/housing have no surface coating.   Pr.3*   Plastic parts >100g consist of one material or of easily separable materials.   Pr.4*   Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.   Pr.5*   Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.   Pr.5*   Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.   Pr.6*   Labels are easily separable. (This requirement does not apply to safety/regulatory labels).   Product lifetime   Pr.7*   Upgrading can be done e.g. with processor, memory, cards or drives   Pr.8*   Upgrading can be done using commonly available tools   Pr.9*   Spare parts are available after end of production for: 5 years   Pr.10*   Service is available after end of production for: 5 years   Pr.10*   Product cover/housing material type: PC   Material type: PC ABS PS   Material type: PC ABS PS   Material type: PC ABS PS   Pr.12*   Electrical cable insulation materials of power cables are PVC free   Pr.13*   Electrical cable insulation materials of signal cables are PVC free   Pr.14*   All cover/housing plastic parts >25g are free from chlorine and bromine.   Pr.15*   All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See   Note B2)   Pr.16*   Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:   Marking: >PC+ABS-FR(40)<, >PC+ABS-FR(40)<, >PC+ABS-FR(40)<, >PC+ABS-FR(40)<, >PC+BS-FR(40)<, >			or to too your outrion to arango to arango to or organization.		<u> </u>	ш
P7.1* Parts that have to be treated separately are easily separable  P7.2* Plastic materials in covers/housing have no surface coating.  P7.3* Plastic parts >100g consist of one material or of easily separable materials.  P7.4* Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.  P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.  P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels).  Product lifetime  P7.7* Upgrading can be done e.g. with processor, memory, cards or drives  P7.8* Upgrading can be done using commonly available tools  P7.9. Spare parts are available after end of production for: 5 years  P7.10 Service is available after end of production for: 5 years  P7.11* Product cover/housing material type:  Material and substance requirements  P7.12 Electrical cable insulation materials of power cables are PVC free.  P7.13 Electrical cable insulation materials of signal cables are PVC free.  P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine.  P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC+ABS+PS-HI FR(40)<	F /		mbly, recycling			
P7.3* Plastic parts >100g consist of one material or of easily separable materials.  P7.4* Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.  P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.  P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels).  Product lifetime  P7.7* Upgrading can be done e.g. with processor, memory, cards or drives  P7.8* Upgrading can be done using commonly available tools  P7.9. Spare parts are available after end of production for: 5 years  P7.10 Service is available after end of production for: 5 years  Material and substance requirements  P7.11* Product cover/housing material type:  Material type: PC ABS  Material type: PC ABS PS  P7.12 Electrical cable insulation materials of power cables are PVC free.  P7.13 Electrical cable insulation materials of signal cables are PVC free  P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine.  P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC+ABS+PS-HI FR(40)<	P7.1*			$\boxtimes$		$\Box$
P7.4* Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.  P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.  P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels).  Product lifetime  P7.7* Upgrading can be done e.g. with processor, memory, cards or drives  P7.8* Upgrading can be done using commonly available tools  P7.9. Spare parts are available after end of production for: 5 years  P7.10 Service is available after end of production for: 5 years  P7.11* Product cover/housing material type:  Material and substance requirements  P7.12 Electrical cable insulation materials of power cables are PVC free.  P7.13 Electrical cable insulation materials of signal cables are PVC free  P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine.  P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC+FR(40)<, >PC+ABS+PS-HI FR(40)<	P7.2*	Plastic m	naterials in covers/housing have no surface coating.			Ħ
P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.  P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels).  Product lifetime  P7.7* Upgrading can be done e.g. with processor, memory, cards or drives  P7.8* Upgrading can be done using commonly available tools  P7.9. Spare parts are available after end of production for: 5 years  P7.10 Service is available after end of production for: 5 years  P7.11* Product cover/housing material type:  Material and substance requirements  P7.12 Electrical cable insulation materials of power cables are PVC free.  P7.13 Electrical cable insulation materials of signal cables are PVC free  P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine.  P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC-FR(40)<, >PC-FR(40)	P7.3*	Plastic p	arts >100g consist of one material or of easily separable materials.			
Product lifetime  Product lifetime  Prost Upgrading can be done e.g. with processor, memory, cards or drives  Prost Upgrading can be done using commonly available tools  Prost Upgrading can be done using cards or drives  Material type: PC ABS PS  Product cover/housing material type: PC Material type: PC ABS PS  Product Lifetime  Naterial type: PC ABS PS  All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See District Distri	P7.4*	Plastic p	arts >25g have material codes according to ISO 11469 referring ISO 1043.			
Product lifetime  Product lifetime  Product lifetime  Product lifetime  Product lifetime  Product cover/housing material type:  Material type: PC ABS  Product cover/housing materials of power cables are PVC free.  Product cable insulation materials of signal cables are PVC free  Product cover/housing plastic parts >25g are free from chlorine and bromine.  Product cover/housing plastic parts >25g in covers / housings are marked according ISO 1043-4:  Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC-FR(40)<, >PC-FR(40)<, >PC-FR(40)<, >PC-FR(40)<<, >PC-FR(40)<<, >PC-FR(40)<<, >PC-FR(40)<<, >PC-FR(40)<<, >PC-FR(40)<	P7.5	Plastic p	arts are free from metal inlays or have inlays that can be removed with commonly available tools	3.		
P7.7* Upgrading can be done e.g. with processor, memory, cards or drives  P7.8* Upgrading can be done using commonly available tools  P7.9. Spare parts are available after end of production for: 5 years  P7.10 Service is available after end of production for: 5 years  Material and substance requirements  P7.11* Product cover/housing material type: Material type: PC ABS  Material type: PC ABS  Material type: PC ABS PS  P7.12 Electrical cable insulation materials of power cables are PVC free.  P7.13 Electrical cable insulation materials of signal cables are PVC free  P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine.  P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC+ABS+PS-HI FR(40)<	P7.6*	Labels a	re easily separable. (This requirement does not apply to safety/regulatory labels).			
P7.8* Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years  Material and substance requirements P7.11* Product cover/housing material type: Material type: PC ABS Material type: PC Material type: PC ABS PS  P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC+ABS+PS-HI FR(40)<		Product	lifetime			
P7.9. Spare parts are available after end of production for: 5 years  P7.10 Service is available after end of production for: 5 years  Material and substance requirements  P7.11* Product cover/housing material type: Material type: PC ABS  Material type: PC ABS  Material type: PC ABS PS  P7.12 Electrical cable insulation materials of power cables are PVC free.  P7.13 Electrical cable insulation materials of signal cables are PVC free  P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine.  P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC+ABS+PS-HI FR(40)<	P7.7*	Upgradir	ng can be done e.g. with processor, memory, cards or drives	$\boxtimes$		
P7.10 Service is available after end of production for: 5 years    Material and substance requirements	P7.8*	Upgradir	ng can be done using commonly available tools	$\boxtimes$		
Material and substance requirements  P7.11* Product cover/housing material type: Material type: PC Material type: PC ABS PS  P7.12 Electrical cable insulation materials of power cables are PVC free.  P7.13 Electrical cable insulation materials of signal cables are PVC free  P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine.  P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC+ABS+PS-HI FR(40)<	P7.9.	Spare pa	arts are available after end of production for: 5 years			
P7.11* Product cover/housing material type:  Material type: PC ABS  Material type: PC Material type: PC Material type: PC Material type: PC ABS PS  P7.12 Electrical cable insulation materials of power cables are PVC free.  P7.13 Electrical cable insulation materials of signal cables are PVC free  P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine.  P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC+ABS+PS-HI FR(40)<	P7.10	Service i	s available after end of production for: 5 years			
Material type: PC ABS Material type: PC Material type: PC ABS PS  P7.12 Electrical cable insulation materials of power cables are PVC free.  P7.13 Electrical cable insulation materials of signal cables are PVC free  P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine.  P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC+ABS+PS-HI FR(40)<		Material	and substance requirements			
P7.12 Electrical cable insulation materials of power cables are PVC free.  P7.13 Electrical cable insulation materials of signal cables are PVC free  P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine.  P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC+ABS+PS-HI FR(40)<	P7.11*		• • • • • • • • • • • • • • • • • • • •			
P7.13 Electrical cable insulation materials of signal cables are PVC free  P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine.  P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC+ABS+PS-HI FR(40)<				BS PS		
P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine.  P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC+ABS+PS-HI FR(40)<	P7.12	Electrica	I cable insulation materials of power cables are PVC free.	$\boxtimes$		
P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC+ABS+PS-HI FR(40)<	P7.13	Electrica	I cable insulation materials of signal cables are PVC free	$\boxtimes$		
Note B2)  P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC+ABS+PS-HI FR(40)<	P7.14	All cover	/housing plastic parts >25g are free from chlorine and bromine.	$\boxtimes$		
P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:  Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC+ABS+PS-HI FR(40)<	P7.15	All printe	ed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21.	(See 🔀		
Marking: >PC+ABS-FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC+ABS+PS-HI FR(40)<		Note B2)				
	P7.16					
	P7 17	Marking:	>PC+ABS+FR(40)<, >PC+ABS-TD10 FR(40)<, PC-FR(40)<, >PC+ABS+PS-HI FR(40)<			

. CAS #:

Chemical specifications of flame retardants in printed circuit boards >25g (without components):

Chemical specifications of flame retardants in printed circuit boards (without components) >25g according

Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in

Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45,

Batteries meet the requirements of the following voluntary program/s: Lithium Manganese Dioxide

TBBPA (additive) , TBBPA (reactive) , Other; chemical name:

Comment: No legal limits exist, this is a market requirement.

Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:

R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)

, CAS #:

, CAS #:

, CAS #:

Of total plastic parts' weight >25g, recycled material content is

Of total plastic parts' weight >25g, biobased material content is

Model number \* XS955dhe

ISO 1043-4:

concentrations above 0.1%:

Light sources are free from mercury

Battery chemical composition:

If mercury is used specify: Number of lamps:

1. Chemical name:

2. Chemical name:

3. Chemical name:

Alt. 2

**Batteries** 

P7.18

P7.19

P7.20

P7.21

P7.22

P8

P8.1\*

P8.2

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

and max. mercury content per lamp:

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

 $\boxtimes$ 

mg

Model number *	XS955dhe			
Issue date *	6-9-2011	Logo	LEXMAR.	Ķ

Product 6	roduct environmental attributes - Market requirements (continued) Requirement met					met	
Item					n.a.		
P9	6,7						
9.1	For the product the	e following power levels	or energy consump	tions are reporte	ed:		=
Energy mo	de *	Power level at 100 V AC	Power level at 115 V AC	Power level 230 V AC	at	Reference / Standard for energy modes and test method *	
Printing		<b>735.4</b> W	<b>737.5</b> W	<b>720.2</b> W		Corporate Standard	
Сору		<b>728.4</b> W	<b>844.7</b> W	<b>824.4</b> W		Corporate Standard	
Scan		<b>126.6</b> W	127.2 W	133.5 W		Corporate Standard	
Ready Mo		108.0 W	117.4 W	108.4 W		Energy Star TEC Test Procedure	
Sleep Mod	le	<b>21.29</b> W	21.15 W	16.95 W		Energy Star TEC Test Procedure	
Off Mode		0.06 W	0.08 W	<i>0.35</i> W		IEC 62301	
charger plu	ower supply / ugged in the wall lisconnected from	W	W	W			
PTEC * Typical End	ergy Consumption	W	W	W			
TEC * Typical En	ergy Consumption	9.462 kWh/week	9.400 kWh/week	8.580 kWh/wee	ek	Energy Star TEC Test Procedure	
ETEC * Annual Ene	ergy Consumption	kWh/year	kWh/year	kWh/yea	ar		
Display res	olution* : N	egapixels					$\boxtimes$
Print Spee	d * : <b>55</b> Imag	es per minute				Corporate Standard	
Default tim	e to enter energy sa	ave mode: 30 minutes					Ħ
P9.2*	Information about	the energy save function	n is provided with th	e product.	ı		
P9.3*	ENERGY STAR®	s the energy requirement version: 1.1 Tier: AL UZ 122 (Blue Angel)	Product category:		n/s:		
P10	Emissions						
		Declared according to	ISO 9296				
P10.1	Mode	Mode description		Declared A-weighted sound power		Declared A-weighted sound pressure level $L_{p\mathrm{Am}}$ (dB)	
				evel $L_{WAd}$ (B)	Opera	ator position Bystander positions	
					(	Desktop (only if product is not operator attended)	
	Idle	* Ready	*	4.2		24	
	Operation	* Duplex Monochrome		7.2		55	
	Other mode	Simplex Monochrom		7.0		53	
	Measured accordi	3 ** 📜 * * *	ECMA-74 (only if not covered l	by ECMA-74 with	h L <sub>pAm</sub>	measurement distance m)	
P10.2	The product meets					m/s: RAL UZ 122 (Blue	

Issue date	ue date * 6-9-2011 Logo LEXM			<b>ARK</b>		
	environm	nental attributes - Market requirements (continued)		Require		
Item	<u> </u>			Yes	No	n.a.
P10.3*		al emissions from printing products			_	_
		formed according to ECMA-328 (ISO/IEC 28360) standard , other specify: RAL	-UZ122	$\boxtimes$		Щ
P10.4	, i	emission rate (print phase) is (mg/h):				
P10.5		Dust 0.37 Ozone 0.29 Styrene 0.053 Benzene 0.008 TVOC 5.4  I emission requirements of the following voluntary program/s are met for:			$\overline{}$	$\overline{}$
F 10.5		Oust Ozone Styrene Benzene	TVOC 🔀		ш	ш
		nagnetic emissions	1000			
P10.6		er display meets the requirement for low frequency electromagnetic fields of the foll	lowing voluntar	y 🔲	П	
	program/			<u> </u>		
P11		able materials for printing products				
P11.1*		Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ		<i>'</i>		
P11.2*	Paper co EN12281	ontaining post-consumer recycled fibers can be used, provided that it meets to a.	he requiremen	its of		
P11.3*	2-sided (	duplex) printing/copying is an integrated product function.		$\boxtimes$		
P12		nics for computing products				
P12.1*	The displ	lay meets the ergonomic requirements of ISO 9241-307 for visual display technolo	gies.			$\boxtimes$
P12.2*	The phys	sical input device meets the requirements of ISO 9995 and ISO 9241-410.				$\boxtimes$
P13	Packagii	ng and documentation				
P13.1*		packaging material type(s): paper weight (kg): 11.632				
		packaging material type(s): <b>PE</b> weight (kg): <b>0.242</b>				
		packaging material type(s): wood weight (kg): 11 packaging material type(s):PP weight(kg):0.359				
		packaging material type(s):PS weight(kg):0.193				
	Product	packaging material type(s):Metal weight(kg):0.024				
P13.2*		plastic packaging is free from PVC.		$\boxtimes$		
P13.3*		nedia for user and product documentation (tick box):				
		c 🔀, Paper 🔀, Other 🗌				
P13.4*	fiber: 0%		onsumer recycl	ed		
Rev. P13.5	User and	I product documentation do not contain chlorine bleached paper				
P14		al information (See Note B4)				
P1. 1		oduct uses RoHS exemptions for lead used in small amounts for specific a				
P2. 1		tery contained within this product should be disposed of properly with a v labeled with the WEEE disposal symbol and instructions for such dispos Guide.				
P. 2. 3		tery contained within this product meets the exception listed. The bate by the customer; however, is designed for easy removal by recyclers and	= -		be	
P. 7. 4	Please I ISO 1043	note that all parts greater than 25g and 200mm2 have material are marked 3.	d according to	o ISO 11469	referi	ing
P. 7. 5	Please n	note that all large case parts are free from metal inlays.				
P. 9. 1	Print spe	eed list is for Mono Letter speed. Color Letter speed is 50 ppm.				
P10. 4	Mono pr – 3.2 mg					
	Specific	nal company information and company environmental policy may be found at c printer and supply item recycling information for your area may be fo Sweden is connected to REPA and El-kretsen	-			

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Model number \* XS955dhe

## Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP) $$	P7.19