

Lexmark VPAT		X746de, X748de, X748dte, X792dtfe, X792dtme, X792dtse, X792dtpe, X792dte, X792de, X925de, X950de, X952dte, X954dhe Revision 6
Section 1194.21 - Software Applications and Operating Systems		Lexmark interprets this section to be intended for software products; we evaluate the Status Messenger, Print driver, Local WIA, Local Twain, and Network Twain drivers for the Windows operating systems here since they are essential to the use of the product.
Criteria	Supporting Features	Remarks and explanations
1194.21(a) When software is designed to run on a system that has a keyboard, product functions shall be executable from a keyboard where the function itself or the result of performing a function can be discerned textually.	Supports	Software functions can be accessed through Keyboard navigation or hot keys; the function itself or the result of performing a function can be discerned textually
1194.21(b) Applications shall not disrupt or disable activated features of other products that are identified as accessibility features, where those features are developed and documented according to industry standards. Applications also shall not disrupt or disable activated features of any operating system that are identified as accessibility features where the application programming interface for those accessibility features has been documented by the manufacturer of the operating system and is available to the product developer.	Supports	Software applications do not disrupt or disable activated accessibility features.
1194.21(c) A well-defined on-screen indication of the current focus shall be provided that moves among interactive interface elements as the input focus changes. The focus shall be programmatically exposed so that Assistive Technology can track focus and focus changes.	Supports	Software controls display focus and are available for use through assistive technology
1194.21(d) Sufficient information about a user interface element including the identity, operation and state of the element shall be available to Assistive Technology. When an image represents a program element, the information conveyed by the image must also be available in text.	Supports	All images used as controls have text labels.
1194.21(e) When bitmap images are used to identify controls, status indicators, or other programmatic elements, the meaning assigned to those images shall be consistent throughout an application's performance.	Supports	Bitmaps are used consistently throughout the applications.
1194.21(f) Textual information shall be provided through operating system functions for displaying text. The minimum information that shall be made available is text content, text input caret location, and text attributes.	Supports	Textual information is provided through system functions that make the information available to assistive technology
1194.21(g) Applications shall not override user selected contrast and color selections and other individual display attributes.	Supports	Applications do not override user selected contrast and color selections and other individual display attributes
1194.21(h) When animation is displayed, the information shall be displayable in at least one non-animated presentation mode at the option of the user.	Not Applicable	Animation is not displayed in the software.
1194.21(i) Color coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	Supports	Color coding is not used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element
1194.21(j) When a product permits a user to adjust color and contrast settings, a variety of color selections capable of producing a range of contrast levels shall be provided.	Not Applicable	Color and contrast settings cannot be adjusted in the software.
1194.21(k) Software shall not use flashing or blinking text, objects, or other elements having a flash or blink frequency greater than 2 Hz and lower than 55 Hz.	Supports	Software does not use flashing or blinking text, objects, or other elements having a flash or blink frequency greater than 2 Hz and lower than 55 Hz.
1194.21(l) When electronic forms are used, the form shall allow people using Assistive Technology to access the information, field elements, and functionality required for completion and submission of the form, including all directions and cues.	Supports	All controls, labels, directions and cues support assistive technology.

Lexmark VPAT		X746de, X748de, X748dte, X792dtfe, X792dtme, X792dtse, X792dtpe, X792dte, X792de, X925de, X950de, X952dte, X954dhe Revision 6
Section 1194.22 - Web-based internet information and applications		The optional Lexmark Accessibility Solution is evaluated here. The embedded web page, although not needed for regular product usage, is also evaluated here. The embedded web page evaluation excludes the "Create Scan Profile" and "Remote Op Panel" functions.
Criteria	Supporting Features	Remarks and explanations
1194.22(a) A text equivalent for every non-text element shall be provided (e.g., via "alt", "longdesc", or in element content).	Supports	All non-text elements have text equivalents provided
1194.22(b) Equivalent alternatives for any multimedia presentation shall be synchronized with the presentation	Not Applicable	No Multimedia Presentations are currently used
1194.22(c) Web pages shall be designed so that all information conveyed with color is also available without color, for example from context or markup	Supports	Web pages are designed so that all information conveyed with color is also available without color.
1194.22(d) Documents shall be organized so they are readable without requiring an associated style sheet.	Supports	Documents are readable without an associated style sheet
1194.22(e) Redundant text links shall be provided for each active region of a server-side image map.	Not Applicable	There are no image maps used
1194.22(f) Client-side image maps shall be provided instead of server-side image maps except where the regions cannot be defined with an available geometric shape.	Not Applicable	There are no image maps used
1194.22(g) Row and column headers shall be identified for data tables.	Not Applicable	There are no data tables
1194.22(h) Markup shall be used to associate data cells and header cells for data tables that have two or more logical levels of row or column headers.	Not Applicable	There are no data tables
1194.22(i) Frames shall be titled with text that facilitates frame identification and navigation	Supports	Frames have text titles for use with assistive technology
1194.22(j) Pages shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Supports	Web page does not use flashing or blinking text, objects, or other elements having a flash or blink frequency greater than 2 Hz and lower than 55 Hz.
1194.22(k) A text-only page, with equivalent information or functionality, shall be provided to make a web site comply with the provisions of this part, when compliance cannot be accomplished in any other way. The content of the text-only page shall be updated whenever the primary page changes.	Supports	Web pages are compliant; text only alternatives are not needed.
1194.22(l) When pages utilize scripting languages to display content, or to create interface elements, the information provided by the script shall be identified with functional text that can be read by assistive technology.	Supports	New page output created by Java Script includes HTML which can be read by assistive technology
1194.22(m) When a web page requires that an applet, plug-in or other application be present on the client system to interpret page content, the page must provide a link to a plug-in or applet that complies with 1194.21(a) through (l).	Does Not Support Not Applicable	Does Not Support - Embedded Web Page (which is not needed for regular product usage) does not provide a link to install Java on the client system. Not Applicable - Lexmark Accessibility Solution- LAS does not require an applet, plug-in or other application be present on the client system to interpret page content.
1194.22(n) When electronic forms are designed to be completed on-line, the form shall allow people using assistive technology to access the information, field elements, and functionality required for completion and submission of the form, including all directions and cues.	Supports	All controls, labels, directions and cues support assistive technology.
1194.22(o) A method shall be provided that permits users to skip repetitive navigation links.	Not Applicable	No repetitive navigation links
1194.22(p) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Supports	No timed responses are required (assumes optional security settings have not been enabled)

Lexmark VPAT		X746de, X748de, X748dte, X792dtfe, X792dtme, X792dtse, X792dtpe, X792dte, X792de, X925de, X950de, X952dte, X954dhe Revision 6
Section 1194.23 - Telecommunications Products		Lexmark does not consider these products to be telecommunications products but they are evaluated here
Criteria	Supporting Features	Remarks and explanations
1194.23(k)(1) Products that have mechanically operated controls or keys shall comply with the following: Controls and Keys shall be tactilely discernible without activating the controls or keys.	Supports	Mechanically operated controls and keys can be tactilely discerned without activation
1194.23(k)(2) Products that have mechanically operated controls or keys shall comply with the following: Controls and Keys shall be operable with one hand and shall not require tight grasping, pinching, and twisting of the wrist. The force required to activate controls and keys shall be 5-lbs. (22.2N) maximum.	Supports with exceptions	Loading paper may require more than 5-lbs force
1194.23(k)(3) Products that have mechanically operated controls or keys shall comply with the following: If key repeat is supported, the delay before repeat shall be adjustable to at least 2 seconds. Key repeat rate shall be adjustable to 2 seconds per character.	Supports	Key repeat is supported, the delay before repeat is adjustable to at least 2 seconds. Key repeat rate is adjustable to 2 seconds per character.
1194.23(k)(4) Products that have mechanically operated controls or keys shall comply with the following: The status of all locking or toggle controls or keys shall be visually discernible, and discernible either through touch or sound.	Supports	Power switch toggles and can be discernible through touch. Status of sleep or hibernate can be determined visually; and via sound by pressing home key first followed by sleep button if needed

Lexmark VPAT		X746de, X748de, X748dte, X792dtfe, X792dtme, X792dtse, X792dtpe, X792dte, X792de, X925de, X950de, X952dte, X954dhe Revision 6
Section 1194.25 - Self-Contained, Closed Products		The optional Lexmark Accessibility Solution and/ or Lexmark Accessibility Speech must be installed on the product to achieve accessibility levels discussed below.
Criteria	Supporting Features	Remarks and explanations
1194.25(a) Self-contained products shall be usable by people with disabilities without requiring an end-user to attach Assistive Technology to the product. Personal headsets for private listening are not Assistive Technology.	Supports	End-users are not required to attach assistive technology to the product. Most typical device functions can be performed using the optional Lexmark Accessibility Speech and Lexmark Accessibility Solution via a workstation or mobile device equipped with Assistive Technology. Alternatively basic copy and fax tasks can be performed using the enhanced number pad mode.
1194.25(b) When a timed response is required, the user shall be alerted and given sufficient time to indicate more time is required.	Supports with exceptions	Some selections timeout after a period of total inactivity and return to the main screen.
1194.25(c) Where a product utilizes touchscreens or contact-sensitive controls, an input method shall be provided that complies with 1194.23 (k) (1) through (4).	Supports with minor exceptions through equivalent facilitation	Most typical device functions can be performed using the optional Lexmark Accessibility Speech and Lexmark Accessibility Solution via a workstation or mobile device equipped with Assistive Technology. The task is completed at the MFP using the number pad. Alternatively basic copy and fax tasks can be performed using the enhanced number pad mode.
1194.25(d) When biometrics forms of user identification or control are used, an alternative form of identification or activation, which does not require the user to possess particular biological characteristics, shall also be provided.	Not Applicable	No biometrics on these products
1194.25(e) When products provide auditory output, the audio signal shall be provided at a standard signal level through an industry standard connector that will allow for private listening. The product must provide the ability to interrupt, pause, and restart the audio at anytime.	Supports with exceptions	Optional Lexmark Accessibility Speech Solution enables playback of a set of brief status messages on demand through the integrated speaker. Messages can be interrupted and restarted
1194.25(f) When products deliver voice output in a public area, incremental volume control shall be provided with output amplification up to a level of at least 65 dB. Where the ambient noise level of the environment is above 45 dB, a volume gain of at least 20 dB above the ambient level shall be user selectable. A function shall be provided to automatically reset the volume to the default level after every use.	Supports with exceptions	Optional Lexmark Accessibility Speech Solution enables playback of a set of brief status messages on demand through the integrated speaker. Volume can be adjusted in 10 increments.
1194.25(g) Color-coding shall not be used as the only means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	Supports	Multiple methods are used to convey information to the end user
1194.25(h) When a product permits a user to adjust color and contrast settings, a range of color selections capable of producing a variety of contrast levels shall be provided.	Not Applicable	User is not able to adjust color or contrast on these products
1194.25(i) Products shall be designed to avoid causing the screen to flicker with a frequency greater than 2 Hz and lower than 55 Hz.	Supports	Product does not use flashing or blinking text, objects, or other elements having a flash or blink frequency greater than 2 Hz and lower than 55 Hz.
1194.25(j)(1) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: The position of any operable control shall be determined with respect to a vertical plane, which is 48 inches in length, centered on the operable control, and at the maximum protrusion of the product within the 48 inch length.	Supports	The measurements below were made using this criteria.
1194.25(j)(2) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Where any operable control is 10 inches or less behind the reference plane, the height shall be 54 inches maximum and 15 inches minimum above the floor.	Supports	The products can be positioned to meet the requirement. Paper trays on copiers may be within 15 inches of the floor, as allowed by the Access Board's Guide to the Section 508 Standards
1194.25(j)(3) Products that are freestanding, non-portable, and intended to be used in one location and have operable controls, shall comply with the following: Where any operable control is more than 10 inches, and not more than 24 inches, behind the reference plane, the height shall be 46 inches maximum and 15 inches minimum above the floor.	Supports	The products can be positioned to meet the requirement. Paper trays on copiers may be within 15 inches of the floor, as allowed by the Access Board's Guide to the Section 508 Standards Note: X792dte, X792dtfe, X792dtme, X792dtse, and X792dtpe accessibility can be further enhanced by configuring with one less paper tray
1194.25(j)(4) Products which are freestanding, non-portable, and intended to be used in one location and which have operable controls shall comply with the following: Operable controls shall not be more than 24 inches behind the reference plane.	Supports	Operable controls for normal operations are not more than 24 inches behind the reference plane.

Section 1194.31 - Functional Performance Criteria		X746de, X748de, X748dte, X792dtfe, X792dtme, X792dtse, X792dtpe, X792dte, X792de, X925de, X950de, X952dte, X954dhe Revision 6
Criteria	Supporting Features	Remarks and explanations
1194.31(a) At least one mode of operation and information retrieval that does not require user vision shall be provided, or support for Assistive Technology used by people who are blind or visually impaired shall be provided.	Supports with minor exceptions through equivalent facilitation	Most typical device functions can be performed using the optional Lexmark Accessibility Speech and Lexmark Accessibility Solution via a workstation or mobile device equipped with Assistive Technology. The task is completed at the MFP using the number pad. Alternatively basic copy and fax tasks can be performed using the enhanced number pad mode.
1194.31(b) At least one mode of operation and information retrieval that does not require visual acuity greater than 20/70 shall be provided in audio and enlarged print output working together or independently, or support for Assistive Technology used by people who are visually impaired shall be provided.	Supports	The product supports operation by users with visual acuity equivalent to 20/70. For visual acuity less than 20/70, most typical device functions can be utilized through the optional Lexmark Accessibility Solution working with Assistive Technology at the desktop or mobile device. Lexmark Accessibility Speech is also optional to voice status at the MFP. Alternatively many typical device functions can be utilized through the enhanced number pad mode.
1194.31(c) At least one mode of operation and information retrieval that does not require user hearing shall be provided, or support for Assistive Technology used by people who are deaf or hard of hearing shall be provided.	Supports	The primary mode of operation is visual; the product does not require hearing.
1194.31(d) Where audio information is important for the use of a product, at least one mode of operation and information retrieval shall be provided in an enhanced auditory fashion, or support for assistive hearing devices shall be provided.	Not Applicable	The primary mode of operation is visual; the product does not require hearing.
1194.31(e) At least one mode of operation and information retrieval that does not require user speech shall be provided, or support for Assistive Technology used by people with disabilities shall be provided.	Supports	User speech is not required for the use of this product
1194.31(f) At least one mode of operation and information retrieval that does not require fine motor control or simultaneous actions and that is operable with limited reach and strength shall be provided.	Supports with exceptions	Loading paper may require more than 5-lbs force

Section 1194.41 - Information, Documentation, and Support		X746de, X748de, X748dte, X792dtfe, X792dtme, X792dtse, X792dtpe, X792dte, X792de, X925de, X950de, X952dte, X954dhe Revision 6
Criteria	Supporting Features	Remarks and explanations
1194.41(a) Product support documentation provided to end-users shall be made available in alternate formats upon request, at no additional charge.	Supports	User's Guide is provided in PDF format that may be viewed on screen or printed; and in HTML format (English only) that may be used with screen reader software.
1194.41(b) End-users shall have access to a description of the accessibility and compatibility features of products in alternate formats or alternate methods upon request, at no additional charge.	Supports	This is available upon request
1194.41(c) Support services for products shall accommodate the communication needs of end-users with disabilities.	Supports	The Technical Support Center provides both phone and email support.