

MS531 Toner Cartridge

Printer: MS531dw

Declaration of Yield:

Average Cartridge Yield	5,000	standard pages
Declared yield value in accordance with ISO/IEC 19752		

Average 5,573
Std Dev 149
90% Lower 5,481
Confidence

For questions concerning testing

contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested **start** **stop**
 23-Aug-2022 26-Aug-2022

Number of cartridges in testing	9	Continuous
Qty. of cartridges used in calculation	9	3
Shake Procedure 1st shake	No shake	Hammermill Tidal MP - 20 lbs. - Letter
2nd shake	No shake	Short Edge Feed (SEF)
Print mode	Continuous	Lexmark Printer Software G3 XL
Number of printers tested	3	Windows 10 Enterprise
Media used	Hammermill Tidal MP - 20 lbs. - Letter	Adobe Acrobat Reader DC ver. 2021.007.20099
Paper feed orientation	Short Edge Feed (SEF)	ISO_IEC_19752_2004_Test_Page.pdf
Driver version	Lexmark Printer Software G3 XL	
Operating system	Windows 10 Enterprise	
Application software	Adobe Acrobat Reader DC ver. 2021.007.20099	
Test page version	ISO_IEC_19752_2004_Test_Page.pdf	

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAD22160328A	7020FSTNLE014	72	74	72	44	50	41	5,440	Y
SCAD22160329A	7020FSTNLE014	72	74	72	44	50	41	5,406	Y
SCAD22160329D	7020FSTNLE014	72	74	72	44	50	41	5,634	Y
SCAD22160A0BC	7020FSTNLE033	72	74	72	44	50	41	5,719	Y
SCAD221603292	7020FSTNLE033	72	74	72	44	50	41	5,621	Y
SCAD22160A0CD	7020FSTNLE033	72	74	72	44	50	41	5,430	Y
SCAD221603283	4602FSTSC107	72	74	72	44	50	41	5,676	Y
SCAD221603294	4602FSTSC107	72	74	72	44	50	41	5,804	Y
SCAD22160A0B8	4602FSTSC107	72	74	72	44	50	41	5,431	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 5.