

## MX431 / MX432 High Yield Toner Cartridge

Printer: MX431adn / MX431adw / MX432adwe

Declaration of Yield: 

<b>Average Cartridge Yield</b>	<b>15,000</b>	<b>standard pages</b>
<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 15,909  
**Std Dev** 363  
**90% Lower Confidence** 15,684

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
<b>Date tested</b>	21-Oct-2019	25-Oct-2019
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No shake
	2nd shake	No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark Printer Software G4 v1.2
Operating system		Windows 7 Professional
Application software		Adobe Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAD192707F94	701992400002G	73	75	71	53	58	48	15,530	Y
SCAD192707F84	701992400002G	73	75	71	53	58	48	16,600	Y
SCAD192707F90	701992400002G	73	75	71	53	58	48	16,150	Y
SCAD192707F85	701992400001N	73	75	71	53	58	48	15,635	Y
SCAD192707F8B	701992400001N	73	75	71	53	58	48	15,660	Y
SCAD192707F8E	701992400001N	73	75	71	53	58	48	16,085	Y
SCAD192707F8A	460192400003L	73	75	71	53	58	48	16,020	Y
SCAD192707F81	460192400003L	73	75	71	53	58	48	16,020	Y
SCAD192707F93	460192400003L	73	75	71	53	58	48	15,480	Y

**Comments and or exceptions:**

- 1.) The print file was generated with number of copies set equal to 5.
- 2.) Cartridge EOL was determined by the print starvation or fade.