

## MX431 / MX432 Toner Cartridge

**Printer: MX431adn/MX431adw/MX432adwe**

Declaration of Yield: 

<b>Average Cartridge Yield</b>	<b>3,000</b>	<b>standard pages</b>
<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 4,061  
**Std Dev** 130  
**90% Lower Confidence** 3,980

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
<b>Date tested</b>	18-Oct-2019	19-Oct-2019
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	No shake
	2nd shake	No shake
Print mode	Continuous	
Number of printers tested	3	
Media used	Hammermill Tidal MP - 20 lbs. - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	Lexmark Printer Software G4 v1.2	
Operating system	Windows 7 Professional	
Application software	Adobe Acrobat version 9	
Test page version	ISO_IEC_19752_2004_Test_Page.pdf	

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAD192697F50	701992400002G	73	75	71	54	59	49	3,895	Y
SCAD192697F52	701992400002G	73	75	71	54	59	49	4,200	Y
SCAD192697F54	701992400002G	73	75	71	54	59	49	4,245	Y
SCAD192697F51	701992400001N	73	75	71	54	59	49	3,995	Y
SCAD192697F4F	701992400001N	73	75	71	54	59	49	4,170	Y
SCAD192697F4C	701992400001N	73	75	71	54	59	49	3,980	Y
SCAD192697F49	460192400003L	73	75	71	54	59	49	4,030	Y
SCAD192697F4E	460192400003L	73	75	71	54	59	49	4,135	Y
SCAD192697F4A	460192400003L	73	75	71	54	59	49	3,900	Y

**Comments and or exceptions:**

- 1.) The print file was generated with number of copies set equal to 5.
- 2.) Cartridge EOL was determined by a print starvation or fade.