Forms and Bar Code Card 3.2

User's Guide

April 2012 **ww.lexmark.com**

Lexmark and Lexmark with diamond design are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.
All other trademarks are the property of their respective owners.

© 2012 Lexmark International, Inc.
All rights reserved.

740 West New Circle Road
Lexington, Kentucky 40550

Contents

Introduction....4

Overview....4

Supported devices....4

Supported fonts and bar codes....6

Supported bar codes....6

Supported fonts....10

SAP support....11

Installing SAP device types....11

Modifying device types format and default settings....11

Using the Visual Bar Code Designer....13

Supported operating systems....13

Installing the Visual Bar Code Designer....13

Generating bar code data....13

Creating and managing forms....15

Forms overview....15

Forms Card menu....15

Bar code menu....18

Storing forms on the printer....18

Capturing raw data for mapping....18

Printing forms from a flash drive....19

Identifying the version of forms on the Forms and Bar Code Card....19

Font limitations....19

Troubleshooting....20

The printer does not respond after installation....20

Make sure the option card is installed correctly....20

Forms Manager cannot detect the printer....20

Check printer connections....20

Make sure the printer is connected to the network....20

International fonts do not print as expected....20

Switch to one of the fonts available on the DLE card....20

Mismatched fonts in Forms Composer and on printed forms....21

Check Forms Composer and printer settings 21
Check that font mapping has not been altered in Forms Composer 21
Check that font mapping has not been altered on the printer 21
Change the fonts in Forms Composer 21
Install matching fonts on the Forms and Bar Code Card 22
Form did not merge 22
Remove unnecessary characters from the beginning of the form 22
Form is printed in plain text 22
Review the activation conditions in Forms Composer 22
Make sure the Formsmerge function is not deactivated by Forms Manager 22
Cannot fax or e-mail merged output 22
Check Forms Composer and printer settings 22
Characters appear as boxes in PDFs viewed with Acrobat Reader 22
Use a different program to view PDFs 22
Not all forms are listed 23
Data filters are not working 23
Cannot add new forms 23
Delete unused forms before adding new forms 23
Defragment the flash memory 23
Bar codes do not print as expected 23
Make sure the Option Card is compatible with the printer on which it is installed 23
Make sure that the Option Card is installed 23
When using a PCL 5 emulation printer driver, make sure that the escape sequence used to generate the bar code is properly constructed 23
Cannot generate bar codes using PCL emulation printer drivers 23
Disable advanced features using a PCL XL emulation printer driver 24
Unexpected results after printing a bar code 24
Make sure the PCL 5 emulation escape sequences are complete 24
Make sure all parameters needed are fully specified 24
Printed bar code is unreadable 24
Make sure Print Quality settings are not too dark or too light 24
Check the paper 24

Notices 25
Edition notice 25

Index 29

Introduction

Overview

The *Forms and Bar Code Card* lets you print a variety of standard forms and bar codes. Using an algorithm, the Forms and Bar Code Card can generate bar codes in either PCL 5 or PostScript emulation.

With PCL 5 emulation, the Forms and Bar Code Card is the functional equivalent of the HP Bar Codes & More font set. It serves as an alternative to an HP LaserJet with JetCAPS BarDIMM Pro (v3.3a), including the FREESCAPE alternate escape code feature, and Intelligent Mail bar code. The Forms and Bar Code Card also provides custom device types for printing with SAPscript in SAP R/3 applications.

Bar code options include the following features:

- OCR-A and OCR-B as bitmap and scalable fonts
- Independently scalable bar heights and widths
- RFID support
- Embedding text with selectable positioning
- Verifying data format, with error reporting
- Automatic bar code data compression, when required
- Automatic bar code checksum calculation and character placement, when required
- Automatic placement of special characters, when required
- Built-in 64MB flash memory

Forms options include the following features:

- Storing and printing forms from an optional flash drive or optional/standard printer hard disk
- Built-in RFID support
- Creating electronic forms to be merged with data
- Sending merged output through fax and e-mail

Notes:

- Forms Composer and Forms Manager are required to create and manage forms.
- The forms files on the Forms and Bar Code Card have the file extensions .lfm and .lff.
- For more information on using RFID when printing forms, see the documentations that came with Forms Composer and with the printer.

Supported devices

- Lexmark C746x, C748x
- Lexmark C792
- Lexmark C925
- Lexmark C950
- Lexmark X548
- Lexmark X746x, X748x

- Lexmark X792
- Lexmark X925
- Lexmark X950, X952, X954
- Lexmark 6500e

Supported fonts and bar codes

Supported bar codes

Type	Availability on Forms and Bar Code Card	
	PCL and PS bar codes	Forms merge bar codes
One-dimensional bar codes		
Australian Post 4-State bar code (37-CUST)	X	X
Australian Post 4-State bar code (52-FF-MET)	X	X
Australian Post 4-State bar code (67-FF-MET)	X	X
British Royal Mail 4-State customer code symbol (RM4SCC)	X	X
Codabar (USD -4, NW -7, Monarch, Code 2 of 7)	X	X
Codabar with mod16 check digit	X	X
Code 128 autoswitch	X	X
Code 128 A	X	X
Code 128 B	X	X
Code 128 C	X	X
Code 3 of 9	X	X
Code 3 of 9 with check digit	X	X
Code 3 of 9 extended	X	X
Code 3 of 9 extended with check digit	X	X
Code 3 of 9 space encoding	X	
Code 3 of 9 space encoding with check digit	X	
Code 93	X	X
Code 93 extended	X	X
Danish PTT 3 of 9	X	X
Dutch Post 4-state bar code	X	X
EAN/JAN-8	X	X
EAN/JAN-8 with 2-digit supplemental	X	X
EAN/JAN-8 with 5-digit supplemental	X	X
EAN/JAN-13	X	X

Type	Availability on Forms and Bar Code Card	
	PCL and PS bar codes	Forms merge bar codes
EAN/JAN-13 with 2-digit supplemental	X	X
EAN/JAN-13 with 5-digit supplemental	X	X
EAN 128	X	X
French Postal 3 of 9 A/R	X	X
German Postal 2 of 5 Leitcode	X	X
German Postal 2 of 5 Identcode	X	X
HIBC 39/128	X	X
Interleaved 2 of 5	X	X
Interleaved 2 of 5 with check digit	X	X
Intelligent Mail	X	X
Industrial 2 of 5	X	X
Industrial 2 of 5 with check digit	X	X
ISBN	X	X
ISBN+5	X	
ISSN	X	X
ISSN+2	X	
ISSN+5	X	
ITF-14	X	
Japan Post 4-state bar code	X	X
Matrix 2 of 5	X	X
Matrix 2 of 5 with check digit	X	X
MSI	X	X
MSI with mod10 check digit	X	X
MSI with mod10 and mod10 check digit	X	X
MSI with mod11 and mod10 check digit	X	X
Singapore Post 4-state bar code	X	X
Swiss Postal	X	X
UCC 128	X	X
UPC-A	X	X
UPC-E	X	X
UPC-A with 2-digit supplemental	X	X
UPC-A with 5-digit supplemental	X	X
UPC-E with 2-digit supplemental	X	X

Type	Availability on Forms and Bar Code Card	
	PCL and PS bar codes	Forms merge bar codes
UPC-E with 5-digit supplemental	X	X
USPS PLANET bar code	X	X
USPS POSTNET 5-digit ZIP code	X	X
USPS POSTNET 9-digit ZIP with 4 code	X	X
USPS POSTNET 11-digit Delivery Point Code	X	X
USPS Expanded POSTNET	X	
USPS Tray label, 10-digit 2 of 5	X	X
USPS Sack label, 8-digit 2 of 5	X	X
USPS Zebra code	X	X
USPS FIM (Facing Identification Marking)	X	X
Two-dimensional bar codes		
Aztec		X
Codablock F	X	X
Data Matrix	X	X
MaxiCode	X	X
MicroPDF417	X	X
PDF417	X	X
QR	X	X
RSS-14	X	X
RSS-14 Expanded	X	X
RSS-14 Limited	X	X
RSS-14 Stacked	X	X
RSS-14 Truncated	X	X
Composite bar codes		
EAN-8	X	X
EAN/JAN-8 with 2-digit supplemental	X	X
EAN/JAN-8 with 5-digit supplemental	X	X
EAN-13	X	X
EAN/JAN-13 with 2-digit supplemental	X	X
EAN/JAN-13 with 5-digit supplemental	X	X
RSS-14 Expanded	X	X
RSS-14 Limited	X	X

Type	Availability on Forms and Bar Code Card	
	PCL and PS bar codes	Forms merge bar codes
RSS-14	X	X
RSS-14 Stacked	X	X
RSS-14 Truncated	X	X
UCC-128	X	X
UPC-A	X	X
UPC-E	X	X
UPC-A with 2-digit supplemental	X	X
UPC-A with 5-digit supplemental	X	X
UPC-E with 2-digit supplemental	X	X
UPC-E with 5-digit supplemental	X	X
Font-based bar codes		
Code 128 bitmap regular	PCL only	
Code 128 bitmap wide	PCL only	
Code 128 scalable regular	PCL only	
Code 128 scalable narrow	PCL only	
Code 128 scalable wide	PCL only	
Code 3 of 9 bitmap	PCL only	
Code 3 of 9 scalable half inch regular	PCL only	
Code 3 of 9 scalable one inch regular	PCL only	
Code 3 of 9 quarter inch regular	PCL only	
Code 3 of 9 small high regular	PCL only	
Code 3 of 9 small low regular	PCL only	
Code 3 of 9 small medium regular	PCL only	
Code 3 of 9 slim regular	PCL only	
Code 3 of 9 wide regular	PCL only	
Interleaved 2 of 5 bitmap	PCL only	
Interleaved 2 of 5 scalable regular	PCL only	
Interleaved 2 of 5 scalable thin	PCL only	
OCR-A	PCL only	
OCR-B digits regular	PCL only	
UPC tall	PCL only	
UPC tall narrow	PCL only	
UPC tall thin	PCL only	

Type	Availability on Forms and Bar Code Card	
	PCL and PS bar codes	Forms merge bar codes
UPC half	PCL only	
UPC half narrow	PCL only	

Supported fonts

To obtain the PCL 5 escape sequences used to select these fonts, print the font list using the printer control panel. For more information about the printer control panel, see the documentation that came with the printer.

Font	Type	Resides
Architext CMC7	Scalable	On option card
CMC7	Scalable	On option card
Code 3 of 9 (4.69)	Bitmap	On option card
Code 3 of 9 (8.11)	Bitmap	On option card
Electrical symbols	Scalable	On option card
Euro and other currency symbols	Scalable	On option card
Line Draw	Bitmap	On option card
Manufacturing symbols	Scalable	On option card
MICR	Scalable	On option card
OCR-A	Bitmap	On option card
OCR-A	Scalable	On option card
OCR-B	Bitmap	On option card
OCR-B	Scalable	On option card
OCR-B in Bubbles	Scalable	On option card
Roman Pillar	Scalable	On option card
Roman Pillar Italic	Scalable	On option card
Roman Pillar Bold	Scalable	On option card
Roman Pillar Bold Italic	Scalable	On option card
Roman Pillar5	Scalable	On option card
UPC 10mil	Bitmap	On option card
UPC 13mil	Bitmap	On option card

SAP support

When used in PCL 5 emulation mode, SAP ERP software has built-in support for many of the functions provided by the Forms and Bar Code Card.

SAP systems support the following device types:

- LEXT622
- LEXW820
- ZLXFORM2

Installing SAP device types

Note: You must be the SAP BASIS administrator to install SAP devices.

1. Start transaction SE38.
2. Execute report RSTXSCRP to load the device type ZLXFORM2.
3. Type the name of the device type in the Object Name field.

   Note: Do not include the .pri extension.
4. Select **IMPORT** mode, and then press the **F8** button (execute).
5. Reset the SAPscript cache:
   a. Call transaction SE38.
   b. Execute the report RSTXDELL, using `client = '*'`.
6. Reset the character code cache:
   a. Start transaction SP12.
   b. Click **character sets** > **Conf buffer (CCC)** > **Invalidate CCC**.

Note: The reset procedure is valid only on the actual instance, so you must connect on the instance where the spool work process is running.

7. Restart the spool work process:
   a. Highlight the spool work process SPO.
   b. Click **Process** > **cancel without core**.

      Note: The spool work process should automatically restart after a few seconds or on the next interrupt.

Modifying device types format and default settings

1. Start transaction SPAD.
2. Click **Full Administration** > **Device Types**.
3. Double-click the device type.
4. Click **Format**, and then double-click the format you want to modify.
5. Click **Change**.

6 Double-click **Printer Initialization**, and then remove the number sign (#) from the beginning of each needed line.

7 Click **Save** > **Save**.

Using the Visual Bar Code Designer

The Visual Bar Code Designer is a separate application that lets the user select the bar code symbology, enter data to be encoded, and then prompts the software to generate the bar code.

Supported operating systems

The Visual Bar Code Designer provides support for the following operating systems:

- Windows 7
- Windows Vista
- Windows XP
- Windows 2000
- Windows NT 4.0
- Windows 98

Installing the Visual Bar Code Designer

1. Insert the installation CD.
2. Run **setup-vbd.exe** from the Designer subdirectory.
3. Review and accept the license agreement.
4. Select the folder where you want to install the Visual Bar Code Designer.
5. Follow the instructions on the computer screen.

Generating bar code data

Visual Bar Code Designer generates the PCL escape sequences, PCL HEX, or PostScript command sequences for bar codes. These data can be used within an application, SAP device type, or as a file to test print the bar code using the Forms and Bar Code Card.

1. Click or **Start**.
2. Click **Programs** or **All Programs**, and then select **Visual Bar Code Designer**.
3. Double-click the bar code symbology you want from the “Barcode list” window.
4. Modify the bar code settings as necessary.
5. From the Edit menu, copy the data stream you want, and then paste the text string in your application.

Notes:

- After the bar code data is generated, the test bar code can be printed by clicking the Print icon in the toolbar. The image of the bar code prints on any printer, including those without a Forms and Bar Code Card installed. The test bar code may be suitable for scanning.

- For additional information, click the Visual Bar Code Designer Help menu, or see the Forms and Bar Code Card *Technical Reference Manual*.

Creating and managing forms

Forms overview

Electronic-forms solutions integrate both electronic and hard-copy documents, and let you create custom forms to create a dynamic document workflow for any business. The forms can be either printer-based or server-based. You can quickly design electronic forms, store them on a printer, automatically merge them with text files, and then print, fax, e-mail, or archive the output.

The electronic-forms solutions contain different modules that automate workflow processes. These modules include Forms Composer and Forms Manager.

Note: Forms Composer and Forms Manager are required software programs that can be purchased separately.

Forms Composer is a design tool that offers the following features:

- Easy-to-use graphical user interface to create forms and map data to the forms
- Importing of existing PDF documents for compatibility
- Creating of documents for printer-based and server-based technologies

The Data pane of Forms Composer allows mapping variable data that comes from the host system. You can set the paper size and input text before downloading the form to the printer flash memory or optional/standard printer hard disk. After a form is designed and is in the printer, data can be sent directly from your host computer over a TCP/IP network, through a USB connection to the printer, through a parallel card to the printer, or through a serial card to the printer. The Forms and Bar Code Card then merges the data with the correct form using predefined activation conditions.

Activation conditions are defined as triggers that let you select the correct formset on the printer memory or printer hard disk. You can define activation conditions when designing your form in Forms Composer or creating a forms directive. Every time you create a new form for a data set, you are creating a project which you must upload to a printer with both flash memory and Forms and Bar Code Card installed.

Forms Manager downloads and manages formsets on printers with the Forms and Bar Code Card installed. You can add formsets to printers, retrieve printer information, and view saved files on the printer. Using Forms Manager, you can also upgrade the Forms and Bar Code Card firmware on the printer.

The Forms and Bar Code Card has firmware that automatically merges the data with the correct form design (formset) and prints the completed form. The host data stream can be SAP RDI, ASCII, or double-byte data encoded in GBK, UTF-8, or UTF-16. The Forms and Bar Code Card uses TrueType fonts and Adobe Font Manager (AFM) to generate PDF output.

Forms Card menu

After the Forms and Bar Code Card is installed, additional menu items are added to the standard printer menus. These menu items can be found in the Forms Card menu.

Menu item	Description
Forms Merge Mode Enabled Disabled Data Capture Disk | Flash Thumbdrive Archive and Print Archive only	• If Forms Merge Mode is enabled, then the merged output is printed. • If Forms Merge Mode is disabled, then the Forms Card passes all received data to the printer. No attempt is made to merge data onto a formset. • When the Forms Card is in Data Capture mode, the incoming data stream is written to a file on the printer storage device. This file can be used as a sample data file during formset creation. • The Thumbdrive option under Data Capture is available only when a USB flash drive is inserted into the printer. When using this feature, make sure a formsmerge (case-sensitive) directory exists in the flash drive. • “Archive and Print” and “Archive only” modes are available only when the printer has a hard disk installed and Formsmerge DLE is configured to use the printer hard disk for formsets. • When the Forms Card is in “Archive only” mode, the merged PDF files are archived in the formsmerge/archive directory. In “Archive and Print“ mode, the merged PDF files are also printed.
Data Filter Global Filter Network Filter USB Filter Parallel Filter Serial Filter	If a data filter is enabled, then the incoming forms job is run through that filter before being processed by the DLE. The following are possible values for each data filter: • Disabled—This indicates that all data filters are off. • NULL—This removes all null characters. • AS400—This removes extraneous lines of data due to AS400 formatting. • PCL—This removes all PCL escape sequences and leaves plain text. • ZPL—This removes Zebra Printer Language directives. • ZPL-F—This it the same as ZPL, except it uses @ as the escape character instead of ^. • OFIS—This removes all Optra Forms™ initialization strings. • OFIS+NULL—This removes all null characters and all Optra Forms initialization strings. • AS400+OFIS—This removes extraneous lines of data due to AS400 and all Optra Forms initialization strings. **Note:** Some data filters may not be available depending on your printer model.

Menu item	Description
Print All Forms	This prints all formset information found on the Forms and Bar Code Card. **Notes:** • If a .ppf file exists for the formset, then the paper tray and output bin information is read from the .ppf file and listed under the .ppf file name. • If both a printer hard disk and flash memory are installed, then both total size and available size for the flash memory are displayed. Only the forms on the user flash is accessible.
Error Page Print On Off	This prints an error page when an error is encountered by the DLE.
Print Port Setting Network Port USB Port Parallel Port Serial Port	This allows Formsmerge to be turned on or off for the selected port(s). Formsmerge is on for all ports by default. **Note:** If a port is on, then all data sent to that port are processed by the Formsmerge code. Otherwise, all data sent to that port are processed by the printer as if the Formsmerge is not installed. Specifically, the data file is printed as determined by the basic Printer Language Setting.
Local Port Timeout 1–100	This allows users to select a timeout value for forms jobs that come in on any of the local ports (serial, USB, or parallel). This setting does not apply to forms jobs sent to the network ports. The default value is 4 seconds. When Formsmerge is active on a local port, then a job will time out when triggered by the Local Port Timeout or the Printer Timeout—whichever is shorter. This terminates the current job as if an “End of Form” character has been reached.
Copy Formsets Copy replace duplicates Copy do not replace	This allows the printer to download forms from a flash drive. **Notes:** • “Copy replace duplicates” allows the user to copy and replace existing formsets of the same name. • “Copy do not replace” does not copy formsets with duplicate names. • When using this feature, make sure a formsmerge (case-sensitive) directory exists in the flash drive.

Bar code menu

Menu item	Description
Alt ESC Code On Off	This allows the use of an alternate escape character when processing PCL escape sequences. **Notes:** • This is a Bar Code DLE function. • On uses an alternate escape code character in addition to the default escape code character. • Off uses the default escape code character.
ESC Character 126 (~) 34 (“) 35 (#) 36 ($) 47 (/) 63 (?) 92 (\) 123 ({) 124 (|) 125 (})	When Alt ESC Code is set to On, the value defined in this setting is used in addition to the default escape character.

Storing forms on the printer

To store forms on the printer, an optional flash memory or printer hard disk must be installed. When installed, use Forms Manager to interact with the optional flash memory or printer hard disk.

Use Forms Manager to do the following:

- Store forms on the flash memory or printer hard disk.
- Erase all forms from the flash memory or printer hard disk.
- View all forms currently stored on the printer.

Capturing raw data for mapping

Capturing raw data is necessary to properly map data to forms. For additional information on capturing raw data, see the documentation that came with Forms Manager.

1. In Forms Manager, select your printer from the Printer list.
2. Click **Printer** > **Properties**.
3. From the Mode section of the Printer Properties dialog, select **Data Capture**, and then click **Apply**.
4. Send the data file to the printer.
5. Refresh the printer in Forms Manager.

   The data file is now listed, and you can select to retrieve it.

Printing forms from a flash drive

The Create Flash File option in Forms Manager is used to add one or more formsets to printers that are not attached to the network. The flash file allows Forms Manager to communicate with these printers. The flash file created contains everything needed to add the formset(s) to the printer. You can save the file to a flash drive and then access it through the USB port on the printer.

For more information on creating flash files, see the Forms Manager documentation.

Notes:

- If formsets on the flash drive, the printer memory, or the printer hard disk contain the same activation conditions, then the formsets on the flash drive are used when those conditions are met.
- This function is supported only on printers with a USB port.

Identifying the version of forms on the Forms and Bar Code Card

Do one of the following:

- Print a Menu Settings page. The current version of forms is listed under Installed Features. For more information on printing a menu settings page, see the printer *User's Guide*.
- Select the printer in Forms Manager, and then view the printer properties.

  Note: Forms Manager is also used when upgrading the Forms and Bar Code Card firmware.

Font limitations

Windows fonts often contain more characters than the installed printer fonts. As a result, the printer may not print all the characters on a form. This is usually a problem only for characters that fall outside of the 0–255 character code range for nonstandard code pages. Print a sample form to check whether all the characters you want are printed.

Troubleshooting

The printer does not respond after installation

Make sure the option card is installed correctly

Turn the printer off, and then reinstall the option card. For more information, see the installation sheet that came with the Forms and Bar Code Card kit.

Forms Manager cannot detect the printer

Try one or more of the following:

Check printer connections

Make sure:

- The printer is turned on.
- The power cord is plugged into the printer and into a properly grounded electrical outlet.
- The printer is not plugged into any surge protectors, uninterruptible power supplies, or extension cords.
- The printer is securely connected to the computer, print server, or other network access point.
- You have resolved any error messages on the printer control panel display.

Make sure the printer is connected to the network

The printer must be on the network and must match the IP or DNS name of the network.

International fonts do not print as expected

The international font set on the client computer does not match the font set on the DLE card.

Switch to one of the fonts available on the DLE card

The following international fonts are recommended for forms printed on a printer with an installed DLE card:

Intl-Univers
Intl-CG Times
Intl-Courier
ArialMT
Times New RomanPSMT

Mismatched fonts in Forms Composer and on printed forms

Try one or more of the following:

Check Forms Composer and printer settings

Forms Composer and/or the printer may not be configured properly. Make sure the workflow properties for the data stream have been properly configured. For more information, see the Forms Composer documentation.

For information on configuring network settings, see the documentation that came with the printer.

Check that font mapping has not been altered in Forms Composer

The fonts.dat file in the Forms Composer directory specifies which fonts are used for font families with nonstandard names. The format for the information contained in the fonts.dat file follows the convention **`font name, regular, bold, italic, bold italic`**. These entries specify which fonts Forms Composer uses under which circumstances.

For example, an entry for the Bookman font family in the fonts.dat file might read **`Bookman, Bookman, Bookman Demi, Bookman Italic, Bookman Demi Italic`**, such as for all instances of Bookman in boldface, Forms Composer uses the font Bookman Demi.

Note: The fonts.dat file only specifies usage for font families with nonstandard names. Thus, a font such as Courier that uses Courier, Courier Bold, Courier Italic, and Courier Bold Italic will not be listed.

To check or alter the fonts.dat file:

1. From the Forms Composer directory, open **fonts.dat** using a text editor.
2. Make necessary changes to the file.
3. Save the file as fonts.dat into the same directory.

Check that font mapping has not been altered on the printer

Forms and Bar Code Card relies on font mapping to specify which fonts are used under which circumstances. The information is contained in the manager.upr file that resides in the Forms Manager directory. When you add a printer to Forms Manager, the manager.upr file is written to it.

To check or alter the manager.upr file for a particular printer:

1. From the Forms Manager\Fonts directory, open **manager.upr** using a text editor.
2. Make necessary changes to the file.
3. Save the file as manager.upr into the same directory, and then delete the manager.bak file.
4. From Forms Manager, delete the printer and its associated files, and then add the printer you just deleted.

Note: See the Forms Manager documentation for more information on adding and deleting printers.

Change the fonts in Forms Composer

Fonts used on the computer that hosts Forms Composer may not match those used by the Forms and Bar Code Card. Use fonts in Forms Composer that match those on the Forms and Bar Code Card.

Install matching fonts on the Forms and Bar Code Card

For more information on installing fonts, see the Forms Manager documentation.

Form did not merge

Remove unnecessary characters from the beginning of the form

A blank page prints because the first element on the page is the character for form feed or carriage return. Form feed or carriage return characters at the beginning of a data stream causes the printer to skip to the next page, so that the print job or page activation conditions may be missed.

Form is printed in plain text

Try one or more of the following:

Review the activation conditions in Forms Composer

The form you are printing may not be activated. Use Forms Composer to set up activation conditions for the form.

Make sure the Formsmerge function is not deactivated by Forms Manager

From Forms Manager, open the Printer Properties menu to activate Formsmerge.

Cannot fax or e-mail merged output

Check Forms Composer and printer settings

Make sure that workflow properties for the data stream have been properly configured. For more information, see the Forms Composer documentation.

For information on configuring network settings, see the documentation that came with the printer.

Characters appear as boxes in PDFs viewed with Acrobat Reader

Acrobat Reader may not correctly display all characters in archived and e-mailed attachments.

Use a different program to view PDFs

Merged output and preview output should match exactly. If boxes appear instead of characters in PDFs, switching to a different PDF viewer (such as Foxit Reader, available from www.foxitsoftware.com) should solve the problem.

Not all forms are listed

Use Forms Manager to view all forms stored on the optional flash memory card or the printer hard disk.

Data filters are not working

Check the Data Filters menu to see if the desired filter is enabled.

Cannot add new forms

Try one or more of the following:

Delete unused forms before adding new forms

Defragment the flash memory

The flash memory may be full. Defragmenting the flash memory frees space that is marked unavailable when files are deleted. You can access this feature from the Printer Properties in Forms Manager.

Bar codes do not print as expected

These are possible solutions. Try one or more of the following:

Make sure the Option Card is compatible with the printer on which it is installed

Make sure that the Option Card is installed

Print a Menu Settings page and make sure the Forms and Bar Code Option is listed under the Printer Information heading.

For more information on printing menus, see the documentation that came with the printer.

When using a PCL 5 emulation printer driver, make sure that the escape sequence used to generate the bar code is properly constructed

The escape sequence must begin with Esc and contain the #T parameter (not case-sensitive) for the bar code to be generated. Default values are used for parameters not explicitly defined in the sequence.

Cannot generate bar codes using PCL emulation printer drivers

The option card does not support bar code printing with PCL XL or HPGL/2 emulation printer drivers. Only printing with PCL 5 is supported.

Disable advanced features using a PCL XL emulation printer driver

1. From a Windows-based application, open the Print Properties dialog.
2. Click the **Graphics** tab.
3. From the Graphic mode list, select **Auto select**.

Unexpected results after printing a bar code

These are possible solutions. Try one or more of the following:

Make sure the PCL 5 emulation escape sequences are complete

PCL 5 escape sequences that generate an embedded bar code should be immediately followed by an escape sequence that *fully* specifies the text font to return to after printing the bar code. For example, Esc **`(s0p12h0s0b4099T`** returns the text to 12-pitch Courier with fixed pitch spacing immediately following the embedded bar code.

Make sure all parameters needed are fully specified

Parameter values are not retained for subsequent bar code PCL 5 escape sequences. Each time a bar code is generated, fully specify all parameters needed for each bar code.

Default values are used for any unspecified parameters.

Printed bar code is unreadable

Make sure Print Quality settings are not too dark or too light

Print Resolution and Toner Darkness settings can affect the quality of printed bar codes. From Print Properties, adjust the Print Quality settings before printing another bar code.

Check the paper

Use only paper that meets printer specifications. For more information, see the documentation that came with the printer.

Notices

Edition notice

April 2012

The following paragraph does not apply to any country where such provisions are inconsistent with local law: LEXMARK INTERNATIONAL, INC., PROVIDES THIS PUBLICATION “AS IS” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions; therefore, this statement may not apply to you.

This publication could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in later editions. Improvements or changes in the products or the programs described may be made at any time.

References in this publication to products, programs, or services do not imply that the manufacturer intends to make these available in all countries in which it operates. Any reference to a product, program, or service is not intended to state or imply that only that product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any existing intellectual property right may be used instead. Evaluation and verification of operation in conjunction with other products, programs, or services, except those expressly designated by the manufacturer, are the user’s responsibility.

For Lexmark technical support, visit **support.lexmark.com**.

For information on supplies and downloads, visit **www.lexmark.com**.

If you don't have access to the Internet, you can contact Lexmark by mail:

Lexmark International, Inc.
Bldg 004-2/CSC
740 New Circle Road NW
Lexington, KY 40550

© 2012 Lexmark International, Inc.

All rights reserved.

UNITED STATES GOVERNMENT RIGHTS

This software and any accompanying documentation provided under this agreement are commercial computer software and documentation developed exclusively at private expense.

Trademarks

Lexmark and Lexmark with diamond design are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Optra Forms is a trademark of Lexmark International, Inc.

PCL® is a registered trademark of the Hewlett-Packard Company.

The following terms are trademarks or registered trademarks of these companies:

Arial	The Monotype Corporation plc
CG Times	Based on Times New Roman under license from The Monotype Corporation plc, is a product of Agfa Corporation
ITC Bookman	International Typeface Corporation
Times New Roman	The Monotype Corporation plc
TrueType	Apple Computer, Inc.
Univers	Linotype-Hell AG and/or its subsidiaries

All other trademarks are the property of their respective owners.

Notice to users in the European Union

This product is in conformity with the protection requirements of EC Council directives 2004/108/EC, 2006/95/EC and 2005/32/EC on the approximation and harmonization of the laws of the Member States relating to electromagnetic compatibility, safety of electrical equipment designed for use within certain voltage limits and the ecodesign of energy-using products.

Compliance is indicated by the CE marking.

The manufacturer of this product is: Lexmark International, Inc., 740 West New Circle Road, Lexington, KY, 40550 USA. The authorized representative is: Lexmark International Technology Hungária Kft., 8 Lechner Ödön fasor, Millennium Tower III, 1095 Budapest HUNGARY, A declaration of conformity to the requirements of the Directives is available upon request from the Authorized Representative.

This product satisfies the Class B limits of EN 55022 and safety requirements of EN 60950.

Products equipped with 2.4GHz Wireless LAN option are in conformity with the protection requirements of EC Council directives 2004/108/EC, 2006/95/EC, and 1999/5/EC on the approximation and harmonization of the laws of the Member States relating to electromagnetic compatibility, safety of electrical equipment designed for use within certain voltage limits and on radio equipment and telecommunications terminal equipment.

Compliance is indicated by the CE marking.

Operation is allowed in all EU and EFTA countries, but is restricted to indoor use only.

The manufacturer of this product is: Lexmark International, Inc., 740 West New Circle Road, Lexington, KY, 40550 USA. The authorized representative is: Lexmark International Technology Hungária Kft., 8 Lechner Ödön fasor, Millennium Tower III, 1095 Budapest HUNGARY, A declaration of conformity to the requirements of the Directives is available upon request from the Authorized Representative.

This product may be used in the countries indicated in the table below.

AT	BE	BG	CH	CY	CZ	DE	DK	EE
EL	ES	FI	FR	HR	HU	IE	IS	IT
LI	LT	LU	LV	MT	NL	NO	PL	PT
RO	SE	SI	SK	TR	UK			

Česky	Společnost Lexmark International, Inc. tímto prohlašuje, že výrobek tento výrobek je ve shodě se základními požadavky a dalšími příslušnými ustanoveními směrnice 1999/5/ES.
Dansk	Lexmark International, Inc. erklærer herved, at dette produkt overholder de væsentlige krav og øvrige relevante krav i direktiv 1999/5/EF.
Deutsch	Hiermit erklärt Lexmark International, Inc., dass sich das Gerät dieses Gerät in Übereinstimmung mit den grundlegenden Anforderungen und den übrigen einschlägigen Bestimmungen der Richtlinie 1999/5/EG befindet.
Ελληνική	ΜΕ ΤΗΝ ΠΑΡΟΥΣΑ Η LEXMARK INTERNATIONAL, INC. ΔΗΛΩΝΕΙ ΟΤΙ ΑΥΤΟ ΤΟ ΠΡΟΪΟΝ ΣΥΜΜΟΡΦΩΝΕΤΑΙ ΠΡΟΣ ΤΙΣ ΟΥΣΙΩΔΕΙΣ ΑΠΑΙΤΗΣΕΙΣ ΚΑΙ ΤΙΣ ΛΟΙΠΕΣ ΣΧΕΤΙΚΕΣ ΔΙΑΤΑΞΕΙΣ ΤΗΣ ΟΔΗΓΙΑΣ 1999/5/ΕΚ.
English	Hereby, Lexmark International, Inc., declares that this type of equipment is in compliance with the essential requirements and other relevant provisions of Directive 1999/5/EC.
Español	Por medio de la presente, Lexmark International, Inc. declara que este producto cumple con los requisitos esenciales y cualesquiera otras disposiciones aplicables o exigibles de la Directiva 1999/5/CE.
Eesti	Käesolevaga kinnitab Lexmark International, Inc., et seade see toode vastab direktiivi 1999/5/EÜ põhinõuetele ja nimetatud direktiivist tulenevatele muudele asjakohastele sätetele.
Suomi	Lexmark International, Inc. vakuuttaa täten, että tämä tuote on direktiivin 1999/5/EY oleellisten vaatimusten ja muiden sitä koskevien direktiivin ehtojen mukainen.
Français	Par la présente, Lexmark International, Inc. déclare que l'appareil ce produit est conforme aux exigences fondamentales et autres dispositions pertinentes de la directive 1999/5/CE.
Magyar	Alulírott, Lexmark International, Inc. nyilatkozom, hogy a termék megfelel a vonatkozó alapvetõ követelményeknek és az 1999/5/EC irányelv egyéb elõírásainak.
Íslenska	Hér með lýsir Lexmark International, Inc. yfir því að þessi vara er í samræmi við grunnkröfur og aðrar kröfur, sem gerðar eru í tilskipun 1999/5/EC.
Italiano	Con la presente Lexmark International, Inc. dichiara che questo questo prodotto è conforme ai requisiti essenziali ed alle altre disposizioni pertinenti stabilite dalla direttiva 1999/5/CE.
Latviski	Ar šo Lexmark International, Inc. deklarē, ka šis izstrādājums atbilst Direktīvas 1999/5/EK būtiskajām prasībām un citiem ar to saistītajiem noteikumiem.
Lietuvių	Šiuo Lexmark International, Inc. deklaruoja, kad šis produktas atitinka esminius reikalavimus ir kitas 1999/5/EB direktyvos nuostatas.
Malti	Bil-preżenti, Lexmark International, Inc., jiddikjara li dan il-prodott huwa konformi mal-ħtiġijiet essenzjali u ma dispożizzjonijiet oħrajn relevanti li jinsabu fid-Direttiva 1999/5/KE.
Nederlands	Hierbij verklaart Lexmark International, Inc. dat het toestel dit product in overeenstemming is met de essentiële eisen en de andere relevante bepalingen van richtlijn 1999/5/EG.
Norsk	Lexmark International, Inc. erklærer herved at dette produktet er i samsvar med de grunnleggende krav og øvrige relevante krav i direktiv 1999/5/EF.

Polski	Niniejszym Lexmark International, Inc. oświadcza, że niniejszy produkt jest zgodny z zasadniczymi wymogami oraz pozostałymi stosownymi postanowieniami Dyrektywy 1999/5/EC.
Português	A Lexmark International Inc. declara que este este produto está conforme com os requisitos essenciais e outras disposições da Diretiva 1999/5/CE.
Slovensky	Lexmark International, Inc. týmto vyhlasuje, že tento produkt spĺňa základné požiadavky a všetky príslušné ustanovenia smernice 1999/5/ES.
Slovensko	Lexmark International, Inc. izjavlja, da je ta izdelek v skladu z bistvenimi zahtevami in ostalimi relevantnimi določili direktive 1999/5/ES.
Svenska	Härmed intygar Lexmark International, Inc. att denna produkt står i överensstämmelse med de väsentliga egenskapskrav och övriga relevanta bestämmelser som framgår av direktiv 1999/5/EG.

Index

B
bar code
  composite 6
  font-based 6
  generating data 13
  generating, troubleshooting 23
  one-dimensional 6
  supported 6
  two-dimensional 6
bar code menu 18
Bar codes do not print as expected 23

C
cannot add new forms 23
cannot fax or e-mail merged output 22
cannot generate bar codes using PCL emulation printer drivers 23
capturing raw data for mapping 18
characters appear as boxes in PDFs viewed with Acrobat Reader 22

D
Data filters are not working 23
data mapping
  capturing raw data 18
devices
  supported 4

E
emission notices 26

F
flash drive
  printing forms from 19
flash memory is full 23
font limitations 19
fonts
  limitations 19
  mismatch in Forms Composer and printed forms 21
  supported 10
form did not merge 22
form is printed in plain text 22
forms
  identifying version 19
  printing from a flash drive 19
  storing 18
Forms and Bar Code Card
  identifying forms version 19
  overview 4
Forms Card menu 15
Forms Composer
  font mismatch, troubleshooting 21
Forms Manager
  cannot detect printer, troubleshooting 20
  capturing raw data for mapping 18
  setting printer to Data Capture mode 18
Forms Manager cannot detect the printer 20
forms overview 15

G
generating bar code data 13

I
installing SAP device types 11
installing Visual Bar Code Designer 13
International fonts do not print as expected 20

M
menu
  bar code 18
  Forms Card 15
merged output
  cannot fax or e-mail, troubleshooting 22
mismatched fonts in Forms Composer and on printed forms 21
modifying device types format and default settings 11

N
not all forms are listed 23
notices 25, 26

O
overview 4

P
PDFs
  problems with 22
Printed bar code is unreadable 24
printer does not respond after installation 20
printing forms from a flash drive 19

S
SAP
  installing device types 11
SAP device types
  installing 11
  modifying format 11
  modifying settings 11
storing forms on the printer 18
supported bar codes 6
supported devices 4
supported operating systems 13

T
troubleshooting
  cannot add new forms 23
  cannot fax or e-mail merged output 22
  cannot generate bar code using PCL emulation printer drivers 23
  flash memory is full 23
  form did not merge 22
  form is printed in plain text 22
  Forms Manager cannot detect printer 20
  not all forms are listed 23
  printer does not respond after installation 20

U
Unexpected results after printing a bar code 24

V
Visual Bar Code Designer
  generating bar code data 13

installing 13
supported operating systems 13