

Printing

Paper handling

Maintenance

Troubleshooting

Administration

Index

**A**

- A4
  - loading
    - manual feed
    - tray 1
    - tray 2
- A5
  - loading
    - manual feed
    - tray 1
    - tray 2
- advanced troubleshooting mode
- menu items
  - auto CRLF/LFCR
  - Parallel Mode 1
  - Parallel Mode 2
  - Parallel Protocol
  - Parallel Strobe Adjust
  - PPDS Activated
  - USB NPA Mode
  - USB Port Enabled
- AppleTalk network printing

**B**

- B5
  - loading
    - manual feed
    - tray 1

- tray 2
- B5 paper
- Busy light

**C**

- card stock
  - loading
    - manual feed
    - tray 1
  - sizes and weights
- cardstock
  - loading
- Complex Page Error light
- configuration mode
  - menu items
    - auto CRLF/LFCR
    - Parallel NPA Mode
  - selecting
- corner bucklers

**D**

- DHCP

**E**

- envelopes
  - loading
    - manual feed

- tray 1
  - sizes and weights
- Error light
  - call for service
  - flushing data
  - memory full
  - print cartridge error
  - print cartridge not installed
  - printer top cover open
- executive
  - loading
    - manual feed
    - tray 1
    - tray 2

**F**

- factory defaults, restore
- Fastbytes
- features
- Flushing light
- Font Error light

**H**

- hex trace mode
- Host Interface Error light



Printing

Paper handling

Maintenance

Troubleshooting

Administration

Index

**I**

Insufficient Defrag Memory Error  
light

**L**

labels  
loading  
manual feed  
tray 1  
sizes and weights

legal  
loading  
manual feed  
tray 1  
tray 2

letter  
loading  
manual feed  
tray 1  
tray 2

letterhead  
loading  
manual feed  
tray 1  
tray 2

LexIP  
Windows 95/98/Me  
Windows NT 4.0/2000

Load Paper light  
manual feed  
tray 1or tray 2  
loading

A4 paper  
manual feed  
tray 1  
tray 2

A5 paper  
manual feed  
tray 1  
tray 2

B5 paper  
manual feed  
tray 1  
tray 2

card stock  
manual feed  
tray 1

envelopes  
manual feed  
tray 1

executive  
manual feed

labels  
manual feed  
tray 1

legal  
manual feed

tray 1  
tray 2  
letter  
manual feed  
tray 1  
tray 2  
letterhead  
manual feed  
tray 1  
tray 2  
transparencies  
manual feed  
tray 1  
loading labels

**M**

Manual Duplex light  
manual duplex, using  
media  
types and sizes  
Memory Full light

**N**

network setup page, print  
Non-NPDS printing  
Novell NetWare  
NPRINTER/RPRITER



Printing

Paper handling

Maintenance

Troubleshooting

Administration

Index

## O

- operator panel
  - button, terms
  - lights
    - Busy
    - Complex Page Error
    - Error
    - Flushing Data
    - Font Error
    - Host Interface Error
    - Insufficient Defrag Memory Error
    - Load Paper
    - Load Paper, manual feeder
    - Load Paper, tray 1 or tray 2
    - Manual Duplex
    - Memory Full
    - Paper Jam
    - Print Cartridge error
    - Printer Top Cover Open
    - Ready/Data
    - Resolution Reduction Warning
    - Resource Save Off Error
    - Service Error
    - Short Paper Error
    - Toner Low
    - Waiting

## P

- paper
  - loading
    - manual feed
    - tray 1
    - tray 2
  - sizes and weights
- Paper Jam light
- Parallel Mode
  - 1
  - 2
  - NPA
- Parallel Protocol
- PPDS Activated
- print cartridge
  - error
  - recycling
  - replacing
- print quality test pages
- print server
  - error conditions
  - light patterns
  - normal conditions
  - print a network setup page
- print to a queue
- printer
  - attendance information
  - features
  - status information

- printer hardware, updating
- printing
  - AppleTalk network
- PSERVER

## Q

- queue-based (non-NPDS) printing

## R

- Ready/Data light
- recycling supplies
- replacing the print cartridge
- reset user defaults
- Resetting user defaults
- Resolution Reduction Warning light
- Resource Save Off Error light
- restore factory defaults

## S

- safety notices
- secondary error codes
  - complex page
  - host interface error
  - insufficient defrag memory
  - memory full
  - PPDS font error



## Printing

## Paper handling

## Maintenance

## Troubleshooting

## Administration

## Index

- resolution reduction
- short paper
- sending a network print job
  - Non-NPDS
  - print to a queue
- service
  - calling for
  - error lights
- Service Error light
- setting the IP address
- shared printing
  - on the network
  - peer-to-peer
  - point and print
  - Windows NT 4.0/2000
- Short Paper Error light
- Special Function Menu
  - CRLF/LFCR setting
  - Hex Trace setting
  - Parallel Mode 1 setting
  - Parallel Mode 2 setting
  - Parallel NPA Mode setting
  - Parallel Protocol
  - Parallel Strobe Adjust setting
  - PPDS Activated setting
  - print quality test pages setting
  - USB NPA Mode setting
  - USB Port Enabled setting
- using

- stack height indicator
- supplies
  - recycling

## T

- TCP/IP
- TCP/IP Setup Utility
- Toner Low light
- transparencies
  - loading
    - manual feed
    - tray 1
    - sizes and weights
  - tray 2
    - corner bucklers
    - stack height indicator
- troubleshooting
  - AppleTalk
  - Hex Trace mode
  - NetWare
  - paper problems
  - print quality problems
  - print quality test pages
  - printing problems
  - resetting user defaults
  - restore factory defaults
  - TCP/IP

## U

- United Kingdom
  - Telecommunications Act 1984
- USB
  - NPA Mode
  - Port Enabled
- user defaults, resetting

## W

- Waiting light

