

Lexmark E350d



*Maximizes performance, reliability,
and environmental efficiency.*

LEXMARKTM

Lexmark E350d

- Up to 35 pages per minute laser output
- 366 MHz processor
- Compact footprint is ideal for users with limited space
- Impressive 2400 Image Quality resolution



Lexmark E350d

Product Specifications

Part Number	33S0425 (E350d)
Product Class	Monochrome Laser
Speed	Up to 35 ppm
Resolution	2400 Image Quality, 1200 Image Quality, 1200 x 1200 dpi, 600 x 600 dpi
Time to First Page	As fast as 6.5 seconds
Processor	366 MHz
Memory (std./max.)	32MB/160MB
Connectivity	
Standard:	Parallel (IEEE 1284 Bi-Di) and a standard Hi Speed USB port.
Optional:	External print servers connecting via parallel or USB port depending on print server model
Operating Systems	Windows, Linux, Mac, UNIX, NetWare, Server 2003 and OS/400 For a complete list, visit www.lexmark.ca .
Emulations	PCL 6, PostScript 3, PPDS Migration Tool
Fonts	PostScript 3 emulation, 89 scalable PCL 6 emulation
Size (WxDxH)	E350d: 15.6 in. x14.1 in. x10.2 in. (W x D x H) (396 mm x 359 mm x 259 mm)
Weight	E350d: 24.5lb (11.1kg)
Acoustics	52 dBA printing; Inaudible idle
Duty Cycle	Up to 35,000 pages per month

In the Box

- Lexmark E350d**
- Lexmark E350d Printer
 - 1,500-page Starter Print Cartridge¹
 - Photoconductor Kit
 - Power Cord
 - Setup Sheet

Media Specifications

Paper Capacity (sheets)	E350d
Standard Input	250 + 1 manual
Maximum Input	800 + 1 manual
Output	150 top or 1 rear
Paper Sources	E350d
Standard Input	2
Maximum Input	3
Output	1 top or 1 rear
Media Types	Plain paper, envelopes, card stock, paper labels, and transparencies
Media Sizes	Letter, legal, A4, A5, executive, universal (3 x 5 in. to 8.5 x 14 in.), statement, JIS B5, folio, and envelopes (7 ³ / ₄ , 9, 10, DL, C5, B5)
Media Weights	Plain paper: 20 lb. (75 g/m ²)

Supplies & Accessories

Supplies	9,000-page High Yield Return Program Print Cartridge ¹	E352H11A
	9,000-page High Yield Print Cartridge ¹	E352H21A
	3,500-page Return Program Print Cartridge ¹	E250A11A
	3,500-page Print Cartridge ¹	E250A21A
	30,000-page Photoconductor Kit ¹	E250X22G
Memory Options	32MB SDRAM	1021257
	64MB SDRAM	1021258
	128MB SDRAM	1021259
	256MB SDRAM	1021260
	32MB Flash Card	1021208

Additional Information

¹ Declared standard yield value in accordance with ISO/IEC 19752

² One flash memory slot available