

T520/T522 Print Cartridge

Printer: T520

Declaration of Yield: **Average Cartridge Yield 7500 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 7984
Std Dev 354
90% Lower Confidence 7800

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 29-Oct-2004 stop 31-Oct-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At toner low 2nd shake At toner low
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	7.4.1
Operating system	Windows 2000
Application software	Adobe Acrobat version 5
Test page version	Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAX041744129	A001871	74	75	74	48	49	48	7,895	Y
CAS041330128	A001875	74	75	74	48	49	48	8,304	Y
CAS041402019	A001887	74	75	74	48	49	48	7,593	Y
CAS041530956	A001990	74	75	74	48	49	48	7,742	Y
CAS041530946	A001871	74	74	74	48	48	48	7,854	Y
CAX041745543	A001875	74	74	74	48	48	48	7,929	Y
CAS041330235	A001887	74	74	74	48	48	48	8,898	Y
CAS041402059	A001990	74	74	74	48	48	48	7,976	Y
CAS041402079	A001871	74	75	74	48	48	48	7,865	Y
CAS041530957	A001875	74	75	74	48	48	48	7,606	Y
CAX041744092	A001887	74	75	74	48	48	48	7,956	Y
CAS041330204	A001990	74	75	74	48	48	48	8,184	Y