LEXMARK™

ISO/IEC 19752 Yield Test Report

PN: 12A6765, 12A6865, 12A6869

T620/T622 Print Cartridge

Printer: T620

Declaration of Yield: **Average Cartridge Yield 30000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average	34126
Std Dev	1186
90% Lower Confidence	33511

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

	start	**stop**
Date tested	19-Jan-2005	27-Jan-2005

Number of cartridges in testing		12
Qty. of cartridges used in calculation		12
Shake Procedure	1st shake	At toner low
	2nd shake	At toner low
Print mode		Continuous
Number of printers tested		4
Media used		Boise Cascade X-9 - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		7.4.1
Operating system		Windows 2000
Application software		Adobe Acrobat version 5
Test page version		Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:		Temperature			Humidity				
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min	Cartridge Yield	Cart used in Calculation
CAX043500FEC	41HY868	74	75	74	48	49	48	34,670	Y
CAX043501D06	NFM7C550	74	75	74	48	49	48	35,631	Y
CAX043510E5B	41KA095	74	75	74	48	49	48	34,899	Y
CAX0435204C0	41AW083	74	75	74	48	49	48	31,321	Y
CAX043510E56	41HY868	74	75	74	48	49	48	34,520	Y
CAX043510E54	NFM7C550	74	75	74	48	49	48	34,855	Y
CAX0435209ED	41KA095	74	75	74	48	49	48	33,522	Y
CAX043510E57	41AW083	74	75	74	48	49	48	33,975	Y
CAX043501CF4	41HY868	74	75	74	48	49	48	34,682	Y
CAX043510E5A	NFM7C550	74	75	74	48	49	48	35,167	Y
CAX043500EE1	41KA095	74	75	74	48	49	48	33,257	Y
CAX0435022FC	41AW083	74	75	74	48	49	48	33,017	Y