

T630, T632, T634 High Yield Print Cartridge

Printer: T630

Declaration of Yield: **Average Cartridge Yield 21000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 22916
Std Dev 1049
90% Lower Confidence 22371

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 30-Sep-2004 stop 5-Oct-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At toner low 2nd shake At toner low
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	8.4.0.0
Operating system	Windows 2000
Application software	Adobe Acrobat version 5.0
Test page version	Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAA041610181	991G23K	75	75	74	51	52	51	22,906	Y
CAC042260257	991G23X	75	75	74	51	52	51	22,003	Y
CAC042290764	991G3T3	75	75	74	51	52	51	22,543	Y
CAX042239709	991G3TC	75	75	74	51	52	51	23,954	Y
CAC042260228	991G23K	74	75	74	51	52	51	22,977	Y
CAC042290762	991G23X	74	75	74	51	52	51	20,960	Y
CAX0422238324	991G3T3	74	75	74	51	52	51	23,979	Y
CAX041611312	991G3TC	74	75	74	51	52	51	24,355	Y
CAC042290759	991G23K	74	75	74	50	52	46	22,662	Y
CAX042238831	991G23X	74	75	74	50	52	46	22,052	Y
CAX041611626	991G3T3	74	75	74	50	52	46	22,315	Y
CAC042260246	991G3TC	74	75	74	50	52	46	24,280	Y

Comments and or exceptions: