

**T632, T634 Extra High Yield Print Cartridge**

Printer: T632

Declaration of Yield: **Average Cartridge Yield 32000 standard pages**  
**Declared yield value in accordance with ISO/IEC 19752**

**Average** 34063  
**Std Dev** 1250  
**90% Lower Confidence** 33414

**For questions concerning testing contact:**

Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested** start 4-Oct-2004 stop 12-Oct-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At toner low
	2nd shake At toner low
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	8.4.0.0
Operating system	Windows 2000
Application software	Adobe Acrobat version 5.0
Test page version	Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAX042059004D	9912997	75	75	74	48	48	47	34,374	Y
CAX041838897D	99104KN	75	75	74	48	48	47	34,914	Y
CAX042198747D	99129B6	75	75	74	48	48	47	33,175	Y
CAX042077216D	99129B8	75	75	74	48	48	47	31,047	Y
CAX042198383D	9912997	74	75	74	48	48	47	34,829	Y
CAX042077154D	99104KN	74	75	74	48	48	47	34,436	Y
CAX041839500D	99129B6	74	75	74	48	48	47	34,602	Y
CAX042058025D	99129B8	74	75	74	48	48	47	33,081	Y
CAX041838919	9912997	74	75	74	48	49	47	36,026	Y
CAX042059318	99104KN	74	75	74	48	49	47	34,643	Y
CAX042086340	99129B6	74	75	74	48	49	47	33,508	Y
CAX042199691	99129B8	74	75	74	48	49	47	34,115	Y

Comments and or exceptions: