



T640, T642, T644 High Yield Print Cartridge

Printer: T640

Declaration of Yield:	Average Cartridge Yield	21000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 23898
Std Dev 925
90% Lower 23324
Confidence

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date tested	23-Mar-2005	30-Mar-2005
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	At toner low
	2nd shake	At toner low
Print mode		Continuous
Number of printers tested		3
Media used		Boise Cascade - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		T640 version 1
Operating system		Windows 2000
Application software		Acrobat version 6.01
Test page version		Down load Free__19752 Test Chart.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS050559166	PL2-1026-L	75	75	72	51	57	45	24,001	Y
CAS050559228	PL2-1037-L	75	75	72	51	57	45	24,561	Y
CAS050559205	PL2-1034-L	75	75	72	51	57	45	24,581	Y
CAS050559265	PL2-1026-L	75	75	72	51	57	45	22,360	Y
CAS050559191	PL2-1026-L	75	75	72	51	57	45	24,259	Y
CAS050559157	PL2-1037-L	75	75	72	51	57	45	25,059	Y
CAS050559181	PL2-1037-L	75	75	72	51	57	45	24,200	Y
CAS050559256	PL2-1034-L	75	75	72	51	57	45	22,538	Y
CAS050559202	PL2-1034-L	74	76	72	45	53	41	23,519	Y

Comments and or exceptions:

also covers:

64004HA 64016HE 64036HE
 64004HE 64017HR 64037HR
 64004HL 64018HL 64038HL
 64004HR