



T640, T642, T644 High Yield Print Cartridge

Printer: T642

Declaration of Yield:	Average Cartridge Yield	21000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 25234
Std Dev 1397
90% Lower Confidence 24368

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date tested	14-Apr-2005	17-Apr-2005
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	At toner low
	2nd shake	At toner low
Print mode	Continuous	
Number of printers tested	3	
Media used	Boise Cascade - 20# - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	T642 version 1	
Operating system	Windows 2000	
Application software	Acrobat version 6.01	
Test page version	Down load Free__19752 Test Chart.pdf	

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS050910634	PL3-104-M	73	75	72	53	58	49	24,001	Y
CAS050910551	PL3-104-M	73	75	72	53	58	49	23,381	Y
CAS050910550	PL3-104-M	73	75	72	53	58	49	23,821	Y
CAS050910616	PL3-107-M	73	75	72	53	58	49	24,402	Y
CAS050910597	PL3-107-M	73	75	72	53	58	49	26,301	Y
CAS050910573	PL3-107-M	73	75	72	53	58	49	26,761	Y
CAS050910572	PL3-110-M	73	75	72	53	58	49	25,501	Y
CAS050910637	PL3-110-M	73	75	72	53	58	49	27,301	Y
CAS050910604	PL3-110-M	73	75	72	53	58	49	25,641	Y

Comments and or exceptions:

also covers:

64004HA	64016HE	64037HR
64004HE	64017HR	64038HL
64004HL	64018HL	
64004HR	64036HE	