

W840 Print Cartridge

Printer: W840

Declaration of Yield: **Average Cartridge Yield 30000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 33156
Std Dev 1270
90% Lower Confidence 32368

For questions concerning testing

contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 23-Aug-2005 stop 30-Aug-2005

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake No shake 2nd shake No shake
Print mode	Continuous
Number of printers tested	3
Media used	Boise Cascade - 20# - Letter
Paper feed orientation	Long Edge Feed (LEF)
Driver version	W840 PCL-XL G4
Operating system	Windows XP SP2
Application software	Adobe Acrobat Professional 6.0.2
Test page version	Download_Free___19752_Test_Chart_V

Cartridge testing data:	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg	Max	Min	Avg	Max	Min		
JP-CT200435-55Q-1001000428	LS	74	75	73	52	56	50	32,661	Y
JP-CT200435-55Q-1001000477	ML	74	75	73	52	56	50	32,640	Y
JP-CT200435-55Q-1001000476	LF	74	75	73	52	56	50	34,270	Y
JP-CT200435-55Q-1001000431	LS	74	75	73	51	53	49	33,240	Y
JP-CT200435-55Q-1001000427	ML	74	75	73	51	53	49	30,950	Y
JP-CT200435-55Q-1001000429	LF	74	75	73	51	53	49	33,370	Y
JP-CT200435-55Q-1001000424	LS	75	76	73	55	60	53	31,920	Y
JP-CT200435-55Q-1001000425	ML	75	76	73	55	60	53	34,890	Y
JP-CT200435-55Q-1001000426	LF	75	76	73	55	60	53	34,460	Y

Comments and or exceptions:

Test ran between Toner Lows with pages removed for Fade.