



ISO/IEC 24711 Yield Test Report

Printer: Pro4000, Pro4000c, Pro5500, Pro5500t

Part Numbers of Cartridges:

Cyan (C) 200, 210, 220

Magenta (M) 200, 210, 220

Yellow (Y) 200, 210, 220

Black (K) 200, 210, 220

Lexmark Inkjet Cartridge Yield:

Average Continuous Composite Color (CMY) Cartridge Yield

500 standard pages

Average Continuous Black (K) Cartridge Yield

625 standard pages

Declared yield in accordance with ISO/IEC 24711

Tested Cartridge Summary:

90% Lower Confidence

Composite Color (CMY) = 594 pages

Black = 676 pages

For questions concerning testing contact:

Lexmark International Inc.

740 West New Circle Rd.

Lexington, Ky. 40550 USA

Attn: Inkjet Supplies Product Manager

Date tested	26-Jan-2012	To	27-Jan-2012
Printer Model Used	Pro5500		
CMY Cartridge Model	200, 210, 220		
Type of cartridge	CMY Individual Tank		
Black Cartridge Model	200, 210, 220		
Type of cartridge	K Cartridge		
Number of cartridges in testing	C= 9	M= 9	Y= 9
Qty. of cartridges used in calculation	C= 9	M= 9	Y= 9
Supplemental Cartridges	Not Applicable		
Print mode	Continuous		
Number of printers tested	3		
Media used	Orange Paper - 20 lbs - Letter		
Paper feed orientation	Short Edge Feed (SEF)		
Computer Model	Generic		
CPU	Intel® Core™ 2 Duo E6750@2.66GHz		
Memory Size	2.64 GHz, 1.99 GB of RAM		
Interface	USB 2.0		
Driver version	Gold 8		
Operating system	Microsoft Windows XP Prof., SP3		
Application software	Adobe Reader 9.0		
Test page version	ISO-IEC 24712 Test suite.pdf (7/20/2006)		
Power (off/on) everyday	Yes		
Pre-generated file used	No		
Header / Footer used	No		



ISO/IEC 24711 Yield Test Report

Printer	Color	Cartridge SN	Temperature C / F			Humidity			Cartridge Yield	Used in Calc
			Avg	Max	Min	Avg	Max	Min		
0FT	C	12RLH72698	22 / 72	23 / 73	22 / 71	49	52	43	725	Y
0FT	C	WHHF227NPG	22 / 72	23 / 73	22 / 71	49	52	43	665	Y
0FT	C	ZZJ9ZF1PXJ	22 / 72	23 / 73	22 / 71	49	52	43	575	Y
0C6	C	ZZP444JN1Z	22 / 72	23 / 73	22 / 71	49	52	43	750	Y
0C6	C	WHH9WPXJMV	22 / 72	23 / 73	22 / 71	49	52	43	675	Y
0C6	C	ZZJM89MXP9	22 / 72	23 / 73	22 / 71	49	52	43	605	Y
0DB	C	Z5MZBPSTGT	22 / 72	23 / 73	22 / 71	49	52	43	750	Y
0DB	C	WHFYSJ4SDL	22 / 72	23 / 73	22 / 71	49	52	43	670	Y
0DB	C	ZZHH198ZCT	22 / 72	23 / 73	22 / 71	49	52	43	590	Y
0FT	K	YVGGN9V8J4	22 / 72	23 / 73	22 / 71	49	52	43	750	Y
0FT	K	1H687WF54N	22 / 72	23 / 73	22 / 71	49	52	43	720	Y
0FT	K	YZ3BMP5JFB	22 / 72	23 / 73	22 / 71	49	52	43	660	Y
0C6	K	YVDHC9YG1	22 / 72	23 / 73	22 / 71	49	52	43	750	Y
0C6	K	WCYWCW1WHD	22 / 72	23 / 73	22 / 71	49	52	43	685	Y
0C6	K	YYHGKXKC55	22 / 72	23 / 73	22 / 71	49	52	43	660	Y
0DB	K	YV2SGJMD1W	22 / 72	23 / 73	22 / 71	49	52	43	750	Y
0DB	K	1GMB6TJVPJ	22 / 72	23 / 73	22 / 71	49	52	43	660	Y
0DB	K	YZ4BY6HTYC	22 / 72	23 / 73	22 / 71	49	52	43	680	Y
0FT	M	XT1M9F85NV	22 / 72	23 / 73	22 / 71	49	52	43	600	Y
0FT	M	ZWGG66F9LZ	22 / 72	23 / 73	22 / 71	49	52	43	515	Y
0FT	M	R9SN2MVCW5	22 / 72	23 / 73	22 / 71	49	52	43	520	Y
0C6	M	XSMPS74FXF	22 / 72	23 / 73	22 / 71	49	52	43	645	Y
0C6	M	ZWG8LZZV5Y	22 / 72	23 / 73	22 / 71	49	52	43	515	Y
0C6	M	R9XWNBFW3F	22 / 72	23 / 73	22 / 71	49	52	43	515	Y
0DB	M	LGDJNR45FF	22 / 72	23 / 73	22 / 71	49	52	43	610	Y
0DB	M	Z2WHNP8VKW	22 / 72	23 / 73	22 / 71	49	52	43	505	Y
0DB	M	12W1L8HGJ4	22 / 72	23 / 73	22 / 71	49	52	43	515	Y
0FT	Y	X7P1Z89LTC	22 / 72	23 / 73	22 / 71	49	52	43	800	Y
0FT	Y	M35FLKKRB9	22 / 72	23 / 73	22 / 71	49	52	43	685	Y
0FT	Y	RKDZSLV2X	22 / 72	23 / 73	22 / 71	49	52	43	635	Y
0C6	Y	WD71P211LP	22 / 72	23 / 73	22 / 71	49	52	43	810	Y
0C6	Y	SW73XGBMCK	22 / 72	23 / 73	22 / 71	49	52	43	675	Y
0C6	Y	PYZL269LNM	22 / 72	23 / 73	22 / 71	49	52	43	610	Y
0DB	Y	WD5V4GKPRT	22 / 72	23 / 73	22 / 71	49	52	43	750	Y
0DB	Y	YJ6D6K97D1	22 / 72	23 / 73	22 / 71	49	52	43	695	Y
0DB	Y	PYG9XY78H5	22 / 72	23 / 73	22 / 71	49	52	43	665	Y

	Raw Average	Std Dev.	90 % LCB
Cyan Cartridge	667	67	626
Magenta Cartridge	549	54	516
Yellow Cartridge	703	70	660
CMY Composite			594
Black Cartridge	702	41	676