

# ISO/IEC 19798 Yield Test Report

---

## Toner Cartridge

---

Printer: **CX833**

### Part Numbers of Cartridges:

**Cyan ( C )** 77Lx0C0, 77L00CG

**Yellow ( Y )** 77Lx0Y0, 77L00YG

**Magenta ( M )** 77Lx0M0, 77L00MG

**Black ( K )** 77Lx0K0, 77L00KG

<b>Lexmark Toner Cartridge Yield Claim:</b>	
Average Continuous Composite Color (CMY) Cartridge Yield	12,000 standard pages
Average Continuous Black (K) Cartridge Yield	15,000 standard pages
Declared yield in accordance with ISO/IEC 19798	

### Tested Cartridge Summary:

90% Lower Confidence

Composite Color (CMY) = **12,630** pages  
Black = **16,318** pages

### For questions concerning testing contact:

Lexmark International Inc.  
740 West New Circle Rd.  
Lexington, Ky. 40550 USA  
Attn: Laser Supplies Product Manager

### Date tested

12-Jan-2024      22-Jan-2024

Number of cartridges in testing	C= 9	M= 9	Y= 9	K= 9
Qty. of cartridges used in calculation	C= 9	M= 9	Y= 9	K= 9
Type of cartridge	Replenishment			
Shake Procedure				
1st shake	No shake			
2nd shake	No shake			
Print mode	Continuous			
Number of printers tested	3			
Media used	Hammermill Tidal MP - 20 lbs. - Letter			
Paper feed orientation	Long Edge Feed (LEF)			
Driver version	Lexmark Printer Software G2 PostScript 3 Emulation PScript5.dll Version 5.2.2			
Operating system	Windows 10 Enterprise			
Application software	Adobe Reader DC			
Test page version	ISO-IEC_24712_Test_suite_v2.pdf			
Power (off/on) everyday	ON			
Pre-generated file used	Y			
Header / Footer used	Y			
Computer Model	Intel(R) Core(TM) i5-10500T CPU @ 2.30GHz			
Computer RAM and CPU type	1024 MB			
PC / Printer connection	Network			

### Comments :

The print file was generated with a 5-page job.

# ISO/IEC 19798 Yield Test Report

## Toner Cartridge

Printer	Color	Cartridge SN	Temperature C / F			Humidity			Cartridge Yield	Used in Calc
			Avg	Max	Min	Avg	Max	Min		
7566FSTCLV013	c	SCAH232991248	23 / 73	24 / 75	23 / 73	49	51	47	12845	Y
5066FSTSFL164	c	SCAH232991225	23 / 73	24 / 75	23 / 73	49	50	47	13080	Y
7566FSTCLV013	c	SCAH23299122B	23 / 73	24 / 75	23 / 73	49	51	47	11940	Y
5066FSTSFL164	c	SCAH232991214	23 / 74	24 / 75	23 / 73	49	49	47	12840	Y
5066FSTSFL164	c	SCAH232991217	23 / 74	24 / 75	23 / 73	49	49	47	13125	Y
5066FSTSFL164	c	SCAH23299122E	23 / 74	24 / 75	23 / 73	49	49	47	12580	Y
7566FSTCLV013	c	SCAH232991218	23 / 74	24 / 76	23 / 73	49	50	46	12600	Y
5066FSTSFL164	c	SCAH232991220	23 / 74	24 / 76	23 / 73	49	50	46	12590	Y
5066FSTSFL164	c	SCAH232991243	23 / 74	24 / 76	23 / 73	49	50	46	12330	Y
7566FSTCLV013	k	SCAH233180F0C	23 / 73	24 / 75	23 / 73	49	50	47	16375	Y
7566FSTCLV013	k	SCAH233180F14	23 / 73	24 / 75	23 / 73	49	50	47	16395	Y
5066FSTSFL164	k	SCAH233180F25	23 / 73	24 / 75	23 / 73	49	50	47	16605	Y
5066FSTSFL164	k	SCAH233180F36	23 / 74	24 / 75	23 / 73	48	49	47	16815	Y
7566FSTCLV013	k	SCAH233180F37	23 / 74	24 / 75	23 / 73	48	49	47	16755	Y
5066FSTSFL164	k	SCAH233180F20	23 / 74	24 / 75	23 / 73	48	49	47	15710	Y
5066FSTSFL164	k	SCAH233180F8F	23 / 74	24 / 76	23 / 73	48	50	46	16810	Y
5066FSTSFL164	k	SCAH233180F39	23 / 74	24 / 76	23 / 73	49	50	46	16500	Y
5066FSTSFL164	k	SCAH233180F28	23 / 74	25 / 77	23 / 73	48	50	46	17110	Y
7566FSTCLV013	m	SCAH233000A51	23 / 73	24 / 75	23 / 73	49	50	47	12835	Y
7566FSTCLV013	m	SCAH233000A84	23 / 73	24 / 75	23 / 73	49	50	47	13065	Y
5066FSTSFL164	m	SCAH233000A5A	23 / 73	24 / 75	23 / 73	49	50	47	13160	Y
5066FSTSFL164	m	SCAH233000A5B	23 / 74	24 / 75	23 / 73	49	49	47	12830	Y
7566FSTCLV013	m	SCAH233000A6E	23 / 74	24 / 75	23 / 73	48	49	47	13630	Y
5066FSTSFL164	m	SCAH233000A70	23 / 74	24 / 75	23 / 73	49	49	47	12670	Y
5066FSTSFL164	m	SCAH233000A55	23 / 74	24 / 76	23 / 73	49	50	46	12620	Y
5066FSTSFL164	m	SCAH233000A73	23 / 74	24 / 76	23 / 73	49	50	46	13100	Y
7566FSTCLV013	y	SCAH232960B33	23 / 73	24 / 75	23 / 73	49	50	47	13350	Y
7566FSTCLV013	y	SCAH232960B1E	23 / 73	24 / 75	23 / 73	49	50	47	12710	Y
7566FSTCLV013	y	SCAH2329405FC	23 / 73	24 / 75	23 / 73	49	50	47	12505	Y
5066FSTSFL164	y	SCAH232960B3E	23 / 74	24 / 75	23 / 73	48	49	47	13265	Y
5066FSTSFL164	y	SCAH232960B35	23 / 74	24 / 75	23 / 73	49	49	47	13100	Y
5066FSTSFL164	y	SCAH232940606	23 / 74	24 / 75	23 / 73	49	49	47	12855	Y
5066FSTSFL164	y	SCAH2329405FA	23 / 74	24 / 76	23 / 73	49	50	46	13340	Y
5066FSTSFL164	y	SCAH2329405F1	23 / 74	24 / 76	23 / 73	49	50	46	12980	Y
5066FSTSFL164	y	SCAH232940267	23 / 74	24 / 76	23 / 73	49	50	46	12480	Y

	Raw Average	Std Dev.	90 % LCB
Cyan Cartridge	12659	371	12429
Magenta Cartridge	12936	344	12723
Yellow Cartridge	12954	339	12744
CMY Composite			12630
Black Cartridge	16564	396	16318