



ISO/IEC 19798 Yield Test Report

Ship With Equipment

Printer: **CX961**

Part Numbers of Cartridges:

Cyan (C) 20LCL12C, 77Lx0C0, 77L00CG **Yellow (Y)** 20LCL12Y, 77Lx0Y0, 77L00YG

Magenta (M) 20LCL12M, 77Lx0M0, 77L00MG **Black (K)** 20LCL12K, 77Lx0K0, 77L00KG

Lexmark Toner Cartridge Yield Claim:

Average Continuous Composite Color (CMY) Cartridge Yield	12,000 standard pages
Average Continuous Black (K) Cartridge Yield	15,000 standard pages
Declared yield in accordance with ISO/IEC 19798	

Tested Cartridge Summary:

90% Lower Confidence

Composite Color (CMY) = **12,759** pages
 Black = **15,525** pages

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested

12-Jan-2024 23-Jan-2024

Number of cartridges in testing	C= 9	M= 9	Y= 9	K= 9
Qty. of cartridges used in calculation	C= 9	M= 9	Y= 9	K= 9
Type of cartridge	Replenishment			
Shake Procedure				
1st shake	No shake			
2nd shake	No shake			
Print mode	Continuous			
Number of printers tested	3			
Media used	Hammermill Tidal MP - 20 lbs. - Letter			
Paper feed orientation	Long Edge Feed (LEF)			
Driver version	Lexmark Printer Software G2 PostScript 3 Emulation PScript5.dll Version 5.2.2			
Operating system	Windows 10 Enterprise			
Application software	Adobe Reader DC			
Test page version	ISO-IEC_24712_Test_suite_v2.pdf			
Power (off/on) everyday	ON			
Pre-generated file used	Y			
Header / Footer used	Y			
Computer Model	Intel(R) Core(TM) i5-10500T CPU @ 2.30GHz			
Computer RAM and CPU type	1024 MB			
PC / Printer connection	Network			

Comments :

The print file was generated with a 5-page job.

ISO/IEC 19798 Yield Test Report

Ship With Equipment

Printer	Color	Cartridge SN	Temperature C / F			Humidity			Cartridge Yield	Used in Calc
			Avg	Max	Min	Avg	Max	Min		
7566FSTMFH233	c	SCAH23299120E	23 / 73	24 / 75	23 / 73	49	50	47	13030	Y
7566FSTMFL089	c	SCAH233180F0F	23 / 74	24 / 75	23 / 73	49	49	47	13165	Y
7566FSTMFH049	c	SCAH2329911FD	23 / 74	24 / 75	23 / 73	49	49	47	12025	Y
7566FSTMFL089	c	SCAH232991236	23 / 74	24 / 76	23 / 73	48	49	46	13530	Y
7566FSTMFH233	c	SCAH232991226	23 / 74	24 / 76	23 / 73	48	49	46	13555	Y
7566FSTMFH049	c	SCAH2329911FC	23 / 74	24 / 76	23 / 73	48	49	46	12440	Y
7566FSTMFL089	c	SCAH232991223	23 / 74	24 / 76	23 / 73	49	50	46	13460	Y
7566FSTMFH233	c	SCAH232991238	23 / 74	24 / 76	23 / 73	49	50	46	13885	Y
7566FSTMFH049	c	SCAH2329911FB	23 / 74	25 / 77	23 / 73	49	50	46	12120	Y
7566FSTMFL089	k	SCAH233180F35	23 / 73	24 / 75	23 / 73	49	50	47	14925	Y
7566FSTMFH233	k	SCAH233180F34	23 / 73	24 / 75	23 / 73	49	50	47	15450	Y
7566FSTMFH049	k	SCAH233180F3A	23 / 73	24 / 75	23 / 73	49	50	47	14865	Y
7566FSTMFL089	k	SCAH233180F0B	23 / 74	24 / 76	23 / 73	49	50	46	16105	Y
7566FSTMFH233	k	SCAH233180F06	23 / 74	24 / 76	23 / 73	49	50	46	16870	Y
7566FSTMFH049	k	SCAH233180ED8	23 / 74	24 / 76	23 / 73	49	50	46	16575	Y
7566FSTMFL089	k	SCAH233180F23	23 / 74	25 / 77	23 / 73	48	49	46	16130	Y
7566FSTMFH233	k	SCAH233180F1A	23 / 74	25 / 77	23 / 73	48	49	46	16580	Y
7566FSTMFH049	k	SCAH23299125A	23 / 74	25 / 77	23 / 74	48	49	46	16310	Y
7566FSTMFH233	m	SCAH233000A58	23 / 73	24 / 75	23 / 73	49	50	47	13200	Y
7566FSTMFL089	m	SCAH233000A8A	23 / 74	24 / 75	23 / 73	49	49	47	13170	Y
7566FSTMFH049	m	SCAH233000996	23 / 74	24 / 75	23 / 73	48	49	47	15655	Y
7566FSTMFL089	m	SCAH23300098E	23 / 74	24 / 76	23 / 73	48	49	46	13465	Y
7566FSTMFH233	m	SCAH233000A72	23 / 74	24 / 76	23 / 73	48	49	46	13835	Y
7566FSTMFH049	m	SCAH233000A75	23 / 74	24 / 76	23 / 73	49	50	46	12800	Y
7566FSTMFL089	m	SCAH233000A71	23 / 74	24 / 76	23 / 73	49	50	46	13665	Y
7566FSTMFH233	m	SCAH23300098F	23 / 74	24 / 76	23 / 73	49	50	46	13535	Y
7566FSTMFH049	m	SCAH233000990	23 / 74	25 / 77	23 / 73	48	49	46	12350	Y
7566FSTMFL089	y	SCAH232960B3F	23 / 73	24 / 75	23 / 73	49	50	47	12680	Y
7566FSTMFH233	y	SCAH232960B27	23 / 73	24 / 75	23 / 73	49	50	47	13100	Y
7566FSTMFH049	y	SCAH232960B1B	23 / 74	24 / 75	23 / 73	48	49	47	12320	Y
7566FSTMFL089	y	SCAH232940619	23 / 74	24 / 75	23 / 73	48	49	47	12925	Y
7566FSTMFH233	y	SCAH232960B36	23 / 74	24 / 75	23 / 73	48	49	47	13435	Y
7566FSTMFH049	y	SCAH232960B3D	23 / 74	24 / 76	23 / 73	49	50	46	12885	Y
7566FSTMFL089	y	SCAH2329405F2	23 / 74	24 / 76	23 / 73	49	50	46	13160	Y
7566FSTMFH233	y	SCAH2329406B	23 / 74	24 / 76	23 / 73	49	50	46	13285	Y
7566FSTMFH049	y	SCAH232960B2B	23 / 74	25 / 77	23 / 73	48	49	46	12695	Y

	Raw Average	Std Dev.	90 % LCB
Cyan Cartridge	13023	675	12605
Magenta Cartridge	13519	922	12948
Yellow Cartridge	12943	345	12729
CMY Composite			12759
Black Cartridge	15979	732	15525