



Lexmark MX432adwe

Scalable solutions. Enterprise-level security.



Lexmark MX432adwe

The Lexmark MX432adwe monochrome all-in-one brings scalable solution support and enterprise-level security to small workgroups at up to 40 ppm*. Compact size with Trusted Platform Module (TPM) standard. ** Print release capability and managed print services (MPS) eligibility. Large easy-to-use touchscreen provides consistent performance across fleet. Print from anywhere with standard Wi-Fi and full mobile support.



Scalable solutions increase efficiency and savings

- ▶ Monochrome all-in-one with Trusted Platform Module (TPM) standard. **
- ▶ With the embedded solutions framework on the MX432adwe, you can add Lexmark or other supported solutions, including third-party print release with badge reader.
- ▶ Large easy-to-use touchscreen provides consistent performance across fleet.

The right fit for your business

- ▶ Compact size integrates seamlessly into tight spaces in your work environment.
- ▶ Provides security and solutions to meet the stringent requirements of different industries.
- ▶ Managed print services (MPS) capabilities make this all-in-one a perfect addition to your printer fleet.

Stay protected with enterprise-level security

- ▶ Lexmark printers and all-in-ones are designed to help protect your data, your device, and your network.
- ▶ Includes standard Trusted Platform Module** that stores encryption keys on separate hardware from the data, along with authentication and system integrity checks.
- ▶ Many banks, governments and schools trust Lexmark security over all others in the industry.

Easy to manage without burden on IT staff

- ▶ Sensors continuously monitor hundreds of data points that provide added benefits, like predictive service and automatic supplies replenishment, when connected to Lexmark Cloud Services.
- ▶ Lexmark Markvision Enterprise is a free device management solution that makes it easy to configure device settings, update security policies, and schedule firmware updates.

Focus on business instead of printers

- ▶ You can count on the high performance of the MX432 with fast print speeds up to 40 ppm* and single-pass two-sided scan speeds of 92 ipm.
- ▶ Print from anywhere with standard Wi-Fi and full mobile support.
- ▶ Steel frames provide durability and long-life reliability from the front office to the warehouse.

Working for the environment

Automatic two-sided printing is standard, along with built-in energy-saving modes that help support ratings of EPEAT® Silver and ENERGY STAR® certified.

* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

** The Trusted Platform Module (TPM) is not available in some countries.

Lexmark MX432adwe



- 1

Multifunction product with 10.9 cm touch screen
353.60 x 411.48 x 360.68 mm

150-Sheet output bin
Dimensions included as part of base model

100-Sheet multipurpose feeder
Dimensions included as part of base model

- 4

250-Sheet tray
Dimensions included as part of base model
- 5

550-Sheet Tray
107 x 370 x 378 mm
- Standard

Optional

P/N 29S8125	Hardware Lexmark MX432adwe
P/N 55B0XA0	Supplies Lexmark 55B0XA0 Extra High Yield Toner Cartridge
55B0ZA0	Lexmark 55B0ZA0 Photoconductor Unit
55B3000	Lexmark 55B3000 Return Programme Toner Cartridge
55B300E	Lexmark 55B300E Corporate Toner Cartridge
55B3H00	Lexmark 55B3H00 High Yield Return Programme Toner Cartridge
55B3H0E	Lexmark 55B3H0E High Yield Corporate Toner Cartridge
55B3X00	Lexmark 55B3X00 Extra High Yield Return Programme Toner Cartridge
55B3X0E	Lexmark 55B3X0E Extra High Yield Corporate Toner Cartridge
P/N 29S0600 29S0800	Paper Handling 550-Sheet Tray 550-Sheet Lockable Tray
P/N 57X9528	Memory Options Intelligent Storage Drive (ISD)
P/N 57X0225 57X0235	Application Solutions Desktop Contactless Reader Contactless Front Solutions Module (Primary Choice)
57X0300 57X0301	Contact Authentication Device Contactless Authentication Device
82S1203 82S1204	IPDS License Bar Code License
P/N 1021294 SPD0002	Connectivity USB (2 Meter) Cable Surge Protective Device, 220-240V
P/N 3073173 35S8502	Furniture Swivel Cabinet Adjustable Stand

Product Specifications		Lexmark MX432adwe
Printing		
Display	Lexmark e-Task 10.9 cm colour touch screen with audible feedback	
Print Speed	Up to: Black: 40 ppm ¹ (A4)	
Time to First Page	As fast as: Black: 5.9 seconds	
Print Resolution	Black: 1200 x 1200 dpi, 2400 IQ (2400 x 600 dpi), 300 x 300 dpi, 1200 IQ (1200 x 600 dpi), 600 x 600 dpi	
Memory	Standard: 2 GB / Maximum: 2 GB	
Hard Disk	Intelligent Storage Drive (optional)	
Recommended Monthly Page Volume	800 - 8,000 pages ²	
Maximum Monthly Duty Cycle	Up to: 80,000 pages per month ³	
Copying		
Copy Speed	Up to: Black: 39 cpm ¹ (A4)	
Time to First Copy	as fast as: Black: 5.9 seconds	
Scanning		
Scanner Type / ADF Scan	Flatbed scanner with automatic document feeder / DADF (single pass Duplex)	
A4/Ltr Duplex Scan Speed / Duplex Scan Speed (A4/Ltr	Up to: Black: 92/96 sides per minute / Colour: 40/42 sides per minute	
A4/Ltr Simplex Scan Speed / Scan Speed (A4/Ltr	Up to: Black: 46/48 sides per minute / Colour: 20/21 sides per minute	
ADF Paper Input Capacity	Up to: 50 pages 75 gsm bond	
Faxing		
Modem Speed	ITU T.30, V.34 Half-Duplex, 33.6 Kbps	
Supplies ⁴		
Laser Cartridge Yields	up to: 20,000 ⁵ -page Black Cartridge	
Imaging Unit Estimated Yield	Up to: 40,000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage	
Cartridge(s) Shipping with Product	3,000 ⁵ -page Black Return Program Toner Cartridge ⁵	
Paper Handling		
Included Paper Handling	100-Sheet Multipurpose Feeder, Integrated Duplex, 150-Sheet Output Bin, 250-Sheet Input	
Optional Paper Handling	550-Sheet Lockable Tray, 550-Sheet Tray	
Paper Input Capacity	Up to: Standard: 350 pages 75 gsm bond / Maximum: 900 pages 75 gsm bond	
Paper Output Capacity	Up to: Standard: 150 pages 75 gsm bond / Maximum: 150 pages 75 gsm bond	
Media Types Supported	Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Specialty Media Guide	
Media Sizes Supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Hagaki Card, Letter, B5 Envelope, Statement, C5 Envelope, Executive, DL Envelope, Folio, 10 Envelope	
General Information ⁶		
Standard Ports	Gigabit Ethernet (10/100/1000), USB Compatible with USB 2.0 Specification (Type B), Front USB 2.0 Specification Hi-Speed Certified port (Type A)	
Noise Level	Operating: 53 dBA (Print) / 58 dBA (Copy) / 56 dBA (Scan)	
Specified Operating Environment	Temperature: 10 to 32°C (50 to 90°F) / Altitude: 0 - 2896 metres / Humidity: 15 to 80% Relative Humidity	
Product Warranty	1-Year Onsite Service, Next Business Day	
Size / Weight	H x W x D: 353.60 x 411.48 x 360.68 mm / 13.61 kg	
ENERGY STAR Typical Electricity Consumption	TEC: 0.52 kilowatt-hours per week	

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average standard page yield value declared in accordance with ISO/IEC 19752. ⁶ Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

© 2022 Lexmark. All rights reserved.

Lexmark, Markvision and the Lexmark logo are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries and regions. Mopria®, the Mopria® Logo, and the Mopria Alliance™ word mark and logo are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.