



Lexmark CX635adwe

Exceptional performance, secure and sustainable



Lexmark CX635adwe

With exceptional performance and secure design, the CX635adwe Multifunction printer (copy/scan/print/fax) delivers enhanced productivity up to 40 ppm* on A4 paper and toner yields up to 20,000 pages mono**, and up to 11,700 pages colour**. Engineered for long life with environmental certifications and advanced power management, this efficient model has high sustainability. Fast time to first print, superior print quality and easy-to-use touch screen.

Secure by design

Lexmark expertise helps customers protect their data, their device and their network. Our security ecosystem is designed to overcome the most complex data challenges. And now we've added the Trusted Platform Module (TPM)***, which includes on-board authentication, system integrity checks, and cryptographic capabilities to create a unique digital system fingerprint. TPM meets stringent industry and US government security standards including Common Criteria and Federal Information Processing Standard (FIPS).

Proprietary technology

We own core technology across hardware, firmware, services, and solutions, creating seamless connections designed to reduce the risk of security gaps between your document, your device and your network. Our expertise is our customer's benefit.

Sustainability

With certifications in Energy Star®, Blue Angel, RoHS, EPEAT® Silver. Models are sustainable for today and beyond. Lexmark is an industry leader of recycled content with products using at least 35% PCR content and continual focus on improvement. This line is also engineered for Long Life and designed to last and reduce waste.

Intelligent Design

Every touch point is designed to withstand high usage while meeting accessibility standards. Steel frames support the device and provide durability to help ensure consistent long-

term performance. Products are designed for long service life with long-life components and are easily serviced with few tools.



Optimised productivity

Increase productivity with optimised performance. Print at up to 40 pages per minute* (A4) and capture information quickly with scan speeds of up to 49 images per minute (A4) for one-sided scanning, and up to 98 images per minute (A4) for two-sided scanning.

Manageability

These IoT-ready devices can be remotely managed, including setup, configuration, consumables management, and diagnostics. Wireless capability gives freedom of access and remote firmware updates make it easy to upgrade to the latest apps and security features. Our mobile printing app makes it easier to monitor and manage your print jobs from remote locations, all from the touch of your phone.

本製品は、FCC 規則および国際的な電磁気排出基準に準じた Class A 機器です。本製品は、電波障害を引き起こすことがあるため、住宅環境での使用を目的としていません。

* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

** Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information. In demonstration of circular economy principles, genuine Lexmark supplies with Unison™ Toner may contain components recovered from the Lexmark Cartridge Collection Programme (LCCP).

*** The Trusted Platform Module (TPM) is not available in some countries.

Lexmark CX635adwe



- 1 **Multifunction product with 17.8 cm touch screen**
491.4 x 479 x 475.1 mm
- 2 **200-Sheet output bin**
基本モデルに含まれる寸法
- 3 **Single sheet multipurpose feeder**
基本モデルに含まれる寸法
- 4 **250-Sheet tray**
基本モデルに含まれる寸法
- 5 **Duo Tray with 100-Sheet MPF**
132.1 x 424.2 x 416.6 mm

- 6 **550-Sheet Tray**
132.1 x 424.2 x 416.6 mm
- 7 **550-Sheet Tray**
132.1 x 424.2 x 416.6 mm
- 8 **Adjustable Stand**
521 x 653 x 625 mm
- 9 **Swivel Cabinet**
263 x 476 x 600 mm



P/N **ハードウェア**
50M7086 Lexmark CX635adwe

P/N **消耗品**
35S8500 ホチキスカートリッジ
75M0W00 Lexmark CS531, 632, 639, CX532, 635, C2335, XC2335 30K Waste Toner Bottle
75M0X10 Lexmark CS632, CX635 Black 20K Toner Cartridge
75M0X20 Lexmark CS632, CX635 Cyan 11.7K Toner Cartridge
75M0X30 Lexmark CS632, CX635 Magenta 11.7K Toner Cartridge
75M0X40 Lexmark CS632, CX635 Yellow 11.7K Toner Cartridge
75M0Z10 Lexmark CS531, 632, 639, CX532, 635 Black 150K Imaging Kit
75M0Z50 Lexmark CS531, 632, 639, CX532, 635 4-Colour 150K Imaging Kit
75M0ZK0 Lexmark CS531, 632, 639, CX532, 635, C2335, XC2335 Black Return Programme 150K Imaging Kit
75M0ZV0 Lexmark CS531, 632, 639, CX532, 635, C2335, XC2335 4-Colour Return Programme 150K Imaging Kit
75M30C0 Lexmark CS531, 632, CX532, 635 Cyan Return Programme 2K Toner Cartridge
75M30K0 Lexmark CS531, 632, CX532, 635 Black Return Programme 3K Toner Cartridge
75M30M0 Lexmark CS531, 632, CX532, 635 Magenta Return Programme 2K Toner Cartridge
75M30Y0 Lexmark CS531, 632, CX532, 635 Yellow Return Programme 2K Toner Cartridge
75M3XC0 Lexmark CS632, CX635 Cyan Return Program 11.7K Toner Cartridge
75M3XK0 Lexmark CS632, CX635 Black Return Program 20K Toner Cartridge
75M3XM0 Lexmark CS632, CX635 Magenta Return Program 11.7K Toner Cartridge
75M3XY0 Lexmark CS632, CX635 Yellow Return Program 11.7K Toner Cartridge

P/N **用紙処理**
50M7550 550 枚給紙トレイ
50M7650 650 枚 2 段トレイ

P/N **Memory Options**
57X9528 インテリジェントストレージドライブ (ISD)

P/N **Application Solutions**
57X0300 Contact Authentication Device
57X0301 Contactless Authentication Device
82S1203 IPDS License
82S1204 Bar Code License

P/N **接続**
1021294 USBケーブル(RoHS) 2m
57X7040 英語キーボードキット

P/N **Furniture**
3073173 スイベル (回転式) キャビネット
40C2300 Adjustable Stand

製品仕様

Lexmark CX635adwe

印刷	
ディスプレイ	Lexmark e-Task 7インチ (17.8 cm) カラータッチスクリーン
印刷速度 (A4 / 印刷速度 (A4、/カラー))	ブラック) : 40 枚/分 ¹ / 上限: 40 枚/分 ¹
ファーストプリント時間 (モノクロ) / ファーストプリント時間 (カラー)	6.3 秒 / 6.3 秒
印刷解像度 (モノクロ) / 印刷解像度	1200 x 1200 dpi, 4800 Colour Quality / カラー: 4800 Colour Quality, 1200 x 1200 dpi
メモリー	標準: 2048 MB / 最大: 2048 MB
ハードディスク	インテリジェントストレージドライブが利用可能; 磁気ハードディスクが利用可能
推奨印刷ページ数/月	1,500 - 10,000 ページ ²
最大負荷サイクル/月: 最高	125,000 ページ/月 ³
コピー	
コピー速度 (A4、ブラック) / コピー速度 (A4、カラー)	最速: 39.5 cpm(コピー枚数/分) ¹ / 最速: 39.5 cpm(コピー枚数/分) ¹
ファーストコピー時間 (モノクロ) / Time to First Copy	as fast as: 6.7 秒 / Colour: 6.6 秒
スキャン	
ADF Scan	DADF (シングルパスデュプレックス)
A4/レター 両面スキャン速度 (ブラック) / A4/レター 両面スキャン速度 (カラー)	最速: 98 / 104 面/分 / 最速: 80 / 84 面/分
A4/レター シンプレックス・スキャン速度 (ブラック) / A4/レター シンプレックス・スキャン速度 (カラー)	最速: 49 / 52 面/分 / 最速: 40 / 42 面/分
コピー/FAX/スキャン時の自動送り給紙容量	上限: 100 ページ (使用用紙: 75 g/m ²)
FAX	
モデム速度	ITU T.30, V.34 Half-Duplex, 33.6 Kbps
消耗品 ⁴	
レーザーカートリッジ印刷可能数 (上限)	20,000 ⁵ 枚 ブラックトナーカートリッジ / 11,700 ⁵ 枚 カラー (CMY) トナーカートリッジ
カートリッジを製品に同梱	3,000 ⁵ ページのブラックスターターリターンプログラムトナーカートリッジ ⁵ , 2,000 ⁵ 枚カラー (CMY) 返却プログラム トナーカートリッジ ⁵
用紙処理	
用紙送り標準	200-Sheet Output Bin, 統合デュプレックス, Single sheet multipurpose feeder, 250-Sheet Tray
用紙送りオプション	650枚デュオトレイ, 550枚トレイ
給紙容量	上限: 標準: 251 ページ (使用用紙: 75 g/m ²) / 最大: 2001 ページ (使用用紙: 75 g/m ²)
排紙容量	上限: 標準: 200 ページ (使用用紙: 75 g/m ²) / 最大: 200 ページ (使用用紙: 75 g/m ²)
??用紙種類	ビニール ラベル, 紙ラベル, カードストック, 普通紙, 封筒, Refer to the Paper & Specialty Media Guide
??用紙サイズ	A6, Oficio, 7 3/4エンベロープ, 9エンベロープ, JIS-B5, A4, 法的, A5, 葉書, 文字, B5封筒, ステートメント, C5封筒, エグゼクティブ, ユニバーサル, DLエンベロープ, フォリオ, 10エンベロープ
全般 ⁶	
インターフェース	ギガビットイーサネット (10/100/1000), フロントUSB 2.0仕?ハイスピード認証ポート (タイプA), 高速認証?背面ポート (USB 2.0 仕?) (タイプA), 802.11a/b/g/n/ac + Apple iBeacon, USB 2.0仕?Hi-Speed認定 (タイプB)
稼働音 (印刷) 動作時 / 稼働音 (コピー) 動作時 / 稼働音 (スキャン) 動作時	53 dBA(デシベル) / 52 dBA(デシベル) / 44 dBA(デシベル)
所定稼働環境	Altitude: 0 - 2900 metres / 湿度: 15 ~ 80% 相?湿度 / Temperature: 10 to 32.2°C (50 to 90°F)
製品保証	1-Year Onsite Service, Next Business Day
外形寸法 (mm : 高 x 幅 x 奥行) / 本体重量	491.4 x 479 x 475.1 mm / 27.05 kg
ENERGY STAR典型的な電力消費量 (TEC)	0.57 kilowatt-hours per week

記載されているすべての情報は、予告なく変更される場合があります。Lexmark は情報のいかなる誤りあるいは欠落についても法的責任を負わないものとします。

¹ ISO / IEC 24734およびISO / IEC 24735 (ESAT) に従って測定した印刷速度およびコピー速度。詳細については、www.lexmark.com/ISOspeedsを参照してください。 ² 「月間推?ページ数」は、顧客が?月デバイスで印刷する予定の平均ページ数に基づいてLexmarkの製品提供を評価するのに役立つページの範?です。Lexmarkでは、最適なデバイスパフォーマンスを得るためには、サプライ品の交換間隔、用紙の取り込み間隔、速度、および一般的な顧客の使用状況などの要素に基づいて、月あたりのページ数を指定範?内に収めることを推?します。 ³ 「最大月間デューティサイクル」は、マルチシフト操作を使用して1か月にデバイスが提供できる最大ページ数として定義されます。このメトリックは、他のLexmarkプリンタとMFPに関する堅牢性の比較を提供します。 ⁴ 特定の地域での使用のために設計された交換用カートリッジを備えた製品機能。詳細は、www.lexmark.com/regionsを参照してください。 ⁵ ISO/IEC 19798に基づき、標準的な印刷内容で連続印刷を行った場合の、ブラックカートリッジまたはコンボジット CMY カートリッジでの平均印刷枚数です。 ⁶ プリンタは、特定のライセンス/契約条件に従って販売されます。詳細については、www.lexmark.com/printerlicenseを参照してください。

本製品は、FCC 規則および国際的な電磁気排出基準に準?した Class A 機器です。本製品は、電波障害を引き起こすことがあるため、住宅環境での使用を目的としていません。

© 2023 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).

