



Lexmark CX735adse

Security and performance



Lexmark CX735adse

The Lexmark CX735adse is designed for performance, security, and ease of use for mid-to-large workgroups at speeds up to 50 ppm*. Single-pass two-sided scanning, ultrasonic multifeed detection, and a 25 cm tablet-like touchscreen make handling your print jobs easy. Toner cartridges that yield up to 28,000/16,200 black/colour pages** keep you going.

Made to last. Easy to upgrade.

- ▶ With durable steel frames, long-life components and high-yield cartridges, printers are intentionally engineered to last seven years or more.
- ▶ Long-lasting Unison™ Toner delivers consistently outstanding print quality, reduces internal wear on long-life components, and protects the print system.
- ▶ Easily upgradeable to the latest apps and security features.



Faster performance and ease of use

- ▶ Scanning is fast and accurate thanks to the single-pass two-sided automatic document feeder with ultrasonic multifeed detection.
- ▶ The large, tablet-like, button-free touchscreen will help you intuitively complete every task, from the basic to the complex.
- ▶ An Intelligent Storage Drive (ISD) is standard on this model, providing faster startup, faster data retrieval and more reliability.

Make a statement with professional colour

Enjoy the benefits of vibrant, professional-quality output allowing you to do more colour printing in-house - saves time and money. Match corporate colours on marketing collateral and brand-sensitive text and graphics with PANTONE® calibration and Lexmark Named Colour Replacement.

Secure by design

- ▶ Lexmark security features help keep your information safe - in the document, on the device, over the network and at all points in between.
- ▶ Always improving security, we now include a standard Trusted Platform Module***, which delivers authentication, system integrity checks, and cryptographic capabilities to create a unique digital system fingerprint.

Sustainability matters

- ▶ Designed for the circular economy.
- ▶ Automatic two-sided printing is standard, along with built-in energy-saving modes that help support ratings of EPEAT® Silver and ENERGY STAR® certified.
- ▶ The award-winning Lexmark Cartridge Collection Programme (LCCP) and Lexmark Equipment Collection Programme (LECP) minimise waste and support recycling (availability varies by country).

Power up with IoT

- ▶ Sophisticated, IoT-enabled printers are loaded with sensors that continuously monitor hundreds of data points.
- ▶ When you connect your device to Lexmark Cloud Services, you can optimise performance and uptime with additional features like predictive service and automatic supplies replenishment.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

** Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See www.lexmark.com/yields for more information. In demonstration of circular economy principles, genuine Lexmark supplies with Unison™ Toner may contain components recovered from the Lexmark Cartridge Collection Programme (LCCP).

*** The Trusted Platform Module (TPM) is not available in some countries.

Lexmark CX735adse



- 1 Multifunction product with 25 cm touch screen
621 x 479 x 533 mm
- 2 550-Sheet tray with 100-sheet multipurpose feeder
Dimensions included as part of base model
- 3 550-Sheet Drawer (incl. Tray)
119 x 463 x 483 mm
- 4 550-Sheet Drawer (incl. Tray)
119 x 463 x 483 mm
- 5 550-Sheet Drawer (incl. Tray)
119 x 463 x 483 mm

- 6 550-Sheet Drawer (incl. Tray)
119 x 463 x 483 mm
- 7 Printer Stand (adjustable height)
521 x 653 x 625 mm
- 8 Convenience Stapler HV
82 x 109 x 121 mm

-  Standard
-  Optional

P/N
47C9620 **Hardware**
Lexmark CX735adse

P/N
71C0W00 **Supplies**
Lexmark CS/CX730, 735, C/XC4342, C4352 170K Waste Container

71C0Z10 Lexmark CS/CX730, 735, C/XC4342, C/XC4352 Black 150K Imaging Unit

71C0Z50 Lexmark CS/CX730, 735, C/XC4342, C/XC4352 Colour (CMY) 150K Imaging Unit

71C20C0 Lexmark CS/CX730, 735 Cyan Return Programme 5K Toner Cartridge

71C20K0 Lexmark CS/CX730, 735 Black Return Programme 5K Toner Cartridge

71C20M0 Lexmark CS/CX730, 735 Magenta Return Programme 5K Toner Cartridge

71C20Y0 Lexmark CS/CX730, 735 Yellow Return Programme 5K Toner Cartridge

81C0X10 Lexmark CX735 Black 28K Toner Cartridge

81C0X20 Lexmark CX735 Cyan 16.2K Toner Cartridge

81C0X30 Lexmark CX735 Magenta 16.2K Toner Cartridge

81C0X40 Lexmark CX735 Yellow 16.2K Toner Cartridge

81C2XC0 Lexmark CX735 Cyan Return Programme 16.2K Toner Cartridge

81C2XK0 Lexmark CX735 Black Return Programme 28K Toner Cartridge

81C2XM0 Lexmark CX735 Magenta Return Programme 16.2K Toner Cartridge

81C2XY0 Lexmark CX735 Yellow Return Programme 16.2K Toner Cartridge

P/N
40C2100 **Paper Handling**
CS72x, CX725 550-Sheet Drawer (incl. Tray)

47C4590 Convenience Stapler

P/N
27X0400 **Memory Options**
500+ GB Hard Disk

P/N
57X0300 **Application Solutions**
57X0301 Contact Authentication Device
Contactless Authentication Device

82S1203 IPDS License

82S1204 Bar Code License

P/N
1021294 **Connectivity**
27X0823 USB Cable (2 meter)
MarkNet N8370 Wireless for CS720, CS725, CX725

27X6410 Lexmark MarkNet N8372 802.11 a/b/g/n/ac Wireless Print Server

SPD0002 Surge protective device

P/N
40C2300 **Furniture**
CS72x, CX725 Printer Stand (adjustable height)

Supports up to four optional 550-sheet trays.

All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at http://www.lexmark.com/publications/furniture_safety/

Product Specifications		Lexmark CX735adse
Printing		
Display	Lexmark e-Task 10.1-inch (25.6 cm) colour touch screen	
Print speed	up to: black: 50 ppm ¹ (A4) / colour: 50 ppm ¹ (A4)	
Time to first page	as fast as: black: 5.6 seconds / colour: 6.1 seconds	
Print resolution	black: 1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi) / colour: 4800 CQ (2400 x 600 dpi), 1200 x 1200 dpi	
Memory	standard: 2048 MB / maximum: 2048 MB	
Hard Disk	Intelligent Storage Drive included; Magnetic Hard Disk (optional)	
Recommended monthly page volume	2000 - 20000 pages ²	
Maximum monthly duty cycle	up to: 150000 pages per month ³	
Copying		
Copy speed	up to: black: 50 cpm ¹ (A4) / colour: 50 cpm ¹ (A4)	
Time to first copy	as fast as: black: 5.7 seconds / colour: 6.3 seconds	
Scanning		
Scanner type / ADF scan	Flatbed scanner with ADF / DADF (single pass Duplex)	
Duplex scan speed	up to: black: 98 / 104 spm (A4) / colour: 98 / 104 spm (A4)	
Simplex scan speed	up to: black: 49 / 52 spm (A4) / colour: 49 / 52 spm (A4)	
ADF paper input capacity	up to: 100 pages	
Faxing		
Modem speed	ITU T.30, V.34 Half-Duplex, 33.6 kbps	
Supplies ⁴		
Cartridge yields	up to: 28,000 ⁵ -page Black Extra High Yield Cartridge / up to: 16,200 ⁵ -page Colour (CMY) Extra High Yield Cartridges	
Imaging unit yield	up to: 150000 pages, based on average 3 pages per print job and 5% coverage ⁶	
Cartridge(s) shipped with product	5,000 ⁵ -page Black and Colour (CMYK) Return Programme Toner Cartridges ⁵	
Paper Handling		
Standard paper handling	100-Sheet Multipurpose Feeder, Integrated Duplex, 300-sheet output bin, 550-Sheet Input	
Optional paper handling	550-Sheet Tray	
Paper input capacity	up to: standard: 650 pages / maximum: 2850 pages	
Paper output capacity	up to: standard: 300 pages / maximum: 300 pages	
Media types supported	Vinyl Labels, Banner Paper, Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Specialty Media Guide	
Media sizes supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Letter, B5 Envelope, Statement, C5 Envelope, Executive, Universal, DL Envelope, Folio, 10 Envelope	
General Information ⁷		
Standard connectivity	Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear Hi-Speed USB port (compatible with USB 2.0 specification, type A), USB 2.0 Specification Hi-Speed Certified (Type B), One Internal Card Slot	
Optional network ports	Internal MarkNet N8370 802.11b/g/n/a Wireless, NFC	
Noise Level	Operating: 53 dBA (Print) / 56 dBA (Copy) / 51 dBA (Scan)	
Specified operating environment	Humidity: 8 to 80% Relative Humidity / Temperature: 10 to 32°C (50 to 90°F) / Altitude: 0 - 2896 Metres (9,500 Feet)	
Product guarantee	1-Year Onsite Service, Next Business Day	
Size / Weight	HxWxD: 621 x 479 x 533 mm / 39.5 kg	
Energy Star Typical Electricity Consumption	TEC: 0.69 kWh per week	

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

¹ Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798. ⁶ Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. ⁷ Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2022 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries and regions. MOPRIA®, the Mopria® Logo, and the Mopria Alliance™ word mark and logo are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT is a trademark of the Green Electronics Council in the United States and other countries. PANTONE® is the property of Pantone LLC. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).