



Lexmark™

## Lexmark CX944adtse

Large-format versatility and performance to round out your fleet



## Lexmark CX944adtse

The Lexmark CX944adtse large-format colour multifunction is designed for security, versatility and performance for large workgroups at speeds up to 65 pages per minute\*. Loaded with standard features, this model includes a 25 cm touchscreen, single-pass two-sided scanning with ultrasonic multi-feed detection, and Optical Character Recognition (OCR).



### Productivity is in the box

- Maximise productivity with workflow solutions like Scan Centre for simple document routing and single-pass two-sided scanning with ultrasonic multi-feed detection for fast and reliable scanning.
- The Intelligent Storage Drive (ISD) provides solid state storage with activation-ready preloaded add-on solutions.
- A large, button-free touchscreen helps users intuitively complete every task, from the basic to the complex.

### Flexible input and output

- Print and scan large-format paper sizes slightly larger than SRA3+ (up to 329 x 483 mm).
- Standard input capacity is 2,180 pages; optional trays expand paper input capacity up to 4,180 pages.
- Several finishing options are available: staple hole punch finisher, booklet finisher or Lexmark's first trifold/Z-fold finisher.

### Professional colour for large-format printing

- Enjoy vibrant colour with standard advanced features like PANTONE® calibration and Lexmark Named Colour

Replacement for consistent branding and professional appearance.

- Replacement cartridges yield up to 45,000/22,000 black/colour pages\*\*.

### Secure by design

- Lexmark security features help keep your information safe - in the document, on the device, over the network and at all points in between.
- Always improving security, we now include a standard Trusted Platform Module\*\*\*, which delivers authentication, system integrity checks, and cryptographic capabilities to create a unique digital system fingerprint.
- A proximity sensor wakes up the device when someone is nearby and automatically logs off when no one is nearby.

### Sustainability matters

- CX944adtse is designed for the circular economy.
- Automatic two-sided printing is standard, along with built-in energy-saving modes that help support ratings of EPEAT® Silver and ENERGY STAR® certified.
- The award-winning Lexmark Cartridge Collection Programme (LCCP) and Lexmark Equipment Collection Programme (LECP) minimise waste and support recycling (availability varies by country).

### Power up with IoT

- Our sophisticated, IoT-enabled printers are loaded with sensors that continuously monitor hundreds of data points.
- When you connect your device to Lexmark Cloud Services, you can optimise performance and uptime with additional features like predictive service and automatic supplies replenishment.


This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

\* Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

\*\* Average continuous black or continuous composite colour (CMY) declared yield in one-sided (simplex) mode up to this number of pages in accordance with ISO/IEC 19798. Actual yield will vary considerably based upon many factors. See [www.lexmark.com/yields](http://www.lexmark.com/yields) for more information.

\*\*\* The Trusted Platform Module (TPM) is not available in some countries.

# Lexmark CX944adtse



1 Multifunction product with 25 cm touch screen  
1141 x 620 x 754 mm

2 100-Sheet multipurpose feeder  
Dimensions included as part of base model

3 2 x 520-Sheet tray  
Dimensions included as part of base model

4 2 x 520-Sheet tray with casters  
Dimensions included as part of base model

5 400-Sheet output bin  
Dimensions included as part of base model

6 2,000-Sheet Tandem Tray with Casters  
305.2 x 668.5 720 mm

7 Caster Spacer  
305 x 669 x 720 mm

8 Envelope Tray  
89.9 x 619.9 x 565.5 mm

9 2,000-Sheet Tray (sidecar)  
491 x 751 x 526 mm

10 Dual Catch Bin  
125 x 474 x 380 mm

11 Tri-Fold/Z-Fold Booklet Finisher  
991 x 232 x 726 mm

12 Booklet Staple (2/3) Hole Punch Finisher  
1056 x 790 x 589 mm

13 Staple (2/3) Hole Punch Finisher  
983 x 962 x 653 mm

14 Work Table  
82 x 303 x 528 mm

 Standard  
 Optional

<b>P/N</b>	<b>Hardware</b> 32D0470
<b>P/N</b>	<b>Supplies</b> 73DOP00
73D0Q00	Lexmark CS943, CX942, 943, 944, XC9445, 55, 65 Black 165K Photoconductor
73D0W00	Lexmark CS943, CX942, 943, 944, XC9445, 55, 65 3-Pack 165K Photoconductor Kit
83D0HC0	Lexmark CS943, CX942, 943, 944, XC9445, 55, 65 35K Waste Container
83D0HKO	Lexmark CX942, 943, 944 Cyan 22K Toner Cartridge
83D0HMO	Lexmark CX942, 943, 944 Black 45K Toner Cartridge
83D0HY0	Lexmark CX942, 943, 944 Magenta 22K Toner Cartridge
	Lexmark CX942, 943, 944 Yellow 22K Toner Cartridge
<b>P/N</b>	<b>Paper Handling</b>
32D0810	Caster Spacer
32D0811	2 x 520-Sheet Tray with Casters
32D0812	2,000-Sheet Tandem Tray with Casters
32D0813	Envelope Tray
32D0816	2,000-Sheet Tray (sidecar)
32D0819	Dual Catch Bin
32D0823	Staple (2/3) Hole Punch Finisher
32D0824	Staple (2/4) Hole Punch Finisher
32D0825	Booklet Staple (2/3) Hole Punch Finisher
32D0826	Booklet Staple (2/4) Hole Punch Finisher
32D0831	Tri-Fold/Z-Fold Booklet Finisher
<b>P/N</b>	<b>Memory Options</b> 27X0400
	500+ GB Hard Disk
<b>P/N</b>	<b>Application Solutions</b>
57X0300	Contact Authentication Device
57X0301	Contactless Authentication Device
82S1203	IPDS License
82S1204	Bar Code License
<b>P/N</b>	<b>Connectivity</b>
1021294	USB Cable (2 meter)
14F0100	RS-232C Serial Interface Card
27X0142	Lexmark MarkNet N8230 Fibre Ethernet Print Server
27X6410	Lexmark MarkNet N8372 802.11 a/b/g/n/ac Wireless Print Server
57X7040	English Keyboard Kit
SPD0002	Surge protective device
<b>P/N</b>	<b>Furniture</b> 32D0809
	CX94x Work Table

You can install one of the following: the Dual Catch Bin or the Staple Hole Punch Finisher or the Booklet Staple Hole Punch Finisher.

To install the Tri-Fold/Z-Fold Finisher, you must also install the Booklet Staple Hole Punch Finisher.

To install the Staple Hole Punch Finisher or Booklet Staple Hole Punch Finisher, you must also install the 2x520-Sheet Tray with Casters, the 2,000-Sheet Tandem Tray with Casters, or the Caster Spacer.

To install the 2,000-Sheet Tray (sidecar), you must also install the 2x520-Sheet Tray with Casters or the 2,000-Sheet Tandem Tray with Casters. It will not work with the Caster Spacer.

To install the Envelope Tray, you must remove Tray 1 and replace it with the Envelope Tray.

Product Specifications		Lexmark CX944adte
<b>Printing</b>		
Display	Lexmark e-Task 10.1-inch (25.6 cm) colour touch screen	
Print speed	up to: black: 65 ppm <sup>1</sup> (A4) / colour: 65 ppm <sup>1</sup> (A4)	
Time to first page	as fast as: black: 4.7 seconds / colour: 5.2 seconds	
Print resolution	black: 1200 x 1200 dpi, 2400 IQ (2400 x 600 dpi) / colour: 1200 x 1200 dpi, 2400 IQ (2400 x 600 dpi)	
Memory	standard: 4096 MB / maximum: 4096 MB	
Hard Disk	Intelligent Storage Drive included; Magnetic Hard Disk (optional)	
Recommended monthly page volume	7,000 - 50,000 pages <sup>2</sup>	
Maximum monthly duty cycle	up to: 340 000 pages per month <sup>3</sup>	
<b>Copying</b>		
Copy speed	up to: black: 65 cpm <sup>1</sup> (A4) / colour: 65 cpm <sup>1</sup> (A4)	
Time to first copy	as fast as: black: 6.6 seconds / colour: 6.3 seconds	
<b>Scanning</b>		
Scanner type / ADF scan	Flatbed scanner with automatic document feeder / DADF (single pass Duplex)	
Duplex scan speed	up to: black: 146/144 spm (A4) / colour: 146/144 spm (A4)	
Simplex scan speed	up to: black: 73.5/72 spm (A4) / colour: 73.5/72 spm (A4)	
ADF paper input capacity	up to: 130 pages	
<b>Faxing</b>		
Modem speed	ITU T.30, V.34 Half-Duplex, 33.6 kbps	
<b>Supplies<sup>4</sup></b>		
Cartridge yields	up to: 22,000 <sup>5</sup> -page colour (CMY) cartridges / up to: 45,000 <sup>5</sup> -page Black Cartridge	
Cartridge(s) shipped with product	18,500 <sup>5</sup> -page black toner cartridge <sup>5</sup> , 11,500 <sup>5</sup> -page Colour (CMY) Toner Cartridges <sup>5</sup>	
<b>Paper Handling</b>		
Standard paper handling	100-Sheet Multipurpose Feeder, 2 x 520-Sheet Tray, 400-Sheet Output Bin, 2 x 520-Sheet Tray/Caster	
Optional paper handling	Booklet staple hole punch finisher, Inline Stapler, Dual Catch Bin, Envelope Tray, Caster spacer, Tri-fold/Z-fold booklet finisher, Staple Punch Finisher, Work table, 2000-Sheet Tray, 2000-Sheet Tandem Tray/Caster	
Paper input capacity	up to: standard: 2180 pages / maximum: 4180 pages	
Paper output capacity	up to: standard: 400 pages / maximum: 2000 pages	
Media types supported	Labels, Card Stock, Plain Paper, Envelopes, Glossy paper, Refer to the Paper & Specialty Media Guide	
Media sizes supported	A6, Oficio, 7 3/4 Envelope, JIS-B4, 9 Envelope, B5, JIS-B5, A3, Ledger, A4, Legal, SRA3, A5, Hagaki card, Letter, B5 Envelope, C4 Envelope, Statement, C5 Envelope, Executive, DL Envelope, Folio, 10 Envelope	
<b>General Information</b>		
Standard connectivity	Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear USB 2.0 Hi-Speed certified port (type A), USB 2.0 Specification Hi-Speed Certified (Type B), One Internal Card Slot	
Optional network ports / Optional local ports	MarkNet N8230 Fiber Ethernet Print Server, Marknet N8372 WiFi Option / Internal RS-232C serial	
Noise Level	Operating: 52 dBA (Print) / 57 dBA (Copy) / 56 dBA (Scan)	
Specified operating environment	Humidity: 8 to 80% Relative Humidity / Altitude: 0 - 2500 Metres (8,200 Feet) / Temperature: 10 to 32°C (50 to 90°F)	
Product guarantee	1-Year Onsite Repair, Next Business Day	
Size / Weight	HxWxD: 1141 x 620 x 754 mm / 115.5 kg	
Energy Star Typical Electricity Consumption	TEC: 1 kWh per week	

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

<sup>1</sup> Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).

<sup>2</sup> "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>3</sup> "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>4</sup> Product functions only with replacement cartridges designed for use in a specific geographical region. See [www.lexmark.com/regions](http://www.lexmark.com/regions) for more details. <sup>5</sup> Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.

This is a Class A device according to international electromagnetic emissions standards (i.e. FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

© 2022 Lexmark. All rights reserved.

Lexmark and the Lexmark logo are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries and regions. MOPRIA<sup>®</sup>, the Mopria<sup>®</sup> Logo, and the Mopria Alliance<sup>™</sup> word mark and logo are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT is a trademark of the Green Electronics Council in the United States and other countries. PANTONE<sup>®</sup> is the property of Pantone LLC. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>).



[lexmark.be](http://lexmark.be)