



Lexmark MX432adwe

Scalable solutions. Enterprise-level security.













Lexmark MX432adwe

The Lexmark MX432adwe monochrome all-in-one brings scalable solution support and enterprise-level security to small workgroups at up to 40 ppm*. Compact size with Trusted Platform Module (TPM) standard. ** Print release capability and managed print services (MPS) eligibility. Large easy-to-use touchscreen provides consistent performance across fleet. Print from anywhere with standard Wi-Fi and full mobile support.



Scalable solutions increase efficiency and savings

- Monochrome all-in-one with Trusted Platform Module (TPM) standard. **
- With the embedded solutions framework on the MX432adwe, you can add Lexmark or other supported solutions, including third-party print release with badge reader.
- Large easy-to-use touchscreen provides consistent performance across fleet.

The right fit for your business

- Compact size integrates seamlessly into tight spaces in your work environment.
- Provides security and solutions to meet the stringent requirements of different industries.
- Managed print services (MPS) capabilities make this all-inone a perfect addition to your printer fleet.

Stay protected with enterprise-level security

- Lexmark printers and all-in-ones are designed to help protect your data, your device, and your network.
- Includes standard Trusted Platform Module** that stores encryption keys on separate hardware from the data, along with authentication and system integrity checks.
- Lexmark's expertise as a leader in document and device security is trusted industry-wide.

Easy to manage without burden on IT staff

- Sensors continuously monitor hundreds of data points that provide added benefits, like predictive service and automatic supplies replenishment, when connected to Lexmark Cloud Services.
- Lexmark Markvision Enterprise is a free device management solution that makes it easy to configure device settings, update security policies, and schedule firmware updates.

Focus on business instead of printers

- You can count on the high performance of the MX432 with fast print speeds up to 40 ppm* and single-pass two-sided scan speeds of 92 ipm.
- Print from anywhere with standard Wi-Fi and full mobile support.
- Steel frames provide durability and long-life reliability from the front office to the warehouse.

Working for the environment

- Automatic two-sided printing is standard, along with builtin energy-saving modes that help support ratings of EPEAT® Silver and ENERGY STAR® certified.
- Keep toner cartridges out of landfills with the Lexmark Cartridge Collection Programme (LCCP) that supports reuse and recycling (availability varies by country).

^{*} Print speeds measured in accordance with ISO/IEC 24734 (ESAT). For more information see: www.lexmark.com/ISOspeeds.

^{**} The Trusted Platform Module (TPM) is not available in some countries.

Lexmark MX432adwe



P/N Hardware 29\$8115 Lexmark MX432adwe P/N Supplies Lexmark 55B0XA0 Extra High 55B0XA0 Yield Toner Cartridge Lexmark 55B0ZA0 55BOZAO Photoconductor Unit Lexmark 55B5000 Return 55B5000 Program Toner Cartridge 55B500E Lexmark 55B500E Corporate Toner Cartridge Lexmark 55B5H00 High Yield 55B5H00 Return Program Toner Cartridge Lexmark 55B5H0E High Yield 55B5H0E Corporate Toner Cartridge Lexmark 55B5X00 Extra High 55B5X00 Yield Return Program Toner Cartridge 55B5X0E Lexmark 55B5X0E Extra High Yield Corporate Toner Cartridge P/N **Paper Handling** 550-Sheet Tray 29S0600 29S0800 550-Sheet Lockable Tray P/N **Memory Options** 57X9528 Intelligent Storage Drive (ISD) P/N **Application Solutions** 57X0225 Desktop Contactless Reader 57X0235 **Contactless Front Solutions** Module (Primary Choice) 57X0300 Contact Authentication Device 57X0301 Contactless Authentication Device IPDS License 82S1203 82S1204 Bar Code License P/N Connectivity SPD0002 Surge Protective Device, 220-240V P/N **Furniture** 35\$8502 Adjustable Stand

- 1 Multifunction product with 10.9 cm touch screen 353.60 x 411.48 x 360.68 mm
- 2 150-Sheet output bin
 Dimensions included as part of base model
- 3 100-Sheet multipurpose feeder
 Dimensions included as part of base model
- 4 250-Sheet tray
 Dimensions included as part of base model
- 5 **550-Sheet Tray** 107 x 370 x 378 mm



Standard



Optional

Product Specifications	Lexmark MX432adwe
Printing	
Display	Lexmark e-Task 10.9 cm (4.3-inch) colour touch screen
Print Speed	Up to: Black: 40 ppm ¹ (A4)
Time to First Page	As fast as: Black: 5.9 seconds
Print Resolution	Black: 1200 x 1200 dpi, 2400 lQ (2400 x 600 dpi), 300 x 300 dpi, 1200 lQ (1200 x 600 dpi), 600 x 600 dpi
Memory	Standard: 2 GB / Maximum: 2 GB
Hard Disk	Intelligent Storage Drive (optional)
Recommended Monthly Page Volume	800 - 8,000 pages ²
Maximum Monthly Duty Cycle	Up to: 80,000 pages per month ³
Copying	
Copy Speed	Up to: Black: 39 cpm ¹ (A4)
Time to First Copy	as fast as: Black: 5.9 seconds
Scanning	
Scanner Type / ADF Scan	Flatbed scanner with automatic document feeder / DADF (single pass Duplex)
A4/Ltr Duplex Scan Speed	Up to: Black: 92/96 Sides per minute / Colour: 40/42 Sides per minute
A4/Ltr Simplex Scan Speed	Up to: Black: 46/48 Sides per minute / Colour: 20/21 Sides per minute
ADF Paper Input Capacity	Up to: 50 pages 75 gsm bond
Faxing	
Modem Speed	ITU T.30, V.34 Half-Duplex, 33.6 Kbps
Supplies ⁴	
Laser Cartridge Yields	up to: 20,000 ⁵ -page Black Cartridge
Imaging Unit Estimated Yield	Up to: 40,000 pages, based on 3 average letter/A4-size pages per print job and \sim 5% coverage
Cartridge(s) Shipping with Product	3,000 ⁵ -page Black Return Programme Toner Cartridge ⁵
Paper Handling	
Included Paper Handling	100-Sheet Multipurpose Feeder, Integrated Duplex, 150-Sheet Output Bin, 250-Sheet Input
Optional Paper Handling	550-Sheet Lockable Tray, 550-Sheet Tray
Paper Input Capacity	Up to: Standard: 350 pages 75 gsm bond / Maximum: 900 pages 75 gsm bond
Paper Output Capacity	Up to: Standard: 150 pages 75 gsm bond / Maximum: 150 pages 75 gsm bond
Media Types Supported	Paper Labels, Card Stock, Plain Paper, Envelopes, Refer to the Paper & Specialty Media Guide
Media Sizes Supported	A6, Oficio, 7 3/4 Envelope, 9 Envelope, JIS-B5, A4, Legal, A5, Hagaki Card, Letter, B5 Envelope, Statement, C5 Envelope, Executive, DL Envelope, Folio, 10 Envelope
General Information ⁶	
Standard Ports	Gigabit Ethernet (10/100/1000), USB Compatible with USB 2.0 Specification (Type B), Front USB 2.0 Specification Hi-Speed Certified port (Type A)
Noise Level	Operating: 53 dBA (Print) / 58 dBA (Copy) / 56 dBA (Scan)
Specified Operating Environment	Temperature: 10 to 32°C (50 to 90°F) / Altitude: 0 - 2896 Metres (9,500 Feet) / Humidity: 15 to 80% Relative Humidity
Product Guarantee	1-Year Onsite Service, Next Business Day
Size / Weight	H x W x D: 353.60 x 411.48 x 360.68 mm / 13.61 kg
ENERGY STAR Typical Electricity Consumption	TEC: 0.52 kilowatt-hours per week

All information is subject to change without notice. Lexmark is not liable for any errors or omissions.

1 Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

© 2022 Lexmark. All rights reserved.

Lexmark, Markvision and the Lexmark logo are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries and regions. Mopria® Logo, and the Mopria Alliance™ word mark and logo are registered and/or unregistered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.



² "Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. ³ "Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. ⁴ Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details. ⁵ Average standard page yield value declared in accordance with ISO/IEC 19752. ⁶ Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.