

## B3340 Starter Toner Cartridge

Printer: B3340dw

Declaration of Yield: 

<b>Average Cartridge Yield</b>	<b>1,500</b>	<b>standard pages</b>
<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 2,580  
**Std Dev** 108  
**90% Lower Confidence** 2,513

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested**      start 17-Oct-2019      stop 17-Oct-2019

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	No shake
	No shake
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Lexmark Printer Software G4 v1.2
Operating system	Windows 7 Professional
Application software	Adobe Acrobat version 9
Test page version	ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	SCAD192697F65	460192400005D	72	73	71	57	58	56	2,595	Y
	SCAD192697F69	460192400005D	72	73	71	57	58	56	2,520	Y
	SCAD192697F59	460192400005D	72	73	71	57	58	56	2,380	Y
	SCAD192697F56	460192400005C	72	73	71	57	58	56	2,590	Y
	SCAD192697F67	460192400005C	72	73	71	57	58	56	2,790	Y
	SCAD192697F66	460192400005C	72	73	71	57	58	56	2,545	Y
	SCAD192697F57	7019924000009	72	73	71	57	58	56	2,610	Y
	SCAD192697F68	7019924000009	72	73	71	57	58	56	2,630	Y
	SCAD192697F58	7019924000009	72	73	71	57	58	56	2,560	Y

**Comments and or exceptions:**

- 1.) The print file was generated with number of copies set equal to 5.
- 2.) EOL was determined by a print starvation or fade.