

## B3340 High Yield Toner Cartridge

Printer: B3340dw

Declaration of Yield: 

<b>Average Cartridge Yield</b>	<b>3,000</b>	<b>standard pages</b>
<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 3,906  
**Std Dev** 168  
**90% Lower Confidence** 3,801

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested**      start 18-Oct-2019      stop 19-Oct-2019

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake 2nd shake
Print mode	No shake
Number of printers tested	No shake
Media used	Continuous
Paper feed orientation	3
Driver version	Hammermill Tidal MP - 20 lbs. - Letter
Operating system	Short Edge Feed (SEF)
Application software	Lexmark Printer Software G4 v1.2
Test page version	Windows 7 Professional
	Adobe Acrobat version 9
	ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAD192707FC2	460192400005D	72	74	71	53	58	49	3,965	Y
SCAD192707FD0	460192400005D	72	74	71	53	58	49	3,635	Y
SCAD192707FC5	460192400005D	72	74	71	53	58	49	4,120	Y
SCAD192707FCF	460192400005C	72	74	71	53	58	49	4,105	Y
SCAD192707FC9	460192400005C	72	74	71	53	58	49	4,035	Y
SCAD192707FC8	460192400005C	72	74	71	53	58	49	3,875	Y
SCAD192707FBF	7019924000009	72	74	71	53	58	49	3,810	Y
SCAD192707FC4	7019924000009	72	74	71	53	58	49	3,715	Y
SCAD192707FC1	7019924000009	72	74	71	53	58	49	3,890	Y

**Comments and or exceptions:**

- 1.) The print file was generated with number of copies set equal to 5.
- 2.) EOL was determined by a print starvation or fade.