

## B3442 Extra High Yield Toner Cartridge

Printer: B3442dw

Declaration of Yield: 

<b>Average Cartridge Yield</b>	<b>6,000</b>	<b>standard pages</b>
<b>Declared yield value in accordance with ISO/IEC 19752</b>		

<p><b>Average</b> 6,901  <b>Std Dev</b> 136  <b>90% Lower Confidence</b> 6,816</p>	<p><b>For questions concerning testing contact:</b>  Lexmark International Inc.  740 West New Circle Rd.  Lexington, Ky. 40550 USA  Attn: Laser Supplies Product Manager</p>
--	--

<p><b>Date tested</b> <b>start</b> 21-Oct-2019  <b>stop</b> 22-Oct-2019</p> <p>Number of cartridges in testing 9  Qty. of cartridges used in calculation 9  Shake Procedure 1st shake No shake  2nd shake No shake</p> <p>Print mode Continuous  Number of printers tested 3  Media used Hammermill Tidal MP - 20 lbs. - Letter  Paper feed orientation Short Edge Feed (SEF)  Driver version Lexmark Printer Software G4 v1.2  Operating system Windows 7 Professional  Application software Adobe Acrobat version 9  Test page version ISO_IEC_19752_2004_Test_Page.pdf</p>
---

Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg	Max	Min	Avg	Max	Min		
SCAD192707FB3	460192400005D	73	75	71	54	57	48	6,875	Y
SCAD192707FB1	460192400005D	73	75	71	54	57	48	6,855	Y
SCAD192707FAE	460192400005D	73	75	71	54	57	48	6,725	Y
SCAD192707FAA	460192400005C	73	75	71	54	57	48	6,975	Y
SCAD192707FAD	460192400005C	73	75	71	54	57	48	6,980	Y
SCAD192707FAB	460192400005C	73	75	71	54	57	48	7,010	Y
SCAD192707FB7	7019924000009	73	75	71	54	57	48	7,125	Y
SCAD192707FAF	7019924000009	73	75	71	54	57	48	6,705	Y
SCAD192707FB2	7019924000009	73	75	71	54	57	48	6,855	Y

**Comments and or exceptions:**

- 1.) The print file was generated with number of copies set equal to 5.
- 2.) EOL was determined by the print starvation or fade.