



E120 Ship With Equipment Print Cartridge

Printer: E120

Part Number: Ship With Equipment Print Cartridge

Declaration of	Average Cartridge Yield	500	standard pages
Yield:	Declared yield value in accordance with ISO/IEC 19752		

Average 584
Std Dev 151
90% Lower 518
Confidence

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

start
Date tested 16-Sep-2005

stop
21-Oct-2005

Number of cartridges in testing	16
Qty. of cartridges used in calculation	16
Shake Procedure	1st shake At fade 2nd shake At fade
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	0
Operating system	Windows 98
Application software	Acrobat version 6.01
Test page version	Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:	Cartridge	Printer	Temperature				Humidity			Cartridge Yield	Cartridge used in Calculation	
			Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg			Max
CAS051862E19	11DV190	69	20	69	21	68	20	61	62	60	415	Yes
CAS051862E21	11DV166	69	20	69	21	68	20	61	62	60	623	Yes
CAS051862E0B	11DV130	69	20	69	21	68	20	61	62	60	595	Yes
CAS051862E0E	11DV087	69	20	69	21	68	20	61	62	60	610	Yes
CAS051862E14	11DV190	69	21	69	21	69	21	61	62	61	517	Yes
CAS051862E23	11DV166	69	21	69	21	69	21	61	62	61	522	Yes
CAS051862E32	11DV130	69	21	69	21	69	21	61	62	61	863	Yes
CAS051862E13	11DV087	69	21	69	21	69	21	61	62	61	593	Yes
CAS051862E64	11DV166	70	21	72	22	68	20	60	62	55	523	Yes
CAS051862E57	11DV130	70	21	72	22	68	20	60	62	55	768	Yes
CAS051862E17	11DV087	70	21	72	22	68	20	60	62	55	294	Yes
CAS051862E42	11DV190	70	21	72	22	68	20	60	62	55	645	Yes
CAS051862E62-SWE	11DV087	72	22	72	22	72	22	53	53	52	761	Yes
CAS050820658-SWE	11DV130	72	22	72	22	72	22	53	53	52	361	Yes
CAS051862DF7-SWE	11DV190	72	22	72	22	72	22	53	53	52	544	Yes
CAS051862DFB-SWE	11DV166	72	22	72	22	72	22	53	53	52	712	Yes

Comments and or exceptions: